

# Maximal Falsifiability: Definitions, Algorithms, and Applications

Alexey Ignatiev<sup>1</sup>, Antonio Morgado<sup>1</sup>, Jordi Planes<sup>3</sup>, and Joao Marques-Silva<sup>1,2</sup>

<sup>1</sup> INESC-ID/IST, Lisbon, Portugal


<sup>2</sup> CASL/CSI, University College Dublin, Ireland

<sup>3</sup> Universitat de Lleida, Spain


21st RCRA International Workshop on  
Experimental Evaluation of Algorithms for solving problems with combinatorial explosion

Vienna, Austria  
July 17, 2014

# Motivation



# Motivation



# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .

# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .



Given  $\mathcal{F}$ ,  $\mathcal{M} \subseteq \mathcal{F}$  is a MaxFalse solution  $\Leftrightarrow \mathcal{F} \setminus \mathcal{M}$  is a MinSAT solution.

# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .



Given  $\mathcal{F}$ ,  $\mathcal{M} \subseteq \mathcal{F}$  is a MaxFalse solution  $\Leftrightarrow \mathcal{F} \setminus \mathcal{M}$  is a MinSAT solution.

## Definition (All-Falsifiable)

A set of clauses  $\mathcal{U}$  is *all-falsifiable* if there exists a truth assignment  $\mathcal{A}$  such that  $\mathcal{A}$  falsifies **all** clauses in  $\mathcal{U}$ .

# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .



Given  $\mathcal{F}$ ,  $\mathcal{M} \subseteq \mathcal{F}$  is a MaxFalse solution  $\Leftrightarrow \mathcal{F} \setminus \mathcal{M}$  is a MinSAT solution.

## Definition (All-Falsifiable)

A set of clauses  $\mathcal{U}$  is *all-falsifiable* if there exists a truth assignment  $\mathcal{A}$  such that  $\mathcal{A}$  falsifies **all** clauses in  $\mathcal{U}$ .

$\mathcal{U}$  is all-falsifiable  $\Leftrightarrow$  all the literals of  $\mathcal{U}$  are *pure*.

## Example

$$\mathcal{F} = \{ x_1 \vee x_2, \neg x_1 \vee x_3, x_2 \vee \neg x_3 \}$$

# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .



Given  $\mathcal{F}$ ,  $\mathcal{M} \subseteq \mathcal{F}$  is a MaxFalse solution  $\Leftrightarrow \mathcal{F} \setminus \mathcal{M}$  is a MinSAT solution.

## Definition (All-Falsifiable)

A set of clauses  $\mathcal{U}$  is *all-falsifiable* if there exists a truth assignment  $\mathcal{A}$  such that  $\mathcal{A}$  falsifies **all** clauses in  $\mathcal{U}$ .

$\mathcal{U}$  is all-falsifiable  $\Leftrightarrow$  all the literals of  $\mathcal{U}$  are *pure*.

## Example

$\mathcal{F} = \{ x_1 \vee x_2, \neg x_1 \vee x_3, x_2 \vee \neg x_3 \}$  — all-falsifiable



# Maximum Falsifiability

**MinSAT:** compute the *smallest* number of simultaneously *satisfied* clauses in  $\mathcal{F}$ .

**MaxFalse:** compute the *largest* number of simultaneously *falsified* clauses in  $\mathcal{F}$ .



Given  $\mathcal{F}$ ,  $\mathcal{M} \subseteq \mathcal{F}$  is a MaxFalse solution  $\Leftrightarrow \mathcal{F} \setminus \mathcal{M}$  is a MinSAT solution.

## Definition (All-Falsifiable)

A set of clauses  $\mathcal{U}$  is *all-falsifiable* if there exists a truth assignment  $\mathcal{A}$  such that  $\mathcal{A}$  falsifies **all** clauses in  $\mathcal{U}$ .

$\mathcal{U}$  is all-falsifiable  $\Leftrightarrow$  all the literals of  $\mathcal{U}$  are *pure*.

## Example

$\mathcal{F} = \{ x_1 \vee x_2, \neg x_1 \vee x_3, x_2 \vee \neg x_3 \}$  — not all-falsifiable

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

Subset  $\mathcal{N} \subseteq \mathcal{F}$  is called a **Minimal Non-Falsifiable Subset** (MNFS) if:

- 1  $\mathcal{N}$  is *not* all-falsifiable
- 2  $\mathcal{N}'$  is all-falsifiable  $\forall \mathcal{N}' : \mathcal{N}' \subsetneq \mathcal{N} \subseteq \mathcal{F}$

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

Subset  $\mathcal{N} \subseteq \mathcal{F}$  is called a **Minimal Non-Falsifiable Subset** (MNFS) if:

- 1  $\mathcal{N}$  is *not* all-falsifiable
- 2  $\mathcal{N}'$  is all-falsifiable  $\forall \mathcal{N}' : \mathcal{N}' \subsetneq \mathcal{N} \subseteq \mathcal{F}$

## Example

$$\mathcal{F} = \{ x_1 \vee x_2, \neg x_1 \vee x_3, x_2 \vee \neg x_3 \}$$

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

Subset  $\mathcal{N} \subseteq \mathcal{F}$  is called a **Minimal Non-Falsifiable Subset** (MNFS) if:

- 1  $\mathcal{N}$  is *not* all-falsifiable
- 2  $\mathcal{N}'$  is all-falsifiable  $\forall \mathcal{N}' : \mathcal{N}' \subsetneq \mathcal{N} \subseteq \mathcal{F}$

## Example

$$\mathcal{F} = \{ \textcolor{red}{x}_1 \vee \textcolor{red}{x}_2, \neg x_1 \vee x_3, \textcolor{red}{x}_2 \vee \neg \textcolor{red}{x}_3 \} \text{ --- MFS}$$

# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

Subset  $\mathcal{N} \subseteq \mathcal{F}$  is called a **Minimal Non-Falsifiable Subset** (MNFS) if:

- 1  $\mathcal{N}$  is *not* all-falsifiable
- 2  $\mathcal{N}'$  is all-falsifiable  $\forall \mathcal{N}' : \mathcal{N}' \subsetneq \mathcal{N} \subseteq \mathcal{F}$

## Example

$\mathcal{F} = \{ x_1 \vee x_2, \neg x_1 \vee x_3, x_2 \vee \neg x_3 \} - \text{MCFS}$



# Definitions

Let  $\mathcal{F}$  be a CNF formula.

Subset  $\mathcal{M} \subseteq \mathcal{F}$  is called a **Maximal Falsifiable Subset** (MFS) if:

- 1  $\mathcal{M}$  is all-falsifiable
- 2  $\mathcal{M}'$  is *not* all-falsifiable  $\forall \mathcal{M}' : \mathcal{M} \subsetneq \mathcal{M}' \subseteq \mathcal{F}$

---

Subset  $\mathcal{C} = \mathcal{F} \setminus \mathcal{M}$  is called a **Minimal Correction** (for Falsifiability) **Subset** (MCFS).

Subset  $\mathcal{N} \subseteq \mathcal{F}$  is called a **Minimal Non-Falsifiable Subset** (MNFS) if:

- 1  $\mathcal{N}$  is *not* all-falsifiable
- 2  $\mathcal{N}'$  is all-falsifiable  $\forall \mathcal{N}' : \mathcal{N}' \subsetneq \mathcal{N} \subseteq \mathcal{F}$

## Example

$\mathcal{F} = \{ \textcolor{red}{x_1} \vee \textcolor{red}{x_2}, \neg \textcolor{red}{x_1} \vee \textcolor{red}{x_3}, \textcolor{gray}{x_2} \vee \neg \textcolor{gray}{x_3} \} \text{ — MNFS}$

# MNFS Properties

Let  $\mathcal{F}$  be a set of clauses.

# MNFS Properties

Let  $\mathcal{F}$  be a set of clauses.

- Each MNFS of  $\mathcal{F}$  consists of exactly two clauses.

# MNFS Properties

Let  $\mathcal{F}$  be a set of clauses.

- Each MNFS of  $\mathcal{F}$  consists of exactly two clauses.
- The number of MNFSes of  $\mathcal{F}$  is  $\mathcal{O}(m^2)$ , where  $m = |\mathcal{F}|$ .

# MNFS Properties

Let  $\mathcal{F}$  be a set of clauses.

- Each MNFS of  $\mathcal{F}$  consists of exactly two clauses.
- The number of MNFSes of  $\mathcal{F}$  is  $\mathcal{O}(m^2)$ , where  $m = |\mathcal{F}|$ .

This **does not hold** for the partial case, i. e. when

$$\mathcal{F} = \mathcal{H} \cup \mathcal{R},$$

where  $\mathcal{H}$  — *hard* clauses, and  $\mathcal{R}$  — *soft (relaxable)* clauses.

# MNFS Properties

Let  $\mathcal{F}$  be a set of clauses.

- Each MNFS of  $\mathcal{F}$  consists of exactly two clauses.
- The number of MNFSes of  $\mathcal{F}$  is  $\mathcal{O}(m^2)$ , where  $m = |\mathcal{F}|$ .

This **does not hold** for the partial case, i. e. when

$$\mathcal{F} = \mathcal{H} \cup \mathcal{R},$$

where  $\mathcal{H}$  — *hard* clauses, and  $\mathcal{R}$  — *soft (relaxable)* clauses.

## Example


$$\mathcal{F} = \mathcal{H} \cup \mathcal{R}$$

$$\mathcal{H} = \{ x \vee y \vee z \}$$

$$\mathcal{R} = \{ x, y, z \}$$

Only **one** MNFS  $\mathcal{N} = \mathcal{R}$ ,  $|\mathcal{N}| = 3$ .

# Connection to Maximal Independent Set




(a) Graph  $\mathcal{G}$

$$\mathcal{F} = \left\{ \begin{array}{l} c_1 = x_{v_1 v_2} \vee x_{v_1 v_3} \\ c_2 = \neg x_{v_1 v_2} \vee x_{v_2 v_3} \vee x_{v_2 v_4} \\ c_3 = \neg x_{v_1 v_3} \vee \neg x_{v_2 v_3} \\ c_4 = \neg x_{v_2 v_4} \end{array} \right\}$$

(b) Set of clauses  $\mathcal{F}$  for  $\mathcal{G}$

Figure: From maximal independent set to maximal falsifiability

# Connection to Maximal Independent Set



(a) Graph  $\mathcal{G}$

$$\mathcal{F} = \left\{ \begin{array}{l} c_1 = x_{v_1 v_2} \vee x_{v_1 v_3} \\ c_2 = \neg x_{v_1 v_2} \vee x_{v_2 v_3} \vee x_{v_2 v_4} \\ c_3 = \neg x_{v_1 v_3} \vee \neg x_{v_2 v_3} \\ c_4 = \neg x_{v_2 v_4} \end{array} \right\}$$


(b) Set of clauses  $\mathcal{F}$  for  $\mathcal{G}$

Figure: From maximal independent set to maximal falsifiability

Graph $\mathcal{G}$	Formula $\mathcal{F}$
edge	MNFS



# Connection to Maximal Independent Set



(a) Graph  $\mathcal{G}$


$$\mathcal{F} = \left\{ \begin{array}{l} c_1 = x_{v_1 v_2} \vee x_{v_1 v_3} \\ c_2 = \neg x_{v_1 v_2} \vee x_{v_2 v_3} \vee x_{v_2 v_4} \\ c_3 = \neg x_{v_1 v_3} \vee \neg x_{v_2 v_3} \\ c_4 = \neg x_{v_2 v_4} \end{array} \right\}$$

(b) Set of clauses  $\mathcal{F}$  for  $\mathcal{G}$

Figure: From maximal independent set to maximal falsifiability

Graph $\mathcal{G}$	Formula $\mathcal{F}$
edge	MNFS
maximal IS	MFS

# Connection to Maximal Independent Set



(a) Graph  $\mathcal{G}$

$$\mathcal{F} = \left\{ \begin{array}{l} c_1 = x_{v_1 v_2} \vee x_{v_1 v_3} \\ c_2 = \neg x_{v_1 v_2} \vee x_{v_2 v_3} \vee x_{v_2 v_4} \\ c_3 = \neg x_{v_1 v_3} \vee \neg x_{v_2 v_3} \\ c_4 = \neg x_{v_2 v_4} \end{array} \right\}$$

(b) Set of clauses  $\mathcal{F}$  for  $\mathcal{G}$

Figure: From maximal independent set to maximal falsifiability

Graph $\mathcal{G}$	Formula $\mathcal{F}$
edge	MNFS
maximal IS	MFS
minimal VC	MCFS

# Minimal hitting set duality

Let  $\mathbb{N}(\mathcal{F})$  and  $\mathbb{C}(\mathcal{F})$  be complete sets of MNFSes and MCFSES of  $\mathcal{F}$ , respectively.

# Minimal hitting set duality

Let  $\mathbb{N}(\mathcal{F})$  and  $\mathbb{C}(\mathcal{F})$  be complete sets of MNFSes and MCFSES of  $\mathcal{F}$ , respectively.

## Theorem

Subformula  $\mathcal{C} \subset \mathcal{F}$  is an MCFS of  $\mathcal{F}$   $\Leftrightarrow$   $\mathcal{C}$  is a minimal hitting set of  $\mathbb{N}(\mathcal{F})$ .

Subformula  $\mathcal{N} \subseteq \mathcal{F}$  is an MNFS of  $\mathcal{F}$   $\Leftrightarrow$   $\mathcal{N}$  is a minimal hitting set of  $\mathbb{C}(\mathcal{F})$ .

# Minimal hitting set duality

Let  $\mathbb{N}(\mathcal{F})$  and  $\mathbb{C}(\mathcal{F})$  be complete sets of MNFSes and MCFSes of  $\mathcal{F}$ , respectively.

## Theorem

Subformula  $\mathcal{C} \subset \mathcal{F}$  is an MCFS of  $\mathcal{F} \iff \mathcal{C}$  is a minimal hitting set of  $\mathbb{N}(\mathcal{F})$ .

Subformula  $\mathcal{N} \subseteq \mathcal{F}$  is an MNFS of  $\mathcal{F} \iff \mathcal{N}$  is a minimal hitting set of  $\mathbb{C}(\mathcal{F})$ .



Enumeration of MNFSes can be done for computing a **lower bound** on the size of any MCFS

# Minimal hitting set duality

Let  $\mathbb{N}(\mathcal{F})$  and  $\mathbb{C}(\mathcal{F})$  be complete sets of MNFSes and MCFSes of  $\mathcal{F}$ , respectively.

## Theorem

Subformula  $\mathcal{C} \subset \mathcal{F}$  is an MCFS of  $\mathcal{F} \iff \mathcal{C}$  is a minimal hitting set of  $\mathbb{N}(\mathcal{F})$ .

Subformula  $\mathcal{N} \subseteq \mathcal{F}$  is an MNFS of  $\mathcal{F} \iff \mathcal{N}$  is a minimal hitting set of  $\mathbb{C}(\mathcal{F})$ .



Enumeration of MNFSes can be done for computing a **lower bound** on the size of any MCFS  $\Rightarrow$  an **upper bound** for MaxFalse.

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

1  $\mathcal{M} \leftarrow \emptyset$



# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

1  $\mathcal{M} \leftarrow \emptyset$

2 **foreach**  $c \in \mathcal{F}$ :

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

1  $\mathcal{M} \leftarrow \emptyset$

2 **foreach**  $c \in \mathcal{F}$ :

3     **if**  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

1  $\mathcal{M} \leftarrow \emptyset$

2 **foreach**  $c \in \mathcal{F}$ :

3     **if**  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :

4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

1  $\mathcal{M} \leftarrow \emptyset$

2 **foreach**  $c \in \mathcal{F}$ :

3     **if**  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :

4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

```
1  $\mathcal{M} \leftarrow \emptyset$ 
2 foreach  $c \in \mathcal{F}$ :
3     if  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :
4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$ 
```

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

- basic idea:

similar to computing MSS, MCS, or MUS (in MaxSAT)

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

```
1  $\mathcal{M} \leftarrow \emptyset$   
2 foreach  $c \in \mathcal{F}$ :  
3   if  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :  
4      $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$ 
```

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

- basic idea:

similar to computing MSS, MCS, or MUS (in MaxSAT)

```
1 foreach  $c \in \mathcal{R}$ :
```

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — **polynomial**

```
1  $\mathcal{M} \leftarrow \emptyset$ 
2 foreach  $c \in \mathcal{F}$ :
3     if  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :
4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$ 
```

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

- basic idea:

similar to computing MSS, MCS, or MUS (in MaxSAT)

```
1 foreach  $c \in \mathcal{R}$ :
2     if  $\mathcal{H} \cup \{\neg c\}$  is satisfiable:
```

# ask a SAT oracle

# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

```
1  $\mathcal{M} \leftarrow \emptyset$ 
2 foreach  $c \in \mathcal{F}$ :
3     if  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :
4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$ 
```

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

- basic idea:

similar to computing MSS, MCS, or MUS (in MaxSAT)

```
1 foreach  $c \in \mathcal{R}$ :
2     if  $\mathcal{H} \cup \{\neg c\}$  is satisfiable:
3          $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg c\}$ 
```

# ask a SAT oracle



# Computing an MFS

- plain formulas (without  $\mathcal{H}$ ) — polynomial

```
1  $\mathcal{M} \leftarrow \emptyset$ 
2 foreach  $c \in \mathcal{F}$ :
3     if  $\mathcal{M} \cap \neg c$  is  $\emptyset$ :
4          $\mathcal{M} \leftarrow \mathcal{M} \cup \{c\}$ 
```

- partial formulas:  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

- basic idea:

similar to computing MSS, MCS, or MUS (in MaxSAT)

```
1 foreach  $c \in \mathcal{R}$ :
2     if  $\mathcal{H} \cup \{\neg c\}$  is satisfiable:
3          $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg c\}$ 
```

# ask a SAT oracle

- heuristics to reduce the number of SAT calls

# Iterative MaxFalse algorithms

- similar to iterative MaxSAT

# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle

# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$

# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$


# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$
- relaxation constraints  $\sum_{r_i} r_i \leq k$

# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$
- relaxation constraints  $\sum_{r_i} r_i \leq k$
- varying  $k$  using 3 algorithms:

linear search UNSAT/SAT



linear search SAT/UNSAT




binary search



# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$
- relaxation constraints  $\sum_{r_i} r_i \leq k$
- varying  $k$  using 3 algorithms:

linear search UNSAT/SAT



linear search SAT/UNSAT



binary search






# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$
- relaxation constraints  $\sum_{r_i} r_i \leq k$
- varying  $k$  using 3 algorithms:


linear search UNSAT/SAT



linear search SAT/UNSAT




binary search



# Iterative MaxFalse algorithms

- similar to iterative MaxSAT
- SAT solver is used as an oracle
- consider formula  $\mathcal{F} = \mathcal{H} \cup \mathcal{R}$
- $\forall c_i \in \mathcal{R}$  modify  $\mathcal{H}$  and  $\mathcal{R}$ :
  - $\mathcal{H} \leftarrow \mathcal{H} \cup \{\neg l_{i_j} \vee r_i\} \quad \forall l_{i_j} \in c_i$
  - $\mathcal{R} \leftarrow \mathcal{R} \setminus \{c_i\}$
- relaxation constraints  $\sum_{r_i} r_i \leq k$
- varying  $k$  using 3 algorithms:


linear search UNSAT/SAT




linear search SAT/UNSAT



binary search



# Performance comparison: MaxFalse for MaxSAT instances



# Summary

- Maximal and maximum falsifiability

# Summary

- Maximal and maximum falsifiability
- New concepts of
  - maximal falsifiable subset (MFS)
  - minimal correction for falsifiability subset (MCFS)
  - minimal non-falsifiable subset (MNFS)

# Summary

- Maximal and maximum falsifiability
- New concepts of
  - maximal falsifiable subset (MFS)
  - minimal correction for falsifiability subset (MCFS)
  - minimal non-falsifiable subset (MNFS)
- Connection to maximal/maximum independent set

# Summary

- Maximal and maximum falsifiability
- New concepts of
  - maximal falsifiable subset (MFS)
  - minimal correction for falsifiability subset (MCFS)
  - minimal non-falsifiable subset (MNFS)
- Connection to maximal/maximum independent set
- Minimal hitting set duality between MNFSes and MCFSes

# Summary

- Maximal and maximum falsifiability
- New concepts of
  - maximal falsifiable subset (MFS)
  - minimal correction for falsifiability subset (MCFS)
  - minimal non-falsifiable subset (MNFS)
- Connection to maximal/maximum independent set
- Minimal hitting set duality between MNFSes and MCFSes
- Native algorithms for computing
  - one MFS
  - MaxFalse solution



# Future Work

- Other “*properties*” of maximal/maximum falsifiability

# Future Work

- Other “*properties*” of maximal/maximum falsifiability
- Other algorithms for
  - computing MFSeS
  - computing MaxFalse solutions

# Future Work

- Other “*properties*” of maximal/maximum falsifiability
- Other algorithms for
  - computing MFSeS
  - computing MaxFalse solutions
- MaxFalse in portfolios of MaxSAT algorithms

# Future Work

- Other “*properties*” of maximal/maximum falsifiability
- Other algorithms for
  - computing MFSes
  - computing MaxFalse solutions
- MaxFalse in portfolios of MaxSAT algorithms
- More practical applications

Thank you for your attention!