
You are currently looking at **version 1.0** of this notebook. To download notebooks and datafiles, as well as get help on Jupyter notebooks in the Coursera platform, visit the [Jupyter Notebook FAQ](https://www.coursera.org/learn/python-text-mining/resources/d9pwm) (<https://www.coursera.org/learn/python-text-mining/resources/d9pwm>). course resource.

Note: Some of the cells in this notebook are computationally expensive. To reduce runtime, this notebook is using a subset of the data.

Case Study: Sentiment Analysis

Data Prep

```
In [ ]: import pandas as pd
import numpy as np

# Read in the data
df = pd.read_csv('Amazon_Unlocked_Mobile.csv')

# Sample the data to speed up computation
# Comment out this line to match with lecture
df = df.sample(frac=0.1, random_state=10)

df.head()
```

```
In [ ]: # Drop missing values
df.dropna(inplace=True)

# Remove any 'neutral' ratings equal to 3
df = df[df['Rating'] != 3]

# Encode 4s and 5s as 1 (rated positively)
# Encode 1s and 2s as 0 (rated poorly)
df['Positively Rated'] = np.where(df['Rating'] > 3, 1, 0)
df.head(10)
```

```
In [ ]: # Most ratings are positive
df['Positively Rated'].mean()
```

```
In [ ]: from sklearn.model_selection import train_test_split

# Split data into training and test sets
X_train, X_test, y_train, y_test = train_test_split(df['Reviews'],
                                                    df['Positively Rated'],
                                                    random_state=0)
```

```
In [ ]: print('X_train first entry:\n\n', X_train.iloc[0])
print('\n\nX_train shape: ', X_train.shape)
```

CountVectorizer

```
In [ ]: from sklearn.feature_extraction.text import CountVectorizer

# Fit the CountVectorizer to the training data
vect = CountVectorizer().fit(X_train)
```

```
In [ ]: vect.get_feature_names()[::2000]
```

```
In [ ]: len(vect.get_feature_names())
```

```
In [ ]: # transform the documents in the training data to a document-term matrix
X_train_vectorized = vect.transform(X_train)

X_train_vectorized
```

```
In [ ]: from sklearn.linear_model import LogisticRegression

# Train the model
model = LogisticRegression()
model.fit(X_train_vectorized, y_train)
```

```
In [ ]: from sklearn.metrics import roc_auc_score

# Predict the transformed test documents
predictions = model.predict(vect.transform(X_test))

print('AUC: ', roc_auc_score(y_test, predictions))
```

```
In [ ]: # get the feature names as numpy array
feature_names = np.array(vect.get_feature_names())

# Sort the coefficients from the model
sorted_coef_index = model.coef_[0].argsort()

# Find the 10 smallest and 10 largest coefficients
# The 10 largest coefficients are being indexed using [-11:-1]
# so the list returned is in order of largest to smallest
print('Smallest Coefs:\n{}\n'.format(feature_names[sorted_coef_index[:10]]))
print('Largest Coefs: \n{}'.format(feature_names[sorted_coef_index[-11:-1]]))
```

Tfidf

```
In [ ]: from sklearn.feature_extraction.text import TfidfVectorizer

# Fit the TfidfVectorizer to the training data specifying a minimum document frequency of 5
vect = TfidfVectorizer(min_df=5).fit(X_train)
len(vect.get_feature_names())
```

```
In [ ]: X_train_vectorized = vect.transform(X_train)

        model = LogisticRegression()
        model.fit(X_train_vectorized, y_train)

        predictions = model.predict(vect.transform(X_test))

        print('AUC: ', roc_auc_score(y_test, predictions))
```

```
In [ ]: feature_names = np.array(vect.get_feature_names())

        sorted_tfidf_index = X_train_vectorized.max(0).toarray()[0].argsort()

        print('Smallest tfidf:\n{}\n'.format(feature_names[sorted_tfidf_index[:10]]))
        print('Largest tfidf: \n{}'.format(feature_names[sorted_tfidf_index[:-11:-1]]))
```

```
In [ ]: sorted_coef_index = model.coef_[0].argsort()

        print('Smallest Coefs:\n{}\n'.format(feature_names[sorted_coef_index[:10]]))
        print('Largest Coefs: \n{}'.format(feature_names[sorted_coef_index[:-11:-1]]))
```

```
In [ ]: # These reviews are treated the same by our current model
        print(model.predict(vect.transform(['not an issue, phone is working',
                                             'an issue, phone is not working'])))
```

n-grams

```
In [ ]: # Fit the CountVectorizer to the training data specifying a minimum
        # document frequency of 5 and extracting 1-grams and 2-grams
        vect = CountVectorizer(min_df=5, ngram_range=(1,2)).fit(X_train)

        X_train_vectorized = vect.transform(X_train)

        len(vect.get_feature_names())
```

