Assignment 2 - STAT 7730

Problem 2 - PCA for image patches

For this homework we will be working with 12 imes 12 image patches. There are 100 grayscale images of outdoor scenes.

```
In [8]: import numpy as np
import cv2
from matplotlib import pyplot as plt
import os
import random as rnd
import math
```

We will first read all the images into numpy arrays

```
In [9]: A = np.zeros((100,600,600))
X = np.zeros((144,100000))

pix_img = 589**2;

path = os.getcwd() + '\HW2\img\\'

for i in range(1,101):
    filname = 'img' + str(i)
    A[i-1,:,:] = cv2.imread(path + filname, 0)
```

To estimate the covariance matrices of the 12×12 patches we will randomly choose $n=10^5$ image patches from the database. Then we will compute all 144 eigenvectors of the covariance matrix sorted such that their corresponding eigenvalues are decreasing.

```
In [10]: sampls = rnd.sample(range(0,100*(600-11)**2),100000)

for j in range(0,100000):
    i = sampls[j]
    num_img = math.floor(i/pix_img)
    n_pix = i % pix_img
    i_1 = math.floor(n_pix / 589)
    i_2 = n_pix % 589
    V = A[num_img,i_1:(i_1 + 12),i_2 : (i_2 + 12)]
    X[:,j] = V.flatten('F')
C = np.cov(X)
L, U = np.linalg.eig(C)
```

Some basic statistics about the values in the data:

```
In [11]: print("Maximum and minimum values of pixel intensities",end = '')
    print(" of the 100 images: \n\t Max: %d" % X.max())
    print("\t Min: %d\n" % X.min())

    print("Mean of all the pixels in the 100 images: %f\n" % np.ndarray.mean(X))
    mu_vec = X.mean(axis = 1)
    mu_vec = mu_vec.reshape((144,1))
    mu_vec_1 = mu_vec.reshape((12,12)).T

    plt.imshow(mu_vec_1.astype(int), cmap='gray', vmin=0, vmax=255)
    print("What does the mean image patch look like?")
    plt.show()


    print("It looks like a dark square, almost black\n")
```

Maximum and minimum values of pixel intensities of the 100 images:

Max: 255 Min: 2

Mean of all the pixels in the 100 images: 34.885862

What does the mean image patch look like?



It looks like a dark square, almost black


Now we will create a figure with the first 36 eigenvectors (in order, from left-to-right, then top-to-bottom) displayed as 12×12 image patches. We can observe the dominant modes of variation in the top left patch.

```
In [12]:    eig_vec = np.zeros((36,12,12))
    img_eig = np.zeros((12*6,12*6))

fig, axs = plt.subplots(6, 6)

j = 0
    for k in range(0,36):
        i = k % 36
        patch = U[:,k]
        patch = patch - patch.min()
        patch = patch*255/patch.max()
        patch = patch.reshape((12,12)).T
        patch = patch.astype(int)
        i_1 = math.floor(i/6)
        i_2 = i % 6
        axs[math.floor(k/6),k % 6].imshow(patch, cmap='gray', vmin=0, vmax=255)

plt.show()
```



```
In [13]: sample_img = A[0,:,:]
sample_img = sample_img.astype(int)


print("We will use the first image of the database to work with")

plt.imshow(sample_img, cmap='gray')
plt.show()

sample_patches = np.zeros((144,2500));

for i in range(0,50):
    for j in range(0,50):
        patch = sample_img[(i*12):(i*12+12),(j*12):(j*12+12)]
        patch = patch.flatten('F');
        sample_patches[:,i*50+j] = patch;
```


We will use the first image of the database to work with




We finally show the PCA versions of the image. Observe that when $d \geq 10$, the PCA version is indeed very similar to the original one, and most of the quality is preserved.

```
In [14]: for d in [20,1,3,5,10,144]:
             fig, axs = plt.subplots(1, 2)
             U_d = U[:,0:d]
             U n = U d.dot(U d.T)
             X_0 = sample_patches - mu_vec.dot(np.ones((1,2500)))
             Z = U_n.dot(X_0) + mu_vec.dot(np.ones((1,2500)))
             Z_{img} = np.zeros((600,600))
             for i in range(0,50):
                 for j in range(0,50):
                     patch = Z[:,i*50+j];
                      patch = patch.reshape((12,12)).T
                      Z_{img}[(i*12):(i*12+12),(j*12):(j*12+12)] = patch
             Z_img = Z_img.astype(int);
             print("d = %d\tprincipal components" % d)
             axs[1].imshow(Z_img, cmap='gray')
             axs[0].imshow(sample_img, cmap='gray')
             plt.show()
```


d = 20 principal components




d = 1 principal components




d = 3 principal components



d = 5 principal components



d = 10 principal components



d = 144 principal components

