

0107451, 0107461 Laboratory 1: Introduction to Linux

Department of Computer and Communications Engineering
Tafila Technical University

1 Submission

There is no lab report for this lab, but you are expected to review, understand, and ask questions about this material. Future labs will build on this material.

2 Purpose

In this lab, you will become familiar with the basic use of a Linux system and its development tools. You will be asked to perform a few exercises and read various manuals available for Linux.

3 Logging In

Linux is a multi-user operating system (it allows multiple users to have accounts and to be logged in at one time). Linux presents a desktop environment that enables users to easily use and configure their computers.

Once you feel marginally comfortable with the desktop, open a terminal window by right-clicking on the desktop and selecting Open Terminal from the pop up menu.

4 Command Line

The command line in Unix is actually just another program, usually called a shell. The shell allows you to run other programs or scripts, and is generally useful for managing your computer once you know which commands to use. Most Linux distributions ship with bash as the default shell. This shouldn't be confused with the terminal emulator, which simply presents a GUI for command-line programs and happens to run bash by default.

When you start a terminal, the first thing you will see is the prompt (often called the command line). As its name would suggest, it is prompting you to enter a command. It should look something like this:

```
[username@host current directory]$
```

Type the commands after the prompt (\$).

Make a new directory to contain your work for this course.

```
$mkdir 451
```

Go to the directory.

```
$cd 451
```

Edit a new file.

```
$leafpad practice
```

A window should open for you to type in. Go back to the command line. Notice anything odd? The prompt didn't reappear. That's because it's waiting for leafpad to finish. We'd like to continue typing commands at the same time, so let's fix this.

leafpad is currently in the foreground. On the command line, type Ctrl-Z. You've just suspended leafpad and placed it in the background. You should have a prompt again. However, because leafpad is suspended, we can't use it until it returns to the foreground or we start running it in the background.

Type `bg`. *leafpad* will now be running in the background while we continue to type commands. If we wanted to return it to the foreground, we could have typed `fg`. To list a list of jobs in the background, use the `jobs` command. Note: you can avoid this whole mess in the future by starting leafpad in the background. Just type an `&` after the command:

```
$leafpad somefile &
```

Now that we have an editor running, type something into the window and save it. Back on the command line, type the following:

```
$ls
```

The file practice should be listed. Now try:

```
$ls -a
```

You should see two additional entries `."` and `.."`. `.` is a reference to the current directory, and `..` is a reference to the parent directory. Type

```
$cd ..  
$ls
```

You should see the 451 directory in the listing, since you're now in the parent directory. You need to know two more things about directories: absolute and relative paths. An absolute path is a path that starts with `"/`. Because it starts with the root of the file system, it will always refer to the same file no matter what your current directory is. A relative path is a path that starts with any other character. It is relative to the current directory, and will refer to different files depending on the current directory. Type `pwd` to see the current absolute path. You should see something like `/home/username`, which indicates you're in the username directory under the home directory. This is where to find your account in Linux. It's the default current directory when you login. You can always go back to it by typing

```
$cd
```

Now try using an absolute path to switch directories. Type (replacing username with your own username):

```
$cd /home/username/451
```

You should now be in your 451 directory. To confirm this, type

```
$pwd
```

To return to your home directory, type:

```
$cd
```

Now switch to the directory again using a relative path:

```
$cd 451
```

Again, use `pwd` to verify that you're in the subdirectory. So far there's no difference, right? Suppose that you were in another user's home directory. In that case, `cd 451` would take you to their 451 directory. However, if you used the absolute path with your username in the path, you would go to your 451 directory. This difference isn't all that interesting now, but be aware of it for future use. There will be occasions when you will want to specify the file or directory you want to work with unambiguously by using an absolute path. You can use relative and absolute paths to describe files and directories in many commands. For example, if you're in your home directory, the following two commands should be equivalent:

```
$ls /
$ls ../../
```

Why does this work? Since the first command uses an absolute path (it starts with /), then it will always return the same result no matter where you are. If you're in the directory /home/username, then ../../ resolves to the parent of the parent of the current directory, or /. If you were in /home/username/451 and typed ls ../../, you would see the directory listing for /home instead. Here's a list of commands you might find helpful. Try a few out, but be careful with the ones that delete files! You don't have permission to delete anything other than your own files, but there isn't a recycling bin to recover your work from!

- mkdir - make a directory
- rmdir - remove a directory
- cd - change current directory
- ls - lists files and directories
- mv - move/rename a file/directory
- rm - remove a file
- cp - copy a file
- less - view a file (use arrow keys or space to scroll). Use q to quit.
- man - display the manual for a subject or command. Similar to less.

A few more general tips:

- Linux has two clipboards to allow more convenient copy/paste while keeping the features of standard cut/copy/paste. When you select text in the terminal or any application, it is copied to the "selection" clipboard; use the middle mouse button (wheel button) to paste into an application. The second clipboard is usually accessed through Ctrl-C and similar shortcuts; however, these do not work in the terminal as they are sent to the program in the terminal.
- You can use the tab key to finish commands and paths. Hit tab twice to see a list of potential matches.
- You can use the arrow keys to look through recently typed commands. In bash, Ctrl-R will search your command history for the text you type.

4.1 Editors

If you aren't already proficient with a Unix editor, you should pick one to become proficient with. The editor leafpad is a useful graphical editor for those new to the command line. There are several other editors available, many with more features. More seasoned programmers tend to use emacs or vi, which are console-based editors. There is an excellent vi tutorial from Purdue University at: <http://ecn.www.ecn.purdue.edu/ECN/Documents/VI/> (you can start the Mozilla web browser by typing mozilla & in your terminal). Emacs, or its GUI version xemacs, is another editor that some have found to be simpler and more flexible than vi.

5 Development Tools

5.1 Compiler

A compiler converts source code into object code or executable code. The GNU Compiler Collection (gcc) is included with Linux. Several versions of the compiler (C, C++, Objective C, Fortran, Java and CHILL) are integrated; this is why we use the name "GNU Compiler Collection." GCC can also refer to the "GNU C Compiler," which is the gcc program on the command line. You will be using a lot of C in this course.

5.2 Compiling and Linking Multiple C Files

Create a three files in your preferred editor:

message.h contains:

```
void print_message();
```

message.c contains:

```
#include <time.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include "message.h"
static const char* message[] = {
    "Hello Tafila!",
    "Goodbye Tafila!",
    "The penguins are coming!",
    "Caffeine is my friend!"
};
void print_message() {
    int index;
    srand(time(NULL));
    index = rand()/(RAND_MAX/4);
    printf("%s\n", message[index]);
}
```

lab1.c contains:

```
#include "message.h"
int main(int argc, char** argv) {
    print_message();
    return 0;
}
```

If your code was typed in correctly you can compile and link the two C files into an executable by typing this sequence of commands:

```
$gcc -c message.c
$gcc -c lab1.c
$gcc -o lab1 lab1.o message.o
```

To run the program, type:

```
$ ./lab1
```

Note: why `./`? Recall the discussion of directory navigation in the previous section? `.` is a reference to the current directory. Since the shell needs to find the file you want to run, you have to specify the complete path (or have the file in a directory stored in the `PATH` environment variable). You can think of `./` as a shortcut for the absolute path up to the current directory. Don't forget this you'll need it to run programs for the rest of the semester. When you use the `-c` option in `gcc`, the C files are compiled into object files (`.o`) that can be linked together into an executable. Because this project is quite small, it is also possible to compile all of the C files at one time with the command

```
$gcc -o lab1 lab1.c message.c
```

Compiling the C files to object files is less memory intensive when you have hundreds of files in a project; in addition, since compiling from C to object is much more expensive than linking object files, compiling to object files will allow you to only recompile files that have changed, rather than an entire project. The *make* utility automates this process.

5.3 Make

The make utility automatically determines which pieces of a large program need to be recompiled and then issues commands to recompile them. It is easier to use than running a series of gcc commands, and less prone to typos. It also allows for ags (such as -g to add debugging information, or -O to enable optimizations) to be added to all files at one time. Please read the GNU Make manual (info make) or find a tutorial online to figure out how to write a Makefile that will compile and link the example in the previous section. There are multiple ways to do this; experiment to see what the differences are and which way avoids recompiling files when only one of the two .c files changes.

6 Additional Information

6.1 Manual pages

Manual pages are your best friends in Unix; they provide information you can digest on almost all commands, applications, system calls, programming languages, etc. For example, to view the manual page for the ping command, type man ping in your terminal. You will see something like this:

```
PING(8)                System Manager's Manual: iputils                PING(8)
NAME
ping, ping6 - send ICMP ECHO_REQUEST to network hosts

SYNOPSIS
ping [-LRUbdfnqrvVaAB] [-c count] [-i interval] [-l preload] [
-p pattern] [-s packetsize] [-t ttl] [-w deadline] [-F flowlabel]
[-I interface] [-M hint] [-Q tos] [-S sndbuf] [-T
timestamp option] [-W timeout] [hop ...] destination

DESCRIPTION
ping uses the ICMP protocol's mandatory ECHO_REQUEST datagram to elicit an ICMP
ECHO_RESPONSE from a host or gateway. ECHO_REQUEST datagrams ("pings") have an
IP and ICMP header, followed by a struct timeval and then an arbitrary number of
"pad" bytes used to fill out the packet.
```

There may also be more help in info pages. The compiler's manual can be reached using info gcc. When they exist, the info pages for a given command may contain more information about what the program does rather than simply a description of its syntax. Man pages are divided into several sections; notice PING(8) in the above example means ping is in section 8. A description of the different sections is in man man. Some important sections are: system calls are in section 2, library functions are in section 3, system programs are in section 1 (or 8 for administrative tools). For example, man read will not show the documentation for the system call read(); you must run *man 2 read* to get the correct entry. In many of the future labs, you will be expected to look up important information in man pages. Take some time now to look up a few things. Try looking up the man page for "ls" and "signal". When you're finished with an info or man page, just type q to quit.

6.2 Outside Sources

If you are new to Unix or need to review, there's plenty of Linux information available online at the Linux Documentation Project: <http://www.tldp.org>