Supplement to GIS Tutorial for ArcGIS Pro 2.8 Fourth Edition, for users of ArcGIS Pro 3.0

This supplement to *GIS Tutorial for ArcGIS Pro 2.8*, fourth edition, by Wilpen L. Gorr and Kristen S. Kurland (Esri Press, 2021), provides updates for using the book if you are running ArcGIS Pro 3.0. Page numbers are given for the locations of the affected steps.

Tutorial 2-2, page 48. Change label properties

1. **In the Contents pane, click ZoningLandUse.** The Feature Layer contextual tab appears on the **ribbon with the tabs Labeling, and Data highlighted.**

Tutorial 2-4, page 59. Extrude a 3D choropleth map

3. **On the Feature Layer contextual tab, in the Extrusion group, click Type, and click Base Height.**

Tutorial 2-6, page 67. Import symbology and use swipe to compare features

5. **On the Feature Layer tab under Compare, click Swipe, and drag the pointer vertically or horizontally to reveal the layer underneath.**

Tutorial 2-8, page 72. Create fire group layer

8. **On the Feature Layer tab, under Effects, drag the transparency slider from 0 to 100%. Drag the transparency back to 0.**

Tutorial 4-2 , page 119. Delete unneeded columns

1. **In the Contents pane, right-click Tracts, and click Data Design > Fields.**

Tutorial 4-2 , page 121. Examine geocodes in tables to be joined

1. **In the Contents pane, right-click CensusData, click Design, and click Fields.**

Tutorial 4-6 , page 141. Create a central point feature class for polygons

1. **Search for and open the Calculate Geometry Attributes tool.**

2. **For Input Features, select BurglariesByNeighborhood. For Geometry Attributes, in the Field textbox, type** CentralPointXCoordinate **and for Property, select Central point x-coordinate.**

3. **Add another field named,** CentralPointYCoordinate**, and for Property, select Central point y-coordinate. Run the tool.**

4. Open the Burglaries By Neighborhood attribute table. The tool created fields with X and Y central point coordinates in state plane feet.

Tutorial 5-7, page 173. Download 311 data from Data.gov

Steps 1-7. Downloading the data, applying the expression, and importing into the geodatabase is not necessary, the table FoodSafetyComplaints is in the Chapter 5 geodatabase. Begin this section at step 8.

Tutorial 5-8, page 175. Connect to ArcGIS server map service

1. On the Insert tab, in the Project group, click Connections > Server > New ArcGIS Server.

Tutorial 6-3, page 187. Merge features

2. Add all five water layers as input datasets: BronxWater, BrooklynWater, ManhattanWater, QueensWater, and StatenIslandWater. Save the output dataset as NYCWater**. Run the tool.**

Tutorial 6-6, page 199. Calculate acreage

1. Search for and open the Calculate Geometry Attributes tool.

2. For Input Features, select BrooklynNeighborhoodsLandUse_Union. For Geometry Attributes, under Field type POLY_AREA, for Property, select Area. For Area Unit select US Survey Acres. For Coordinate System, select BrooklynLandUse. Run the tool.

Tutorial 7-2, page 223. Your Turn

In the Contents pane, open the StudyArea table, and note the Shape_Length and Shape_Area values, which are in feet. It's useful for campus architects and planners to know the acreage of the campus. This can be automatically calculated for the new StudyArea polygon using the Calculate Geometry Attributes tool covered in chapter 6.

Tutorial 8-1, page 243. Geocode data by zip code

4. In the Geoprocessing pane, complete the tool parameters as follows.

- Input Table: AttendeesPARegion.csv
- Input Address Locator: PARegionZIP_CreateLocator
- Input Address Fields: Single Field
- Single Line Input: ZIPCode

Tutorial 9-1, page 260. Spatially join school buffers to drug violations

2. Type or make the selections as follows, using your original Schools_Buffer.

- Target Features: DrugViolations
- Join Features: Schools_Buffer
- Output Feature Class: DrugViolations_Buffers_Join
- Join Operation: Join One To Many

Tutorial 9-3, page 270. Create multiple-ring service area polygons

2. Click the Service Area Layer context tab > Import Facilities, and for Input Locations, select Pools. Leave Append to Existing Locations unchecked. Check Snap to Network. Run the tool.

Tutorial 9-3, page 272-273. Spatially join service areas and pool tag owners

2. In the Contents pane, right-click Polygons and click Joins and Relates > Add Spatial Join. Make the selection as shown, run the tool, and close it when finished.

3. Open the Polygons attribute table and examine the Join_Count and Name fields to see that there are 374 sampled pool tag holders in the 0 to 1 minute travel-time range from all pools, 512 in the 1 to 2 range, and so on. Export the features, naming the new result Join_Pooltags.

4. In the Join_Pooltags attribute table, click the Options button > Fields View, change the Field Name and Alias of Join_Count to Join_Count_Pooltags, save the changes, and close all tables.

5. In the Contents pane, right-click the Join_Pooltags layer, click Joins and Relates > Add Spatial Join, type or make selections as shown, and run the tool. Note that you can specify the Merge rule for each field in the Output Fields panel as shown in the figure.

- Join Features: PittsburghBlockCentroids
- Fields: Age_5_17
- Merge Rule: Sum

6. Export the result, naming it Join_Pooltags_Blocks.

Tutorial 9-4, page 278. Configure and run the Location-Allocation model

2. Click the Location-Allocation Layer contextual tab.

Tutorial 10-2, page 307. Create a threshold contour layer for locating a service

2. Make the following selections or type as shown. You'll create only one contour, 250, for the threshold defining a target area.

- Input raster: HeartAttackDensity
- Output polyline features: Threshold
- Contour values: 250

Tutorial 10-3, page 317. Configure a kernel density process

2. **Right-click Kernel Density, and rename it** FHHChld Kernel Density**.**

Tutorial 11-1, page 331. Exaggerate and apply a shade and time to a surface

1. **In the Contents pane, under Elevation Surfaces, click Ground, and click the Elevation Surface Layer tab.**

Tutorial 11-2, page 335. Change the TIN's symbology

2. **On the TIN Layer tab, in the Drawing group, click the Symbology down arrow and the Slope button.**

Tutorial 11-2, page 335. Add realistic preset trees using a table of a tree's genus (type)

Steps 1-6. The Add Preset layer gallery has been deprecated in the ArcGIS Pro 3.0 release. You can draw preset layers from ArcGIS Pro 2.9 and earlier versions, but you can no longer create or modify them.

Tutorial 12-4, page 395. Create a dashboard

1. **In the upper right of your screen, click the App Launcher button, and click Dashboards Classic.**

Tutorial 12-4, page 401. Add an action to the Artist Selector

2. **Click the Actions tab, click Add Target, and select Graffiti Data List.**

Tutorial 13-4, page 425. Create a coded value domain

1. **Right-click GraffitiCalls, and click Data Design > Domains.**

Tutorial 13-4, page 428. Apply a coded value domain

1. **In the Contents pane, right-click GraffitiCalls, and click Data Design > Fields.**

Tutorial 13-4, page 430. Set the editing option for a web layer in ArcGIS Online

4. **Scroll down and turn on Enable Editing. Then turn on Keep track of who edited the data (editor name, date and time).**