

# Numerical Methods for Mean Field Games

## *Lecture 4* *Deep Learning Methods: Part I* *MFC and MKV FBSDE*

Mathieu LAURIÈRE

New York University Shanghai

UM6P Vanguard Center, Université Cadi AYYAD,  
University Côte d'Azur, & GE2MI  
Open Doctoral Lectures  
July 5 – 7, 2023

# Outline

---

## 1. Introduction

## 2. Deep Learning for MFC

## 3. Deep Learning for MKV FBSDE

## 4. Two Examples of Extensions

## 5. Conclusion

Numerical methods discussed so far:

- ODE system for LQ setting
- FBPDE system
- FBSDE system

## “Classical” Numerical Methods for MFG: Some references

---

Some methods based on the deterministic approach to MFG/MFC:

- Finite difference & Newton method: [Achdou and Capuzzo-Dolcetta, 2010], [Achdou et al., 2012], ...
- (Semi-)Lagrangian approach: [Carlini and Silva, 2014, Carlini and Silva, 2015], [Carlini and Silva, 2018], [Calzola et al., 2022], ...
- Augmented Lagrangian & ADMM: [Benamou and Carlier, 2015], [Andreev, 2017a], [Achdou and Laurière, 2016], ...
- Primal-dual algo.: [Briceño Arias et al., 2018], [Briceño Arias et al., 2019], ...
- Gradient descent based methods [Laurière and Pironneau, 2016], [Pfeiffer, 2016], [Lavigne and Pfeiffer, 2022], ...
- Monotone operators [Almulla et al., 2017], [Gomes and Saúde, 2018], [Gomes and Yang, 2020], ...
- Policy iteration [Cacace et al., 2021], [Cui and Koeppl, 2021], [Camilli and Tang, 2022], [Tang and Song, 2022], [Laurière et al., 2023], ...
- Finite elements [Benamou and Carlier, 2015], [Andreev, 2017b], ...
- Cubature [de Raynal and Trillos, 2015], ...
- Gaussian processes [Mou et al., 2022], ...
- Kernel-based representation [Liu et al., 2021], ...
- Fourier approximation [Nurbekyan et al., 2019], ...

Some methods based on the probabilistic approach to MFG/MFC:

- Cubature [\[de Raynal and Trillos, 2015\]](#), ...
- Markov chain approximation: [\[Bayraktar et al., 2018\]](#), ...
- Probabilistic approach and Picard: [\[Chassagneux et al., 2019\]](#), [\[Angiuli et al., 2019\]](#), ...
- Probabilistic approach and regression: [\[Balata et al., 2019\]](#), ...
- ...

Many of these methods are very **efficient** and have been **analyzed** in detail

However, they are usually limited to problems with:

- (relatively) **small dimension**
- (relatively) **simple structure**

⇒ motivations to develop **machine learning** methods (see lectures 4, 5, 6)

- In this lecture and the following one, we will use deep learning to solve MFGs
- At a high level, there are two main ingredients:
  - ▶ Approximation using [deep neural networks](#)
  - ▶ Minimization of a loss function using [stochastic gradient descent](#)
- Many variants and refinements, ...
- See e.g. [\[LeCun et al., 2015, Goodfellow et al., 2016\]](#), ...

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- Example: Regression:  $\xi = (x, f(x))$  for some  $f$ ,  $\mathbb{L}(\varphi, \xi) = \|\varphi(x) - f(x)\|^2$



# Ingredient 1: Neural Networks

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- Example: Regression:  $\xi = (x, f(x))$  for some  $f$ ,  $\mathbb{L}(\varphi, \xi) = \|\varphi(x) - f(x)\|^2$
- **Idea:** Instead of min. over all  $\varphi(\cdot)$ , min. over parameters  $\theta$  of  $\varphi_{\theta}(\cdot)$
- Example: **Feedforward fully-connected neural network:**
  - ▶  $\varphi_{\theta}(\cdot)$
  - ▶ with **weights & biases**  $\theta = (\beta^{(k)}, w^{(k)})_{k=1, \dots, \ell}$
  - ▶ activation functions  $\psi^{(i)}$ : sigmoid, tanh, ReLU, ...; applied coordinate-wise

$$\underbrace{\varphi_{\theta}(x)}_{\varphi(\theta, x)} = \psi^{(\ell)} \left( \beta^{(\ell)} + w^{(\ell)} \dots \psi^{(2)} \left( \beta^{(2)} + w^{(2)} \underbrace{\psi^{(1)}(\beta^{(1)} + w^{(1)}x)}_{\text{one hidden layer}} \right) \dots \right)$$

- ▶ Depth = number of layers; width of a layer = dimension of bias vector

## Ingredient 1: Neural Networks – Comments

---

- Many other architectures (convolutional neural networks, recurrent neural networks, ...), see e.g. [\[Leijnen and Veen, 2020\]](#)
- Successes of deep learning in many fields: natural language processing, computer vision, drug design, ... and even games!
- Combination with reinforcement learning (see lecture 6)
- Universal approximation theorems [\[Cybenko, 1989\]](#), [\[Hornik, 1991\]](#), ...
- Connections with numerical analysis, see e.g. [\[Després, 2022\]](#)

**Differentiation:** can compute partial derivatives by automatic differentiation (AD) at every  $(\theta, x)$ :

- With respect to parameters:  $\nabla_{\theta} \varphi(\theta, x)$

$$\nabla_{\beta^{(\ell)}} \varphi(\theta, x) = \dots, \quad \nabla_{w^{(2)}} \varphi(\theta, x) = \dots$$

$\Rightarrow$  can perform gradient descent on these parameters

**Differentiation:** can compute partial derivatives by automatic differentiation (AD) at every  $(\theta, x)$ :

- With respect to parameters:  $\nabla_{\theta} \varphi(\theta, x)$

$$\nabla_{\beta^{(\ell)}} \varphi(\theta, x) = \dots, \quad \nabla_{w^{(2)}} \varphi(\theta, x) = \dots$$

$\Rightarrow$  can perform gradient descent on these parameters

- With respect to state variable:  $\nabla_x \varphi(\theta, x)$  can be computed by AD too

$$\partial_{x_1} \varphi(\theta, x) = \dots$$

$\Rightarrow$  can be used in PDEs (see lecture 5)

## Ingredient 2: Stochastic Gradient Descent

---

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- **Parameterization:**  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\tilde{\mathbb{L}}(\theta, \xi)]$ , where  $\tilde{\mathbb{L}}(\theta, \xi) := \mathbb{L}(\varphi_{\theta}, \xi)$

## Ingredient 2: Stochastic Gradient Descent

---

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- **Parameterization:**  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\tilde{\mathbb{L}}(\theta, \xi)]$ , where  $\tilde{\mathbb{L}}(\theta, \xi) := \mathbb{L}(\varphi_{\theta}, \xi)$
- **Setting:** the distribution of  $\xi$  is unknown so we cannot compute  $\mathbb{E}_{\xi}$ , but
  - ▶ we have some samples (i.e. random realizations) of  $\xi$
  - ▶ we know  $\mathbb{L}$

## Ingredient 2: Stochastic Gradient Descent

---

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- **Parameterization:**  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\tilde{\mathbb{L}}(\theta, \xi)]$ , where  $\tilde{\mathbb{L}}(\theta, \xi) := \mathbb{L}(\varphi_{\theta}, \xi)$
- **Setting:** the distribution of  $\xi$  is unknown so we cannot compute  $\mathbb{E}_{\xi}$ , but
  - ▶ we have some samples (i.e. random realizations) of  $\xi$
  - ▶ we know  $\mathbb{L}$
- Example: Regression:  $\xi = (x, f(x))$ ,  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\|\varphi_{\theta}(x) - f(x)\|^2]$

## Ingredient 2: Stochastic Gradient Descent

- **Goal:** Minimize over  $\varphi(\cdot)$ ,  $\mathbb{J}(\varphi) := \mathbb{E}_{\xi}[\mathbb{L}(\varphi, \xi)]$
- **Parameterization:**  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\tilde{\mathbb{L}}(\theta, \xi)]$ , where  $\tilde{\mathbb{L}}(\theta, \xi) := \mathbb{L}(\varphi_{\theta}, \xi)$
- **Setting:** the distribution of  $\xi$  is unknown so we cannot compute  $\mathbb{E}_{\xi}$ , but
  - ▶ we have some samples (i.e. random realizations) of  $\xi$
  - ▶ we know  $\mathbb{L}$
- Example: Regression:  $\xi = (x, f(x))$ ,  $\tilde{\mathbb{J}}(\theta) := \mathbb{E}_{\xi}[\|\varphi_{\theta}(x) - f(x)\|^2]$

---

### Algorithm: Stochastic Gradient Descent

---

**Input:** Initial param.  $\theta_0$ ; data  $S = (\xi_s)_{s=1, \dots, |S|}$ ; nb of steps  $K$ ; learning rates  $(\eta^{(k)})_k$

**Output:** Parameter  $\theta^*$  s.t.  $\varphi_{\theta^*}$  (approximately) minimizes  $\tilde{\mathbb{J}}$

- 1 Initialize  $\theta^{(0)} = \theta_0$
  - 2 **for**  $k = 0, 1, 2, \dots, K - 1$  **do**
  - 3     Pick  $s \in S$  randomly
  - 4     Compute the gradient  $\nabla_{\theta} \tilde{\mathbb{L}}(\theta^{(k-1)}, \xi_s) = \frac{d}{d\theta} \mathbb{L}(\varphi_{\theta^{(k-1)}}, \xi_s)$
  - 5     Set  $\theta^{(k)} = \theta^{(k-1)} - \eta^{(k)} \nabla_{\theta} \tilde{\mathbb{L}}(\theta^{(k-1)}, \xi_s)$
  - 6 **return**  $\theta^{(K)}$
-



## Ingredient 2: Stochastic Gradient Descent – Comments

---

- Many variants:
  - ▶ Learning rate: `ADAM` (Adaptive Moment Estimation) [\[Kingma and Ba, 2014\]](#), ...
  - ▶ Samples: Mini-batches, ...
- Proofs of convergence e.g. using stochastic approximation [\[Robbins and Monro, 1951\]](#), [\[Borkar, 2009\]](#)
- In practice: many details to be discussed, see e.g. [\[Bottou, 2012\]](#); choice of hyperparameters
  - ▶ architecture
  - ▶ initialization
  - ▶ learning rate
  - ▶ loss function
  - ▶ ...

- Consider the task: minimize over  $\varphi$  the **population risk**:

$$\mathcal{R}(\varphi) = \mathbb{E}_{x,y}[L(\varphi(x), y)]$$

with  $x \sim \mu$  and  $y = f(x) + \epsilon$  for some noise  $\epsilon$  where  $f$  is unknown

- Consider the task: minimize over  $\varphi$  the **population risk**:

$$\mathcal{R}(\varphi) = \mathbb{E}_{x,y}[L(\varphi(x), y)]$$

with  $x \sim \mu$  and  $y = f(x) + \epsilon$  for some noise  $\epsilon$  where  $f$  is unknown

- In practice:
  - ▶ minimize over a **hypothesis class**  $\mathcal{F}$  of  $\varphi$
  - ▶ finite number of samples,  $S = (x_m, y_m)_{m=1,\dots,M}$ : **empirical risk**:

$$\hat{\mathcal{R}}_S(\varphi) = \frac{1}{M} \sum_{m=1}^M L(\varphi(x_m), y_m) \quad (+ \text{ regu})$$

- ▶ finite number of **optimization steps**, say  $k$

We are interested in:

- **Approximation error:** Letting  $\varphi^* = \operatorname{argmin}_{\varphi \in \mathcal{F}} \operatorname{dist}(\varphi, f)$ ,

$$\epsilon_{\text{approx}} = \operatorname{dist}(\varphi^*, f)$$

- **Estimation error:** Letting  $\hat{\varphi}_S = \operatorname{argmin}_{\varphi \in \mathcal{F}} \hat{\mathcal{R}}_S(\varphi)$

$$\epsilon_{\text{estim}} = \operatorname{dist}(\hat{\varphi}_S, \varphi^*)$$

- **Optimization error:** After  $k$  steps, we get  $\varphi_S^{(k)}$ ;

$$\epsilon_{\text{optim}} = \operatorname{dist}(\varphi_S^{(k)}, \hat{\varphi}_S)$$

We are interested in:

- **Approximation error:** Letting  $\varphi^* = \operatorname{argmin}_{\varphi \in \mathcal{F}} \operatorname{dist}(\varphi, f)$ ,

$$\epsilon_{\text{approx}} = \operatorname{dist}(\varphi^*, f)$$

- **Estimation error:** Letting  $\hat{\varphi}_S = \operatorname{argmin}_{\varphi \in \mathcal{F}} \hat{\mathcal{R}}_S(\varphi)$

$$\epsilon_{\text{estim}} = \operatorname{dist}(\hat{\varphi}_S, \varphi^*)$$

- **Optimization error:** After  $k$  steps, we get  $\varphi_S^{(k)}$ ;

$$\epsilon_{\text{optim}} = \operatorname{dist}(\varphi_S^{(k)}, \hat{\varphi}_S)$$

- **Generalization error** of the learnt  $\varphi_S^{(k)}$ :

$$\epsilon_{\text{gene}} = \epsilon_{\text{approx}} + \epsilon_{\text{estim}} + \epsilon_{\text{optim}}$$

## 1. Introduction

## 2. Deep Learning for MFC

- Deep learning for stochastic optimal control
- Adaptation to MFC

## 3. Deep Learning for MKV FBSDE

## 4. Two Examples of Extensions

## 5. Conclusion

## 1. Introduction

## 2. Deep Learning for MFC

- Deep learning for stochastic optimal control
- Adaptation to MFC

## 3. Deep Learning for MKV FBSDE

## 4. Two Examples of Extensions

## 5. Conclusion

- An optimal control is a “temporally extended” optimization problem
- Numerically, we cannot minimize over all possible controls
- We can parameterize the control function
- and then optimize over the parameters
- See e.g. [\[Gobet and Munos, 2005\]](#), [\[Han and E, 2016\]](#), ...



## Stochastic optimal control problem:

Minimize over  $\alpha(\cdot, \cdot)$

$$J(\alpha(\cdot, \cdot)) = \mathbb{E} \left[ \int_0^T f(X_t, \alpha(t, X_t)) dt + g(X_T) \right],$$

with

$$X_0 \sim m_0, \quad dX_t = b(X_t, \alpha(t, X_t)) dt + \sigma dW_t$$

**Stochastic optimal control problem:** (1) neural network  $\varphi_\theta$ ,

Minimize over **neural network** parameters  $\theta$

$$J(\theta) = \mathbb{E} \left[ \int_0^T f(X_t, \varphi_\theta(t, X_t)) dt + g(X_T) \right],$$

with

$$X_0 \sim m_0, \quad dX_t = b(X_t, \varphi_\theta(t, X_t)) dt + \sigma dW_t$$

**Stochastic optimal control problem:** (1) neural network  $\varphi_\theta$ , (2) time discretization

Minimize over **neural network** parameters  $\theta$  and  $N_T$  time steps

$$J^{N_T}(\theta) = \mathbb{E} \left[ \sum_{n=0}^{N_T-1} f(X_n, \varphi_\theta(t_n, X_n)) \Delta t + g(X_{N_T}) \right],$$

with

$$X_0 \sim m_0, \quad X_{n+1} - X_n = b(X_n, \varphi_\theta(t_n, X_n)) \Delta t + \sigma \Delta W_n$$

**Stochastic optimal control problem:** (1) neural network  $\varphi_\theta$ , (2) time discretization

Minimize over **neural network** parameters  $\theta$  and  $N_T$  time steps

$$J^{N_T}(\theta) = \mathbb{E} \left[ \sum_{n=0}^{N_T-1} f(X_n, \varphi_\theta(t_n, X_n)) \Delta t + g(X_{N_T}) \right],$$

with

$$X_0 \sim m_0, \quad X_{n+1} - X_n = b(X_n, \varphi_\theta(t_n, X_n)) \Delta t + \sigma \Delta W_n$$

→ neural network induces an approximation error

→ time discretization induce extra errors

**Stochastic optimal control problem:** (1) neural network  $\varphi_\theta$ , (2) time discretization

Minimize over **neural network** parameters  $\theta$  and  $N_T$  time steps

$$J^{N_T}(\theta) = \mathbb{E} \left[ \sum_{n=0}^{N_T-1} f(X_n, \varphi_\theta(t_n, X_n)) \Delta t + g(X_{N_T}) \right],$$

with

$$X_0 \sim m_0, \quad X_{n+1} - X_n = b(X_n, \varphi_\theta(t_n, X_n)) \Delta t + \sigma \Delta W_n$$

→ neural network induces an approximation error

→ time discretization induce extra errors

To implement SGD, at each iteration we pick a sample  $\xi = (X_0, \Delta W_0, \dots, \Delta W_{N_T-1})$

## 1. Introduction

## 2. Deep Learning for MFC

- Deep learning for stochastic optimal control
- **Adaptation to MFC**

## 3. Deep Learning for MKV FBSDE

## 4. Two Examples of Extensions

## 5. Conclusion

## MFC problem:

Minimize over  $\alpha(\cdot, \cdot)$

$$J(\alpha(\cdot, \cdot)) = \mathbb{E} \left[ \int_0^T f(X_t, \mu_t, \alpha(t, X_t)) dt + g(X_T, \mu_T) \right],$$

where  $\mu_t = \mathcal{L}(X_t)$  with

$$X_0 \sim m_0, \quad dX_t = b(X_t, \mu_t, \alpha(t, X_t)) dt + \sigma dW_t$$

**MFC problem:** (1) Finite pop.,

Minimize over **decentralized** controls  $\alpha(\cdot, \cdot)$  with  $N$  agents

$$J^N(\alpha(\cdot, \cdot)) = \mathbb{E} \left[ \frac{1}{N} \sum_{i=1}^N \int_0^T f(X_t^i, \mu_t^N, \alpha(t, X_t^i)) dt + g(X_T^i, \mu_T^N) \right],$$

where  $\mu_t^N = \frac{1}{N} \sum_{j=1}^N \delta_{X_t^j}$ , with

$$X_0^j \sim m_0, \quad dX_t^j = b(X_t^j, \mu_t^N, \alpha(t, X_t^j)) dt + \sigma dW_t^j$$



# MFC: Approximate Problem

---

**MFC problem:** (1) Finite pop., (2) neural network  $\varphi_\theta$ ,

Minimize over **neural network** parameters  $\theta$  with  $N$  agents

$$J^N(\theta) = \mathbb{E} \left[ \frac{1}{N} \sum_{i=1}^N \int_0^T f(X_t^i, \mu_t^N, \varphi_\theta(t, X_t^i)) dt + g(X_T^i, \mu_T^N) \right],$$

where  $\mu_t^N = \frac{1}{N} \sum_{j=1}^N \delta_{X_t^j}$ , with

$$X_0^j \sim m_0, \quad dX_t^j = b(X_t^j, \mu_t^N, \varphi_\theta(t, X_t^j)) dt + \sigma dW_t^j$$

# MFC: Approximate Problem

---

**MFC problem:** (1) Finite pop., (2) neural network  $\varphi_\theta$ , (3) time discretization

Minimize over **neural network** parameters  $\theta$  with  $N$  agents and  $N_T$  time steps

$$J^{N, N_T}(\theta) = \mathbb{E} \left[ \frac{1}{N} \sum_{i=1}^N \sum_{n=0}^{N_T-1} f(X_n^i, \mu_n^N, \varphi_\theta(t_n, X_n^i)) \Delta t + g(X_{N_T}^i, \mu_{N_T}^N) \right],$$

where  $\mu_n^N = \frac{1}{N} \sum_{j=1}^N \delta_{X_n^j}$ , with

$$X_0^j \sim m_0, \quad X_{n+1}^j - X_n^j = b(X_n^j, \mu_n^N, \varphi_\theta(t_n, X_n^j)) \Delta t + \sigma \Delta W_n^j$$

# MFC: Approximate Problem

---

**MFC problem:** (1) Finite pop., (2) neural network  $\varphi_\theta$ , (3) time discretization

Minimize over **neural network** parameters  $\theta$  with  $N$  agents and  $N_T$  time steps

$$J^{N, N_T}(\theta) = \mathbb{E} \left[ \frac{1}{N} \sum_{i=1}^N \sum_{n=0}^{N_T-1} f(X_n^i, \mu_n^N, \varphi_\theta(t_n, X_n^i)) \Delta t + g(X_{N_T}^i, \mu_{N_T}^N) \right],$$

where  $\mu_n^N = \frac{1}{N} \sum_{j=1}^N \delta_{X_n^j}$ , with

$$X_0^j \sim m_0, \quad X_{n+1}^j - X_n^j = b(X_n^j, \mu_n^N, \varphi_\theta(t_n, X_n^j)) \Delta t + \sigma \Delta W_n^j$$

→ neural network induces an approximation error

→ finite population and time discretization induce extra errors

**MFC problem:** (1) Finite pop., (2) neural network  $\varphi_\theta$ , (3) time discretization

Minimize over **neural network** parameters  $\theta$  with  $N$  agents and  $N_T$  time steps

$$J^{N, N_T}(\theta) = \mathbb{E} \left[ \frac{1}{N} \sum_{i=1}^N \sum_{n=0}^{N_T-1} f(X_n^i, \mu_n^N, \varphi_\theta(t_n, X_n^i)) \Delta t + g(X_{N_T}^i, \mu_{N_T}^N) \right],$$

where  $\mu_n^N = \frac{1}{N} \sum_{j=1}^N \delta_{X_n^j}$ , with

$$X_0^j \sim m_0, \quad X_{n+1}^j - X_n^j = b(X_n^j, \mu_n^N, \varphi_\theta(t_n, X_n^j)) \Delta t + \sigma \Delta W_n^j$$

→ neural network induces an approximation error

→ finite population and time discretization induce extra errors

Note: we aim for a decentralized control, whereas for a general  $N$ -agent control problem, the optimal control is not always of this type

- The following kind of convergence result (bound on the **approximation error**) can be proved, see [\[Carmona and Laurière, 2022\]](#):

## Approximation theorem

Under suitable assumptions (in particular regularity of the value function),

$$\left| \inf_{\alpha(\cdot, \cdot)} J(\alpha(\cdot, \cdot)) - \inf_{\theta \in \Theta} J^{N, N_T}(\theta) \right| \leq \epsilon_1(N) + \epsilon_2(\dim(\theta)) + \epsilon_3(N_T)$$

- The following kind of convergence result (bound on the **approximation error**) can be proved, see [Carmona and Laurière, 2022]:

## Approximation theorem

Under suitable assumptions (in particular regularity of the value function),

$$\left| \inf_{\alpha(\cdot, \cdot)} J(\alpha(\cdot, \cdot)) - \inf_{\theta \in \Theta} J^{N, N_T}(\theta) \right| \leq \epsilon_1(N) + \epsilon_2(\dim(\theta)) + \epsilon_3(N_T)$$

- The **estimation error** for shallow neural networks can be analyzed using techniques similar to [Carmona and Laurière, 2021]

- The following kind of convergence result (bound on the **approximation error**) can be proved, see [Carmona and Laurière, 2022]:

## Approximation theorem

Under suitable assumptions (in particular regularity of the value function),

$$\left| \inf_{\alpha(\cdot, \cdot)} J(\alpha(\cdot, \cdot)) - \inf_{\theta \in \Theta} J^{N, N_T}(\theta) \right| \leq \epsilon_1(N) + \epsilon_2(\dim(\theta)) + \epsilon_3(N_T)$$

- The **estimation error** for shallow neural networks can be analyzed using techniques similar to [Carmona and Laurière, 2021]
- The **optimization error** remains to be studied

- The following kind of convergence result (bound on the **approximation error**) can be proved, see [\[Carmona and Laurière, 2022\]](#):

## Approximation theorem

Under suitable assumptions (in particular regularity of the value function),

$$\left| \inf_{\alpha(\cdot, \cdot)} J(\alpha(\cdot, \cdot)) - \inf_{\theta \in \Theta} J^{N, N_T}(\theta) \right| \leq \epsilon_1(N) + \epsilon_2(\dim(\theta)) + \epsilon_3(N_T)$$

- The **estimation error** for shallow neural networks can be analyzed using techniques similar to [\[Carmona and Laurière, 2021\]](#)
- The **optimization error** remains to be studied
- Many extensions and refinements to be investigated



# Approximation Error Analysis: Main Ingredients of the Proof

## Proposition 1 ( $N$ agents & decentralized controls):

Under suitable assumptions, there exists a decentralized control  $\alpha^*$  s.t. ( $d = \text{dimension of } X_t$ )

$$\left| \inf_{\alpha(\cdot)} J(\alpha(\cdot)) - J^N(\alpha^*(\cdot)) \right| \leq \epsilon_1(N) \in \tilde{O}(N^{-1/d}).$$

**Proof:** propagation of chaos type argument [Carmona and Delarue, 2018]

# Approximation Error Analysis: Main Ingredients of the Proof

## Proposition 1 ( $N$ agents & decentralized controls):

Under suitable assumptions, there exists a decentralized control  $\alpha^*$  s.t. ( $d = \text{dimension of } X_t$ )

$$\left| \inf_{\alpha(\cdot)} J(\alpha(\cdot)) - J^N(\alpha^*(\cdot)) \right| \leq \epsilon_1(N) \in \tilde{O}(N^{-1/d}).$$

**Proof: propagation of chaos** type argument [Carmona and Delarue, 2018]

## Proposition 2 (approximation by neural networks): Under suitable assumptions

There exists a set of parameters  $\theta \in \Theta$  for a one-hidden layer  $\hat{\varphi}_\theta$  s.t.

$$\left| J^N(\alpha^*(\cdot)) - J^N(\hat{\varphi}_\theta(\cdot)) \right| \leq \epsilon_2(\dim(\theta)) \in O\left(\dim(\theta)^{-\frac{1}{3(d+1)}}\right).$$

**Proof: Key difficulty:** approximate  $v^*(\cdot)$  by  $\hat{\varphi}_\theta(\cdot)$  while controlling  $\|\nabla \hat{\varphi}_\theta(\cdot)\|$  by  $\|\nabla v^*(\cdot)\|$

→ universal approximation without rate of convergence is not enough

→ approximation rate for the derivative too, e.g. from [Mhaskar and Micchelli, 1995]

# Approximation Error Analysis: Main Ingredients of the Proof

## Proposition 1 ( $N$ agents & decentralized controls):

Under suitable assumptions, there exists a decentralized control  $\alpha^*$  s.t. ( $d = \text{dimension of } X_t$ )

$$\left| \inf_{\alpha(\cdot)} J(\alpha(\cdot)) - J^N(\alpha^*(\cdot)) \right| \leq \epsilon_1(N) \in \tilde{O}(N^{-1/d}).$$

**Proof:** propagation of chaos type argument [Carmona and Delarue, 2018]

## Proposition 2 (approximation by neural networks): Under suitable assumptions

There exists a set of parameters  $\theta \in \Theta$  for a one-hidden layer  $\hat{\varphi}_\theta$  s.t.

$$\left| J^N(\alpha^*(\cdot)) - J^N(\hat{\varphi}_\theta(\cdot)) \right| \leq \epsilon_2(\text{dim}(\theta)) \in O\left(\text{dim}(\theta)^{-\frac{1}{3(d+1)}}\right).$$

**Proof: Key difficulty:** approximate  $v^*(\cdot)$  by  $\hat{\varphi}_\theta(\cdot)$  while controlling  $\|\nabla \hat{\varphi}_\theta(\cdot)\|$  by  $\|\nabla v^*(\cdot)\|$   
→ universal approximation without rate of convergence is not enough  
→ approximation rate for the derivative too, e.g. from [Mhaskar and Micchelli, 1995]

## Proposition 3 (Euler-Maruyama scheme):

For a specific neural network  $\hat{\varphi}_\theta(\cdot)$ ,

$$\left| J^N(\hat{\varphi}_\theta(\cdot)) - J^{N, N_T}(\hat{\varphi}_\theta(\cdot)) \right| \leq \epsilon_3(N_T) \in O\left(N_T^{-1/2}\right).$$

**Key point:**  $O(\cdot)$  independent of  $N$  and  $\text{dim}(\theta)$

**Proof:** analysis of **strong error rate** for Euler scheme (reminiscent of [Bossy and Talay, 1997])

- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N, N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**

- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N, N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**


- Structure:

- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N, N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**

- Structure:




- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N,N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**

- Structure:




## Implementation

- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N,N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**

- Structure:






- Key idea: replace optimal control problem by (finite dim.) optimization problem:

- ▶ Loss function = cost:  $J^{N, N_T}(\theta) = \mathbb{E}[\mathbb{L}(\varphi_\theta, \xi)]$
- ▶ One sample:  $\xi = (X_0^j, (\Delta W_n^j)_{n=0, \dots, N_T-1})_{j=1, \dots, N}$

→ can use **Stochastic Gradient Descent**

- Structure:




# Numerical Illustration 1: LQ MFC

**Benchmark** to assess **empirical convergence of SGD**: LQ problem with explicit sol.


**Example:** Linear dynamics, quadratic costs of the type

$$f(x, \mu, v) = \underbrace{(\bar{\mu} - x)^2}_{\text{distance to mean position}} + \underbrace{v^2}_{\text{cost of moving}}, \quad \bar{\mu} = \underbrace{\int \mu(\xi) d\xi}_{\text{mean position}}, \quad g(x) = x^2$$

Numerical example with  $d = 10$  (see [\[Carmona and Laurière, 2022\]](#)):



total cost (= loss function)



$L^2$ -error on the control

## Numerical Illustration 2: min-LQ MFC with common noise

The following model is inspired by [Salhab et al., 2015] and [Achdou and Lasry, 2019].

### MFC with simple CN:

Dynamics:  $dX_t = \phi_t(X_t, \epsilon_t^0)dt + \sigma dW_t$ ,  $\epsilon_t^0 = 0$  until  $t = T/2$ , and then  $\xi_1$  or  $\xi_2$  w.p.  $1/2$

Running cost  $|\phi_t(X_t, \epsilon_t^0)|^2$ , final cost  $(X_T - \epsilon_T^0)^2 + \bar{Q}_T(\bar{m}_T - X_T)^2$

Parameter values:  $\sigma = 0.1$ ,  $T = 1$ ,  $\xi_1 = -1.5$ ,  $\xi_2 = +1.5$

Numerical results:

- **neural network**  $\varphi_\theta(t, X_t, \epsilon_t^0)$ , taking as an input the **common noise**
- benchmark solution computed by solving a **system of 6 PDEs** (see [Achdou and Lasry, 2019])

## Numerical Illustration 2: min-LQ MFC with common noise


---

Here the common noise takes one among two values, at time  $T/2$ .

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .




$t = 0$

Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .




$t = 0.1$

Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .




$t = 0.2$

Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 0.3$


Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)



## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .




$t = 0.4$

Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .




$t = 0.5$

Until  $T/2$ : concentrate around mid-point = 0

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 0.6$


Until  $T/2$ : concentrate around mid-point = 0

After  $T/2$ : move towards the target selected by common noise

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 0.7$


Until  $T/2$ : concentrate around mid-point = 0

After  $T/2$ : move towards the target selected by **common noise**

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 0.8$


Until  $T/2$ : concentrate around mid-point = 0

After  $T/2$ : move towards the target selected by common noise

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 0.9$


Until  $T/2$ : concentrate around mid-point = 0

After  $T/2$ : move towards the target selected by **common noise**

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 2: min-LQ MFC with common noise

Here the common noise takes one among two values, at time  $T/2$ .



$t = 1$

Until  $T/2$ : concentrate around mid-point = 0

After  $T/2$ : move towards the target selected by common noise

More details in [\[Carmona and Laurière, 2022\]](#)

## Numerical Illustration 3: MFC with Interactions Through the Controls

---

**Price Impact Model** [Carmona and Lacker, 2015, Carmona and Delarue, 2018]:

- Price process: with  $\nu^\alpha =$  population's distribution over actions,

$$dS_t^\alpha = \gamma \int_{\mathbb{R}} a d\nu_t^\alpha(a) dt + \sigma_0 dW_t^0$$

- Typical agent's inventory:  $dX_t^\alpha = \alpha_t dt + \sigma dW_t$
- Typical agent's wealth:  $dK_t^\alpha = -(\alpha_t S_t^\alpha + c_\alpha(\alpha_t)) dt$
- Typical agent's portfolio value:  $V_t^\alpha = K_t^\alpha + X_t^\alpha S_t^\alpha$



## Numerical Illustration 3: MFC with Interactions Through the Controls

**Price Impact Model** [Carmona and Lacker, 2015, Carmona and Delarue, 2018]:

- Price process: with  $\nu^\alpha =$  population's distribution over actions,

$$dS_t^\alpha = \gamma \int_{\mathbb{R}} a d\nu_t^\alpha(a) dt + \sigma_0 dW_t^0$$

- Typical agent's inventory:  $dX_t^\alpha = \alpha_t dt + \sigma dW_t$
- Typical agent's wealth:  $dK_t^\alpha = -(\alpha_t S_t^\alpha + c_\alpha(\alpha_t)) dt$
- Typical agent's portfolio value:  $V_t^\alpha = K_t^\alpha + X_t^\alpha S_t^\alpha$

**Objective:** minimize

$$J(\alpha) = \mathbb{E} \left[ \int_0^T c_X(X_t^\alpha) dt + g(X_T^\alpha) - V_T^\alpha \right]$$

## Numerical Illustration 3: MFC with Interactions Through the Controls

**Price Impact Model** [Carmona and Lacker, 2015, Carmona and Delarue, 2018]:

- Price process: with  $\nu^\alpha =$  population's distribution over actions,

$$dS_t^\alpha = \gamma \int_{\mathbb{R}} a d\nu_t^\alpha(a) dt + \sigma_0 dW_t^0$$

- Typical agent's inventory:  $dX_t^\alpha = \alpha_t dt + \sigma dW_t$
- Typical agent's wealth:  $dK_t^\alpha = -(\alpha_t S_t^\alpha + c_\alpha(\alpha_t)) dt$
- Typical agent's portfolio value:  $V_t^\alpha = K_t^\alpha + X_t^\alpha S_t^\alpha$

**Objective:** minimize

$$J(\alpha) = \mathbb{E} \left[ \int_0^T c_X(X_t^\alpha) dt + g(X_T^\alpha) - V_T^\alpha \right]$$

Equivalent problem:

$$J(\alpha) = \mathbb{E} \left[ \int_0^T \left( c_\alpha(\alpha_t) + c_X(X_t^\alpha) - \gamma X_t^\alpha \int_{\mathbb{R}} a d\nu_t^\alpha(a) \right) dt + g(X_T^\alpha) \right]$$

## Numerical Illustration 3: MFC with Interactions Through the Controls

**Price Impact Model** [Carmona and Lacker, 2015, Carmona and Delarue, 2018]:

- Price process: with  $\nu^\alpha =$  population's distribution over actions,

$$dS_t^\alpha = \gamma \int_{\mathbb{R}} a d\nu_t^\alpha(a) dt + \sigma_0 dW_t^0$$

- Typical agent's inventory:  $dX_t^\alpha = \alpha_t dt + \sigma dW_t$
- Typical agent's wealth:  $dK_t^\alpha = -(\alpha_t S_t^\alpha + c_\alpha(\alpha_t)) dt$
- Typical agent's portfolio value:  $V_t^\alpha = K_t^\alpha + X_t^\alpha S_t^\alpha$

**Objective:** minimize

$$J(\alpha) = \mathbb{E} \left[ \int_0^T c_X(X_t^\alpha) dt + g(X_T^\alpha) - V_T^\alpha \right]$$



Equivalent problem:

$$J(\alpha) = \mathbb{E} \left[ \int_0^T \left( c_\alpha(\alpha_t) + c_X(X_t^\alpha) - \gamma X_t^\alpha \int_{\mathbb{R}} a d\nu_t^\alpha(a) \right) dt + g(X_T^\alpha) \right]$$

We take:  $c_\alpha(v) = \frac{1}{2} c_\alpha v^2$ ,  $c_X(x) = \frac{1}{2} c_X x^2$  and  $g(x) = \frac{1}{2} c_g x^2$

## Numerical Illustration 3: MFC with Interactions Through the Controls

Control learnt (left) and associated state distribution (right)





$$T = 1, c_X = 2, c_\alpha = 1, c_g = 0.3, \sigma = 0.5, \gamma = 0.2$$

See Section 2 in [\[Carmona and Laurière, 2023\]](#) for more details.

## Numerical Illustration 3: MFC with Interactions Through the Controls

Control learnt (left) and associated state distribution (right)



$$T = 1, c_X = 2, c_\alpha = 1, c_g = 0.3, \sigma = 0.5, \gamma = 1$$

See Section 2 in [\[Carmona and Laurière, 2023\]](#) for more details.

### Code

Sample code to illustrate: [IPython notebook](#)

<https://colab.research.google.com/drive/1QYWz4Sclw9goRZsbd0uB6wR6a0Uu0a3k?usp=sharing>

- Deep learning for MFC using a direct approach where the control is parameterized as a neural network
- Applied to the price impact model discussed above

- DL for stochastic control [[Gobet and Munos, 2005](#)], [[Han and E, 2016](#)], ...
- Various possible implementations; example: 1 NN per time step instead of a single 1 NN as a function of time
- Extensions to finite-player games [[Hu, 2021](#)]
- Extension to MFC presented here [[Carmona and Laurière, 2022](#)]; see also [[Carmona and Laurière, 2023](#)]
- Related works with mean field: [[Fouque and Zhang, 2020](#)] (MFC with delay), [[Germain et al., 2019](#)], [[Agram et al., 2020](#)], [[Dayanikli et al., 2023](#)] (with population-dependent controls), ...

# Outline

---

1. Introduction

2. Deep Learning for MFC

3. Deep Learning for MKV FBSDE

4. Two Examples of Extensions

5. Conclusion



- Goal: solve an FBSDE system
- The backward process has a value  $Y_0$  at time 0, but it is not known
- Try to guess the correct initial condition so that the terminal condition is satisfied
- This yields a new optimal control problem
- See e.g. [\[Kohlmann and Zhou, 2000\]](#), [\[Sannikov, 2008\]](#), ...
- For the new optimal control problem, use deep learning [\[E et al., 2017\]](#)

Solutions of sto. control problems can be characterized by **FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T) & \rightarrow \text{control/cost} \end{cases}$$

(stemming from sto. Pontryagin's or Bellman's principle:  $F = f$  or  $F = \partial_x H$ )

Solutions of sto. control problems can be characterized by **FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T) & \rightarrow \text{control/cost} \end{cases}$$

(stemming from sto. Pontryagin's or Bellman's principle:  $F = f$  or  $F = \partial_x H$ )

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

Solutions of sto. control problems can be characterized by **FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T) & \rightarrow \text{control/cost} \end{cases}$$

(stemming from sto. Pontryagin's or Bellman's principle:  $F = f$  or  $F = \partial_x H$ )

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation** as a new **optimal control problem**

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}})\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, Y_t)dt + \mathbf{z}(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

Solutions of sto. control problems can be characterized by **FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T) & \rightarrow \text{control/cost} \end{cases}$$

(stemming from sto. Pontryagin's or Bellman's principle:  $F = f$  or  $F = \partial_x H$ )

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

→ recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation as a new optimal control problem**

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}})\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, Y_t)dt + \mathbf{z}(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

→ **New optimal control problem:** apply previous method, replacing  $y_0(\cdot), \mathbf{z}(\cdot, \cdot)$  by NN

Solutions of sto. control problems can be characterized by **FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T) & \rightarrow \text{control/cost} \end{cases}$$

(stemming from sto. Pontryagin's or Bellman's principle:  $F = f$  or  $F = \partial_x H$ )

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation as a new optimal control problem**

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}})\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, Y_t)dt + \mathbf{z}(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

$\rightarrow$  **New optimal control problem:** apply previous method, replacing  $y_0(\cdot), \mathbf{z}(\cdot, \cdot)$  by NN

Note: This problem is *not* the original stochastic control problem !

## Application to Solve PDEs

---

This method can be used to solve PDEs [\[E et al., 2017\]](#)

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

This method can be used to solve PDEs [E et al., 2017]

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

- $u$  solves the PDE

$$\begin{cases} u(T, x) = G(x) \\ \frac{\partial u}{\partial t}(t, x) + B(t, x) \frac{\partial u}{\partial x}(t, x) + \frac{1}{2} \sigma^2 \frac{\partial^2 u}{\partial x^2}(t, x) + F(t, x) = 0 \end{cases}$$

- $X$  solves the SDE:

$$dX_t = B(t, x)dt + \sigma dW_t$$

- $(Y, Z)$  solves the BSDE:

$$\begin{cases} Y_T = G(X_T) \\ dY_t = -F(t, X_t)dt + Z_t dW_t \end{cases}$$



This method can be used to solve PDEs [E et al., 2017]

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

- $u$  solves the PDE

$$\begin{cases} u(T, x) = G(x) \\ \frac{\partial u}{\partial t}(t, x) + B(t, x) \frac{\partial u}{\partial x}(t, x) + \frac{1}{2} \sigma^2 \frac{\partial^2 u}{\partial x^2}(t, x) + F(t, x) = 0 \end{cases}$$

- $X$  solves the SDE:

$$dX_t = B(t, x)dt + \sigma dW_t$$

- $(Y, Z)$  solves the BSDE:

$$\begin{cases} Y_T = G(X_T) \\ dY_t = -F(t, X_t)dt + Z_t dW_t \end{cases}$$

- In fact  $Z_t = \sigma \partial_x u(t, X_t)$

This method can be used to solve PDEs [E et al., 2017]

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

- $u$  solves the PDE

$$\begin{cases} u(T, x) = G(x) \\ \frac{\partial u}{\partial t}(t, x) + B(t, x) \frac{\partial u}{\partial x}(t, x) + \frac{1}{2} \sigma^2 \frac{\partial^2 u}{\partial x^2}(t, x) + F(t, x) = 0 \end{cases}$$

- $X$  solves the SDE:

$$dX_t = B(t, x)dt + \sigma dW_t$$

- $(Y, Z)$  solves the BSDE:

$$\begin{cases} Y_T = G(X_T) \\ dY_t = -F(t, X_t)dt + Z_t dW_t \end{cases}$$

- In fact  $Z_t = \sigma \partial_x u(t, X_t)$
- Connection also works with  $dX_t = dW_t$  and a different  $Y_t \dots$

This method can be used to solve PDEs [E et al., 2017]

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

- $u$  solves the PDE

$$\begin{cases} u(T, x) = G(x) \\ \frac{\partial u}{\partial t}(t, x) + B(t, x) \frac{\partial u}{\partial x}(t, x) + \frac{1}{2} \sigma^2 \frac{\partial^2 u}{\partial x^2}(t, x) + F(t, x) = 0 \end{cases}$$

- $X$  solves the SDE:

$$dX_t = B(t, x)dt + \sigma dW_t$$

- $(Y, Z)$  solves the BSDE:

$$\begin{cases} Y_T = G(X_T) \\ dY_t = -F(t, X_t)dt + Z_t dW_t \end{cases}$$

- In fact  $Z_t = \sigma \partial_x u(t, X_t)$
- Connection also works with  $dX_t = dW_t$  and a different  $Y_t \dots$
- Application: solve a PDE by solving the corresponding (F)BSDE

This method can be used to solve PDEs [E et al., 2017]

**Feynman-Kac formula:** correspondence  $u(t, X_t) = Y_t$  where

- $u$  solves the PDE

$$\begin{cases} u(T, x) = G(x) \\ \frac{\partial u}{\partial t}(t, x) + B(t, x) \frac{\partial u}{\partial x}(t, x) + \frac{1}{2} \sigma^2 \frac{\partial^2 u}{\partial x^2}(t, x) + F(t, x) = 0 \end{cases}$$

- $X$  solves the SDE:

$$dX_t = B(t, x)dt + \sigma dW_t$$

- $(Y, Z)$  solves the BSDE:

$$\begin{cases} Y_T = G(X_T) \\ dY_t = -F(t, X_t)dt + Z_t dW_t \end{cases}$$

- In fact  $Z_t = \sigma \partial_x u(t, X_t)$
- Connection also works with  $dX_t = dW_t$  and a different  $Y_t \dots$
- Application: solve a PDE by solving the corresponding (F)BSDE
- Ex. HJB equation. Many variations/extensions

Solutions of MFG (and MFC) can be characterized by **MKV FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T, \mathcal{L}(X_T)) & \rightarrow \text{control/cost} \end{cases}$$

Solutions of MFG (and MFC) can be characterized by **MKV FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T, \mathcal{L}(X_T)) & \rightarrow \text{control/cost} \end{cases}$$

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

Solutions of MFG (and MFC) can be characterized by **MKV FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T, \mathcal{L}(X_T)) & \rightarrow \text{control/cost} \end{cases}$$

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation as a MFC problem** [Carmona and Laurière, 2022]

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}}, \mathcal{L}(X_T^{y_0, \mathbf{z}}))\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + z(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

Solutions of MFG (and MFC) can be characterized by **MKV FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T, \mathcal{L}(X_T)) & \rightarrow \text{control/cost} \end{cases}$$

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation as a MFC problem** [Carmona and Laurière, 2022]

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}}, \mathcal{L}(X_T^{y_0, \mathbf{z}}))\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + z(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

$\rightarrow$  **New MFC problem:** apply previous method, replacing  $y_0(\cdot), z(\cdot, \cdot)$  by NN



Solutions of MFG (and MFC) can be characterized by **MKV FBSDEs** of the form

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0 & \rightarrow \text{state} \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + Z_t \cdot dW_t, & Y_T = G(X_T, \mathcal{L}(X_T)) & \rightarrow \text{control/cost} \end{cases}$$

**Shooting:** Guess  $Y_0$  and  $(Z_t)_t$

$\rightarrow$  recover sol.  $(X, Y, Z)$  is found by opt. control of 2 **forward** SDEs

**Reformulation as a MFC problem** [Carmona and Laurière, 2022]

**Minimize** over  $y_0(\cdot)$  and  $\mathbf{z}(\cdot) = (z_t(\cdot))_{t \geq 0}$

$$\mathfrak{J}(y_0(\cdot), \mathbf{z}(\cdot)) = \mathbb{E} \left[ \|Y_T^{y_0, \mathbf{z}} - G(X_T^{y_0, \mathbf{z}}, \mathcal{L}(X_T^{y_0, \mathbf{z}}))\|^2 \right],$$

under the constraint that  $(X^{y_0, \mathbf{z}}, Y^{y_0, \mathbf{z}})$  solve:  $\forall t \in [0, T]$

$$\begin{cases} dX_t = B(t, X_t, \mathcal{L}(X_t), Y_t)dt + dW_t, & X_0 \sim m_0, \\ dY_t = -F(t, X_t, \mathcal{L}(X_t), Y_t)dt + z(t, X_t) \cdot dW_t, & Y_0 = y_0(X_0). \end{cases}$$

$\rightarrow$  **New MFC problem:** apply previous method, replacing  $y_0(\cdot), z(\cdot, \cdot)$  by NN

NB: This problem is *not* the original MFG or MFC





## Numerical Illustration 1: Comparison with Picard Solver

**Example of MKV FBSDE** from [Chassagneux et al., 2019] ( $\rho$  = coupling parameter)

$$\begin{aligned}dX_t &= -\rho Y_t dt + \sigma dW_t, & X_0 &= x_0 \\dY_t &= \operatorname{atan}(\mathbb{E}[X_t])dt + Z_t dW_t, & Y_T &= G'(X_T) := \operatorname{atan}(X_T)\end{aligned}$$

Comes from the **MFG** defined by  $dX_t^\alpha = \alpha_t dt + dW_t$  and

$$J(\alpha; \mu) = \mathbb{E} \left[ G(X_T^\alpha) + \int_0^T \left( \frac{1}{2} \alpha_t^2 + X_t^\alpha \operatorname{atan} \left( \int x \mu_t(dx) \right) \right) dt \right]$$


# Numerical Illustration 1: Comparison with Picard Solver

**Example of MKV FBSDE** from [Chassagneux et al., 2019] ( $\rho$  = coupling parameter)


$$\begin{aligned}dX_t &= -\rho Y_t dt + \sigma dW_t, & X_0 &= x_0 \\dY_t &= \text{atan}(\mathbb{E}[X_t])dt + Z_t dW_t, & Y_T &= G'(X_T) := \text{atan}(X_T)\end{aligned}$$

Comes from the **MFG** defined by  $dX_t^\alpha = \alpha_t dt + dW_t$  and

$$J(\alpha; \mu) = \mathbb{E} \left[ G(X_T^\alpha) + \int_0^T \left( \frac{1}{2\rho} \alpha_t^2 + X_t^\alpha \text{atan} \left( \int x \mu_t(dx) \right) \right) dt \right]$$



[Chassagneux et al., 2019]



NN (FBSDE system)

More details in [Carmona and Laurière, 2022]

### Example: MFG for inter-bank borrowing/lending

[Carmona et al., 2015]

$X$  = log-monetary reserve,  $\alpha$  = rate of borrowing/lending to central bank, cost:

$$J(\alpha; \bar{m}) = \mathbb{E} \left[ \int_0^T \left[ \frac{1}{2} \alpha_t^2 - q \alpha_t (\bar{m}_t - X_t) + \frac{\epsilon}{2} (\bar{m}_t - X_t)^2 \right] dt + \frac{c}{2} (\bar{m}_T - X_T)^2 \right]$$

where  $\bar{m} = (\bar{m}_t)_{t \geq 0}$  = conditional mean of the population states given  $W^0$ , and

$$dX_t = [a(\bar{m}_t - X_t) + \alpha_t]dt + \sigma \left( \sqrt{1 - \rho^2} dW_t + \rho dW_t^0 \right)$$

## Numerical Illustration 2: LQ MFG with Common Noise

### Example: MFG for inter-bank borrowing/lending

[Carmona et al., 2015]


$X$  = log-monetary reserve,  $\alpha$  = rate of borrowing/lending to central bank, cost:

$$J(\alpha; \bar{m}) = \mathbb{E} \left[ \int_0^T \left[ \frac{1}{2} \alpha_t^2 - q \alpha_t (\bar{m}_t - X_t) + \frac{\epsilon}{2} (\bar{m}_t - X_t)^2 \right] dt + \frac{c}{2} (\bar{m}_T - X_T)^2 \right]$$


where  $\bar{m} = (\bar{m}_t)_{t \geq 0} =$  conditional mean of the population states given  $W^0$ , and

$$dX_t = [a(\bar{m}_t - X_t) + \alpha_t]dt + \sigma \left( \sqrt{1 - \rho^2} dW_t + \rho dW_t^0 \right)$$

NN for FBSDE system VS (semi) analytical solution (LQ structure)



Samples of  $X$



Samples of  $Y$

More details in [Carmona and Laurière, 2022]

## Numerical Illustration 2: LQ MFG with Common Noise

### Example: MFG for inter-bank borrowing/lending

[Carmona et al., 2015]


$X$  = log-monetary reserve,  $\alpha$  = rate of borrowing/lending to central bank, cost:

$$J(\alpha; \bar{m}) = \mathbb{E} \left[ \int_0^T \left[ \frac{1}{2} \alpha_t^2 - q \alpha_t (\bar{m}_t - X_t) + \frac{\epsilon}{2} (\bar{m}_t - X_t)^2 \right] dt + \frac{c}{2} (\bar{m}_T - X_T)^2 \right]$$


where  $\bar{m} = (\bar{m}_t)_{t \geq 0}$  = conditional mean of the population states given  $W^0$ , and

$$dX_t = [a(\bar{m}_t - X_t) + \alpha_t] dt + \sigma \left( \sqrt{1 - \rho^2} dW_t + \rho dW_t^0 \right)$$

NN for FBSDE system VS (semi) analytical solution (LQ structure)



$L^2$  error on  $X$



$L^2$  error on  $Y$

More details in [Carmona and Laurière, 2022]



### Code

Sample code to illustrate: [IPython notebook](#)

<https://colab.research.google.com/drive/1w5pMwMxvoVRXFZ1y71-zecyctBTdVl37?usp=sharing>

- Deep learning for MKV FBSDEs
- Applied to the systemic risk model discussed above

- Convergence of the DeepBSDE method [[Han and Long, 2020](#)]
- Extension to finite-player games [[Han et al., 2022](#)]
- Analysis of the different types of errors to be done for MKV case
- The new MFC problem is not standard
- Deep learning of MKV FBSDEs as presented here [[Carmona and Laurière, 2022](#)]; see also [[Carmona and Laurière, 2023](#)]
- Related works on deep learning for MKV FBSDEs: [[Fouque and Zhang, 2020](#)] (MFC with delay), [[Germain et al., 2019](#)], [[Aurell et al., 2022b](#)], ...
- Similar “shooting” strategy can be applied to (infinite-dimensional) ODE systems obtained in graphon games [[Aurell et al., 2022a](#)]. Code (Gökçe Dayanıklı):

`https://github.com/gokce-d/GraphonEpidemics`

# Outline

---

1. Introduction

2. Deep Learning for MFC

3. Deep Learning for MKV FBSDE

4. Two Examples of Extensions

- Solving Stackelberg MFG with Deep MKV FBSDE
- Computing MFC Value Function with DBDP

5. Conclusion

# Outline

---

1. Introduction

2. Deep Learning for MFC

3. Deep Learning for MKV FBSDE

4. Two Examples of Extensions

- Solving Stackelberg MFG with Deep MKV FBSDE
- Computing MFC Value Function with DBDP

5. Conclusion

MFG with a **Stackelberg** (leader-follower) structure:

- A Principal chooses a policy  $\lambda$
- A population of agents react and form a Nash equilibrium:

$$J^\lambda(\alpha, \mu) := \mathbb{E} \left[ \int_0^T f(t, X_t, \alpha_t, \mu_t; \lambda(t)) dt + g(X_T, \mu_T; \lambda(T)) \right],$$

- This is an MFG parameterized by  $\lambda$
- The resulting mean field flow  $\hat{\mu}^\lambda$  incurs a cost to the principal

$$J^0(\lambda) := \int_0^T f_0(t, \hat{\mu}_t^\lambda, \lambda(t)) dt + g_0(\hat{\mu}_T^\lambda, \lambda(T))$$

Related works: Holmström-Milgrom (1987), Sannikov (2008, 2013), Djehiche-Helgesson (2014), Cvitanović *et al* (2018), Carmona-Wang (2018), Elie *et al* (2019)

Reminder:

- MFG solution can be characterized using a MKV FBSDE system
- This MKV FBSDE can be rewritten as a control problem
  - ▶ 2 forward equations
  - ▶ terminal cost

**Stackelberg MFG:**

- The above terminal cost can be combined with the principal's cost
- We obtain an MFC problem [Elie et al., 2019]
- From here we can apply the methods discussed previously

Reminder:

- MFG solution can be characterized using a MKV FBSDE system
- This MKV FBSDE can be rewritten as a control problem
  - ▶ 2 forward equations
  - ▶ **terminal cost**

## Stackelberg MFG:

- The above **terminal cost** can be combined with the **principal's cost**
- We obtain an **MFC problem** [Elie et al., 2019]
- From here we can apply the methods discussed previously

For more details, see:

- [Aurell et al., 2022b] with application to epidemics management (finite state MFG): principal gives guidelines (social distancing, etc.) and population reacts
- **Code available** ((Gökçe Dayanıklı)):

<https://github.com/gokce-d/StackelbergMFG>

- Extension to other Stackelberg MFGs: [Dayanikli and Lauriere, 2023]
- Similarities with DA for **mean field optimal transport** [Baudalet et al., 2023]

# Outline

---

1. Introduction

2. Deep Learning for MFC

3. Deep Learning for MKV FBSDE

4. Two Examples of Extensions

- Solving Stackelberg MFG with Deep MKV FBSDE
- **Computing MFC Value Function with DBDP**

5. Conclusion



## Social optimum: Mean Field Control

Reminder from lecture 2 about mean field (type) control or control of McKean-Vlasov (MKV) dynamics

Definition (Mean field control (MFC) problem)

$\alpha^*$  is a solution to the MFC problem if it minimizes

$$J^{MFC}(\alpha) = \mathbb{E} \left[ \int_0^T f(X_t^\alpha, \alpha_t, m_t^\alpha) dt + g(X_T^\alpha, m_T^\alpha) \right].$$

Main difference with MFG: here not only  $X$  but  $m$  too is controlled by  $\alpha$ .

# Social optimum: Mean Field Control

Reminder from lecture 2 about [mean field \(type\) control](#) or [control of McKean-Vlasov \(MKV\) dynamics](#)

## Definition (Mean field control (MFC) problem)

$\alpha^*$  is a solution to the MFC problem if it minimizes

$$J^{MFC}(\alpha) = \mathbb{E} \left[ \int_0^T f(X_t^\alpha, \alpha_t, m_t^\alpha) dt + g(X_T^\alpha, m_T^\alpha) \right].$$

Main difference with MFG: here not only  $X$  but  $m$  too is controlled by  $\alpha$ .

**Optimality conditions?** Several approaches:

- Dynamic programming value function depending on  $m$ ; [value function  \$V\$](#)
- Calculus of variations taking  $m$  as a state; adjoint state  $u$
- Pontryagin's maximum principle for the (MKV process)  $X$ ; adjoint state  $Y$

**Dynamic programming** for MFC [[Laurière and Pironneau, 2014](#)], [[Bensoussan et al., 2015](#)], [[Pham and Wei, 2017](#)], [[Djete et al., 2022](#)], ...

→ [Algorithm?](#)

For standard (non-mean field) stochastic optimal control problems, [Huré et al., 2019] have introduced the **Deep Backward Dynamic Programming (DBDP)**:

**Idea:** learn  $Y_n$  and  $Z_n$  at each  $n$  as functions of  $X_n$ , backward in time:

- Initialize  $\hat{Y}_{N_T} = g$  and then, for  $n = N_T - 1, \dots, 0$ , either:
- Version 1: Let  $(\hat{Y}_n, \hat{Z}_n) = \text{minimizer over } (Y_n, Z_n) \text{ of:}$

$$\mathbb{E} \left[ |\hat{Y}_{n+1}(X_{n+1}) - Y_n(X_n) - f(t_n, X_n, Y_n(X_n), \textcolor{red}{Z}_n(X_n))\Delta t - \textcolor{red}{Z}_n(X_n) \cdot \Delta W_{n+1}| \right]$$

For standard (non-mean field) stochastic optimal control problems, [Huré et al., 2019] have introduced the **Deep Backward Dynamic Programming (DBDP)**:

**Idea:** learn  $Y_n$  and  $Z_n$  at each  $n$  as functions of  $X_n$ , backward in time:

- Initialize  $\hat{Y}_{N_T} = g$  and then, for  $n = N_T - 1, \dots, 0$ , either:
- Version 1: Let  $(\hat{Y}_n, \hat{Z}_n) = \text{minimizer over } (Y_n, Z_n) \text{ of:}$

$$\mathbb{E} \left[ |\hat{Y}_{n+1}(X_{n+1}) - Y_n(X_n) - f(t_n, X_n, Y_n(X_n), \hat{Z}_n(X_n))\Delta t - \hat{Z}_n(X_n) \cdot \Delta W_{n+1}| \right]$$

- or Version 2: Let  $(\hat{Y}_n, \hat{Z}_n) = \text{minimizer over } (Y_n, Z_n) \text{ of:}$

$$\mathbb{E} \left[ |\hat{Y}_{n+1}(X_{n+1}) - Y_n(X_n) - f(t_n, X_n, Y_n(X_n), \sigma^\top D_x Y_n(X_n))\Delta t - D_x Y_n(X_n)^\top \sigma \Delta W_{n+1}| \right]$$

For standard (non-mean field) stochastic optimal control problems, [\[Huré et al., 2019\]](#) have introduced the **Deep Backward Dynamic Programming (DBDP)**:

**Idea:** learn  $Y_n$  and  $Z_n$  at each  $n$  as functions of  $X_n$ , backward in time:

- Initialize  $\hat{Y}_{N_T} = g$  and then, for  $n = N_T - 1, \dots, 0$ , either:
- Version 1: Let  $(\hat{Y}_n, \hat{Z}_n) = \text{minimizer over } (Y_n, Z_n) \text{ of:}$

$$\mathbb{E} \left[ |\hat{Y}_{n+1}(X_{n+1}) - Y_n(X_n) - f(t_n, X_n, Y_n(X_n), \textcolor{red}{Z}_n(X_n))\Delta t - \textcolor{red}{Z}_n(X_n) \cdot \Delta W_{n+1}| \right]$$

- or Version 2: Let  $(\hat{Y}_n, \hat{Z}_n) = \text{minimizer over } (Y_n, Z_n) \text{ of:}$

$$\mathbb{E} \left[ |\hat{Y}_{n+1}(X_{n+1}) - Y_n(X_n) - f(t_n, X_n, Y_n(X_n), \sigma^\top D_x Y_n(X_n))\Delta t - D_x Y_n(X_n)^\top \sigma \Delta W_{n+1}| \right]$$

For more details on deep learning methods for (non-mean field) optimal control problems, see e.g. [\[Germain et al., 2021b\]](#)

- Can we apply the same idea to MFC, replacing  $V$  by a neural network?
- Main challenge: the value function  $V$  takes  $m \in \mathcal{P}(\mathbb{R}^d)$  as an input
- We need to approximate  $m$

- Can we apply the same idea to MFC, replacing  $V$  by a neural network?
- Main challenge: the value function  $V$  takes  $m \in \mathcal{P}(\mathbb{R}^d)$  as an input
- We need to approximate  $m$
- One possibility:

$$V(t, m_t) \approx \tilde{V}(t, m_t^N) \approx \tilde{V}_\theta(t, X_t^1, \dots, X_t^N)$$

where  $\tilde{V}_\theta$  is a neural network which is **symmetric** with respect to the inputs

- See the **lecture 5** for more details
- See [\[Germain et al., 2021a\]](#) for more details about the implementation and [\[Germain et al., 2022\]](#) for the analysis
- See also e.g. [\[Dayanikli et al., 2023\]](#) for different approximations of the population (combined with direct approach instead of DBDP)

# Outline

---

1. Introduction
2. Deep Learning for MFC
3. Deep Learning for MKV FBSDE
4. Two Examples of Extensions
5. Conclusion



## Summary

---

- Two algorithms based on the stochastic approach
- Direct approach without any optimality condition
- DeepBSDE: recasting (MKV) FBSDEs as control problems
- Many possible extensions and variations
- Many **open questions** for mathematicians (proofs of approximation, rates of convergence, ...)
- Some surveys on DL for control/games:  
[Germain et al., 2021b, Carmona and Laurière, 2023, Hu and Laurière, 2023]

Next lecture: deep learning methods for the PDE approach

Thank you for your attention

Questions?

Feel free to reach out: `mathieu.lauriere@nyu.edu`

# References I

---

- [Achdou et al., 2012] Achdou, Y., Camilli, F., and Capuzzo-Dolcetta, I. (2012).  
Mean field games: numerical methods for the planning problem.  
*SIAM J. Control Optim.*, 50(1):77–109.
- [Achdou and Capuzzo-Dolcetta, 2010] Achdou, Y. and Capuzzo-Dolcetta, I. (2010).  
Mean field games: numerical methods.  
*SIAM J. Numer. Anal.*, 48(3):1136–1162.
- [Achdou and Lasry, 2019] Achdou, Y. and Lasry, J.-M. (2019).  
Mean field games for modeling crowd motion.  
In Chetverushkin, B. N., Fitzgibbon, W., Kuznetsov, Y. A., Neittaanmäki, P., Periaux, J., and Pironneau, O., editors, *Contributions to Partial Differential Equations and Applications*, chapter 4, pages 17–42. Springer International Publishing.
- [Achdou and Laurière, 2016] Achdou, Y. and Laurière, M. (2016).  
Mean Field Type Control with Congestion (II): An augmented Lagrangian method.  
*Appl. Math. Optim.*, 74(3):535–578.
- [Agram et al., 2020] Agram, N., Bakdi, A., and Oksendal, B. (2020).  
Deep learning and stochastic mean-field control for a neural network model.  
*Available at SSRN 3639022*.
- [Almulla et al., 2017] Almulla, N., Ferreira, R., and Gomes, D. (2017).  
Two numerical approaches to stationary mean-field games.  
*Dyn. Games Appl.*, 7(4):657–682.

[Andreev, 2017a] Andreev, R. (2017a).

Preconditioning the augmented Lagrangian method for instationary mean field games with diffusion.

*SIAM J. Sci. Comput.*, 39(6):A2763–A2783.

[Andreev, 2017b] Andreev, R. (2017b).

Preconditioning the augmented lagrangian method for instationary mean field games with diffusion.

*SIAM Journal on Scientific Computing*, 39(6):A2763–A2783.

[Angiuli et al., 2019] Angiuli, A., Graves, C. V., Li, H., Chassagneux, J.-F., Delarue, F., and Carmona, R. (2019).

Cemracs 2017: numerical probabilistic approach to MFG.

*ESAIM: ProcS*, 65:84–113.

[Aurell et al., 2022a] Aurell, A., Carmona, R., Dayanikli, G., and Laurière, M. (2022a).

Finite state graphon games with applications to epidemics.

*Dynamic Games and Applications*, 12(1):49–81.

[Aurell et al., 2022b] Aurell, A., Carmona, R., Dayanikli, G., and Lauriere, M. (2022b).

Optimal incentives to mitigate epidemics: a stackelberg mean field game approach.

*SIAM Journal on Control and Optimization*, 60(2):S294–S322.

## References III

---

- [Balata et al., 2019] Balata, A., Huré, C., Laurière, M., Pham, H., and Pimentel, I. (2019).  
A class of finite-dimensional numerically solvable mckean-vlasov control problems.  
*ESAIM: Proceedings and Surveys*, 65:114–144.
- [Baudalet et al., 2023] Baudalet, S., Frénais, B., Laurière, M., Machtalay, A., and Zhu, Y. (2023).  
Deep learning for mean field optimal transport.  
*arXiv preprint arXiv:2302.14739*.
- [Bayraktar et al., 2018] Bayraktar, E., Budhiraja, A., and Cohen, A. (2018).  
A numerical scheme for a mean field game in some queueing systems based on markov chain approximation method.  
*SIAM Journal on Control and Optimization*, 56(6):4017–4044.
- [Benamou and Carlier, 2015] Benamou, J.-D. and Carlier, G. (2015).  
Augmented lagrangian methods for transport optimization, mean field games and degenerate elliptic equations.  
*Journal of Optimization Theory and Applications*, 167(1):1–26.
- [Bensoussan et al., 2015] Bensoussan, A., Frehse, J., and Yam, S. C. P. (2015).  
The master equation in mean field theory.  
*J. Math. Pures Appl. (9)*, 103(6):1441–1474.
- [Borkar, 2009] Borkar, V. S. (2009).  
*Stochastic approximation: a dynamical systems viewpoint*, volume 48.  
Springer.

## References IV

---

- [Bossy and Talay, 1997] Bossy, M. and Talay, D. (1997).  
A stochastic particle method for the McKean-Vlasov and the Burgers equation.  
*Math. Comp.*, 66(217):157–192.
- [Bottou, 2012] Bottou, L. (2012).  
Stochastic gradient descent tricks.  
In *Neural Networks: Tricks of the Trade: Second Edition*, pages 421–436. Springer.
- [Briceño Arias et al., 2019] Briceño Arias, L. M., Kalise, D., Kobeissi, Z., Laurière, M., Mateos González, A., and Silva, F. J. (2019).  
On the implementation of a primal-dual algorithm for second order time-dependent mean field games with local couplings.  
*ESAIM: ProcS*, 65:330–348.
- [Briceño Arias et al., 2018] Briceño Arias, L. M., Kalise, D., and Silva, F. J. (2018).  
Proximal methods for stationary mean field games with local couplings.  
*SIAM J. Control Optim.*, 56(2):801–836.
- [Cacace et al., 2021] Cacace, S., Camilli, F., and Goffi, A. (2021).  
A policy iteration method for mean field games.  
*ESAIM: Control, Optimisation and Calculus of Variations*, 27:85.

- [Calzola et al., 2022] Calzola, E., Carlini, E., and Silva, F. J. (2022).  
A high-order lagrange-galerkin scheme for a class of fokker-planck equations and applications to mean field games.  
*arXiv preprint arXiv:2207.08463*.
- [Camilli and Tang, 2022] Camilli, F. and Tang, Q. (2022).  
Rates of convergence for the policy iteration method for mean field games systems.  
*Journal of Mathematical Analysis and Applications*, 512(1):126138.
- [Carlini and Silva, 2014] Carlini, E. and Silva, F. J. (2014).  
A fully discrete semi-Lagrangian scheme for a first order mean field game problem.  
*SIAM J. Numer. Anal.*, 52(1):45–67.
- [Carlini and Silva, 2015] Carlini, E. and Silva, F. J. (2015).  
A semi-Lagrangian scheme for a degenerate second order mean field game system.  
*Discrete Contin. Dyn. Syst.*, 35(9):4269–4292.
- [Carlini and Silva, 2018] Carlini, E. and Silva, F. J. (2018).  
On the discretization of some nonlinear fokker–planck–kolmogorov equations and applications.  
*SIAM Journal on Numerical Analysis*, 56(4):2148–2177.

- [Carmona and Delarue, 2018] Carmona, R. and Delarue, F. (2018).  
*Probabilistic theory of mean field games with applications. I*, volume 83 of *Probability Theory and Stochastic Modelling*.  
Springer, Cham.  
Mean field FBSDEs, control, and games.
- [Carmona et al., 2015] Carmona, R., Fouque, J.-P., and Sun, L.-H. (2015).  
Mean field games and systemic risk.  
*Commun. Math. Sci.*, 13(4):911–933.
- [Carmona and Lacker, 2015] Carmona, R. and Lacker, D. (2015).  
A probabilistic weak formulation of mean field games and applications.  
*Ann. Appl. Probab.*, 25(3):1189–1231.
- [Carmona and Laurière, 2021] Carmona, R. and Laurière, M. (2021).  
Convergence analysis of machine learning algorithms for the numerical solution of mean field control and games i: The ergodic case.  
*SIAM Journal on Numerical Analysis*, 59(3):1455–1485.
- [Carmona and Laurière, 2022] Carmona, R. and Laurière, M. (2022).  
Convergence analysis of machine learning algorithms for the numerical solution of mean field control and games: li—the finite horizon case.  
*The Annals of Applied Probability*, 32(6):4065–4105.



## References VII

---

- [Carmona and Laurière, 2023] Carmona, R. and Laurière, M. (2023).  
Deep learning for mean field games and mean field control with applications to finance.  
*Machine Learning and Data Sciences for Financial Markets: A Guide to Contemporary Practices*, page 369.
- [Chassagneux et al., 2019] Chassagneux, J.-F., Crisan, D., and Delarue, F. (2019).  
Numerical method for FBSDEs of McKean-Vlasov type.  
*Ann. Appl. Probab.*, 29(3):1640–1684.
- [Cui and Koepl, 2021] Cui, K. and Koepl, H. (2021).  
Approximately solving mean field games via entropy-regularized deep reinforcement learning.  
In *International Conference on Artificial Intelligence and Statistics*, pages 1909–1917. PMLR.
- [Cybenko, 1989] Cybenko, G. (1989).  
Approximation by superpositions of a sigmoidal function.  
*Mathematics of control, signals and systems*, 2(4):303–314.
- [Dayanikli and Lauriere, 2023] Dayanikli, G. and Lauriere, M. (2023).  
A machine learning method for stackelberg mean field games.  
*arXiv preprint arXiv:2302.10440*.
- [Dayanikli et al., 2023] Dayanikli, G., Lauriere, M., and Zhang, J. (2023).  
Deep learning for population-dependent controls in mean field control problems.  
*arXiv preprint arXiv:2306.04788*.

## References VIII

---

- [de Raynal and Trillos, 2015] de Raynal, P. C. and Trillos, C. G. (2015).  
A cubature based algorithm to solve decoupled mckean–vlasov forward–backward stochastic differential equations.  
*Stochastic Processes and their Applications*, 125(6):2206–2255.
- [Després, 2022] Després, B. (2022).  
*Neural Networks and Numerical Analysis*, volume 6.  
Walter de Gruyter GmbH & Co KG.
- [Djete et al., 2022] Djete, M. F., Possamaï, D., and Tan, X. (2022).  
Mckean–vlasov optimal control: the dynamic programming principle.  
*The Annals of Probability*, 50(2):791–833.
- [E et al., 2017] E, W., Han, J., and Jentzen, A. (2017).  
Deep learning-based numerical methods for high-dimensional parabolic partial differential equations and backward stochastic differential equations.  
*Commun. Math. Stat.*, 5(4):349–380.
- [Elie et al., 2019] Elie, R., Mastrolia, T., and Possamaï, D. (2019).  
A tale of a principal and many, many agents.  
*Mathematics of Operations Research*, 44(2):440–467.
- [Fouque and Zhang, 2020] Fouque, J.-P. and Zhang, Z. (2020).  
Deep learning methods for mean field control problems with delay.  
*Frontiers in Applied Mathematics and Statistics*, 6:11.

## References IX

---

- [Germain et al., 2021a] Germain, M., Laurière, M., Pham, H., and Warin, X. (2021a). Deepsets and their derivative networks for solving symmetric pdes. *arXiv preprint arXiv:2103.00838*.
- [Germain et al., 2019] Germain, M., Mikael, J., and Warin, X. (2019). Numerical resolution of mckean-vlasov fbsdes using neural networks. *arXiv preprint arXiv:1909.12678*.
- [Germain et al., 2021b] Germain, M., Pham, H., and Warin, X. (2021b). Neural networks-based algorithms for stochastic control and pdes in finance. *arXiv preprint arXiv:2101.08068*.
- [Germain et al., 2022] Germain, M., Pham, H., and Warin, X. (2022). Rate of convergence for particle approximation of pdes in wasserstein space. *Journal of Applied Probability*, 59(4):992–1008.
- [Gobet and Munos, 2005] Gobet, E. and Munos, R. (2005). Sensitivity analysis using Itô-Malliavin calculus and martingales, and application to stochastic optimal control. *SIAM J. Control Optim.*, 43(5):1676–1713.
- [Gomes and Saúde, 2018] Gomes, D. A. and Saúde, J. (2018). Numerical methods for finite-state mean-field games satisfying a monotonicity condition. *Applied Mathematics & Optimization*.

- [Gomes and Yang, 2020] Gomes, D. A. and Yang, X. (2020).  
The hessian riemannian flow and newton's method for effective hamiltonians and mather measures.  
*ESAIM: Mathematical Modelling and Numerical Analysis*, 54(6):1883–1915.
- [Goodfellow et al., 2016] Goodfellow, I., Bengio, Y., and Courville, A. (2016).  
*Deep learning*.  
MIT press.
- [Han and E, 2016] Han, J. and E, W. (2016).  
Deep learning approximation for stochastic control problems.  
*Deep Reinforcement Learning Workshop, NIPS, arXiv preprint arXiv:1611.07422*.
- [Han et al., 2022] Han, J., Hu, R., and Long, J. (2022).  
Convergence of deep fictitious play for stochastic differential games.  
*Frontiers of Mathematical Finance*, 1(2):279–311.
- [Han and Long, 2020] Han, J. and Long, J. (2020).  
Convergence of the deep bsde method for coupled fbsdes.  
*Probability, Uncertainty and Quantitative Risk*, 5:1–33.
- [Hornik, 1991] Hornik, K. (1991).  
Approximation capabilities of multilayer feedforward networks.  
*Neural networks*, 4(2):251–257.

# References XI

---

[Hu, 2021] Hu, R. (2021).

Deep fictitious play for stochastic differential games.

*Communications in Mathematical Sciences*, 19(2):325–353.

[Hu and Laurière, 2023] Hu, R. and Laurière, M. (2023).

Recent developments in machine learning methods for stochastic control and games.

*arXiv preprint arXiv:2303.10257*.

[Huré et al., 2019] Huré, C., Pham, H., and Warin, X. (2019).

Some machine learning schemes for high-dimensional nonlinear pdes.

*arXiv preprint arXiv:1902.01599*, page 2.

[Kingma and Ba, 2014] Kingma, D. P. and Ba, J. (2014).

Adam: A method for stochastic optimization.

*arXiv preprint arXiv:1412.6980*.

[Kohlmann and Zhou, 2000] Kohlmann, M. and Zhou, X. Y. (2000).

Relationship between backward stochastic differential equations and stochastic controls: a linear-quadratic approach.

*SIAM Journal on Control and Optimization*, 38(5):1392–1407.

[Laurière and Pironneau, 2014] Laurière, M. and Pironneau, O. (2014).

Dynamic programming for mean-field type control.

*C. R. Math. Acad. Sci. Paris*, 352(9):707–713.

## References XII

---

- [Laurière and Pironneau, 2016] Laurière, M. and Pironneau, O. (2016).  
Dynamic programming for mean-field type control.  
*J. Optim. Theory Appl.*, 169(3):902–924.
- [Laurière et al., 2023] Laurière, M., Song, J., and Tang, Q. (2023).  
Policy iteration method for time-dependent mean field games systems with non-separable hamiltonians.  
*Applied Mathematics & Optimization*, 87(2):17.
- [Lavigne and Pfeiffer, 2022] Lavigne, P. and Pfeiffer, L. (2022).  
Generalized conditional gradient and learning in potential mean field games.  
*arXiv preprint arXiv:2209.12772*.
- [LeCun et al., 2015] LeCun, Y., Bengio, Y., and Hinton, G. (2015).  
Deep learning.  
*nature*, 521(7553):436–444.
- [Leijnen and Veen, 2020] Leijnen, S. and Veen, F. v. (2020).  
The neural network zoo.  
In *Proceedings*, volume 47, page 9. MDPI.
- [Liu et al., 2021] Liu, S., Jacobs, M., Li, W., Nurbekyan, L., and Osher, S. J. (2021).  
Computational methods for first-order nonlocal mean field games with applications.  
*SIAM Journal on Numerical Analysis*, 59(5):2639–2668.

## References XIII

---

- [Mhaskar and Micchelli, 1995] Mhaskar, H. N. and Micchelli, C. A. (1995).  
Degree of approximation by neural and translation networks with a single hidden layer.  
*Advances in Applied Mathematics*, 16:151–183.
- [Mou et al., 2022] Mou, C., Yang, X., and Zhou, C. (2022).  
Numerical methods for mean field games based on gaussian processes and fourier features.  
*Journal of Computational Physics*, 460:111188.
- [Nurbekyan et al., 2019] Nurbekyan, L. et al. (2019).  
Fourier approximation methods for first-order nonlocal mean-field games.  
*Portugaliae Mathematica*, 75(3):367–396.
- [Pfeiffer, 2016] Pfeiffer, L. (2016).  
Numerical methods for mean-field type optimal control problems.  
*Pure Appl. Funct. Anal.*, 1(4):629–655.
- [Pham and Wei, 2017] Pham, H. and Wei, X. (2017).  
Dynamic programming for optimal control of stochastic McKean-Vlasov dynamics.  
*SIAM J. Control Optim.*, 55(2):1069–1101.
- [Robbins and Monro, 1951] Robbins, H. and Monro, S. (1951).  
A stochastic approximation method.  
*The annals of mathematical statistics*, pages 400–407.

[Salhab et al., 2015] Salhab, R., Malhamé, R. P., and Le Ny, J. (2015).

A dynamic game model of collective choice in multi-agent systems.

In *2015 IEEE 54th Annual Conference on Decision and Control (CDC)*, pages 4444–4449, Osaka, Japon.

[Sannikov, 2008] Sannikov, Y. (2008).

A continuous-time version of the principal-agent problem.

*The Review of Economic Studies*, 75(3):957–984.

[Tang and Song, 2022] Tang, Q. and Song, J. (2022).

Learning optimal policies in potential mean field games: Smoothed policy iteration algorithms.

*arXiv preprint arXiv:2212.04791*.



