

SECTION – 3

DB2 ARCHITECTURE

Contents

2

- ❑ DB2 Storage Model
- ❑ Tablespaces - Characteristics
- ❑ Directory Hierarchy – OS File System
- ❑ Required Tablespaces
- ❑ Summary


DB2 Storage Model

3


To understand the DB2 storage model, we need to understand the following architecture:

Instance – DB2


Database - MyDB



Tablespace - tb2




Container – C3



DB2 Tablespace : Characteristics

- ❑ Tablespace are logical objects between the logical tables and physical container
- ❑ All tables, indexes, and other data are stored in a table space
- ❑ A tablespace is made up of containers
- ❑ Containers are made up of pages
- ❑ Page is the lowest unit of storage in DB2
- ❑ Page sizes are in denominations of
 - ▣ 4K, 8K, 16K and 32K




Containers can be files,
directories or raw devices

Directory Hierarchy – OS File System

5

Typical Directory Hierarchy Tree



Required Tablespaces in DB2

6

Each database must have a minimal set of table spaces that are used for storing system, user and temporary data:

- 1) **SYSCATSPACE (0)** : contains the metadata
- 2) **TEMPSPACE (1)** : system temporary tablespace used for storing intermediate results of SQL operations
- 3) **USERSPACE1 (2)** : used to store user created data

Summary

7

Let's summarize this lecture :

- Databases are made up of tablespaces
- Tablespaces are the logical layer b/w logical tables and physical containers
- Tablespaces are made up of containers
- Containers are made up of pages (4/8/16/32 k)
- OS file system directories for DB2
- 3 tablespaces required at a minimum