Control y Sistemas

Trabajo práctico: Modelado de sistemas hidráulicos

Referencias de símbolos



Realice los siguientes ejercicios en Simscape.

1)

EXAMPLE 7.4.3 Liquid-Level System with a Flow Source

■ **Problem**

The cylindrical tank shown in Figure 7.4.3 has a bottom area A. The total mass inflow rate from the flow source is $\hat{q}_{mi}(t)$, a given function of time. The total mass outflow rate $\hat{q}_{mo}$ is not given and must be determined. The outlet resistance R is the linearized resistance about the reference condition (h_r, q_{mir}). Develop a model of h, the deviation of the liquid height from the constant reference height h_r, where $\hat{h} = h_r + h$.



Figure 7.4.3 A liquid-level system with a flow source.

2)

7.23 (a) Develop a model of the two liquid heights in the system shown in Figure P7.23. The inflow rate $q_{mi}(t)$ is a mass flow rate. (b) Using the values $R_1 = R$, $R_2 = 3R$, $A_1 = A$, and $A_2 = 4A$, find the transfer function $H_2(s)/Q_{mi}(s)$.



3)

EXAMPLE 7.4.10 A Liquid-Level System with a Pump

■ **Problem**

Figure 7.4.12 shows a liquid-level system with a pump input and a drain whose linear resistance is R_2. The inlet from the pump to the tank has a linear resistance R_1. The resistances were linearized about the reference height $h = hr$. Obtain a linearized model of the liquid height h.



Figure 7.4.12 A liquid-level system with a pump.

4)

7.28 In Figure P7.28 the piston of area A is connected to the axle of the cylinder of radius R, mass m, and inertia I about its center. Develop a dynamic model of the axle's translation x, with the pressures p_1 and p_2 as the inputs.