

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 1: International Agreements & ICAO

Syllabus Source: CAE Oxford (pp. 21-52) | Pass Target: >= 90% AviationExam

1. HISTORICAL EVOLUTION & CHICAGO CONVENTION (1944)

Prior to World War II, international aviation was governed by fragmented regional treaties such as the 1919 Paris Convention (which first codified national sovereignty over airspace) and the 1928 Havana Convention. The massive technological advances of World War II created an urgent need for a unified global framework. On 7 December 1944, representatives of 52 Allied and neutral nations signed the Convention on International Civil Aviation in Chicago. It entered into force on 4 April 1947 after ratification by the 26th State, officially establishing the International Civil Aviation Organization (ICAO).

[*] OFFICIAL DEFINITION - Preamble of the Chicago Convention

WHEREAS the future development of international civil aviation can greatly help to create and preserve friendship and understanding among the nations and peoples of the world, yet its abuse can become a threat to the general security; ... THEREFORE, the undersigned governments have concluded certain principles and arrangements in order that international civil aviation may be developed in a safe and orderly manner.

2. EXHAUSTIVE ANALYSIS OF CHICAGO CONVENTION ARTICLES

The Chicago Convention consists of 96 articles divided into four parts. The following 22 articles are frequently and rigorously tested in EASA examinations:

Article	Official Legal Requirement & Exam Core
Art. 1: Sovereignty	Every Contracting State has complete and exclusive sovereignty over the airspace above its territory.
Art. 2: Territory	Territory consists of the land areas and adjacent territorial waters (up to 12 NM) under the sovereignty of the State. Airspace over the High Seas is international and has no State sovereignty.
Art. 3: Civil vs State Aircraft	Applies SOLELY to civil aircraft. Aircraft used in military, customs, and police services are deemed State aircraft. State aircraft cannot fly over or land on foreign territory without authorization by special agreement.
Art. 3 bis: Non-use of Weapons	Contracting States must refrain from resorting to the use of weapons against civil aircraft in flight. In case of interception, the lives of persons on board must not be endangered. States may require landing at a designated airport.
Art. 5: Non-scheduled Flights	Aircraft of Contracting States not engaged in scheduled international services have the right to fly into or in transit non-stop across territory and make stops for non-traffic purposes without prior permission, subject to the right of the State to require landing.
Art. 6: Scheduled Air Services	No scheduled international air service may be operated over or into the territory of a Contracting State except with special permission or authorization of that State.
Art. 7: Cabotage	Each Contracting State has the right to refuse permission to the aircraft of other States to take on passengers, cargo, and mail destined for another point within its own territory for remuneration.

Art. 8: Pilotless Aircraft	No aircraft capable of being flown without a pilot shall be flown without a pilot over the territory of a Contracting State without special authorization.
Art. 9: Prohibited Areas	States may restrict or prohibit aircraft from flying over certain areas of territory for reasons of military necessity or public safety, provided no distinction is made between national and foreign aircraft.

Article	Official Legal Requirement & Exam Core (Continued)
Art. 10: Customs Airports	Every aircraft entering a State must land at a designated customs airport if required by regulations.
Art. 11: Applicability of Air Regulations	Domestic air laws and regulations apply to all aircraft without distinction as to nationality.
Art. 12: Rules of the Air	Over the High Seas, the rules in force are those established by ICAO (Annex 2) WITHOUT EXCEPTION. Over land, national rules apply.
Art. 13: Entry and Clearance	The laws and regulations of a State regarding immigration, customs, quarantine, and passports must be complied with upon entry, departure, or while within territory.
Art. 16: Search of Aircraft	Authorities of a Contracting State have the right to search foreign aircraft upon landing or departure without causing unreasonable delay.
Art. 22 & 23: Facilitation	States agree to adopt all practicable measures to facilitate air navigation and prevent unnecessary delays.
Art. 24: Customs Duties on Fuel	Fuel, lubricating oils, spare parts, and regular equipment on board an aircraft of a Contracting State on arrival shall be exempt from customs duty and inspection fees.
Art. 29: Documents on Board	Every aircraft on an international flight MUST carry: 1) Certificate of Registration, 2) Certificate of Airworthiness, 3) Crew Licences, 4) Journey Log Book, 5) Aircraft Radio Licence, 6) Passenger Manifest (names and places of embarkation/destination), 7) Cargo Manifest.
Art. 31 & 32: C of A and Licences	Every aircraft must have a valid C of A issued by State of Registry. Flight crew must hold licences issued or validated by State of Registry.
Art. 33: Mutual Recognition	Certificates of Airworthiness and licences issued or validated by the State of Registry MUST be recognized as valid by other States, provided the requirements equal or exceed minimum ICAO standards.
Art. 37: Adoption of Standards	ICAO shall adopt International Standards and Recommended Practices (SARPs) in Annexes.
Art. 38: Notification of Differences	Any State that finds it impracticable to comply with an international Standard MUST immediately give notification to ICAO of differences. Notification is mandatory for Standards.
Art. 83 bis: Transfer of Functions	Enables transfer of State of Registry functions (licensing, airworthiness, ops) to the State of the Operator in cases of dry/wet lease, charter, or interchange of aircraft.

[!] EXAM TRAP (AVIATIONEXAM) - AviationExam Traps on Articles 3, 7, 12, 24 and 38

- State Aircraft Status: Military, police, and customs are State aircraft. An unarmed military transport carrying civilian cargo is STILL a State aircraft! - High Seas Jurisdiction: No State has sovereignty over the High Seas. ICAO Annex 2 applies universally without exception. - Customs on Fuel: Fuel inside aircraft tanks is exempt from customs duties. Fuel unloaded into ground tanks is NOT exempt! - Article 38 Differences: Compulsory ONLY for Standards (compulsory). Recommended Practices do NOT legally require formal notification under Art. 38.

3. THE NINE FREEDOMS OF THE AIR

Commercial transit and traffic rights are granted through bilateral Air Transport Agreements (e.g. Bermuda Agreements). ICAO classifies these traffic rights into 9 distinct Freedoms of the Air:

Freedom	Category	Official ICAO Definition	Practical Airline Scenario
1st Freedom (Overflight)	Technical	The right to fly across the territory of another State without landing.	British Airways flying London to Athens over France.
2nd Freedom (Tech Stop)	Technical	The right to land in foreign territory for non-traffic purposes (refueling, crew rest, mechanical).	Iberia landing in the Azores (Portugal) for fuel en-route to South America.
3rd Freedom (Outbound Traffic)	Commercial	The right to put down passengers, mail, and cargo taken on in the airline's Home State into a foreign State.	Lufthansa flying passengers from Frankfurt to New York.
4th Freedom (Inbound Traffic)	Commercial	The right to take on passengers, mail, and cargo in a foreign State and put them down in the airline's Home State.	Lufthansa flying passengers from New York to Frankfurt.
5th Freedom (Intermediate Traffic)	Commercial	The right to carry traffic between two foreign States on a flight originating or terminating in the airline's Home State.	Emirates flying Dubai -> London -> New York, boarding commercial passengers in London for New York.
6th Freedom (Hub Traffic)	Extended	The right to carry traffic between two foreign States via a commercial transit stop in the airline's Home State.	Air France carrying passengers from Madrid to Tokyo via Paris CDG hub.
7th Freedom (Stand-Alone Foreign)	Extended	The right to carry traffic between two foreign States entirely outside the Home State, with no connection to home.	Ryanair (Irish airline) operating scheduled flights between Rome (Italy) and Berlin (Germany).
8th Freedom (Consecutive Cabotage)	Cabotage	The right to carry traffic between two domestic points in a foreign State on a flight starting or ending in Home State.	Air France operating Paris -> Madrid -> Barcelona, carrying passengers between Madrid and Barcelona.
9th Freedom (Pure Cabotage)	Cabotage	The right to operate domestic passenger services entirely within a foreign State without any connection to Home State.	Lufthansa operating scheduled domestic flights between Madrid and Seville in Spain.

4. STRUCTURE AND GOVERNANCE OF ICAO

ICAO is a specialized agency of the United Nations headquartered in Montreal, Quebec, Canada. Its governance consists of three principal organs:

- The Assembly: Sovereign body comprising all 193 Contracting States. Meets once every 3 YEARS. Each State has ONE vote. Key functions: elects the Council, reviews technical work, approves triennial budget, and amends the Convention by a 2/3 vote.

- The Council: Permanent governing executive body responsible to the Assembly, comprising 36 Contracting States elected for a 3-year term. Categories of election: 1) States of chief importance in air transport, 2) States making largest contribution to provision of facilities, 3) States ensuring geographic representation. Key functions: ADOPTS ANNEXES (SARPs) by a 2/3 vote, appoints the Secretary General, manages finances, and investigates any situation presenting avoidable obstacles to international air navigation.
- Air Navigation Commission (ANC): Composed of 19 independent technical experts nominated by Contracting States and appointed by the Council. Responsible for drafting and updating all Annexes and PANS.
- Regional Offices: 7 offices: Paris (EUR/NAT), Dakar (WACAF), Nairobi (ESAF), Cairo (MID), Bangkok (APAC), Lima (SAM), and Mexico City (NACC).

5. MASTER CATALOGUE: ALL 19 ICAO ANNEXES

Annex	Title	Core Scope & Key EASA Exam Focus
Annex 1	Personnel Licensing	Licences for flight crew, ATCOs, flight engineers, maintenance engineers; medical classes 1, 2, 3.
Annex 2	Rules of the Air	Visual flight rules (VFR), instrument flight rules (IFR), right of way, lights, signals, interception.
Annex 3	Meteorological Service	METAR, TAF, SIGMET, AIRMET, GAMET, aerodrome forecasts, world area forecast system (WAFS).
Annex 4	Aeronautical Charts	17 chart types including SID, STAR, Instrument Approach, Aerodrome Obstacle Charts Type A and B.
Annex 5	Units of Measurement	SI units and non-SI alternatives: altitude in feet, speed in knots, distance in nautical miles.
Annex 6	Operation of Aircraft	Part I: Commercial Air Transport Aeroplanes, Part II: General Aviation, Part III: Helicopters.
Annex 7	Aircraft Nationality & Registration	Lettering height (30 cm wings/fuselage), hyphen rule, fireproof identification plate near entrance.
Annex 8	Airworthiness of Aircraft	Type Certificates, C of A, continuing airworthiness, applicability to MTOM > 5,700 kg, multi-engine.
Annex 9	Facilitation	Simplification of customs, immigration, General Declaration, crew identity, transit rules.
Annex 10	Aeronautical Telecommunications	Vol I: Nav Aids (ILS, VOR, DME), Vol II: Voice procedures, Vol III: Data, Vol IV: Radar, Vol V: Spectrum.
Annex 11	Air Traffic Services	Air Traffic Control (ATC), Flight Information Service (FIS), Alerting Service, Airspace classes A-G.
Annex 12	Search and Rescue (SAR)	Rescue Coordination Centres (RCC), emergency phases (INCERFA, ALERFA, DETRESFA), search patterns.
Annex 13	Aircraft Accident Investigation	Accident/Incident definitions, notification, State of Occurrence, sole objective: PREVENT recurrence.
Annex 14	Aerodromes	Vol I: Aerodrome Design & Operations (runways, taxiways, markings, lighting, RFFS), Vol II: Heliports.
Annex 15	Aeronautical Information Services	AIP (GEN, ENR, AD), AIRAC 28-day cycle, NOTAM, SNOWTAM, ASHTAM, AICs, pre-flight bulletins.
Annex 16	Environmental Protection	Vol I: Aircraft noise certification (Chapters 3, 4, 14), Vol II: Engine emissions, Vol III: CO2 emissions.
Annex 17	Security	Safeguarding civil aviation against acts of unlawful interference, cockpit door security, screening.
Annex 18	Dangerous Goods	Technical Instructions for Safe Transport of Dangerous Goods by Air, packaging, labelling, NOTOC.

Annex 19

Safety Management

State Safety Programmes (SSP) and Safety Management Systems (SMS) for operators and aerodromes.

6. INTERNATIONAL PENAL AND LIABILITY CONVENTIONS

Convention & Year	Legal Scope	Key Principles & Detailed Exam Specifics
Tokyo Convention (1963)	Offences Committed on Board Aircraft	Jurisdiction of the State of Registry over criminal acts committed on board. Bestows extensive powers on the Pilot-in-Command: authority to impose reasonable restraint on disruptive passengers, require assistance from crew or passengers, disembark offenders in any Contracting State, and deliver serious offenders to police authorities.
The Hague Convention (1970)	Suppression of Unlawful Seizure (Hijacking)	Establishes universal jurisdiction over hijackers. Any State where the offender is found must either extradite the offender or prosecute without exception ('Aut dedere aut judicare'). Defines hijacking as an extraditable offence in all bilateral treaties.
Montreal Convention (1971)	Suppression of Unlawful Acts Against Safety	Criminalizes acts of sabotage, violence against crew/passengers that endanger flight safety, placing bombs on aircraft, destruction of aircraft in service, and destruction of air navigation facilities.
Rome Convention (1933 / 1952)	Damage Caused by Foreign Aircraft to 3rd Parties	Strict (absolute) liability of aircraft operators for surface damage caused to persons or property on the ground. Proof of fault is not required; victim needs only prove damage caused by aircraft or falling objects.
Warsaw Convention (1929)	Air Carrier Liability (Historic)	Unified liability limits for passenger injury/death (originally 125,000 gold francs), checked baggage, and cargo loss. Established liability presumption against carrier unless carrier proves all necessary measures were taken.
Montreal Convention (1999)	Modernised Air Carrier Liability	Completely modernized passenger carrier liability into a TWO-TIER SYSTEM using SDRs (Special Drawing Rights): Tier 1 (Strict liability up to ~128,821 SDRs, carrier cannot contest), Tier 2 (Unlimited liability based on fault, carrier liable unless proving damage was not due to its negligence). Eliminates passenger ticket technicality defenses.

7. EUROPEAN AVIATION REGULATORY ARCHITECTURE

- **EASA (European Union Aviation Safety Agency):** Headquartered in Cologne, Germany. Established by Basic Regulation (EU) 2018/1139. Responsible for: drafting European aviation legislation (Cover Regulations, AMC & GM), issuing Type Certificates for aircraft/engines/propellers, approving design and production organizations (Part-21), approving non-EU maintenance organizations, and standardization inspections across EU National Aviation Authorities (NAAs).
- **EUROCONTROL:** Headquartered in Brussels, Belgium. Founded in 1960. 41 Member States. Operates the Network Manager Operations Centre (NMOC) managing air traffic flow management (ATFM) slots across Europe to prevent sector overload, and the Central Route Charges Office (CRCO) collecting overflight navigation charges.

- ECAC (European Civil Aviation Conference): Established in 1955, located in Paris. 44 European States. Consultative intergovernmental body promoting safety harmonization, aviation security audit programs, and environmental policies.

AviationExam 10-Question Comprehensive Drill

- Q1: Who adopts ICAO Annexes?: The Council of ICAO by a two-thirds (2/3) majority vote.
- Q2: Under which Article must a State notify differences to ICAO Standards?: Article 38 of the Chicago Convention.
- Q3: Does the Chicago Convention apply to military or customs aircraft?: NO. Under Article 3, it applies exclusively to civil aircraft.
- Q4: Over the High Seas, whose rules of the air apply?: ICAO Rules of the Air (Annex 2) apply without exception (Article 12).
- Q5: Carrying passengers between two domestic points in a foreign State is which freedom?: 8th Freedom (consecutive cabotage) or 9th Freedom (pure stand-alone cabotage).
- Q6: Which Convention gives the Pilot-in-Command authority to restrain unruly passengers?: The Tokyo Convention (1963).
- Q7: Under the Montreal Convention 1999, what is the carrier's liability system?: A two-tier system: strict liability up to ~128,821 SDRs, and unlimited fault-based liability thereafter.
- Q8: What is the purpose of Article 83 bis?: Allows transfer of State of Registry regulatory functions to the State of the Operator in aircraft leases.
- Q9: What is the legal status of an ICAO Recommended Practice?: Desirable, but not essential. Notification of differences under Art. 38 is not strictly mandatory.
- Q10: Where are EASA and EUROCONTROL headquartered?: EASA is in Cologne (Germany); EUROCONTROL is in Brussels (Belgium).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 2: Airworthiness & MEL Systems

Syllabus Source: CAE Oxford (pp. 53-58) | Pass Target: >= 90% AviationExam

1. REGULATORY FRAMEWORK: ANNEX 8 VS ANNEX 6

Airworthiness is the intrinsic safety of an aircraft to operate safely within authorized flight operating limits. Under the ICAO regulatory framework, airworthiness is split across two core Annexes:

- Annex 8 (Airworthiness of Aircraft): Deals with technical, physical, and design standards: structural integrity, propulsion reliability, systems crashworthiness, avionics testing, and continuing airworthiness.
- Annex 6 (Operation of Aircraft): Deals with operational safety standards: flight instruments, operating limitations, emergency equipment, performance operating minimums, and maintenance operational management.

[*] OFFICIAL DEFINITION - Annex 8 Applicability Scope (EASA ECQB Core)
The international airworthiness standards of ICAO Annex 8, Part III apply to aeroplanes with a Maximum Take-Off Mass (MTOM) GREATER THAN 5,700 kg, powered by at least TWO engines, and intended for the international carriage of passengers, cargo, or mail.

2. CERTIFICATION CHAIN: PROTOTYPE TO COMMERCIAL AIRLINE

An aircraft design and individual airframe pass through strict legal certification stages:

Certificate	Issuing Authority	Legal Scope & Operational Purpose
1. Permit to Fly	State of Registry or State of Design	Allows non-certified prototype aircraft or aircraft with minor airworthiness defects to fly for flight testing, prototype evaluation, or ferry flight to a maintenance facility.
2. Type Certificate (TC)	State of Design / Manufacture	Certifies that the design (model) of the aircraft meets all applicable Airworthiness Codes (e.g. EASA CS-25 for large aeroplanes, CS-23 for light aeroplanes). Held by the manufacturer (Airbus, Boeing).
3. Supplemental TC (STC)	State of Design	Issued to an organization that introduces major modifications or alterations to an existing certified aircraft type (e.g. winglet installation, cargo conversion, glass cockpit upgrade).
4. Certificate of Airworthiness (C of A)	State of Registry	Issued to EACH INDIVIDUAL aircraft certifying it conforms to the approved Type Certificate and is in condition for safe operation. Must be carried on board on every international flight (Art. 29).

[!] EXAM TRAP (AVIATIONEXAM) - State of Manufacture vs State of Registry

AviationExam Trap: Who issues what? - The TYPE CERTIFICATE (TC) is issued by the STATE OF DESIGN / MANUFACTURE (e.g. France for Airbus, USA for Boeing). - The CERTIFICATE OF AIRWORTHINESS (C of A) for each individual aircraft is issued or validated by the STATE OF REGISTRY.

3. CONTINUING AIRWORTHINESS: EASA PART-M, PART-CAMO & PART-145

A Certificate of Airworthiness remains valid only if continuing airworthiness is maintained in accordance with EASA Part-M:

- Airworthiness Directives (AD): Legally enforceable rules issued by the State of Design or EASA to correct an unsafe condition found in an aircraft type. ADs are MANDATORY. Failure to comply with an AD invalidates the C of A immediately, grounding the aircraft.
- Service Bulletins (SB): Technical documents issued by aircraft or engine manufacturers suggesting improvements, modifications, or specialized inspections. SBs are NON-MANDATORY by default, unless mandated by an Airworthiness Directive.
- Certificate of Release to Service (CRS): Issued by appropriately licensed Part-145 certifying staff after any maintenance, overhaul, repair, or modification before the aircraft is permitted to fly.
- Airworthiness Review Certificate (ARC - EASA Form 15a/b/c): Under EASA Part-M, a standard C of A has an unlimited duration, but is legally valid ONLY when accompanied by a valid ARC, which must be renewed ANNUALLY (1-year validity). Form 15a is issued by the Authority; Form 15b is issued by an approved CAMO; Form 15c by a CAO.

4. MINIMUM EQUIPMENT LIST (MEL) & CDL ARCHITECTURE

Commercial transport aircraft may depart with inoperative instruments or equipment ONLY under strict approved relief rules:

- MMEL (Master Minimum Equipment List): Established by the manufacturer and approved by the State of Design. Lists items that may temporarily be inoperative under specified operating conditions.
- MEL (Minimum Equipment List): Established by the OPERATOR for each aircraft type, based on the MMEL, and approved by the State of the Operator. The MEL can be MORE restrictive than the MMEL, but NEVER LESS restrictive.
- Configuration Deviation List (CDL): Lists external missing aerodynamic or structural parts (e.g. flap track fairings, landing gear doors, static wicks) permitted for dispatch, along with associated aircraft performance penalties.

MEL Rectification Interval Categories (AviationExam Core)

Rectification Category	Mandatory Legal Repair Time Limit
Category A	No standard calendar time limit. Must be repaired within the specific time interval listed in the remarks column of the MEL (e.g. 5 flight cycles, 10 flight hours).
Category B	Must be rectified within THREE (3) consecutive calendar days (72 hours), excluding the day the defect was entered in the logbook.
Category C	Must be rectified within TEN (10) consecutive calendar days (240 hours), excluding the day the defect was discovered.
Category D	Must be rectified within ONE HUNDRED AND TWENTY (120) consecutive calendar days, excluding the day of discovery.

5. MAINTENANCE RECORDS & COMPONENT RELEASE (EASA FORM 1)

Continuing airworthiness records must be preserved to prove compliance: - Maintenance records must be retained until 36 MONTHS after the aircraft has been permanently withdrawn from service. - EASA Form 1: The official Authorized Release Certificate certifying that a component or part has been manufactured or maintained in accordance with approved data.

6. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: Under EASA Part-M, what is the validity period of an Airworthiness Review Certificate (ARC)?

- [A]: 6 months
- [B]: 1 year
- [C]: 2 years
- [D]: Unlimited provided maintenance is carried out

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The ARC is valid for 1 year and must be re-issued annually by an approved CAMO or authority.

Q2: What is the legal status of an Airworthiness Directive (AD) versus a Service Bulletin (SB)?

- [A]: Both are voluntary recommendations.
- [B]: SBs are mandatory; ADs are optional.
- [C]: ADs are mandatory; SBs are non-mandatory unless mandated by an AD.
- [D]: ADs only apply to military aircraft.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. An Airworthiness Directive is legally binding and mandatory. A Service Bulletin is recommended by the manufacturer but only becomes legally mandatory if incorporated into an AD.

Q3: Can an operator depart with an item inoperative that is NOT listed in the MEL?

- [A]: Yes, at the discretion of the Commander.
- [B]: Yes, if operating in daylight VMC.
- [C]: NO, all inoperative items must be covered by relief in the MEL or repaired before flight.
- [D]: Yes, for domestic ferry flights.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under Part-CAT, an aircraft cannot be dispatched with an inoperative item unless specifically permitted by the approved MEL.

Q4: What is the maximum allowable rectification interval for Category C MEL items?

- [A]: 3 calendar days (72 hours)
- [B]: 10 calendar days (240 hours)
- [C]: 30 calendar days
- [D]: 120 calendar days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Category C items must be rectified within 10 consecutive calendar days excluding the day of discovery.

Q5: What document certifies that an individual aircraft component has been maintained to approved data?

- [A]: EASA Form 1
- [B]: EASA Form 15b
- [C]: Certificate of Airworthiness
- [D]: Journey Log Book

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. EASA Form 1 is the official Authorised Release Certificate for aircraft components and parts.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 3: Nationality & Registration Marks

Syllabus Source: CAE Oxford (pp. 59-66) | Pass Target: >= 90% AviationExam

1. LEGAL FOUNDATIONS: CHICAGO CONVENTION & ANNEX 7

Under Article 17 of the Chicago Convention, aircraft have the nationality of the State in which they are registered. Annex 7 specifies international standards for nationality and registration marks, placement, lettering dimensions, and identification plates.

- Dual Registration Prohibited (Art. 18): An aircraft cannot be validly registered in more than one State at the same time. However, registration may be transferred from one State to another.
- Domestic Law Governs (Art. 19): The registration or transfer of registration of aircraft in any Contracting State shall be made in accordance with its national laws and regulations.
- Display of Marks (Art. 20): Every aircraft engaged in international air navigation shall bear its appropriate nationality and registration marks.

2. STRUCTURE OF MARKS: NATIONALITY VS REGISTRATION

- Nationality Mark: Selected from the series of nationality symbols included in the radio call signs allocated to the State of Registry by the International Telecommunication Union (ITU). Examples: G = United Kingdom, F = France, D = Germany, EC = Spain, EI = Ireland, N = USA, HB = Switzerland, OO = Belgium, PH = Netherlands.
- Registration Mark: Consists of letters, numbers, or a combination assigned by the State of Registry or common mark registering authority.
- The Hyphen Rule: When the first character of the registration mark is a LETTER, it MUST be preceded by a HYPHEN (e.g. G-ABCD, EC-MNA, F-GZTA). In the USA, 'N' followed by numbers requires no hyphen (e.g. N12345).
- Common Mark: Assigned by ICAO to the common mark registering authority of an international operating agency (such as Arab Air Cargo). Preceded by a symbol assigned by ICAO.

3. LOCATION AND MINIMUM SIZING RULES (ANNEX 7)

Location on Aircraft	Position Specifics	Min. Height	Orientation & Spacing
Wings (Lower Surface)	Port (left) half of lower wing surface.	At least 30 cm (300 mm)	Tops of letters directed toward leading edge.
Fuselage / Vertical Tail	Each side of fuselage (between wings and tail) OR upper halves of vertical tail surfaces.	At least 30 cm (300 mm)	If multi-tail, displayed on outer sides of outer vertical fins.
Lighter-than-Air (Airships)	Tail surface or envelope.	At least 50 cm (500 mm)	Visible from ground and both sides.
Lighter-than-Air (Balloons)	Two places near maximum diameter on opposite sides.	At least 50 cm (500 mm)	Equatorial position.

Lettering Proportions & Typography Standards

- Letters must be capital letters in Roman characters without ornamentation. - Width of each character (except I and 1) shall be 2/3 of its height. - Thickness of lines (stroke) shall be 1/6 of the character height. - Spacing between characters shall not be less than 1/4 of a character width, nor more than 1/2 of character width.

4. THE AIRCRAFT IDENTIFICATION PLATE

Every aircraft engaged in international air navigation must carry an identification plate inscribed with its nationality mark and registration mark: - Material: Must be made of FIREPROOF METAL or other fireproof material of suitable physical properties. - Location: Secured in a prominent position NEAR THE MAIN ENTRANCE of the aircraft.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: Can an aircraft be validly registered in more than one State at the same time?

- [A]: Yes, in up to 3 States with bilateral approval.
- [B]: NO, dual registration is strictly prohibited by Article 18.
- [C]: Yes, if operated under wet lease.
- [D]: Only within EU Member States.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Article 18 of the Chicago Convention explicitly prohibits dual registration.

Q2: Who allocates the series of nationality mark symbols used by States?

- [A]: ICAO
- [B]: The International Telecommunication Union (ITU)
- [C]: EASA
- [D]: United Nations Security Council

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Nationality marks are selected from radio call sign series allocated by the ITU.

Q3: What is the minimum height of registration marks displayed on aeroplane wings?

- [A]: 15 cm
- [B]: 30 cm (300 mm)
- [C]: 50 cm
- [D]: 60 cm

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Annex 7 specifies at least 30 cm for wings and fuselage of heavier-than-air aircraft (50 cm for airships/balloons).

Q4: Which of the following letter combinations is strictly prohibited in an aircraft registration mark?

- [A]: EC-ABC
- [B]: G-PAN
- [C]: D-AIBA

- [D]: F-GLZK

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Combinations that can be confused with distress signals (PAN, SOS, XXX, TTT) or Q-codes (QAA-QNZ) are strictly prohibited.

Q5: Where must the fireproof aircraft identification plate be located?

- [A]: Inside the cockpit on the instrument panel
- [B]: On the exterior near the main entrance
- [C]: Inside the main landing gear bay
- [D]: On the vertical fin next to the registration mark

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under Annex 7, the identification plate must be secured in a prominent position near the main entrance.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 4: Flight Crew Licensing & Medical

Syllabus Source: CAE Oxford (pp. 67-100) | Pass Target: >= 90% AviationExam

1. EUROPEAN REGULATORY FRAMEWORK (PART-FCL)

Flight Crew Licensing in Europe is governed by Commission Regulation (EU) No 1178/2011 (Part-FCL). A licence grants basic piloting privileges, but is valid **ONLY** when accompanied by a valid Class or Type Rating, a valid Medical Certificate, and proof of language proficiency (ICAO English Level 4 minimum).

2. LICENCES: AGE LIMITS, EXPERIENCE & PRIVILEGES

Licence	Min Age	Minimum Experience Requirements	Privileges & Limitations
LAPL(A)	17 years	30 hours flight time (15 dual, 6 solo).	Light Aircraft Pilot Licence. Max 2,000 kg MTOM, max 4 persons, non-commercial only. Valid only in EASA Member States (non-ICAO).
PPL(A)	17 years	45 hours flight time (25 dual, 10 solo including 5 solo cross-country with 1 qualifying flight >= 150 NM with 2 landings).	Private Pilot Licence. Fly without remuneration as PIC or co-pilot in non-commercial ops. ICAO Annex 1 compliant. (Exception: can receive payment if working as authorized FI or FE).
CPL(A)	18 years	Modular: 200 hours (or Integrated: 150 hours). Breakdown: 100 hrs PIC, 20 hrs cross-country PIC with 300 NM flight, 10 hrs instrument, 5 hrs night.	Commercial Pilot Licence. Exercise all PPL privileges; act as PIC in commercial air transport on single-pilot aeroplanes; act as co-pilot in multi-pilot aeroplanes.
MPL(A)	18 years	Minimum 240 hours of flight and simulator training in an approved course.	Multi-crew Pilot Licence. Exercise co-pilot privileges in commercial air transport restricted to multi-pilot aeroplanes.
ATPL(A)	21 years	1,500 hours total flight time (see detailed breakdown below).	Airline Transport Pilot Licence. Act as PIC or co-pilot in commercial air transport on multi-pilot aeroplanes.

ATPL(A) 1,500-Hour Mandatory Breakdown (AviationExam Core)

To qualify for the issue of an ATPL(A), the applicant must complete at least 1,500 hours of flight time including:

- 500 hours in multi-pilot operations on aeroplanes.
- 250 hours as PIC, OR at least 500 hours as PICUS (PIC Under Supervision), OR 70 hours PIC and the remainder as PICUS.
- 200 hours of cross-country flight time, of which at least 100 hours must be as PIC or PICUS.
- 75 hours of instrument flight time, of which a maximum of 30 hours may be instrument ground time (FSTD).
- 100 hours of night flight as PIC or co-pilot.

[!] EXAM TRAP (AVIATIONEXAM) - Commercial Remuneration for PPL Holders

Can a PPL holder receive remuneration for flying? Answer: NO, as a general rule.

EXCEPTION: A PPL holder who holds an authorized Flight Instructor (FI) or Flight Examiner (FE) certificate may receive remuneration for providing flight instruction or testing.

3. RATINGS: CLASS, TYPE, INSTRUMENT (IR) & REVALIDATION

- **Class Rating:** Authorizes pilot on non-complex, single-pilot aeroplanes: SEP (Single Engine Piston - valid 2 years), MEP (Multi Engine Piston - valid 1 year), TMG (Touring Motor Glider).
- **Type Rating:** Required for: 1) Each multi-pilot aeroplane (e.g. A320, B737), 2) Single-pilot high-performance complex aeroplanes. Valid 1 year.
- **Instrument Rating (IR):** Authorizes flight under IFR with Category I minimums (DH $\geq$ 200 ft). Valid 1 year.

Revalidation vs Renewal (Crucial Regulatory Distinction)

- **Revalidation:** The administrative action taken within the period of validity of a rating which allows the holder to continue to exercise the privileges (performed BEFORE expiry).
- **Renewal:** The administrative action taken AFTER a rating has expired for the purpose of renewing the privileges. Requires refresher training at an ATO + proficiency check with examiner.

[!] EXAM TRAP (AVIATIONEXAM) - SEP Class Rating Revalidation Rules (Very Frequently Tested)

For revalidation of a Single-Engine Piston (SEP) class rating by experience, the pilot must within the 12 MONTHS preceding the expiry date of the rating: 1. Complete at least 12 HOURS of flight time, including: - 6 hours as PIC; - 12 take-offs and 12 landings; AND - A training flight of at least 1 HOUR with a Flight Instructor (FI). OR: Pass a proficiency check with an examiner within the 3 months preceding expiry.

4. RECENT EXPERIENCE REQUIREMENTS (PART-FCL.060)

A pilot shall NOT act as PIC or co-pilot carrying passengers unless:

- **Day Flight:** Has carried out at least 3 take-offs and 3 landings in the preceding 90 DAYS on the same class/type or approved FSTD.
- **Night Flight:** Has carried out at least 1 take-off and 1 landing at NIGHT in the preceding 90 DAYS as flying pilot, UNLESS holding an active Instrument Rating (IR).

5. PART-MED: MEDICAL CERTIFICATION & VALIDITY

Medical Class	Applies To	Standard Validity & Age Reductions
Class 1	CPL, ATPL, MPL (Commercial Air Transport)	12 months (Under 60 years). Reduced to 6 months if: aged 60+, OR aged 40+ in single-pilot commercial passenger operations.
Class 2	PPL, Sailplane, Balloon (Private flying)	60 months (Under 40 years). 24 months (40 to 49 years). 12 months (50 years and over).
LAPL	LAPL(A), LAPL(H)	60 months (Under 40 years). 24 months (40 years and over).

Decrease in Medical Fitness: Mandatory Reporting

A pilot MUST notify the Aero-Medical Examiner (AME) and suspend flight privileges in cases of: - Hospital admission or clinic stay exceeding 12 hours. - Any significant surgical operation or invasive procedure. - Illness causing incapacity to fly for 21 DAYS or more (Class 1) or 30 DAYS or more (Class 2/LAPL). - Pregnancy: Pilot may fly until end of the 26th week of gestation under multi-pilot ops with Class 1 medical.

6. AGE LIMITATIONS FOR COMMERCIAL OPERATIONS (PART-FCL.065)

[!] EXAM TRAP (AVIATIONEXAM) - The Rule of 60 and 65 (Part-FCL.065)

- Age 60 to 64: A pilot licence holder who has reached age 60 shall NOT act as pilot in commercial air transport EXCEPT as member of a multi-pilot crew, and provided the other pilot is UNDER 60 YEARS OF AGE. - Age 65: Absolute cutoff. No pilot aged 65 or over may act as pilot in commercial air transport.

7. ATPL THEORY VALIDITY & CREDITING RULES

- ATPL Theoretical Knowledge Examination Pass: Remains valid for the issue of a CPL(A) or IR(A) for a period of 36 MONTHS from the day the pilot successfully passes all theoretical exams. - IR Validity to ATPL: Provided an IR(A) or type rating is kept valid (or renewed within 7 years of last expiry), the ATPL theoretical examination credits remain valid indefinitely for the issue of an ATPL(A). - Multi-Crew Cooperation (MCC): Mandatory before flying multi-pilot aircraft. 25 hours theoretical instruction and at least 20 hours simulator (or 16 hours in FNPT II).

8. PART-MED CLINICAL EXAMINATION STANDARDS

Clinical Parameter	Regulatory Medical Standards (EASA Part-MED Class 1)
Visual Acuity	Distant visual acuity 6/9 (0.7) in each eye, 6/6 (1.0) with both eyes. Refractive error limits: +5.0 to -6.0 diopters. Astigmatism max 2.0 diopters. Spare pair of glasses mandatory.
Color Vision	Normal trichromatic color vision required. Tested with Ishihara 24 plates (must pass 15 plates on first try). If failed, advanced testing (CAD test / Anomaloscope) required.
Hearing (Audiometry)	Pure tone audiometry: Max hearing loss of 20 dB at 500, 1000, 2000 Hz; max 35 dB at 3000 Hz in each ear separately.
Cardiovascular (ECG)	Standard resting 12-lead ECG required at initial exam, every 5 years up to age 30, every 2 years up to age 40, annually up to age 50, and at all subsequent medicals.
Alcohol & Drugs	Blood Alcohol Concentration (BAC) limit: 0.20 g/l (0.02%). Bottle-to-throttle rule: Minimum 8 hours between alcohol consumption and flight duty.

9. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the total flight time required for the issue of an ATPL(A)?

- [A]: 500 hours
- [B]: 1,000 hours
- [C]: 1,500 hours
- [D]: 2,000 hours

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. 1,500 hours total flight time is mandatory for ATPL(A), including 500 hours multi-pilot and 250 hours PIC (or 500 PICUS).

Q2: What is the validity of a Class 1 medical certificate for a 45-year-old pilot flying single-pilot commercial pas

- [A]: 6 months

- [B]: 12 months
- [C]: 24 months
- [D]: 60 months

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Under Part-MED, Class 1 validity is reduced from 12 months to 6 months for pilots aged 40 and over operating single-pilot commercial passenger operations (or age 60+ in any commercial air transport).

Q3: What are the recent experience requirements to carry passengers by day under Part-FCL.060?

- [A]: 3 take-offs and landings in the preceding 60 days
- [B]: 3 take-offs and landings in the preceding 90 days
- [C]: 5 take-offs and landings in the preceding 90 days
- [D]: 10 hours in the preceding 30 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The pilot must have completed at least 3 take-offs and landings as flying pilot on the same type/class or FSTD in the preceding 90 days.

Q4: Under what conditions may a pilot aged 62 act as pilot in commercial air transport?

- [A]: In single-pilot operations only
- [B]: As a member of a multi-pilot crew, provided the other pilot is under 60
- [C]: Never, commercial operations stop at 60
- [D]: Only during domestic daytime flights

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Between ages 60 and 64, commercial air transport is permitted only in a multi-pilot crew where the other pilot is under age 60.

Q5: What is the revalidation requirement by experience for a Single-Engine Piston (SEP) class rating?

- [A]: 10 hours flight time in the preceding 6 months
- [B]: 12 hours flight time including 6 hours PIC, 12 take-offs/landings, and 1 hour with an FI within the preceding 12 months
- [C]: Passing a theoretical examination every 2 years
- [D]: 3 take-offs and landings within the preceding 90 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. SEP revalidation by experience requires 12 hours (6 PIC, 12 take-offs/landings, 1 hour training flight with FI) within the 12 months preceding expiry.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 5: Rules of the Air & SERA

Syllabus Source: CAE Oxford (pp. 101-156) | Pass Target: >= 90% AviationExam

1. REGULATORY AUTHORITY & PIC RESPONSIBILITIES (SERA)

Standard European Rules of the Air (SERA) are established by Commission Implementing Regulation (EU) No 923/2012 and ICAO Annex 2. The Pilot-in-Command (PIC) has final authority over the disposition of the aircraft and is responsible for compliance with the rules of the air, but may deviate in an emergency in the interest of safety.

2. VISUAL METEOROLOGICAL CONDITIONS (VMC) MINIMA TABLE

VMC minima define when a flight may proceed under Visual Flight Rules (VFR). AviationExam questions strictly test exact cloud distance and visibility numbers across airspace classes:

Altitude / Level Band	Airspace Classes	Min. Flight Visibility	Distance from Clouds
FL 100 and above	Classes A, B, C, D, E, F, G	8 km	1,500 m horizontal, 1,000 ft (300 m) vertical.
Below FL 100 (or above 3,000 ft AMSL whichever is higher)	Classes B, C, D, E, F, G (Class A: IFR only)	5 km	1,500 m horizontal, 1,000 ft (300 m) vertical.
At or below 3,000 ft AMSL (or 1,000 ft AGL whichever is higher)	Classes F and G	5 km*	Clear of clouds and with the surface in sight. (*Reduced to 1,500 m if speed <= 140 kt IAS).

[!] EXAM TRAP (AVIATIONEXAM) - VFR in Class A Airspace & Special VFR (CTR)

1. Airspace Class A: VFR flights are STRICTLY PROHIBITED (IFR only). 2. Special VFR (Control Zone CTR only): Granted by ATC when weather is below VMC: - Ground visibility: at least 1,500 m (800 m for helicopters); - Ceiling: at least 600 ft (180 m); - Clear of clouds and in sight of the surface; - Maximum indicated airspeed: 140 kt IAS.

3. MINIMUM SAFE HEIGHTS FOR VFR FLIGHTS

- Congested Areas (Cities, Towns, Open-Air Gatherings): At least 1,000 ft (300 m) above the highest obstacle within a 600 m radius of the aircraft, and high enough to permit safe emergency landing.
- Other Areas (Rural / Sea): At least 500 ft (150 m) above ground or water, or 500 ft above the highest obstacle within 150 m of the aircraft.

4. SEMICIRCULAR CRUISING LEVELS (SERA.5015)

Cruising levels are based on MAGNETIC TRACK. In RVSM airspace (FL 290 to FL 410), vertical separation is 1,000 ft:

Magnetic Track	IFR Cruising Levels	VFR Cruising Levels (Above 3,000 ft)
Track 000° to 179° (EAST)	ODD Flight Levels (FL 050, 070, 090, 110, 130...)	ODD + 500 ft (FL 055, 075, 095, 115...)

**Track 180° to 359°
(WEST)**

EVEN Flight Levels (FL 060, 080, 100,
120, 140...)

EVEN + 500 ft (FL 065, 085, 105,
125...)

5. RIGHT-OF-WAY RULES (COLLISION AVOIDANCE)

- Hierarchy: Balloons > Gliders > Airships > Power-driven aircraft. (Aircraft towing another has right of way over power-driven aircraft).
- Converging: When two aircraft converge at approximately the same level, the aircraft having the other on its RIGHT shall give way.
- Approaching Head-on: Each aircraft shall alter its heading to the RIGHT.
- Overtaking: The aircraft being overtaken has right-of-way. The overtaking aircraft keeps clear by altering heading to the RIGHT.
- Landing: Aircraft in flight or on ground shall give way to aircraft landing or in final approach. Between two approaching to land, the LOWER aircraft has right of way, but shall not cut in.

6. AIRCRAFT LIGHTS (SERA.3215)

Navigation lights must be displayed from SUNSET TO SUNRISE (and any other period prescribed by authority):

- Port Wing Light: RED light showing an unbroken arc of 110° from dead ahead to port.
- Starboard Wing Light: GREEN light showing an unbroken arc of 110° from dead ahead to starboard.
- Tail Light: WHITE light showing an unbroken arc of 140° visible aft.
- Anti-Collision Lights: Flashing red or white light displayed by day and night to indicate operating engines.

7. ATC LIGHT GUN SIGNALS (TOWER TO AIRCRAFT)

Light Signal	Meaning to Aircraft IN FLIGHT	Meaning to Aircraft ON GROUND
Steady Green	Cleared to land	Cleared for take-off
Flashing Green	Return for landing (followed by steady green)	Cleared to taxi
Steady Red	Give way to other aircraft and continue circling	STOP immediately
Flashing Red	Aerodrome unsafe, DO NOT LAND	Taxi clear of runway in use
Flashing White	Land at this aerodrome and proceed to apron	Return to starting point on aerodrome
Red Pyrotechnic	Notwithstanding previous instructions, DO NOT LAND for the time being	--

8. VISUAL GROUND SIGNALS IN AERODROME SIGNAL AREA

Ground Signal Symbol	Official Meaning & Requirement (Annex 14 / SERA)
Red square with yellow diagonals	Landings prohibited; prohibition is likely to be prolonged.
Red square with one yellow diagonal	Special precautions landing: state of maneuvering area poor, land with care.
White dumb-bell	Landings, take-offs, and taxiing must be confined to paved/hard surfaces.
White dumb-bell with black bars	Take-offs and landings on runways only, but other movements not confined to paved taxiways.
White cross on runway/taxiway	Runway or taxiway unserviceable; closed to all aircraft movements.

Landing T (White or Orange)	Landings and take-offs shall be in a direction parallel to the shaft toward the crossarm.
Tetrahedron (White or Orange)	Indicates landing direction: aircraft lands in direction towards which apex points.
Arrow on runway (Yellow/White)	Preceding area before displaced threshold fit for taxi and take-off, but NOT for landing.

9. MARSHALLING SIGNALS (ANNEX 2 / SERA.3301)

Signal Action	Marshaller Visual Description & Crew Action
Wingman / Identify Gate	Raise right arm fully vertical, wand pointing up; left wand pointed horizontally toward gate.
Straight Ahead	Bend arms repeatedly upward and backward from elbows with wands pointing up.
Turn Left	Point left arm and wand down; move right arm repeatedly upward/backward.
Turn Right	Point right arm and wand down; move left arm repeatedly upward/backward.
Normal Stop	Cross arms and wands overhead rapidly with wands crossed.
Emergency Stop	Abruptly cross arms overhead and wave wands vigorously side to side.
Insert Chocks	Arms extended palms inwards; swing arms from outwards to cross below waist.
Cut Engines	Extend arm with wand at throat level; draw wand across throat in slicing motion.

10. INTERCEPTION PROCEDURES (ANNEX 2 / SERA)

[!] EXAM TRAP (AVIATIONEXAM) - Interception of Civil Aircraft (AviationExam Core)

- Interception is a measure of last resort. - Intercepted aircraft must immediately: 1) Follow instructions given by intercepting aircraft; 2) Notify ATS unit immediately; 3) Squawk Mode A Code 7700 (unless instructed otherwise); 4) Monitor emergency frequency 121.5 MHz (and 243.0 MHz). - Interceptor Day Signals: - Rocking wings and slow left turn: 'You have been intercepted, follow me'. Response: Rocking wings ('Understood, will comply'). - Abrupt breakaway climb and turn: 'You may proceed'.

11. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What does a flashing red light from the aerodrome control tower indicate to an aircraft in flight?

- [A]: Cleared to land
- [B]: Aerodrome unsafe, DO NOT LAND
- [C]: Give way to other aircraft and continue circling
- [D]: Return for landing

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Flashing red in flight means aerodrome unsafe, do not land (steady red means give way and continue circling).

Q2: In Class G airspace at 2,000 ft AMSL, what are the VMC minima for an aeroplane flying at 130 kt IAS?

- [A]: 8 km visibility and 1,500 m horizontal from clouds

- [B]: 5 km visibility, 1,500 m horizontal, 1,000 ft vertical
- [C]: 1,500 m visibility, clear of clouds and in sight of the surface
- [D]: Special VFR clearance required

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. At or below 3,000 ft AMSL (or 1,000 ft AGL) in Class F/G, VMC visibility is 5 km, but may be reduced to 1,500 m if speed is ≤ 140 kt, clear of clouds and surface in sight.

Q3: What visual aerodrome signal indicates that landings are prohibited?

- [A]: A red square with a single yellow diagonal
- [B]: A red square with two yellow diagonals
- [C]: A white dumb-bell
- [D]: A landing T

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A red square with yellow cross diagonals signifies that landings are prohibited and prohibition is likely prolonged.

Q4: Two power-driven aircraft are converging at approximately the same altitude. Which aircraft has the right of way?

- [A]: The faster aircraft
- [B]: The aircraft that has the other on its right
- [C]: The aircraft that has the other on its left
- [D]: The heavier aircraft

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. The aircraft which has the other on its right shall give way; therefore, the aircraft that has the other on its left has right of way.

Q5: What are the minimum weather conditions for a Special VFR flight in a CTR?

- [A]: Ground visibility $\geq 1,500$ m, ceiling ≥ 600 ft, clear of clouds, ground in sight
- [B]: Visibility ≥ 5 km, clear of clouds
- [C]: Visibility ≥ 800 m and ceiling $\geq 1,000$ ft
- [D]: Any condition provided IFR traffic is absent

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Under SERA, Special VFR requires ground visibility $\geq 1,500$ m (800 m helo) and cloud ceiling ≥ 600 ft.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 6: Instrument Departures (SID & NADP)

Syllabus Source: CAE Oxford (pp. 157-172) | Pass Target: >= 90% AviationExam

1. PANS-OPS DEPARTURE DESIGN GRADIENTS

Instrument departure procedures (ICAO Doc 8168 PANS-OPS) provide obstacle clearance from the end of the runway until the aircraft reaches the minimum en-route altitude (MEA). Design assumes all engines operating.

[*] OFFICIAL DEFINITION - Procedure Design Gradient (PDG) = 3.3%

The standard PANS-OPS Procedure Design Gradient (PDG) is 3.3% (~200 ft/NM). It consists of: 1. Obstacle Identification Surface (OIS): 2.5% 2. Obstacle Clearance Margin: 0.8% -> Total Standard PDG = 3.3%. A steeper climb gradient is published ONLY if required by obstacles or airspace.

2. STRAIGHT VS TURNING DEPARTURES

- Screen Height at DER: The departure procedure assumes the aircraft crosses the Departure End of Runway (DER) at a minimum screen height of 5 m (16 ft) with wings level.
- Straight Departure: Track does not diverge by more than 15° from runway centerline heading.
- Turning Departure: Specified whenever track requires a turn of MORE THAN 15°. No turn shall be initiated below 120 m (394 ft) above aerodrome elevation (or DER).
- Turn Design Parameters: Average bank angle: 15° (max 21°). Speed limits are specified per category.

3. NOISE ABATEMENT DEPARTURE PROCEDURES (NADP 1 VS NADP 2)

ICAO Annex 6 and PANS-OPS define two standardized noise abatement departure procedures for jet aeroplanes:

Procedure	Climb Profile & Flap Retraction Schedule
NADP 1 (Noise Close to Aerodrome)	Climb at V2 + 10 to 20 kt with take-off flaps to 800 ft (or higher). At 800 ft to 3,000 ft, reduce to climb thrust, maintain climb speed with flaps intact. At 3,000 ft, accelerate and retract flaps.
NADP 2 (Noise Distant from Aerodrome)	Climb at V2 + 10 to 20 kt to 800 ft. At 800 ft, accelerate while retracting flaps on schedule, then reduce to climb thrust. Continue climb to 3,000 ft.

4. OMNIDIRECTIONAL DEPARTURES & OBSTACLE CLEARANCES

Used when no specific SID route is published. The departure is divided into two distinct phases: - Phase 1: Aircraft climbs straight ahead on runway centerline to at least 120 m (394 ft) above aerodrome elevation. - Phase 2: Aircraft initiates turn towards the en-route track while maintaining at least 3.3% PDG. - Obstacle clearance: 90 m (295 ft) MOC provided throughout the turn area, increasing with distance from aerodrome.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the standard Procedure Design Gradient (PDG) under PANS-OPS for instrument departures?

- [A]: 2.5%
- [B]: 3.3%
- [C]: 5.0%
- [D]: 6.5%

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The standard PDG is 3.3% (consisting of 2.5% Obstacle Identification Surface + 0.8% safety margin).

Q2: What is the assumed screen height over the Departure End of Runway (DER)?

- [A]: 0 m
- [B]: 5 m (16 ft)
- [C]: 10.7 m (35 ft)
- [D]: 15 m (50 ft)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. PANS-OPS assumes 5 m (16 ft) screen height over DER (Note: CS-25 engine-out performance assumes 35 ft, but PANS-OPS obstacle assessment starts at 5 m).

Q3: What is the minimum altitude above aerodrome elevation before a turn may be initiated on a turning departure?

- [A]: 90 m (295 ft)
- [B]: 120 m (394 ft)
- [C]: 150 m (492 ft)
- [D]: 300 m (984 ft)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. No turn shall be initiated below 120 m (394 ft) above the elevation of the aerodrome.

Q4: Which noise abatement departure procedure provides noise relief for areas close to the aerodrome?

- [A]: NADP 1
- [B]: NADP 2
- [C]: Continuous Descent Departure
- [D]: Balanced Field Take-off

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. NADP 1 provides noise relief close to the airport by maintaining flaps and climbing steeply to 3,000 ft before accelerating.

Q5: What average bank angle is assumed in the design of turning departures under PANS-OPS?

- [A]: 10°
- [B]: 15° (maximum 21°)
- [C]: 25°
- [D]: 30°

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. PANS-OPS departure design assumes an average bank angle of 15°, not to exceed 21°.

Q6: In an omnidirectional departure, what is the minimum height above aerodrome elevation before initiating a

- [A]: 90 m
- [B]: 120 m (394 ft)
- [C]: 150 m
- [D]: 300 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In Phase 1 of an omnidirectional departure, the aircraft must climb straight ahead on runway heading to at least 120 m (394 ft) before beginning any turn.

Q7: Under what circumstances is a departure climb gradient steeper than the standard 3.3% published on a SI

- [A]: Always for jet aircraft operations
- [B]: When dictated by obstacle clearance requirements or airspace restrictions
- [C]: Only during summer high-temperature operations
- [D]: Whenever the runway length is less than 2,000 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A gradient steeper than the standard 3.3% PDG is published only when required by obstacles in the climb path or by ATC airspace constraints.

Chapter 7: Approach Procedures & ILS Minima

Syllabus Source: CAE Oxford (pp. 173-206) | Pass Target: >= 90% AviationExam

1. THE FIVE APPROACH SEGMENTS

Under ICAO Doc 8168 (PANS-OPS), an instrument approach procedure is divided into up to five distinct segments. Each segment begins and ends at designated fixes, with specific obstacle clearance margins (MOC):

Approach Segment	Fix Boundaries	Operational Purpose & Minimum Obstacle Clearance (MOC)
1. Arrival Segment	En-route airway to Initial Approach Fix (IAF)	Transitions aircraft from en-route ATS route to the terminal area. Often defined by a Standard Terminal Arrival (STAR). MOC conforms to en-route criteria.
2. Initial Segment	IAF to Intermediate Fix (IF)	Provides initial descent and maneuvering to align with the intermediate approach. MOC is at least 300 m (984 ft) in the primary area. Reversal or racetrack procedures occur in this segment.
3. Intermediate Segment	IF to Final Approach Fix (FAF / FAP)	The segment where aircraft configuration and speed are adjusted for final approach. Optimum descent gradient is FLAT (max gradient 5.2% / 3.0°). MOC tapers from 300 m down to 150 m (492 ft).
4. Final Approach Segment	FAF / FAP to Runway Threshold or MAPt	Precision Approach: Guided by ILS/MLS glidepath to Decision Altitude/Height (DA/H). Non-Precision: Guided by VOR/NDB/LOC to Minimum Descent Altitude/Height (MDA/H).
5. Missed Approach Segment	MAPt or DA/H to holding fix or en-route	Executed if visual reference is not established. Divided into 3 PHASES: Initial (no turn permitted), Intermediate (climb at 2.5% gradient, MOC 30 m), and Final (climb to safe level, MOC 50 m).

2. AIRCRAFT APPROACH CATEGORIES (A, B, C, D, E)

Aircraft categories are determined by Vat, which is the indicated airspeed at the runway threshold. Vat equals the stall speed in landing configuration (Vso) multiplied by 1.3, or 1.23 x Vs1g, at maximum certified landing mass:

Category	Vat Threshold Speed Range	Representative Aircraft Models
Category A	Less than 91 kt	Light singles and twins (Cessna 172, Piper PA-28, DA-42)
Category B	91 kt to 120 kt	Heavy twins, regional turboprops (King Air, ATR-42, ATR-72, Dash-8)
Category C	121 kt to 140 kt	Medium commercial airliners (Airbus A320, Boeing 737, Embraer 190)
Category D	141 kt to 165 kt	Heavy wide-body airliners (Boeing 777, 747, 787, Airbus A330, A350)
Category E	166 kt to 210 kt	Special high-performance military and experimental aircraft

3. REVERSAL & RACETRACK MANEUVERS

- 45°/180° Procedure Turn: Fly outbound on reversal track, turn 45° off track, fly for 1 MINUTE (Categories A and B) or 1 MIN 15 SEC (Categories C, D, and E), then execute a 180° turn in the opposite direction to intercept inbound track.
- 80°/260° Procedure Turn: Fly outbound on reversal track, turn 80° off track, immediately followed by a 260° turn in the opposite direction to intercept the inbound track.
- Base Turn: Aircraft flies outbound on a specified radial or dead reckoning track, then executes a turn to intercept the final approach track.
- Racetrack Procedure: Aircraft flies outbound parallel to inbound track for a specified time (1 to 3 minutes), then makes a turn to intercept the inbound track.

4. EXHAUSTIVE ILS PRECISION APPROACH MINIMA (CAT I TO CAT IIIC)

Precision approaches provide continuous electronic glidepath and azimuth guidance. Official EASA minima:

ILS Category	Decision Height (DH)	Minimum Runway Visual Range (RVR)
Category I (Cat I)	Not lower than 200 ft (60 m)	Not less than 550 m RVR (or 800 m visibility without RVR)
Category II (Cat II)	Lower than 200 ft but not lower than 100 ft (30 m)	Not less than 300 m RVR
Category IIIA (Cat IIIA)	Lower than 100 ft or NO Decision Height	Not less than 175 m RVR
Category IIIB (Cat IIIB)	Lower than 50 ft or NO Decision Height	Less than 175 m but not less than 50 m RVR
Category IIIC (Cat IIIC)	NO Decision Height	NO Runway Visual Range limitations (Zero-Zero)

[!] EXAM TRAP (AVIATIONEXAM) - DA/H vs MDA/H and the Missed Approach Initiation

- Decision Altitude/Height (DA/H): Used in PRECISION approaches. If visual reference is not established upon reaching DA/H, an IMMEDIATE MISSED APPROACH must be initiated. The aircraft may dip slightly below DA/H during the go-around.
- Minimum Descent Altitude/Height (MDA/H): Used in NON-PRECISION approaches. The aircraft MUST NEVER descend below MDA/H without visual reference. Level flight at MDA is permitted until reaching the Missed Approach Point (MAPt).

5. CONTINUOUS DESCENT FINAL APPROACH (CDFA)

CDFA is a technique for flying the final approach segment of a non-precision instrument approach procedure as a continuous descent, without level-offs, from an altitude/height at or above the FAF to a point approximately 15 m (50 ft) above the landing runway threshold or to the point where the missed approach is initiated. Under EASA Air Operations (Part-CAT), CDFA is mandatory for non-precision approaches unless approved otherwise.

6. AVIATIONEXAM REAL EXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the minimum Runway Visual Range (RVR) for an ILS Category I approach?

- [A]: 300 m
- [B]: 550 m
- [C]: 800 m

- [D]: 175 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under EASA CS-AWO and Part-CAT, the standard minimum RVR for an ILS Category I precision approach is 550 m (or 800 m flight visibility if no RVR system is available).

Q2: In a precision approach, what must be done if visual reference is not established at the Decision Altitude/H

- [A]: Level off and fly to the MAPt before executing go-around.
- [B]: Initiate an immediate missed approach.
- [C]: Descend an additional 50 ft to search for approach lights.
- [D]: Revert to localizer-only non-precision minimums.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. At DA/H on a precision approach, an immediate go-around must be initiated without delay if visual reference is not established. Level flight at DA/H is strictly prohibited.

Q3: What Vat speed range corresponds to Aircraft Category C?

- [A]: Less than 91 kt
- [B]: 91 kt to 120 kt
- [C]: 121 kt to 140 kt
- [D]: 141 kt to 165 kt

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Category C Vat is 121 to 140 kt (representative of Airbus A320 and Boeing 737 at maximum landing mass).

Q4: What is the Minimum Obstacle Clearance (MOC) provided in the intermediate approach segment?

- [A]: 300 m (984 ft)
- [B]: 150 m (492 ft)
- [C]: 90 m (295 ft)
- [D]: 50 m (164 ft)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In the intermediate segment, MOC is 150 m in the primary area, reducing from the 300 m MOC of the initial approach segment.

Q5: During a 45°/180° procedure turn for a Category C aeroplane, how long must the outbound leg be flown aft

- [A]: 1 minute
- [B]: 1 minute 15 seconds
- [C]: 1 minute 30 seconds
- [D]: 2 minutes

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. PANS-OPS specifies 1 min for Categories A and B, and 1 min 15 sec for Categories C, D, and E.

Q6: What is the standard design climb gradient for the intermediate and final phases of a missed approach?

- [A]: 2.0%
- [B]: 2.5%
- [C]: 3.3%
- [D]: 5.0%

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Standard missed approach design climb gradient under PANS-OPS is 2.5%.

Q7: Under Category II ILS operations, what is the allowable Decision Height range?

- [A]: 200 ft to 150 ft
- [B]: Lower than 200 ft but not lower than 100 ft
- [C]: Lower than 100 ft but not lower than 50 ft
- [D]: No Decision Height

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Category II Decision Height is between 100 ft and 200 ft (RVR not less than 300 m).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 8: Circling Approach Procedures

Syllabus Source: CAE Oxford (pp. 207-214) | Pass Target: >= 90% AviationExam

1. DEFINITION & OPERATIONAL CRITERIA

A circling approach is the visual phase of an instrument approach to bring an aircraft into position for landing on a runway which is not suitably located for a straight-in approach. A straight-in approach is considered unacceptable if the final approach track alignment differs from the runway centerline by MORE THAN 30°, or if the final descent gradient exceeds standard criteria (6.5% for Cat A/B, 6.1% for Cat C/D).

[*] OFFICIAL DEFINITION - Visual Reference Requirement in Circling

Visual reference to the runway environment (threshold, runway markings, or lights) must be MAINTAINED CONTINUOUSLY throughout the circling maneuver. The aircraft must remain at or above the circling MDA/H until positioned to make a normal landing on the intended runway.

2. CIRCLING AREA RADII & OBSTACLE CLEARANCE (MOC)

The circling area is constructed by drawing arcs from the threshold of each usable runway. The radius of the arc depends on the aircraft category speed (bank angle 20° or rate 3°/s):

Category	Max Circling Speed	Circling Radius from Thresholds	Minimum Obstacle Clearance (MOC)
Cat A	100 kt	1.68 NM (3.11 km)	90 m (295 ft)
Cat B	135 kt	2.66 NM (4.93 km)	90 m (295 ft)
Cat C	180 kt	4.20 NM (7.78 km)	120 m (394 ft)
Cat D	205 kt	5.28 NM (9.78 km)	120 m (394 ft)
Cat E	240 kt	6.94 NM (12.85 km)	150 m (492 ft)

3. DESCENT BELOW CIRCLING MDA/H & MISSED APPROACH

Descent below circling MDA/H is permitted ONLY when: 1. Required visual reference to the runway environment is established and maintained; 2. The runway threshold is in sight to the pilot; 3. The aircraft is in a position from which a normal descent to landing can be made on the runway using normal maneuvers.

[!] EXAM TRAP (AVIATIONEXAM) - Loss of Visual Reference While Circling (Guaranteed Exam Question)

If visual reference is lost at any time while circling to land: 1. The pilot must initiate an IMMEDIATE CLIMBING TURN TOWARDS THE LANDING RUNWAY. 2. Establish the aircraft overhead the aerodrome to ensure terrain clearance. 3. Join and follow the published missed approach procedure for the INSTRUMENT RUNWAY initially used.

4. PROHIBITED CIRCLING SECTORS & TERRAIN BUFFERS

Where prominent obstacles or terrain exist in a specific sector around an aerodrome, visual maneuvering may be prohibited in that sector (e.g. 'Circling prohibited North of RWY 09/27'). - The pilot must strictly contain all circling flight within the permitted visual sector. - If cleared to circle, turning into a prohibited sector constitutes an immediate breach of ATC clearance and terrain clearance.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: When is an instrument approach classified as a circling approach?

- [A]: Whenever the wind on landing runway exceeds 15 kt.
- [B]: When final approach track alignment differs by more than 30° from runway centerline.
- [C]: Whenever the pilot requests a visual traffic circuit.
- [D]: Only when the cloud base is below 1,000 ft.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under PANS-OPS, if final approach track differs by > 30° from runway centerline, only circling minima are authorized.

Q2: What is the circling area radius for a Category C aircraft?

- [A]: 1.68 NM
- [B]: 2.66 NM
- [C]: 4.20 NM
- [D]: 5.28 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Cat C circling radius is 4.20 NM from runway thresholds (based on 180 kt max speed).

Q3: What is the Minimum Obstacle Clearance (MOC) provided in a Category C circling area?

- [A]: 90 m (295 ft)
- [B]: 120 m (394 ft)
- [C]: 150 m (492 ft)
- [D]: 300 m (984 ft)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Cat A and B have 90 m MOC; Cat C and D have 120 m MOC; Cat E has 150 m MOC.

Q4: If visual reference is lost while circling to land on runway 27 after an instrument approach on runway 09, what should the pilot do?

- [A]: Turn immediately towards runway 09 and descend.
- [B]: Make an immediate climbing turn towards runway 27 and join the missed approach for runway 09.
- [C]: Continue visually on downwind and attempt landing.
- [D]: Climb straight ahead on present heading to MSA.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The pilot must make an immediate climbing turn towards the landing runway (rwy 27) and establish overhead before following the missed approach for runway 09.

Q5: May a pilot descend below the circling MDA/H while still on the downwind leg?

- [A]: Yes, if the runway lights are visible
- [B]: NO, the aircraft must remain at or above circling MDA/H until aligned and in a normal descent position
- [C]: Yes, if cleared by ATC
- [D]: Only in daylight VMC

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Descent below circling MDA/H is prohibited until the aircraft is in a position from which a normal descent to landing can be executed.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 9: Holding Procedures & Standards

Syllabus Source: CAE Oxford (pp. 215-226) | Pass Target: >= 90% AviationExam

1. HOLDING PATTERN GEOMETRY & STANDARDS

- Standard Pattern: Racetrack pattern using RIGHT-HAND turns (non-standard pattern uses left-hand turns).
- Rate of Turn: 3° per second (Rate 1 turn) or 25° bank angle, whichever requires less bank.
- Outbound Timing: 1 MINUTE at or below 14,000 ft (4,250 m). 1.5 MINUTES above 14,000 ft.
- Timing Point: Outbound timing begins over or abeam the holding fix, whichever occurs later (or on wings level if abeam point cannot be identified).

2. MAXIMUM HOLDING SPEEDS (PANS-OPS / EASA)

Altitude Band	Normal Maximum Holding Speed	Turbulence Conditions
Up to 14,000 ft	230 kt (Cat A & B: 170 kt)	280 kt (or 0.8 Mach whichever is less)
Above 14,000 ft up to 20,000 ft	240 kt	280 kt (or 0.8 Mach whichever is less)
Above 20,000 ft up to 34,000 ft	265 kt	280 kt (or 0.8 Mach whichever is less)
Above 34,000 ft	0.83 Mach	0.83 Mach

3. THE THREE ENTRY SECTORS (WITH 5° BUFFER)

Entry is determined by the aircraft heading relative to the 3 entry sectors with a 5° flexibility buffer:

- Sector 1 (Parallel Entry - 110° sector): Fly to fix, turn to parallel outbound track on reciprocal heading, fly for 1 (or 1.5) min, turn left towards holding side to intercept inbound track.
- Sector 2 (Offset / Teardrop Entry - 70° sector): Fly to fix, turn to a heading 30° to the holding side, fly for 1 (or 1.5) min, turn right to intercept inbound track.
- Sector 3 (Direct Entry - 180° sector): Fly to fix, turn directly right to follow the holding pattern.

4. HOLDING IN MOUNTAINOUS TERRAIN & WIND DRIFT

[!] EXAM TRAP (AVIATIONEXAM) - Triple Drift Rule & Mountainous MOC

1. Triple Drift Rule: On the outbound leg, apply THREE TIMES (3x) the inbound drift angle in the opposite direction. 2. Mountainous Terrain MOC: Standard MOC in the primary holding area is 300 m (984 ft / 1,000 ft). In designated mountainous areas, the Minimum Obstacle Clearance is doubled to at least 600 m (2,000 ft).

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the maximum holding speed under PANS-OPS up to 14,000 ft in normal conditions?

- [A]: 210 kt
- [B]: 230 kt
- [C]: 240 kt
- [D]: 250 kt

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under PANS-OPS, normal max holding speed up to 14,000 ft is 230 kt (170 kt for Cat A/B).

Q2: When does outbound timing begin in a holding pattern if the abeam position cannot be determined?

- [A]: Passing 90° to the holding track.
- [B]: Immediately upon wings level on outbound heading.
- [C]: 30 seconds after initiating the turn.
- [D]: When crossing the holding radial on DME.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Outbound timing begins over or abeam the fix, or upon wings level if the abeam position cannot be identified.

Q3: What angular size corresponds to Sector 2 (Offset / Teardrop entry)?

- [A]: 70°
- [B]: 110°
- [C]: 180°
- [D]: 90°

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Sector 1 (Parallel) is 110°; Sector 2 (Offset) is 70°; Sector 3 (Direct) is 180°.

Q4: If an aircraft applies 4° left drift correction on the inbound leg, what drift correction should be applied on the outbound leg?

- [A]: 4° right
- [B]: 8° right
- [C]: 12° right
- [D]: 16° right

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under the triple drift rule, outbound drift is 3 x inbound drift = 3 x 4° = 12° in the opposite direction (right).

Q5: What is the maximum holding speed above 14,000 ft up to 20,000 ft under PANS-OPS in turbulence?

- [A]: 240 kt
- [B]: 280 kt (or 0.8 Mach whichever is less)
- [C]: 300 kt
- [D]: 265 kt

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In turbulence, maximum holding speed is 280 kt or 0.8 Mach (whichever is less) up to FL 340.

Q6: What is the width of the buffer area extending beyond the boundary of the primary holding area under PANS-OPS?

- [A]: 2.5 NM
- [B]: 5.0 NM
- [C]: 8.0 NM
- [D]: 10.0 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The buffer area extends 5.0 NM beyond the primary holding area boundary; obstacle clearance tapers to zero at the outer edge.

Q7: What is the maximum holding speed under PANS-OPS above 34,000 ft in all flight conditions?

- [A]: 265 kt
- [B]: 280 kt
- [C]: 0.83 Mach
- [D]: 0.88 Mach

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under PANS-OPS, the maximum holding speed above FL 340 is 0.83 Mach.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 10: Altimeter Setting & Temperature Error

Syllabus Source: CAE Oxford (pp. 227-238) | Pass Target: >= 90% AviationExam

1. PRESSURE SETTINGS: QNH, QFE, STANDARD

- QNH (Altimeter setting): Station pressure reduced to MSL according to ISA. Indicates ALTITUDE above MSL. On the ground at the aerodrome, it indicates aerodrome elevation.
- QFE: Atmospheric pressure at aerodrome elevation (or runway threshold). Indicates HEIGHT above aerodrome datum. On the ground, it reads ZERO.
- Standard Setting (1013.25 hPa / 29.92 inHg): Used for vertical separation en-route. Indicates FLIGHT LEVEL (FL).

2. TRANSITION ALTITUDE, LEVEL & LAYER

Element	Authority / Publication	Operational Rule & Altimeter Reference
Transition Altitude (TA)	Published on instrument charts (Fixed)	Altitude at or below which vertical position is controlled by reference to ALTITUDES (QNH).
Transition Level (TRL)	Calculated and issued by ATC (Variable)	Lowest available FLIGHT LEVEL above the TA. Controlled by reference to Standard (1013.25). Varies with actual QNH.
Transition Layer	Airspace between TA and TRL	Airspace between TA and TRL (at least 1,000 ft thick). LEVEL CRUISING FLIGHT IN THIS LAYER IS STRICTLY PROHIBITED.

[!] EXAM TRAP (AVIATIONEXAM) - Altimeter Changeover Point

- In CLIMB: Altimeter is changed from QNH to STANDARD (1013.25 hPa) when PASSING THE TRANSITION ALTITUDE (TA).
- In DESCENT: Altimeter is changed from STANDARD (1013.25) to QNH when PASSING THE TRANSITION LEVEL (TRL).

3. STEP-BY-STEP WORKED EXAMPLE (FOR DUMMIES / PASO A PASO)

Pressure altimeters are calibrated to the International Standard Atmosphere (ISA). In temperatures colder than ISA, the true altitude is LOWER than the indicated altitude ('High to low or hot to cold, look out below!').

[*] OFFICIAL DEFINITION - PRACTICAL CALCULATION: Altimeter Temperature Error and Terrain Clearance Correction

SCENARIO (PANS-OPS / EASA Cold Weather Altimetry Correction): - Aerodrome elevation: 2,000 ft. Published Minimum Safe Altitude (MSA): 6,000 ft. - Reported ambient temperature at aerodrome: -15°C. SOLUTION PASO A PASO (FOR DUMMIES): Step 1: Calculate Standard ISA Temperature at Aerodrome Elevation (2,000 ft): - ISA Temp = $15^{\circ}\text{C} - (2^{\circ}\text{C} \times 2) = +11^{\circ}\text{C}$. Step 2: Calculate ISA Deviation (Delta-ISA): - Delta-ISA = Actual (-15°C) - Standard (+11°C) = -26°C (Colder than ISA!). Step 3: Calculate Height Above Altimeter Source (Datum): - Height = 6,000 ft (MSA) - 2,000 ft (Elevation) = 4,000 ft (4 units of 1,000 ft). Step 4: Apply the 4 ft per 1,000 ft Rule of Thumb: - Error = $4 \text{ ft} \times 4 \times 26 = 416 \text{ ft}$. - Because air is colder than standard, True Altitude is 416 ft LOWER than indicated! FINAL ANSWER: To maintain the published 6,000 ft true clearance over obstacles, the pilot MUST fly an indicated altitude of at least 6,416 ft (6,000 + 416 ft)!

4. LOWEST USABLE FLIGHT LEVEL UNDER LOW PRESSURE

When atmospheric pressure drops below 1013.25 hPa, Flight Levels sink closer to terrain. For example, at QNH 980 hPa (33 hPa below standard): - $33 \text{ hPa} \times 27 \text{ ft/hPa} = \sim 891 \text{ ft}$ loss of true clearance. - ATC must raise the Transition Level and lowest usable Flight Level by 1,000 ft to preserve safety margins.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)**Q1: In climb, when does the altimeter subscale setting change from QNH to Standard 1013.25?**

- [A]: At the Transition Level (TRL)
- [B]: Passing the Transition Altitude (TA)
- [C]: Leaving controlled airspace
- [D]: At 10,000 ft

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In climb, altimeters are set to 1013.25 upon passing the Transition Altitude (TA).

Q2: In air colder than ISA, does the altimeter overread or underread?

- [A]: It underreads (true altitude is higher than indicated).
- [B]: It overreads (true altitude is lower than indicated).
- [C]: It indicates correctly because pressure remains unchanged.
- [D]: It only errors when climbing above FL 100.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In cold air, air columns shrink; pressure levels drop closer to ground. The altimeter overreads (shows higher than actual true altitude).

Q3: Is level cruising flight permitted within the Transition Layer?

- [A]: Yes, if authorized by ATC.
- [B]: Yes, under VFR only.
- [C]: NO, level flight within the transition layer is strictly prohibited.
- [D]: Only during holding procedures.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Cruising in level flight within the Transition Layer is strictly prohibited.

Q4: If QNH is 980 hPa (substantially below standard), what happens to the lowest usable Flight Level?

- [A]: It is lower than usual
- [B]: It is higher than usual to guarantee minimum obstacle clearance
- [C]: It is unaffected
- [D]: Flight Levels are suspended

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Low atmospheric pressure compresses pressure levels towards the surface, requiring ATC to raise the lowest usable Flight Level to maintain terrain clearance.

Q5: If an aircraft flies from an area of high pressure into an area of low pressure without adjusting altimeter setting, what happens?

- [A]: The altimeter will underread and aircraft will climb
- [B]: The altimeter will overread and true altitude will be dangerously lower than indicated
- [C]: Airspeed indicator will fail
- [D]: Autopilot will disconnect automatically

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. 'High to low, look out below!' The altimeter registers the lower ambient pressure as higher altitude, causing the pilot or autopilot to fly closer to terrain than indicated.

Q6: What is the maximum permitted tolerance when checking a primary altimeter against aerodrome elevation?

- [A]: +/- 20 ft
- [B]: +/- 60 ft (to +/- 75 ft depending on test conditions)
- [C]: +/- 150 ft
- [D]: +/- 250 ft

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under PANS-OPS, the pre-flight ground altimeter check tolerance is +/- 60 to 75 ft of the published aerodrome/runway elevation.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 11: Parallel Runway Operations

Syllabus Source: CAE Oxford (pp. 239-252) | Pass Target: >= 90% AviationExam

1. MODES OF OPERATION & MINIMUM CENTERLINE SPACING

Simultaneous operations on parallel or near-parallel runways are governed by ICAO Doc 4444 (PANS-ATM) and Doc 8168. Minimum centerline separation distances are strictly tested:

Operational Mode	Min. Centerline Spacing	Operational Criteria & Stagger Requirements
Independent Parallel Approaches	At least 1,035 m (3,400 ft)	Simultaneous approaches where radar separation between aircraft on adjacent ILS localizers is NOT required. Requires dedicated radar monitor controllers.
Dependent Parallel Approaches	At least 915 m (3,000 ft)	Simultaneous approaches where radar separation minima (stagger) between aircraft on adjacent extended centerlines IS required (usually 1.5 or 2.0 NM).
Independent Parallel Departures	At least 1,035 m (3,400 ft)	Simultaneous departures where departure tracks diverge immediately by at least 15° after take-off.
Segregated Parallel Operations	At least 760 m (2,500 ft)	One runway is used exclusively for departures, and the other runway is used exclusively for arrivals.

2. PROTECTED ZONES: NOZ AND NTZ

- Normal Operating Zone (NOZ): An airspace corridor extending from runway threshold to point where aircraft intercepts ILS, within which aircraft are expected to maneuver.
- No Transgression Zone (NTZ): A non-maneuvering corridor of at least 610 m (2,000 ft) width located centrally between the two extended runway centerlines. Penetration by an aircraft requires immediate controller breakout instructions.

[!] EXAM TRAP (AVIATIONEXAM) - NTZ Penetration & Breakout Instructions

When an aircraft is observed penetrating the NTZ, the radar controller immediately instructs the threatened aircraft on the adjacent localizer to execute a BREAKOUT MANEUVER (e.g. 'Turn left immediately heading 270, climb to 3,000 ft'). The pilot must execute the breakout without delay.

3. PRECISION RUNWAY MONITOR (PRM) SYSTEMS

PRM radar systems provide fast radar updates (≤ 2.5 seconds) and high-resolution displays. When PRM is in use, independent parallel approaches can be conducted on runways with centerline spacing as close as 1,035 m without staggered separation.

4. INTERSECTING & CONVERGING RUNWAY OPERATIONS

For operations on intersecting or converging runways, take-off and landing clearances are coordinated so that aircraft flight paths never cross simultaneously. When wake turbulence from an intersecting departure crosses the arrival path, a full 2-minute (or 3-minute for intermediate intersection) separation is applied.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the minimum runway centerline spacing for independent parallel instrument approaches?

- [A]: 760 m (2,500 ft)
- [B]: 915 m (3,000 ft)
- [C]: 1,035 m (3,400 ft)
- [D]: 1,500 m (5,000 ft)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Independent parallel approaches require at least 1,035 m (3,400 ft) centerline spacing.

Q2: What is the minimum width of the No Transgression Zone (NTZ) between parallel runway centerlines?

- [A]: 300 m
- [B]: 610 m (2,000 ft)
- [C]: 915 m
- [D]: 1,035 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The NTZ must be at least 610 m (2,000 ft) wide and located midway between the two extended runway centerlines.

Q3: For independent parallel departures, what is the minimum track divergence required immediately after take-off?

- [A]: 10°
- [B]: 15°
- [C]: 30°
- [D]: 45°

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Tracks must diverge by at least 15° immediately after take-off for independent parallel departures.

Q4: What is the minimum runway centerline spacing for segregated parallel operations?

- [A]: 610 m
- [B]: 760 m (2,500 ft)
- [C]: 915 m
- [D]: 1,035 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Segregated parallel operations (one runway arrival, one runway departure) require at least 760 m spacing.

Q5: What is the required radar stagger distance between aircraft on adjacent parallel ILS localizers during departures?

- [A]: 1.0 NM
- [B]: 1.5 NM to 2.0 NM
- [C]: 3.0 NM
- [D]: 5.0 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Dependent parallel approaches require a radar stagger of 1.5 NM (or 2.0 NM) between successive arrivals on parallel localizers.

Q6: During independent parallel approaches, what immediate action is required from an aircraft instructed to e

- [A]: Request reason from ATC before turning
- [B]: Disconnect autopilot and comply immediately with heading and climb/descent instructions without delay
- [C]: Continue on localizer until visual contact is made
- [D]: Squawk 7600

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A breakout instruction is issued when another aircraft penetrates the No Transgression Zone (NTZ). The pilot must comply immediately.

Q7: Under PANS-ATM, what is the maximum convergence or divergence angle for two runways to be classified

- [A]: 5°
- [B]: 10°
- [C]: 15°
- [D]: 30°

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Non-intersecting runways whose extended centerlines have an angle of convergence or divergence of 15° or less are classified as near-parallel runways.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 12: SSR and ACAS (TCAS II)

Syllabus Source: CAE Oxford (pp. 253-262) | Pass Target: >= 90% AviationExam

1. SECONDARY SURVEILLANCE RADAR (SSR) MODES

- Mode A: 4-digit octal code (4,096 combinations) for aircraft identification assigned by ATC.
- Mode C: Transmits automated pressure altitude (referenced to 1013.25 hPa) in 100 ft increments.
- Mode S: Transmits unique 24-bit aircraft address; selective interrogation; enhanced surveillance parameters (Downlink Airborne Parameters - DAP: selected altitude, roll angle, IAS, Mach).

[!] EXAM TRAP (AVIATIONEXAM) - Mandatory Emergency Transponder Codes (Memorize 100%)

- 7500: Unlawful Interference (Hijacking). - 7600: Lost Communications (Radio Failure). - 7700: General Emergency / Distress. - 7000: Standard VFR conspicuity in Europe (1200 in USA). - 2000: Default IFR entry code into uncontrolled airspace or oceanic control without assigned code.

2. AIRBORNE COLLISION AVOIDANCE SYSTEM (ACAS II / TCAS II)

ACAS II interrogates Mode C/S transponders of nearby aircraft to provide warnings based on Time to CPA (tau):

Warning Level	Display Symbol	Time to CPA (Tau)	Cockpit Action & Pilot Response
Traffic Advisory (TA)	Amber solid circle	20 to 48 seconds to CPA	Audio: 'TRAFFIC, TRAFFIC'. Visual scan only. NO EVASIVE MANEUVER PERMITTED.
Resolution Advisory (RA)	Red solid square	15 to 35 seconds to CPA	Audio: 'CLIMB', 'DESCEND', etc. Vertical evasive instruction. Pilot MUST disconnect autopilot and comply immediately.

[!] EXAM TRAP (AVIATIONEXAM) - Pilot Response Time & Absolute Priority of TCAS RA

1. Response Time: Pilot must initiate response within 5 SECONDS for initial RA, and within 2.5 SECONDS for an increased or reversal RA (G-load 0.25 g initial, 0.35 g reversal). 2. RA vs ATC Clearance: TCAS RA OVERRULES ATC CLEARANCE. If an RA contradicts an ATC instruction, the pilot MUST follow the RA without hesitation, and advise ATC as soon as possible ('TCAS RA').

3. TCAS II VERSION 7.1 'LEVEL OFF' MODIFICATION

TCAS II Version 7.1 introduced a critical safety enhancement: the 'Adjust Vertical Speed, Adjust' RA was replaced by 'Level Off, Level Off'. This instructs the crew to reduce vertical climb/descent to zero ft/min, preventing excessive vertical excursions during crossing encounters.

4. MODE S DOWNLINK AIRBORNE PARAMETERS (DAPS)

- Basic DAP: Flight status (airborne/ground), Mode A code, 24-bit aircraft address, aircraft identification (callsign).
- Enhanced DAP: Selected altitude, roll angle, true track angle, ground speed, magnetic heading, indicated airspeed (IAS) / Mach, and vertical rate (barometric or inertial).

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the transponder code for an aircraft experiencing unlawful interference (hijacking)?

- [A]: 7700
- [B]: 7600
- [C]: 7500
- [D]: 7000

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. 7500 = hijacking; 7600 = radio failure; 7700 = general emergency.

Q2: In the event of a TCAS Resolution Advisory (RA) contradicting an ATC instruction, what action is required?

- [A]: Follow ATC instruction and ignore TCAS.
- [B]: Ask ATC for clarification before maneuvering.
- [C]: Follow TCAS RA immediately and advise ATC as soon as possible.
- [D]: Turn 90° horizontally to avoid conflict.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. TCAS RA takes absolute priority over ATC clearances. Comply immediately with RA.

Q3: What is the maximum pilot reaction time allowed to respond to an initial TCAS Resolution Advisory?

- [A]: 2.5 seconds
- [B]: 5.0 seconds
- [C]: 10.0 seconds
- [D]: 15.0 seconds

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Reaction time must be within 5 seconds for initial RA, and within 2.5 seconds for an increased or reversal RA.

Q4: Which transponder code should be set by an IFR aircraft entering an airspace region without an assigned

- [A]: 7000
- [B]: 2000
- [C]: 1200
- [D]: 7700

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Mode A Code 2000 is the standard IFR code when no code has been assigned by ATC.

Q5: Under TCAS II Version 7.1, what new resolution advisory replaced 'Adjust Vertical Speed, Adjust'?

- [A]: 'Maintain Vertical Speed'
- [B]: 'Level Off, Level Off'
- [C]: 'Descend Immediately'
- [D]: 'Climb and Turn Left'

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. TCAS II version 7.1 replaced 'Adjust Vertical Speed' with 'Level Off, Level Off' to eliminate pilot over-corrections.

Q6: What is the required pilot response time for an increased or reversal TCAS Resolution Advisory (RA)?

- [A]: 5.0 seconds
- [B]: 2.5 seconds
- [C]: 1.0 second
- [D]: 10.0 seconds

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Pilot reaction time for a reversal or increased rate RA is 2.5 seconds (with 0.35 g target acceleration).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 13: Airspace Classes (A to G)

Syllabus Source: CAE Oxford (pp. 263-278) | Pass Target: >= 90% AviationExam

1. MASTER AIRSPACE CLASSIFICATION TABLE (ICAO & SERA)

Airspace is categorized into 7 classes (A to G). Classes A to E are Controlled Airspace; Classes F and G are Uncontrolled Airspace. Separation and communications requirements vary strictly by class:

Class	Flights	Separation Provided	Radio Comms	ATC Clearance & Key Rules
Class A	IFR only	IFR from IFR	Continuous 2-way	ATC Clearance MANDATORY. VFR is STRICTLY PROHIBITED.
Class B	IFR & VFR	All flights from all flights	Continuous 2-way	ATC Clearance MANDATORY. Full separation provided to all.
Class C	IFR & VFR	IFR from IFR & VFR. VFR from IFR only.	Continuous 2-way	ATC Clearance MANDATORY. VFR receives traffic info on other VFR.
Class D	IFR & VFR	IFR from IFR only.	Continuous 2-way	ATC Clearance MANDATORY. Traffic information given to VFR on all flights.
Class E	IFR & VFR	IFR from IFR only.	Continuous 2-way for IFR only	Clearance MANDATORY for IFR. VFR does NOT need clearance or radio!
Class F	IFR & VFR	None (Advisory only)	Continuous for participating IFR	Uncontrolled. IFR receives air traffic advisory service.
Class G	IFR & VFR	None	Continuous for IFR where required	Uncontrolled. Flight Information Service (FIS) on request.

[!] EXAM TRAP (AVIATIONEXAM) - Class E Airspace: The Famous AviationExam Trap
Question: Is an ATC clearance required to fly VFR in Class E airspace? Answer: NO. In Class E, VFR flights do NOT require an ATC clearance and do NOT require two-way radio comms. Only IFR flights require ATC clearance and continuous communication in Class E.

2. SPEED LIMITATIONS IN AIRSPACE

- General Speed Limit: A maximum speed of 250 kt IAS applies to all flights operating below FL 100 (or 10,000 ft AMSL), EXCEPT in Class A and B airspace, or when authorized by ATC.

3. SPECIAL USE AIRSPACE

- Prohibited Area (P): Airspace within which flight of aircraft is strictly prohibited.
- Restricted Area (R): Flight of aircraft is restricted in accordance with specified conditions.
- Danger Area (D): Activities dangerous to flight may exist at specified times. Flight is not legally barred, but caution required.

- Temporary Segregated Area (TSA): Airspace temporarily segregated for exclusive use of specific users.
- Temporary Reserved Area (TRA): Airspace temporarily reserved for specific operations with civil transit permitted under ATC.

4. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: In which airspace classes are VFR flights strictly prohibited?

- [A]: Class A only
- [B]: Classes A and B
- [C]: Classes A, B, and C
- [D]: Class G

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Class A airspace is reserved exclusively for IFR flights; VFR is prohibited.

Q2: In Class C airspace, does ATC separate VFR flights from other VFR flights?

- [A]: Yes, full separation is provided.
- [B]: No, VFR receives only traffic information in respect of other VFR flights.
- [C]: Only during night operations.
- [D]: Only above FL 100.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. In Class C, IFR is separated from IFR and VFR. VFR is separated from IFR, but receives only traffic information regarding other VFR.

Q3: Does a VFR flight require an ATC clearance to enter Class E airspace?

- [A]: Yes, clearance is mandatory for all flights.
- [B]: No, VFR flights do not require ATC clearance in Class E.
- [C]: Yes, unless squawking 7000.
- [D]: Only when entering a control zone.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Class E is controlled for IFR only. VFR flights do not require ATC clearance or two-way radio communication.

Q4: What is the standard speed limitation for aircraft operating below FL 100 in Class D airspace?

- [A]: 200 kt IAS
- [B]: 250 kt IAS
- [C]: 280 kt IAS
- [D]: No speed limit applies

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. 250 kt IAS is the standard maximum speed below FL 100 across classes C to G.

Q5: What is the definition of a Danger Area (D)?

- [A]: Airspace where flight of aircraft is completely prohibited
- [B]: Airspace within which activities dangerous to the flight of aircraft may exist at specified times
- [C]: Airspace reserved exclusively for supersonic military flight
- [D]: Airspace surrounding a nuclear power plant

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A Danger Area denotes airspace within which activities dangerous to flight may occur at specified times (flight is not legally barred, unlike a Prohibited area).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 14: Air Traffic Services & Emergencies

Syllabus Source: CAE Oxford (pp. 279-296) | Pass Target: >= 90% AviationExam

1. THE THREE CORE AIR TRAFFIC SERVICES (ATS)

- 1. Air Traffic Control (ATC): Prevents collisions between aircraft and between aircraft and obstacles on the maneuvering area, and expedites and maintains an orderly flow of traffic. (Subdivided into: Area Control ACC, Approach Control APP, Aerodrome Control TWR).
- 2. Flight Information Service (FIS): Provides advice and information useful for the safe and efficient conduct of flights (weather, changes in serviceability of nav aids, traffic information).
- 3. Alerting Service (ALRS): Notifies appropriate organizations regarding aircraft in need of search and rescue aid, and assists such organizations as required. Provided to ALL aircraft provided with ATC, or submitting a flight plan.

2. AUTOMATIC TERMINAL INFORMATION SERVICE (ATIS)

Continuous broadcast of routine non-control information at busy aerodromes (Voice-ATIS and D-ATIS):

- Identified by a designator letter from the ICAO spelling alphabet (Alpha to Zulu), updated sequentially.
- Updated whenever a significant change in meteorological or operational conditions occurs.
- Pilot must acknowledge current ATIS code upon initial contact with ATC.

3. THE THREE EMERGENCY PHASES (ANNEX 11 / 12)

Emergency Phase	Official Activation Criteria (AviationExam Core)
1. INCERFA (Uncertainty Phase)	No communication received within 30 minutes after time it should have been received, OR aircraft fails to arrive within 30 minutes of ETA.
2. ALERFA (Alert Phase)	Following INCERFA, attempts to communicate fail; OR aircraft cleared to land fails to land within 5 minutes of ETA; OR operating efficiency impaired.
3. DETRESFA (Distress Phase)	Following ALERFA, or fuel on board considered exhausted, or information indicates aircraft about to make forced landing or has crashed.

4. MANDATORY READBACK REQUIREMENTS (SERA.8015)

The flight crew shall read back to the air traffic controller safety-related parts of ATC clearances and instructions which are transmitted orally. The following parts shall ALWAYS be read back:

- 1. Route Clearances: Any ATC route clearance, SID, STAR, or route modification.
- 2. Clearances and Instructions to Enter, Land On, Take Off On, Hold Short Of, Cross, or Taxi On: Any runway instruction must be read back completely with runway designator.
- 3. Runway-in-use, Altimeter Settings, SSR Codes: Crucial numerical flight parameters.
- 4. Newly Assigned Level Instructions, Heading and Speed Instructions: Vertical and horizontal vectors.
- 5. Transition Levels: Whether given by ATC or ATIS.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What condition triggers the declaration of INCERFA (Uncertainty Phase)?

- [A]: Aircraft fails to land within 5 minutes of landing clearance.
- [B]: No communication within 30 minutes after time it should have been received.
- [C]: Fuel on board is below reserve.
- [D]: Pilot squawks 7600.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. INCERFA is declared when no communication has been received within 30 minutes of the time it should have been received.

Q2: An aircraft that has been cleared to land fails to land within what time interval to trigger ALERFA?

- [A]: 2 minutes
- [B]: 5 minutes
- [C]: 10 minutes
- [D]: 15 minutes

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. An aircraft cleared to land that fails to land within 5 minutes of estimated landing time triggers an immediate Alert Phase (ALERFA).

Q3: When the fuel on board is considered exhausted, which emergency phase is declared?

- [A]: INCERFA
- [B]: ALERFA
- [C]: DETRESFA
- [D]: PAN PAN

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Fuel exhaustion triggers the Distress Phase (DETRESFA).

Q4: To whom is the Alerting Service (ALRS) provided?

- [A]: Only to IFR flights in Class A airspace
- [B]: To all aircraft provided with air traffic control service and to any other aircraft submitting a flight plan
- [C]: Exclusively to commercial passenger airliners
- [D]: Only during search and rescue operations

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Alerting service is provided to all aircraft receiving ATC service, having filed a flight plan, or otherwise known to ATS.

Q5: Which ATS unit provides air traffic control service to en-route controlled flights?

- [A]: Aerodrome Control Tower (TWR)
- [B]: Approach Control Unit (APP)
- [C]: Area Control Centre (ACC)

- [D]: Flight Information Centre (FIC)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. The Area Control Centre (ACC) is responsible for en-route air traffic control.

Q6: What emergency frequency must be continuously monitored by aircraft equipped with VHF radio when op

- [A]: 121.5 MHz
- [B]: 123.45 MHz
- [C]: 118.0 MHz
- [D]: 136.0 MHz

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Under SERA and ICAO Annex 10, 121.5 MHz is the international VHF aeronautical emergency frequency and must be monitored whenever practicable.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 15: Separation & Wake Turbulence

Syllabus Source: CAE Oxford (pp. 297-330) | Pass Target: >= 90% AviationExam

1. VERTICAL SEPARATION & RVSM

- Standard Vertical Separation: 1,000 ft below FL 290; 2,000 ft above FL 290.
- RVSM (Reduced Vertical Separation Minimum): 1,000 ft vertical separation between FL 290 and FL 410 inclusive for approved aircraft. Above FL 410, separation is 2,000 ft.

2. HORIZONTAL RADAR & PROCEDURAL SEPARATION

- Standard Radar Separation: 5 NM en-route; 3 NM in terminal areas (reduced to 2.5 NM under special radar criteria).
- Non-Radar Longitudinal Separation: 15 minutes standard; reduced to 10 minutes if navigation aids permit frequent position determination; 5 minutes for climbing/descending aircraft on same track; 3 minutes for departing aircraft.
- DME Separation: 20 NM on same track; 10 NM if leading aircraft maintains >= 20 kt higher true airspeed.
- Mach Number Technique: Used in oceanic/continental airspace: 80 NM or 10 minutes when longitudinal separation is based on Mach number.

3. NON-RADAR LATERAL SEPARATION BY TRACK DIVERGENCE

Lateral separation between two aircraft departing or navigating along diverging tracks: - VOR: Tracks diverge by at least 15° and at least one aircraft is at or beyond 15 NM from the VOR. - NDB: Tracks diverge by at least 30° and at least one aircraft is at or beyond 15 NM from the NDB. - Dead Reckoning (DR): Tracks diverge by at least 45° and at least one aircraft is at or beyond 15 NM from intersection.

4. WAKE TURBULENCE CATEGORIES & MINIMA MATRIX

Category	Certified Take-Off Mass (MTOM)	Radar Wake Separation (Trailing)
SUPER	Airbus A380-800	Behind Super: Heavy 6 NM, Medium 7 NM, Light 8 NM.
HEAVY (H)	136,000 kg or more	Behind Heavy: Heavy 4 NM, Medium 5 NM, Light 6 NM.
MEDIUM (M)	Between 7,000 kg and 136,000 kg	Behind Medium: Heavy/Medium Radar min, Light 5 NM.
LIGHT (L)	7,000 kg or less	Light twins and single-engine aircraft.

[!] EXAM TRAP (AVIATIONEXAM) - Timed Departure Wake Turbulence Separation (Non-Radar)

When taking off behind a HEAVY aircraft from the same runway: - Full length of runway: 2 MINUTES separation. - From an INTERMEDIATE intersection (displaced threshold): 3 MINUTES separation (due to vortex drift).

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the maximum certified take-off mass for a HEAVY wake turbulence category aircraft?

- [A]: 100,000 kg or more
- [B]: 136,000 kg or more
- [C]: 150,000 kg or more
- [D]: 300,000 kg or more

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The HEAVY wake turbulence category applies to aircraft of 136,000 kg (300,000 lbs) or more.

Q2: What is the radar wake turbulence separation for a LIGHT aircraft following a HEAVY aircraft on approach?

- [A]: 4 NM
- [B]: 5 NM
- [C]: 6 NM
- [D]: 7 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Heavy behind Heavy is 4 NM; Medium behind Heavy is 5 NM; Light behind Heavy is 6 NM.

Q3: When departing behind a Heavy aircraft from an intermediate intersection, what is the required time separation?

- [A]: 2 minutes
- [B]: 3 minutes
- [C]: 4 minutes
- [D]: 5 minutes

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. From an intermediate intersection, 3 minutes separation is required (compared to 2 minutes from full length).

Q4: What is the standard non-radar longitudinal separation between two aircraft on the same track if navigation aids are not available?

- [A]: 5 minutes
- [B]: 10 minutes
- [C]: 15 minutes
- [D]: 20 minutes

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Standard procedural separation is 15 minutes, reduced to 10 minutes when nav aids permit frequent updates.

Q5: What is the vertical separation applied in RVSM airspace between FL 290 and FL 410?

- [A]: 500 ft
- [B]: 1,000 ft
- [C]: 2,000 ft
- [D]: 4,000 ft

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Reduced Vertical Separation Minimum (RVSM) provides 1,000 ft vertical separation between FL 290 and FL 410.

Q6: What is the radar wake turbulence separation for a MEDIUM aircraft following a HEAVY aircraft on approach?

- [A]: 3 NM
- [B]: 4 NM
- [C]: 5 NM
- [D]: 6 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Heavy behind Heavy is 4 NM; Medium behind Heavy is 5 NM; Light behind Heavy is 6 NM.

Q7: What is the minimum lateral divergence angle required between two departing aircraft navigating via VOR?

- [A]: 10°
- [B]: 15° (at or beyond 15 NM)
- [C]: 30°
- [D]: 45°

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Lateral separation by VOR requires tracks diverging by at least 15° at a distance of at least 15 NM from the facility.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 16: Control of Aircraft & Emergencies

Syllabus Source: CAE Oxford (pp. 331-356) | Pass Target: >= 90% AviationExam

1. SPEED CONTROL LIMITATIONS (ATC)

ATC may apply speed control to maintain separation. However, speed adjustments must not be applied or continued within 4 NM of the runway threshold on final approach. Speed reductions should not normally be below 160 kt IAS for jet aircraft on intermediate/final approach.

2. FUEL EMERGENCIES: MINIMUM FUEL VS MAYDAY FUEL

[!] EXAM TRAP (AVIATIONEXAM) - MINIMUM FUEL vs MAYDAY MAYDAY MAYDAY FUEL

- 'MINIMUM FUEL': Informs ATC that all planned aerodrome options are committed and that any change to clearance may result in landing with less than planned final reserve fuel. IT IS NOT AN EMERGENCY and DOES NOT CONFER PRIORITY. - 'MAYDAY MAYDAY MAYDAY FUEL': Distress message. Declares that calculated usable fuel on landing will be LESS than the mandatory final reserve fuel. Confers ABSOLUTE PRIORITY.

3. RADIO COMMUNICATIONS FAILURE PROCEDURES (SERA.8035)

- Transponder Setting: Squawk Mode A Code 7600 immediately.
- In VMC: Continue to fly in VMC; land at the nearest suitable aerodrome; report arrival to the appropriate ATS unit by the most expeditious means.
- In IMC (Controlled Airspace): Maintain last assigned speed and level for 7 MINUTES (or 3 minutes if being radar vectored), then adjust level/speed in accordance with filed flight plan. Proceed to destination radio aid and commence descent at expected approach time (EAT) or ETA.

4. EMERGENCY DESCENT PROCEDURES IN CONTROLLED AIRSPACE

When an aircraft is forced to execute an immediate emergency descent (e.g. rapid cabin depressurization): 1. Turn immediately 30° (or 45°) left or right to clear the airway centerline. 2. Transmit distress message: 'MAYDAY MAYDAY MAYDAY [Callsign] EMERGENCY DESCENT'. 3. Squawk Mode A Code 7700; select emergency frequency 121.5 MHz. 4. Turn on all exterior aircraft lights to maximize conspicuity.

5. DISTRESS AND URGENCY RADIOTELEPHONY COMMUNICATIONS

Category & Spoken Prefix	Operational Definition & Circumstances	Transmission Contents & Radiotelephony Status
Distress (MAYDAY)	Grave and imminent danger requiring immediate assistance.	MAYDAY MAYDAY MAYDAY, Callsign, Position, Level, Nature of distress, Intentions. Absolute priority.
Urgency (PAN PAN)	Condition concerning safety of aircraft/person, not requiring immediate assistance.	PAN PAN PAN PAN PAN PAN, Callsign, Position, Level, Nature of urgency. Priority over all except distress.
Medical Transport	Aircraft protected under Geneva Conventions transporting medical personnel/supplies.	Prefix 'PAN PAN MEDICAL' announces protected status.

6. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: Does transmitting the phrase 'MINIMUM FUEL' give the aircraft priority over other traffic?

- [A]: Yes, immediate clearance to land.
- [B]: No, it is not an emergency and confers no priority.
- [C]: Only if flying in Class A airspace.
- [D]: Yes, priority over all VFR flights.

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. 'MINIMUM FUEL' indicates that the flight cannot accept undue delays, but confers NO PRIORITY. Priority is only granted by declaring 'MAYDAY MAYDAY MAYDAY FUEL'.

Q2: In IMC, following a communications failure while being radar vectored, how long must the assigned speed be maintained?

- [A]: 3 minutes
- [B]: 7 minutes
- [C]: 15 minutes
- [D]: Until reaching destination

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Under SERA.8035, if under radar vectors, maintain speed/level for 3 minutes (compared to 7 minutes if on a published route).

Q3: Within what distance of the runway threshold must ATC cease applying speed control?

- [A]: 2 NM
- [B]: 4 NM
- [C]: 8 NM
- [D]: 10 NM

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Speed control shall not be applied or continued within 4 NM of the threshold on final approach.

Q4: Which distress call prefix is used when an aircraft is threatened by grave and imminent danger and requires immediate assistance?

- [A]: PAN PAN
- [B]: MAYDAY spoken three times
- [C]: SECURITE
- [D]: EMERGENCY

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The international spoken distress signal is 'MAYDAY' spoken three times.

Q5: If an aircraft suffers complete radio failure in VMC, what action should the PIC take?

- [A]: Squawk 7600 and continue to destination at assigned Flight Level

- [B]: Continue in VMC, land at the nearest suitable aerodrome, and notify ATS expeditiously
- [C]: Circle in present position for 45 minutes
- [D]: Descend immediately to 500 ft AGL

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under SERA.8035, if in VMC, the aircraft must remain in VMC, land at the nearest suitable aerodrome, and report to ATS.

Q6: In radiotelephony phraseology, what standard word indicates that a transmission has ended and no response is expected?

- [A]: ROGER
- [B]: OVER
- [C]: OUT
- [D]: WILCO

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. 'OUT' signifies that the exchange is finished and no answer is expected ('OVER' signifies my transmission has ended and I expect an answer).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 17: AIS, AIP & AIRAC System

Syllabus Source: CAE Oxford (pp. 357-374) | Pass Target: >= 90% AviationExam

1. THE INTEGRATED AERONAUTICAL INFORMATION PACKAGE (IAIP)

Under ICAO Annex 15, the purpose of the Aeronautical Information Service (AIS) is to ensure the flow of aeronautical data and information necessary for the safety, regularity, and efficiency of air navigation. The Integrated Aeronautical Information Package (IAIP) consists of:

- AIP (Aeronautical Information Publication): Basic permanent regulatory document for flight operations. Divided into 3 PARTS: GEN (General), ENR (En-Route), and AD (Aerodromes).
- AIP Amendments (AIP AMDT): Permanent changes to the AIP. Regular amendments or AIRAC amendments.
- AIP Supplements (AIP SUP): Temporary changes of long duration (3 MONTHS OR LONGER) or changes with extensive text or graphics. Published on conspicuous YELLOW paper.
- NOTAM (Notice to Airmen): Information of urgent operational significance that cannot be published in the AIP in time. Maximum validity: 3 MONTHS.
- PIB (Pre-flight Information Bulletin): Recapitulation of current NOTAMs and urgent information prepared for flight crews prior to departure.
- AIC (Aeronautical Information Circulars): Notices regarding flight safety, technical, administrative, or legislative matters: White (Administrative), Yellow (Operational / ATC), Pink (Flight Safety awareness), Mauve (Airspace restrictions).

2. THE AIRAC SYSTEM (AVIATIONEXAM CORE)

The Aeronautical Information Regulation and Control (AIRAC) system governs the publication of operationally significant changes on predetermined dates based on a 28-DAY INTERVAL:

- Standard AIRAC Cycle: 28 days. Effective dates are Thursdays at 00:00 UTC.
- Publication Lead Time: Information must be dispatched by AIS at least 42 DAYS prior to the effective date so as to reach recipients at least 28 days before.
- Major Operational Changes: For significant changes (e.g. major airspace restructuring, new ATS routes, new runway), information must be dispatched at least 56 DAYS in advance.

3. NOTAM STRUCTURE & Q-CODE DECODING

NOTAM Item	Operational Meaning & Contents
Q) Line	Contains FIR, 5-letter Q-code (e.g. QFAXX), Traffic (I/V/IV), Purpose (N/B/O/M), Scope (A/E/W), Lower/Upper FL, Coordinates & Radius.
Item A)	ICAO 4-letter location indicator of the aerodrome or FIR (e.g. LEMD, EGLL).
Item B)	Ten-figure date/time group indicating start of validity (YYMMDDHHMM UTC).
Item C)	Ten-figure date/time group indicating end of validity, or 'PERM' for permanent changes, or 'EST' for estimated duration.
Item D)	Daily or periodic schedule of operation (if applicable).
Item E)	Plain-language decoded text of the NOTAM detailing the operational condition.
Items F) & G)	Lower and upper altitude or flight level limits (e.g. GND / FL 120).

4. GLOBAL REPORTING FORMAT (GRF) & SNOWTAM

Condition Code	Runway Contaminant & Depth	Reported Braking Action
RWYCC 6	DRY	Normal braking performance and directional control.
RWYCC 5	FROST, WET (≤ 3 mm water), SLUSH (≤ 3 mm)	Good braking action.
RWYCC 3	COMPACTED SNOW (temp $\leq -15^{\circ}\text{C}$)	Medium braking action.
RWYCC 2	WET COMPACTED SNOW	Medium to poor braking action.
RWYCC 1	ICE	Poor braking action.
RWYCC 0	WET ICE, WATER ON COMPACTED SNOW	LESS THAN POOR / NIL (Operations prohibited).

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the interval between consecutive AIRAC effective dates?

- [A]: 14 days
- [B]: 28 days
- [C]: 42 days
- [D]: 56 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The AIRAC cycle is based on predetermined dates separated by 28 days.

Q2: What is the maximum validity period of a standard NOTAM?

- [A]: 24 hours
- [B]: 1 month
- [C]: 3 months
- [D]: 6 months

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. A NOTAM has a maximum validity period of 3 months.

Q3: What paper color is used to publish AIP Supplements (AIP SUP)?

- [A]: White
- [B]: Pink
- [C]: Yellow
- [D]: Blue

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. AIP Supplements are printed on yellow paper to make them conspicuous.

Q4: How many days in advance must information for major AIRAC changes be dispatched?

- [A]: 28 days
- [B]: 42 days
- [C]: 56 days

- [D]: 90 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Major operational changes require 56 days advance dispatch (standard changes require 42 days).

Q5: Under the Global Reporting Format (GRF), what does a Runway Condition Code (RWYCC) of 6 represent?

- [A]: Poor braking action on wet ice
- [B]: Dry runway with normal braking
- [C]: Standing water / aquaplaning risk
- [D]: Compacted snow

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. RWYCC 6 indicates a dry runway with normal braking performance.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 18: Aerodrome Design & OLS Surfaces

Syllabus Source: CAE Oxford (pp. 375-398) | Pass Target: >= 90% AviationExam

1. AERODROME REFERENCE CODE (ANNEX 14)

Annex 14 classifies aerodrome facilities using a two-element reference code based on critical aircraft design:

Code No.	Airplane Reference Field Length	Code Letter	Wingspan & Outer Main Gear Wheel Span
Code 1	Reference Field Length < 800 m	Code A	Wingspan < 15 m (Gear span < 4.5 m)
Code 2	Field Length 800 m to < 1,200 m	Code B	Wingspan 15 m to < 24 m (Gear span 4.5 to < 6 m)
Code 3	Field Length 1,200 m to < 1,800 m	Code C	Wingspan 24 m to < 36 m (Gear span 6 to < 9 m) [A320, B737]
Code 4	Field Length >= 1,800 m	Code D	Wingspan 36 m to < 52 m (Gear span 9 to < 14 m) [B767]
--	--	Code E	Wingspan 52 m to < 65 m (Gear span 9 to < 14 m) [B777, A350]
--	--	Code F	Wingspan 65 m to < 80 m (Gear span 14 to < 16 m) [A380, B747-8]

2. RUNWAY STRIPS, CLEARWAYS & STOPWAYS

- **Runway Strip:** A defined area including runway and stopway intended: 1) To reduce damage if aircraft veers off runway, 2) To protect aircraft flying over during take-off or landing. For Code 3/4 precision runways, extends 60 m beyond each runway end, with a total width of at least 280 m (140 m each side of centerline) or 300 m (150 m each side).
- **Clearway:** Rectangular area on ground or water under control of aerodrome, selected or prepared as suitable area over which an aeroplane may make a portion of its initial climb to a specified height. Maximum length shall not exceed HALF THE LENGTH OF TORA (Clearway max = 0.5 x TORA). Upward slope max 1.25%.
- **Stopway:** Defined rectangular area on ground at end of take-off run available, prepared as suitable area in which an aircraft can be stopped in the event of an abandoned take-off. Width equal to runway.

3. DECLARED DISTANCES (TORA, TODA, ASDA, LDA)

Declared distances are the operational lengths available for aircraft performance calculations:

Declared Distance	Calculation Formula & Operational Definition
TORA (Take-Off Run Available)	Length of runway declared available and suitable for the ground run of an aircraft taking off.
TODA (Take-Off Distance Available)	TORA + Clearway. (The length of TORA plus length of clearway, if provided).
ASDA (Accelerate-Stop Distance Available)	TORA + Stopway. (The length of TORA plus length of stopway, if provided).

LDA (Landing Distance Available)

Length of runway declared available and suitable for the ground run of an aeroplane landing. Measured from threshold.

[!] EXAM TRAP (AVIATIONEXAM) - Displaced Threshold & Practical Calculation Exercise

When a runway threshold is **DISPLACED** (moved down the runway): - Landing Distance Available (LDA) is **REDUCED** by the displacement distance. - Take-Off Run Available (TORA), TODA, and ASDA are **NOT** reduced for take-off in that direction. - The area preceding a displaced threshold is suitable for take-off and roll, but **NEVER** for landing.

4. RUNWAY END SAFETY AREA (RESA)

An area symmetrical about extended runway centerline intended to reduce risk of damage to aircraft undershooting or overrunning runway. For Code 3 and 4 runways: minimum length is 90 m (recommended 240 m); width must be at least **TWICE** the width of the associated runway.

5. OBSTACLE LIMITATION SURFACES (OLS)

OLS Surface	Dimensions & Operational Protection Objective
Approach Surface	Inclined plane preceding threshold. Slope varies from 2.0% (Code 4 precision) to 3.3%.
Transitional Surface	Complex surface sloping upward and outward from runway strip edges to the inner horizontal surface. Standard slope: 14.3% (1:7) for Code 3/4 runways.
Inner Horizontal Surface	Circular horizontal plane located 45 m above aerodrome elevation (radius 4,000 m for Code 4). Protects visual maneuvering area.
Conical Surface	Surface sloping upward and outward from perimeter of inner horizontal surface at a 5% slope to a specified height (100 m for Code 4).
Balked Landing Surface	Inclined plane located after threshold at a specified distance protecting aircraft executing a missed approach at very low altitude.

6. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)**Q1: What is the maximum allowable length of a clearway relative to TORA?**

- [A]: 25% of TORA
- [B]: 50% of TORA
- [C]: Equal to TORA
- [D]: Unlimited provided slope is < 1.25%

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under ICAO Annex 14, the length of a clearway shall not exceed half the length of the take-off run available (0.5 x TORA).

Q2: At what height above aerodrome elevation is the Inner Horizontal Surface established?

- [A]: 30 m
- [B]: 45 m
- [C]: 60 m
- [D]: 100 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The Inner Horizontal Surface is located 45 m above the aerodrome elevation datum.

Q3: What is the standard minimum length of a Runway End Safety Area (RESA) for Code 4 runways?

- [A]: 60 m
- [B]: 90 m (recommended 240 m)
- [C]: 120 m
- [D]: 300 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Standard minimum RESA length is 90 m, with 240 m recommended by ICAO.

Q4: Given: Runway length = 2,500 m, Displaced threshold = 300 m, Clearway = 400 m, Stopway = 200 m. What is the LDA?

- [A]: 2,500 m
- [B]: 2,200 m
- [C]: 2,700 m
- [D]: 2,900 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. LDA is measured from the threshold to runway end: 2,500 m - 300 m displacement = 2,200 m.

Q5: What is the slope of the transitional surface for a Code 4 precision approach runway?

- [A]: 5.0%
- [B]: 10.0%
- [C]: 14.3% (1:7)
- [D]: 20.0%

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. The transitional surface slope for Code 4 runways is 14.3% (or 1:7).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 19: Aerodrome Markings & Signage

Syllabus Source: CAE Oxford (pp. 399-424) | Pass Target: >= 90% AviationExam

1. RUNWAY MARKINGS (WHITE)

Runway markings are WHITE (except yellow for displaced threshold arrows/chevrons and runway lead-in lines):

Runway Width	Number of Runway Threshold Stripes (Piano Keys)
18 m runway width	4 stripes
23 m runway width	6 stripes
30 m runway width	8 stripes
45 m runway width	12 stripes (Standard commercial jet runway)
60 m runway width	16 stripes

- Aiming Point: Two conspicuous white rectangular stripes located 400 m from threshold on runways >= 2,400 m.
- Touchdown Zone Markings: Pairs of rectangular stripes arranged symmetrically about runway centerline at 150 m intervals.
- Runway Centerline Markings: Uniformly spaced stripes and gaps: stripe length plus gap length is not less than 50 m and not more than 75 m (typically 30 m stripe and 20 m gap).
- Chevrons (Yellow): Painted on paved areas preceding threshold (blast pads, stopways) indicating area unfit for normal taxiing, take-off, or landing.

2. TAXIWAY MARKINGS & HOLDING POSITIONS (YELLOW)

- Pattern A Holding Position: Two solid yellow lines and two dashed yellow lines across taxiway. Solid lines on taxiway side; dashed lines on runway side. Aircraft MUST NOT cross solid lines towards runway without ATC clearance.
- Pattern B Holding Position: Ladder pattern ('railway tracks'). Critical area holding point for Category II / III operations. Aircraft holds here in Low Visibility Procedures (LVP) to protect ILS localizer/glidepath.
- Intermediate Holding Position: Single dashed yellow line across taxiway. Aircraft holds here until cleared by ground controller.

3. AERODROME SIGNS: MANDATORY VS INFORMATION

Sign Type	Color Scheme	Operational Meaning & Pilot Mnemonic
Mandatory Instruction Sign	WHITE letters on RED background	Identifies entrance to runway, critical area, or prohibited zone (e.g. '09-27', 'NO ENTRY', 'CAT II/III'). Must not be crossed without ATC clearance.
Location Sign	YELLOW letters on BLACK background	Identifies the taxiway or runway where the aircraft is currently located ('Black square, you are there'). Yellow border.
Direction / Destination Sign	BLACK letters on YELLOW background	Indicates designation and direction of intersecting taxiways ('Yellow lead you to the fellow'). Always includes an arrow.

Runway Exit Sign	BLACK letters on YELLOW background	Identifies runway exit taxiway (e.g. 'B ->'). Located on same side as exit.
Aerodrome Identification Sign	WHITE letters on any conspicuous color	Identifies aerodrome from air (placed on hangar roof or tower).

4. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: How many stripes are displayed on a runway threshold marking for a 45 m wide runway?

- [A]: 8
- [B]: 12
- [C]: 16
- [D]: 6

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A 45 m runway has 12 stripes (30 m has 8; 60 m has 16). Formula:
 Stripes = Width x 4 / 15.

Q2: What visual appearance designates a mandatory instruction sign at an aerodrome?

- [A]: Yellow inscription on black background
- [B]: Black inscription on yellow background
- [C]: White inscription on red background
- [D]: White inscription on green background

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Mandatory instruction signs (e.g. STOP, NO ENTRY, runway designations) have WHITE text on a RED background.

Q3: What marking identifies an unserviceable portion of a runway or taxiway?

- [A]: A single yellow diagonal line
- [B]: A white or yellow cross (X)
- [C]: A red circle
- [D]: A dashed white box

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Unserviceable areas are marked with crosses (white on runways, yellow on taxiways).

Q4: What color is used for taxiway centerline markings?

- [A]: White
- [B]: Yellow
- [C]: Red
- [D]: Blue

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. All taxiway markings, holding lines, and guidance lines are YELLOW (runway markings are white).

Q5: What visual appearance designates a location sign (identifying the taxiway or runway on which the aircraft

- [A]: Yellow text on black background with yellow border
- [B]: Black text on yellow background
- [C]: White text on red background
- [D]: White text on green background

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Location signs display YELLOW text on a BLACK background with a yellow border ('Yellow on black is where you're at; Black on yellow is where to go').

Q6: What is the meaning of a runway-holding position marking consisting of two continuous yellow lines and t

- [A]: Intermediate holding position on apron
- [B]: Mandatory runway-holding position: when approaching from continuous lines, MUST NOT cross without ATC clearance
- [C]: Road-holding position for ground vehicles
- [D]: De-icing entry line

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Pattern 'A' runway-holding position consists of two continuous lines on taxiway side and two dashed lines on runway side. An aircraft approaching from the continuous side must stop.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 20: Aerodrome Lighting & PAPI Systems

Syllabus Source: CAE Oxford (pp. 425-446) | Pass Target: >= 90% AviationExam

1. RUNWAY LIGHTING COLORS (MASTER PROGRESSION)

Lighting System	Color(s)	Location & Warning Progression
Runway Edge Lights	Variable WHITE	White, EXCEPT that on instrument runways the last 600 m (or 1/3, whichever is less) are YELLOW / AMBER to warn of runway end.
Runway Threshold Lights	GREEN	Unbroken transverse line of green lights showing in direction of approach. May include green wing bars.
Runway End Lights	RED	Unbroken transverse line of red lights showing in direction of take-off / rollout.
Runway Centerline Lights	WHITE, RED/WHITE, RED	White from threshold to 900 m from end; Alternating RED and WHITE from 900 m to 300 m from end; RED for the final 300 m.
Touchdown Zone (TDZ) Lights	WHITE barrettes	Extends from threshold for 900 m (or midpoint). Transverse rows of white barrettes.
Taxiway Edge / Centerline	BLUE edge / GREEN centerline	Taxiway edge lights are BLUE; Centerline lights are GREEN (flashing or alternate yellow/green in runway lead-on).

2. PRECISION APPROACH PATH INDICATOR (PAPI)

PAPI consists of a wing bar of 4 multi-lamp units on the left side of the runway. Standard glidepath: 3.0°:

- 4 White Lights: High (above 3° 30').
- 3 White, 1 Red: Slightly High (3° 10').
- 2 White, 2 Red: ON GLIDEPATH (3° 00' - 'Two red, two white, you're all right').
- 1 White, 3 Red: Slightly Low (2° 50').
- 4 Red Lights: Low (below 2° 30' - 'All red, you're dead').

3. VISUAL APPROACH SLOPE INDICATORS (VASIS & 3-BAR VASIS)

System Type	Visual Display Geometry & Pilot Guidance
Standard VASIS (2-Bar)	Upwind and downwind bars. Standard 3° glidepath. Red over White = On slope; Red over Red = Low; White over White = High.
3-Bar VASIS	Developed for wide-body aircraft with large eye-to-wheel height (e.g. B747). Uses middle bar as common bar. Flight crew of large aircraft fly upper glidepath (Bar 2 and 3).
T-VASIS	T-shaped light arrays on both sides of runway. Inverted 'T' indicates fly down (high); upright 'T' indicates fly up (low).

4. APPROACH LIGHTING SYSTEMS (ALS)

- Simple Approach Lighting System (SALS): Single row of lights extending at least 420 m from threshold with a 30 m crossbar at 300 m.

- Calvert Precision Approach System: Extends 900 m from threshold with 5 crossbars at 150 m intervals. Centerline lights and side row barrettes.
- Stop Bars: Unidirectional red lights embedded across taxiway at runway holding positions. Extinguished when ATC clearance is given.
- Runway Guard Lights: Pair of flashing yellow lights (wig-wags) located at taxiway/runway intersection to warn of approaching runway.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What color are runway centerline lights in the final 300 m of the runway?

- [A]: Alternate red and white
- [B]: White
- [C]: Red
- [D]: Yellow

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Centerline lights are white to 900 m, alternate red/white from 900 m to 300 m, and all RED for the final 300 m.

Q2: What is the PAPI indication for an aircraft on the correct glidepath?

- [A]: 3 white and 1 red
- [B]: 2 white and 2 red
- [C]: 4 white
- [D]: 1 white and 3 red

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Two red and two white indicates the aircraft is on the 3.0° glidepath.

Q3: What color are runway edge lights in the last 600 m of a precision instrument runway?

- [A]: Red
- [B]: Yellow / Amber
- [C]: Green
- [D]: Blue

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The last 600 m (or one third of runway length) of edge lights are yellow to warn of approaching runway end.

Q4: What color are taxiway edge lights and taxiway centerline lights?

- [A]: White edge and green centerline
- [B]: Blue edge and green centerline
- [C]: Yellow edge and blue centerline
- [D]: Green edge and white centerline

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under Annex 14, taxiway edge lights are blue and centerline lights are green.

Q5: What does a red stop bar light embedded across a taxiway indicate to a pilot?

- [A]: Proceed with caution
- [B]: Runway holding position: MUST NOT CROSS until light is extinguished by ATC
- [C]: Rapid exit taxiway
- [D]: De-icing pad entrance

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. An illuminated red stop bar is an absolute stop signal. Never cross an active red stop bar, even if verbal clearance was received.

Q6: On a precision instrument runway, what color are Touchdown Zone (TDZ) lights and how far do they extend?

- [A]: Green lights extending 300 m
- [B]: White barrettes extending from threshold for 900 m (or midpoint of runway)
- [C]: Alternating yellow and red lights for 600 m
- [D]: Blue lights for 1,200 m

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. TDZ lights consist of white barrettes extending from the threshold for 900 m (or to runway midpoint, whichever is less).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 21: Obstacles & Rescue Services (RFFS)

Syllabus Source: CAE Oxford (pp. 447-460) | Pass Target: >= 90% AviationExam

1. RESCUE AND FIRE FIGHTING SERVICES (RFFS CATEGORIES 1 TO 10)

RFFS category is determined by the overall length of the longest aeroplane using the aerodrome and its maximum fuselage width:

RFFS Category	Aircraft Overall Length	Max Fuselage Width	Representative Types
Category 1	0 m up to 9 m	2 m	Light singles (C152, PA-28)
Category 5	24 m up to 28 m	4 m	Regional turboprops (ATR-42)
Category 6	28 m up to 39 m	5 m	Regional jets (CRJ-900, E190)
Category 7	39 m up to 49 m	5 m	Single-aisle airliners (A320, B737-800)
Category 8	49 m up to 61 m	7 m	Wide-body twin-aisle (B767, B787, A330)
Category 9	61 m up to 76 m	8 m	Heavy airliners (B777, B747, A350)
Category 10	76 m up to 90 m	8 m	Very heavy airliners (Airbus A380-800)

[!] EXAM TRAP (AVIATIONEXAM) - RFFS Operational Response Time (AviationExam Core)

- Operational Objective: The operational objective of the RFFS is to achieve a response time of TWO (2) MINUTES to any point of each operational runway, and not exceeding THREE (3) MINUTES to any other part of the movement area. - Response Time Definition: The time between the initial call to the RFFS and the first responding vehicle(s) applying foam at the required rate.

2. EXTINGUISHING AGENT QUANTITIES & DISCHARGE RATES

Annex 14 specifies minimum amounts of usable water for foam production and discharge rates: - Category 6: 7,900 liters of water (Level B foam), discharge rate 4,000 L/min, complementary agent 225 kg. - Category 7: 12,100 liters of water (Level B foam), discharge rate 5,300 L/min, complementary agent 225 kg. - Category 9: 24,300 liters of water (Level B foam), discharge rate 9,000 L/min, complementary agent 450 kg.

3. OBSTACLE MARKING & LIGHTING STANDARDS

- **Marking Colors:** Fixed obstacles must be colored in a chequered pattern (orange/white or red/white) or alternating contrasting horizontal bands (at least 7 bands of orange/white or red/white).
- **Low-Intensity Lights:** Fixed red lights used for obstacles with height less than 45 m.
- **Medium-Intensity Lights:** Flashing red or flashing white lights used for obstacles between 45 m and 150 m.
- **High-Intensity Lights:** Flashing white lights (up to 200,000 cd day, 2,000 cd night) used for obstacles exceeding 150 m height (e.g. broadcast masts, tall cooling towers).

4. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the maximum acceptable RFFS response time to any point of an operational runway in optimum conditions?

- [A]: 1 minute
- [B]: 2 minutes (not exceeding 3 minutes to other movement areas)
- [C]: 4 minutes
- [D]: 5 minutes

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The operational objective is 2 minutes to runway points, and max 3 minutes to any movement area.

Q2: Which RFFS category applies to an Airbus A320 with an overall length of 37.6 m and fuselage width of 3.95 m?

- [A]: Category 5
- [B]: Category 6
- [C]: Category 7
- [D]: Category 8

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Length 28 to 39 m with width up to 5 m corresponds to RFFS Category 6 (B737-800 is Cat 7 if length exceeds 39 m).

Q3: What type of lighting is required on obstacles exceeding 150 m in height?

- [A]: Low-intensity fixed red lights
- [B]: Medium-intensity flashing red lights
- [C]: High-intensity flashing white lights
- [D]: Green strobe lights

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Annex 14 mandates high-intensity flashing white lights for obstacles taller than 150 m.

Q4: What is the principal extinguishing agent required for aerodrome rescue and fire fighting?

- [A]: CO2 gas
- [B]: Dry chemical powder
- [C]: Water with foam-producing chemical (AFFF)
- [D]: Halon 1301

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Foam produced from water and film-forming fluoroprotein or aqueous film-forming foam (AFFF) is the primary agent.

Q5: What minimum amount of complementary dry chemical powder is required for RFFS Category 7?

- [A]: 100 kg
- [B]: 225 kg
- [C]: 450 kg

- [D]: 900 kg

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under Annex 14, Category 6 and 7 aerodromes require at least 225 kg of complementary dry chemical powder or gaseous agent.

Q6: What visual markings are required on service vehicles authorized to operate on aerodrome movement areas?

- [A]: Conspicuous single yellow or orange color, or display flashing yellow beacons
- [B]: Plain white with red stripes
- [C]: Military camouflage
- [D]: Blue flashing lights only

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. Movement area service vehicles must be colored conspicuously (yellow/orange) and display flashing yellow obstacle beacons.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 22: Facilitation (Annex 9)

Syllabus Source: CAE Oxford (pp. 461-470) | Pass Target: >= 90% AviationExam

1. PURPOSE & CORE DOCUMENTS (ANNEX 9)

Annex 9 aims to prevent unnecessary delays to aircraft, crews, passengers, and cargo, especially in the administration of customs, immigration, quarantine, and health clearance procedures.

- General Declaration (GenDec): The basic document of entry and departure for an aircraft, signed by pilot-in-command or authorized agent, reporting aircraft registration, flight routing, number of crew and passengers, and public health declaration.
- Passenger Manifest: List of passenger names, embarkation points, and disembarkation points. Contracting States shall not require passenger manifests where automated systems exist.
- Cargo Manifest: Commercial document detailing air waybill numbers, nature of goods, packages, and destination.
- Crew Member Certificate (CMC): Standardized identification card issued to operating crew members to facilitate entry without visa during layover.

2. INADMISSIBLE PERSONS VS DEPORTEES

- Inadmissible Person: A person who is or will be refused admission to a State by its authorities (e.g. expired visa, fraudulent passport). The OPERATOR that transported the person is legally responsible for their custody and return transportation to their point of embarkation.
- Deportee: A person who had legally entered a State but is formally ordered to leave by government authorities. The State ordering deportation is responsible for custody and arranging transit.

3. AIRCRAFT DISINSECTION & PUBLIC HEALTH

Disinsection of aircraft cabins and flight decks is carried out to prevent the spread of mosquito-borne diseases (e.g. malaria, dengue). Permitted methods under WHO/ICAO include disinsection on arrival, pre-flight and top-of-descent spraying, or residual insecticide treatment.

4. FACILITATION OF AIR CARGO & TRANSIT PASSENGERS

- Direct Transit: Contracting States shall ensure that passengers in direct airside transit without leaving the airport international transit area are not required to hold transit visas, except under special national security declarations.
- Air Cargo Clearance: Customs clearance for standard air cargo shall be completed as soon as possible and in any event within 4 hours of arrival, utilizing electronic data interchange (EDI).

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: Who is financially and operationally responsible for removing an inadmissible passenger from a State?

- [A]: The passenger's country of nationality

- [B]: The State of destination
- [C]: The aircraft operator that carried the passenger
- [D]: ICAO Facilitation Fund

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under Annex 9, the operator that transported an inadmissible person is responsible for transporting them back to point of origin.

Q2: What is the primary purpose of the General Declaration (GenDec)?

- [A]: Flight plan filing with ATC
- [B]: Aircraft entry and clearance document for customs, immigration, and public health
- [C]: Weight and balance calculation
- [D]: Continuing airworthiness tracking

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The GenDec is the official clearance document for customs, immigration, and public health.

Q3: What document permits operating flight crew members visa-free temporary entry during international layovers?

- [A]: Student pilot licence
- [B]: Crew Member Certificate (CMC)
- [C]: Part-MED certificate
- [D]: Operator flight release

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The Crew Member Certificate (CMC) facilitates temporary visa-free entry for active crew during layovers.

Q4: Are transit passengers remaining in the airport international transit area required to obtain transit visas upon arrival?

- [A]: Yes, always
- [B]: No, Contracting States shall not require transit visas for direct transit passengers
- [C]: Only for stays exceeding 2 hours
- [D]: Yes, if arriving from outside Europe

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under Annex 9, direct transit passengers remaining airside do not require visas.

Q5: What is the primary purpose of the Health section in the General Declaration?

- [A]: Reporting crew duty time
- [B]: Declaring on-board health conditions, disinsection, and any illness before landing
- [C]: Verifying passenger vaccine records only
- [D]: Registering dangerous goods cargo

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The health section of the GenDec reports details of any illness on board and disinsection carried out during flight.

Q6: How long may an operating flight crew member stay in a State without a visa using a Crew Member Certificate?

- [A]: 24 hours only
- [B]: For the duration of the scheduled layover / turn-around
- [C]: 30 days
- [D]: Visas are always required for flight crew

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The CMC allows operating crew to remain visa-free for the scheduled layover period until their next departure flight.

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 23: Search and Rescue (Annex 12)

Syllabus Source: CAE Oxford (pp. 471-482) | Pass Target: >= 90% AviationExam

1. SAR ORGANIZATION & RESCUE COORDINATION CENTRES (RCC)

ICAO Annex 12 mandates that Contracting States establish Search and Rescue Services on a 24-hour basis. A Rescue Coordination Centre (RCC) is established in each Search and Rescue Region (SRR) to direct SAR operations.

2. GROUND-AIR VISUAL SIGNAL CODE FOR SURVIVORS

Ground signals made by survivors to search aircraft using fabric strips, wood, or trodden snow:

Visual Symbol	Meaning to Search Aircraft (Annex 12 Appendix 1)
V	Require assistance
X	Require medical assistance
N	NO or Negative
Y	YES or Affirmative
-> (Arrow)	Proceeding in this direction
LL	All well / All survivors located
JL	Operation completed

[!] EXAM TRAP (AVIATIONEXAM) - Search Aircraft Acknowledgment Signals

When a search aircraft observes survivor ground signals: - DAY: Rocking wings (for aeroplanes) or flashing landing lights twice (for helicopters). - NIGHT: Flashing landing lights or navigation lights TWICE. - If signal NOT understood: Aeroplane completes a 360° turn to the right, or displays red pyrotechnics.

3. DROPPABLE EMERGENCY EQUIPMENT COLOR STREAMERS

Containers or packages containing survival equipment dropped to survivors are indicated by colored streamers: - RED: Medical supplies and first aid equipment. - BLUE: Food and water. - YELLOW: Blankets and protective clothing. - BLACK: Miscellaneous survival equipment (knives, compasses, cooking equipment).

4. EMERGENCY LOCATOR TRANSMITTER (ELT) FREQUENCIES

- 406.0 MHz: Digital satellite frequency monitored by COSPAS-SARSAT satellite constellation. Transmits unique 24-bit aircraft hex code for instant identification. - 121.5 MHz: VHF civilian emergency frequency used for terminal acoustic/radio homing by rescue aircraft.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What does the ground-air survivor symbol 'X' signify to search aircraft?

- [A]: Require assistance
- [B]: Require medical assistance
- [C]: No or Negative
- [D]: Aircraft destroyed

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The single 'V' means 'Require assistance'; the 'X' means 'Require medical assistance'.

Q2: How does a search aeroplane acknowledge that survivor ground signals have been seen and understood?

- [A]: Firing a red flare
- [B]: Rocking wings
- [C]: Circling to the right 360°
- [D]: Pitching nose up and down

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Rocking wings by day (or flashing lights twice at night) confirms signals are understood.

Q3: Which satellite frequency is used by modern ELTs for global satellite alerting through COSPAS-SARSAT?

- [A]: 121.5 MHz
- [B]: 243.0 MHz
- [C]: 406.0 MHz
- [D]: 1090 MHz

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. 406.0 MHz is the digital satellite beacon frequency (121.5 MHz is for VHF homing).

Q4: What color streamer indicates that a dropped survival package contains food and water?

- [A]: Red
- [B]: Blue
- [C]: Yellow
- [D]: Black

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Under Annex 12, Blue denotes food and water (Red = medical, Yellow = blankets/clothing, Black = miscellaneous).

Q5: What does the ground-air visual signal 'LL' signify?

- [A]: Require food and water
- [B]: All well
- [C]: Land here
- [D]: Lost direction

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. 'LL' indicates 'All well'.

Q6: What is the international military UHF aeronautical emergency frequency monitored by SAR units?

- [A]: 121.5 MHz
- [B]: 243.0 MHz
- [C]: 406.0 MHz
- [D]: 1090 MHz

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. 243.0 MHz is the international UHF military aeronautical emergency frequency.

Q7: What does the ground-air survivor visual symbol 'V' signify to search aircraft?

- [A]: Require medical assistance
- [B]: Require assistance
- [C]: All well
- [D]: Operation completed

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Single 'V' signifies 'Require assistance' ('X' is require medical assistance; 'LL' is all well).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 24: Security & Unlawful Interference

Syllabus Source: CAE Oxford (pp. 483-492) | Pass Target: >= 90% AviationExam

1. SECURITY ARCHITECTURE & OBJECTIVES

Annex 17 establishes Standards and Recommended Practices to safeguard international civil aviation against acts of unlawful interference. Each Contracting State must designate an appropriate authority for civil aviation security.

- Security Restricted Area (SRA): Airside areas where access is controlled to ensure civil aviation security (e.g. passenger boarding areas, baggage sorting areas, aprons). All persons and vehicles are screened 100%.
- 100% Hold Baggage Screening: All originating hold baggage must be screened prior to being loaded onto commercial aircraft.
- Flight Deck Security Door: On commercial aeroplanes with MTOM > 54,000 kg or passenger seating > 19, the flight crew compartment door must be capable of being locked from the inside and resist small arms fire and grenade shrapnel.

2. UNRULY PASSENGER THREAT LEVELS (ICAO DOC 9811)

- Level 1: Disruptive Behavior: Verbal abuse, failure to follow crew instructions, non-violent disruptive conduct.
- Level 2: Physically Abusive Behavior: Physical contact, pushing, shoving, kicking, damage to cabin property.
- Level 3: Life-Threatening Behavior: Display or threat of weapons, credible terroristic threat, direct physical injury.
- Level 4: Attempted / Actual Flight Deck Breach: Attempt to force cockpit entry, hijack attempt, sabotage.

3. IN-FLIGHT SECURITY OFFICERS (SKY MARSHALS)

Under Annex 17, the deployment of In-Flight Security Officers (IFSOs) shall be subject to bilateral agreement between the States involved. When deployed, IFSOs are government personnel authorized to carry firearms on board. The Pilot-in-Command retains ultimate command of the aircraft, but the IFSO operates in accordance with their national mandate.

4. REGULATED AGENTS & AIR CARGO SECURITY

A Regulated Agent (RA) is an agent, freight forwarder, or entity that conducts business with an operator and applies security controls accepted by the competent authority. Cargo from a regulated agent or known consignor maintains secure chain of custody and may be loaded without duplicate screening.

5. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: Which aircraft are required to have an armored, lockable flight deck security door under Annex 6/17?

- [A]: All commercial aircraft without exception
- [B]: Aeroplanes with MTOM > 5,700 kg only
- [C]: Passenger aeroplanes with MTOM > 54,000 kg or seating capacity > 19 passengers

- [D]: Multi-engine turboprops only

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Armored, bullet-resistant lockable cockpit doors are required on passenger aeroplanes exceeding 54,000 kg MTOM or more than 19 passenger seats.

Q2: Under ICAO threat classifications, what level corresponds to an attempted cockpit breach?

- [A]: Level 1
- [B]: Level 2
- [C]: Level 3
- [D]: Level 4

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [D]. Level 4 is the highest threat level, denoting an attempted or actual breach of the flight crew compartment.

Q3: What transponder code must be squawked in the event of unlawful interference (hijack)?

- [A]: 7000
- [B]: 7500
- [C]: 7600
- [D]: 7700

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Squawk Mode A Code 7500 denotes hijacking / unlawful interference.

Q4: What is the legal status of In-Flight Security Officers (IFSOs) on international commercial flights?

- [A]: Permitted on all flights without prior notification
- [B]: Permitted only with mutual agreement between the State of the Operator and the State of destination
- [C]: Strictly prohibited by ICAO
- [D]: Mandatory on all flights over 5 hours

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Annex 17 mandates that deployment of armed security officers is subject to bilateral agreement between States.

Q5: What is a 'Regulated Agent' in the context of aviation security under Annex 17?

- [A]: An armed police officer at the airport
- [B]: An agent, freight forwarder, or entity that conducts business with an operator and applies security controls accepted by the competent authority
- [C]: A customs broker
- [D]: An airline ticketing manager

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. A Regulated Agent is an entity authorized to apply approved security screening and chain-of-custody controls to air cargo.

Q6: Which international convention was the first to address offenses and certain other acts committed on board?

- [A]: Tokyo Convention (1963)
- [B]: Hague Convention (1970)
- [C]: Montreal Convention (1971)
- [D]: Rome Convention (1952)

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [A]. The Tokyo Convention of 1963 was the first international convention establishing jurisdiction and powers of the aircraft commander over offenses on board.

Q7: What is the primary focus of the 1971 Montreal Convention regarding aviation safety?

- [A]: Economic regulation of air fares
- [B]: Suppression of unlawful acts against the safety of civil aviation (sabotage, explosive devices, and damaging facilities)
- [C]: Suppression of unlawful seizure of aircraft (hijacking)
- [D]: Carrier liability for lost baggage

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The Montreal Convention of 1971 covers acts of sabotage, damage to air navigation facilities, and placing destructive devices (the Hague Convention of 1970 covers hijacking).

ATPL EASA STUDY GUIDE | 010 - AIR LAW

Chapter 25: Accident Investigation (Annex 13)

Syllabus Source: CAE Oxford (pp. 493-506) | Pass Target: >= 90% AviationExam

1. ACCIDENT VS SERIOUS INCIDENT VS INCIDENT (ANNEX 13)

[*] OFFICIAL DEFINITION - Definition of an Accident

An occurrence associated with the operation of an aircraft between the time any person boards with the intention of flight until such time as all persons have disembarked, in which: 1. A person is FATALLY or SERIOUSLY INJURED (except self-inflicted, natural causes, or stowaways); 2. The aircraft sustains DAMAGE OR STRUCTURAL FAILURE adversely affecting strength, performance, or flight characteristics, requiring major repair; OR 3. The aircraft is MISSING or completely inaccessible.

- Fatal Injury: An injury resulting in death within 30 DAYS of the date of the accident.
- Serious Injury: An injury requiring hospitalization > 48 hours within 7 days; fracture of bone (except simple fingers/toes/nose); lacerations causing severe hemorrhage; internal organ damage; or 2nd/3rd degree burns over > 5% of body surface.
- Serious Incident: An incident involving circumstances indicating that there was a high probability of an accident (e.g. near collision requiring evasive maneuver, landing on taxiway, uncontained engine failure).

2. SOLE OBJECTIVE OF INVESTIGATION (ABSOLUTE EXAM CORE)

[!] EXAM TRAP (AVIATIONEXAM) - Sole Objective: Prevention of Accidents (NOT Blame)

The sole objective of the investigation of an accident or incident under Annex 13 shall be the PREVENTION of accidents and incidents. It is explicitly NOT the purpose of this activity to apportion blame or liability.

3. STATE RESPONSIBILITIES & PROTECTION OF RECORDS

- Investigation Responsibility: The State of OCCURRENCE institutes the inquiry.
- Accredited Representatives: State of Registry, State of Operator, State of Design, and State of Manufacture are entitled to appoint an Accredited Representative.
- Non-Disclosure of Records: Cockpit voice recordings (CVR), witness statements, and personal medical information must NOT be made available for purposes other than accident investigation (e.g. criminal liability).
- Final Report Target: The State conducting investigation shall release Final Report as soon as possible, ideally within 12 MONTHS.

4. FLIGHT DATA & COCKPIT VOICE RECORDERS (PRESERVATION)

- Flight Data Recorder (FDR): Must record parameters for at least the preceding 25 HOURS of operation. - Cockpit Voice Recorder (CVR): Must retain information recorded during at least the last 2 HOURS (increased to 25 hours for newly manufactured large aeroplanes). - In the event of an accident or serious incident, the operator must PRESERVE all original recorded data without erasure.

5. MANDATORY OCCURRENCE REPORTING (EU NO 376/2014)

Under Regulation (EU) No 376/2014, any occurrence which may represent a significant risk to aviation safety must be reported by the flight crew, operator, or ATS provider to the competent authority within 72 HOURS of becoming aware of the occurrence.

6. AVIATIONEXAM PRACTICE QUESTIONS (WITH EXPLANATIONS)

Q1: What is the sole objective of an aircraft accident investigation under ICAO Annex 13?

- [A]: To determine who is legally liable
- [B]: The prevention of accidents and incidents
- [C]: To assist insurance claims settlement
- [D]: To penalize regulatory violations

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. The sole objective under Annex 13 is explicitly the prevention of accidents and incidents, NOT to apportion blame or liability.

Q2: Under Annex 13, a fatal injury is defined as an injury resulting in death within how many days?

- [A]: 7 days
- [B]: 14 days
- [C]: 30 days
- [D]: 60 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. A fatal injury is one resulting in death within 30 days of the accident.

Q3: Are Cockpit Voice Recorder (CVR) recordings allowed to be used for criminal prosecution of the crew?

- [A]: Yes, without restriction
- [B]: NO, CVR recordings are strictly protected from disclosure for non-investigative purposes
- [C]: Only if requested by the airline
- [D]: Only in fatal accidents

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [B]. Annex 13 strictly protects CVR recordings from disclosure for purposes other than accident investigation.

Q4: What is the minimum recording duration of a Flight Data Recorder (FDR) on commercial air transport aeroplanes?

- [A]: 2 hours
- [B]: 10 hours
- [C]: 25 hours
- [D]: 60 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under ICAO Annex 6 and Part-CAT, modern FDRs must retain data for at least 25 hours.

Q5: Under Regulation (EU) No 376/2014, within how many hours must a mandatory safety occurrence report be

- [A]: 24 hours
- [B]: 48 hours
- [C]: 72 hours
- [D]: 7 days

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Mandatory safety occurrences must be reported within 72 hours of becoming aware of the occurrence.

Q6: Which State has the primary responsibility to institute and conduct an aircraft accident investigation under

- [A]: The State of Registry
- [B]: The State of the Operator
- [C]: The State of Occurrence
- [D]: The State of Manufacture

[?] OFFICIAL RATIONALE & ANALYSIS - Detailed Answer Explanation

CORRECT: [C]. Under Annex 13, the State of Occurrence is responsible for instituting and conducting the investigation.