Curso: Java COMPLETO - Programação Orientada a Objetos + Projetos

http://educandoweb.com.br

Prof. Dr. Nelio Alves

Capítulo: Projeto JavaFX com JDBC

Objetivo geral:

- Introduzir o aluno ao desenvolvimento de aplicações JavaFX com JDBC
- Permitir que o aluno conheça os fundamentos e a utilização das ferramentas, de modo que ele possa depois prosseguir estudando, de forma confortável, as especificidades que desejar

REQUISITOS: OO & Lambda & JDBC & JavaFX

PROJETO: https://github.com/acenelio/workshop-javafx-jdbc

Github project

Checklist:

Gitignore: Java

Local project created

Checklist:

- User libraries: JavaFX, MySQLConnector
- Run configurarions -> VM arguments:
 - --module-path C:\java-libs\javafx-sdk\lib --add-modules=javafx.fxml,javafx.controls
- Git:
 - o git init
 - o git remote add origin https://github.com/acenelio/workshop-javafx-jdbc.git
 - o git pull origin master
- Gitignore:

build folders

bin/

target/

nbproject/private/

build/

nbbuild/

dist/

nbdist/

Main view

- Create FXML "MainView" (package "gui")
- Load FXML in Main
- Update Main.java

Main view design

- Design MainView.fxml
- Customize menu items
- Update Main.java

```
<?xml version="1.0" encoding="UTF-8"?>
<?import javafx.scene.control.Menu?>
<?import javafx.scene.control.MenuBar?>
<?import javafx.scene.control.MenuItem?>
<?import javafx.scene.control.ScrollPane?>
<?import javafx.scene.layout.VBox?>
<ScrollPane maxHeight="-Infinity" maxWidth="-Infinity" minHeight="-Infinity" minWidth="-Infinity"</pre>
prefHeight="400.0" prefWidth="600.0" xmlns="http://javafx.com/javafx/10.0.1"
xmlns:fx="http://javafx.com/fxml/1">
      <VBox prefHeight="326.0" prefWidth="513.0">
         <children>
            <MenuBar>
              <menus>
                <Menu mnemonicParsing="false" text="Registration">
                    <MenuItem mnemonicParsing="false" text="Seller" />
                        <MenuItem mnemonicParsing="false" text="Departments" />
                  </items>
                </Menu>
                <Menu mnemonicParsing="false" text="Help">
                    <MenuItem mnemonicParsing="false" text="About" />
                  </items>
                </Menu>
              </menus>
            </MenuBar>
         </children>
      </VBox>
   </content>
</ScrollPane>
```

Main view controller

Checklist:

- Create controller
- In view, associate controller, ids, events

About view

Checklist:

- Include util classes to the project (Alerts.java, Constraints.java)
 https://github.com/acenelio/javafx5/blob/master/src/gui/util/Alerts.java
 https://github.com/acenelio/javafx5/blob/master/src/gui/util/Constraints.java
- Create About.fxml (VBox)
- In Main.java, expose mainScene reference
- In MainViewController.java, create loadView method

DepartmentList view design

- Create DepartmentList.fxml (VBox)
- In MainViewController.java, load DepartmentList

```
<?xml version="1.0" encoding="UTF-8"?>
<?import javafx.geometry.Insets?>
<?import javafx.scene.control.Button?>
<?import javafx.scene.control.Label?>
<?import javafx.scene.control.TableColumn?>
<?import javafx.scene.control.TableView?>
<?import javafx.scene.control.ToolBar?>
<?import javafx.scene.layout.VBox?>
<?import javafx.scene.text.Font?>
<VBox maxHeight="-Infinity" maxWidth="-Infinity" minHeight="-Infinity" minWidth="-Infinity"</pre>
prefHeight="400.0" prefWidth="600.0" xmlns="http://javafx.com/javafx/10.0.1"
xmlns:fx="http://javafx.com/fxml/1">
  <children>
      <Label text="Department Registration">
         <font>
            <Font name="System Bold" size="14.0" />
         </font>
         <padding>
            <Insets left="5.0" top="5.0" />
         </padding>
      </Label>
      <ToolBar prefHeight="40.0" prefWidth="200.0">
          <Button fx:id="btNew" mnemonicParsing="false" text="New" />
        </items>
      </ToolBar>
      <TableView prefHeight="200.0" prefWidth="200.0">
        <columns>
          <TableColumn prefWidth="75.0" text="Id" />
          <TableColumn prefWidth="75.0" text="Name" />
        </columns>
      </TableView>
  </children>
</VBox>
```

DepartmentList controller

Checklist:

- Create model.entities.Department.java https://github.com/acenelio/demo-dao-jdbc/blob/master/src/model/entities/Department.java
- Create DepartmentListController.java
- In view, associate controller, ids, events

DepartmentService

Checklist:

- Create model.services.DepartmentService.java with findAll method
- In DepartmentListController:
 - o Create DepartmentService dependency with set method
 - o Create ObservableList<Department>
 - o Create updateTableViewData method

Initializing action as parameter

Checklist:

- Add a Consumer<T> parameter to loadView method
- After loading view, call accept from the Consumer
- Add a consumer instance on loadView calls

Adding database access

Prerequisites:

- MySQL server installed and running
- Database created and instantiated https://github.com/acenelio/demo-dao-jdbc/blob/master/database.sql
- Data access layer implemented (DAO pattern): https://github.com/acenelio/demo-dao-jdbc

- Add model.entities.Seller.java
- Add db.properties do project
- Add data access packages to project:
 - o db
 - o model.dao
 - o model.dao.impl
- In DepartmentService, add DepartmentDao dependency with Factory call

DepartmentForm (dialog) design

- Create gui.util.Utils.java with currentStage method
- Create DepartmentForm.fxml (AnchorPane)
 - o GridPane 3x3 (anchors: 20 top, 20 left)
 - o Id text box: not editable
 - Label error: red
 - HBox (spacing: 5)
- In DepartmentListController, create createDialogForm method
- Call createDialogForm on "new" button action

```
<?xml version="1.0" encoding="UTF-8"?>
<?import javafx.scene.control.Button?>
<?import javafx.scene.control.Label?>
<?import javafx.scene.control.TextField?>
<?import javafx.scene.layout.AnchorPane?>
<?import javafx.scene.layout.ColumnConstraints?>
<?import javafx.scene.layout.GridPane?>
<?import javafx.scene.layout.HBox?>
<?import javafx.scene.layout.RowConstraints?>
<AnchorPane prefHeight="139.0" prefWidth="532.0" xmlns="http://javafx.com/javafx/10.0.1"</pre>
xmlns:fx="http://javafx.com/fxml/1">
   <children>
      <GridPane layoutX="33.0" layoutY="32.0" prefHeight="95.0" prefWidth="499.0"</pre>
AnchorPane.leftAnchor="20.0" AnchorPane.topAnchor="20.0">
        <columnConstraints>
          <ColumnConstraints hgrow="SOMETIMES" maxWidth="161.0" minWidth="10.0" prefWidth="63.0" />
          <ColumnConstraints hgrow="SOMETIMES" maxWidth="270.0" minWidth="10.0" prefWidth="160.0" />
            <ColumnConstraints hgrow="SOMETIMES" maxWidth="245.0" minWidth="10.0" prefWidth="243.0" />
        </columnConstraints>
        <rowConstraints>
          <RowConstraints minHeight="10.0" prefHeight="30.0" vgrow="SOMETIMES" />
          <RowConstraints minHeight="10.0" prefHeight="30.0" vgrow="SOMETIMES" />
          <RowConstraints minHeight="10.0" prefHeight="30.0" vgrow="SOMETIMES" />
        </rowConstraints>
         <children>
            <Label text="Id" />
            <Label text="Name" GridPane.rowIndex="1" />
            <Label textFill="RED" GridPane.columnIndex="2" GridPane.rowIndex="1" />
            <TextField editable="false" GridPane.columnIndex="1" />
            <TextField GridPane.columnIndex="1" GridPane.rowIndex="1" />
            <HBox prefHeight="100.0" prefWidth="200.0" spacing="5.0" GridPane.columnIndex="1"</pre>
GridPane.rowIndex="2">
               <children>
                  <Button mnemonicParsing="false" text="Save" />
                  <Button mnemonicParsing="false" text="Cancel" />
            </HBox>
         </children>
      </GridPane>
   </children>
</AnchorPane>
```

DepartmentFormController

Checklist:

- Create DepartmentFormController.java
- In view, associate controller, ids, events

Passing a Department object to DepartmentForm view

Checklist:

- In DepartmentFormController
 - o Create a Department dependency with set method
 - Create updateFormData method
- In DepartmentListController
 - o Update onBtNewAction method
 - Update createDialogForm method

Saving a new Department

Checklist:

- In Utils, implement tryParseToInt method
- In DepartmentService, create saveOrUpdate method
- In DepartmentFormController
 - Create a DepartmentService dependency with set method
 - Implement onBtSaveAction
 - o Implement onBtCancelAction
- In DepartmentListController, inject DepartmentService instance

Observer design pattern to update tableview

Checklist:

- Create interface gui.listeners.DataChangeListener
- In DepartmentFormController (subject)
 - o Create List<DataChangeListener> dependency with subscribe method
 - Notify subscribers when needed
- In DepartmentListController (observer)
 - Implement DataChangeListener interface
 - Subscribe for DepartmentFormController

Validation exception

- Create model.exceptions.ValidationException
- In DepartmentFormController
 - o In getFormData method, implement verifications and throw ValidationException
 - o Implement setErrorMessages method
 - o In onBtSaveAction, catch ValidationException

Update department

References:

https://stackoverflow.com/questions/32282230/fxml-javafx-8-tableview-make-a-delete-button-in-each-row-and-delete-the-row-a

Checklist:

- In DepartmentListController
 - o Create new attribute: TableColumn<Department, Department> tableColumnEDIT;
 - o Create initEditButtons method
 - In updateTableViewData, call initEditButtons
- In DepartmentList.fxml
 - o Include new table column
 - Associate id

```
private void initEditButtons() {
       tableColumnEDIT.setCellValueFactory(param -> new ReadOnlyObjectWrapper<>(param.getValue()));
       tableColumnEDIT.setCellFactory(param -> new TableCell<Department, Department>() {
              private final Button button = new Button("edit");
              @Override
              protected void updateItem(Department obj, boolean empty) {
                      super.updateItem(obj, empty);
                      if (obj == null) {
                             setGraphic(null);
                             return;
                      }
                      setGraphic(button):
                      button.setOnAction(
                      event -> createDialogForm(
                             obj, "/gui/DepartmentForm.fxml",Utils.currentStage(event)));
              }
       });
}
```

Remove department

References:

 $\underline{\text{https://stackoverflow.com/questions/32282230/fxml-javafx-8-tableview-make-a-delete-button-in-each-row-and-delete-the-row-a}$

- In Alerts, create showConfirmation method
- In DepartmentService, create remove method
- In DepartmentListController
 - Create new attribute: TableColumn
 Department
 Department
 tableColumnREMOVE
 - Create initRemoveButtons method
 - Catch DbIntegrityException
 - In updateTableViewData, call initRemoveButtons
- In DepartmentList.fxml
 - o Include new table column
 - o Associate id

```
public static Optional<ButtonType> showConfirmation(String title, String content) {
       Alert alert = new Alert(AlertType. CONFIRMATION);
       alert.setTitle(title);
       alert.setHeaderText(null);
       alert.setContentText(content);
       return alert.showAndWait();
}
private void initRemoveButtons() {
       tableColumnREMOVE.setCellValueFactory(param -> new ReadOnlyObjectWrapper<>(param.getValue()));
       tableColumnREMOVE.setCellFactory(param -> new TableCell<Department, Department>() {
        private final Button button = new Button("remove");
        @Override
        protected void updateItem(Department obj, boolean empty) {
            super.updateItem(obj, empty);
            if (obj == null) {
                setGraphic(null);
                return;
            }
            setGraphic(button);
            button.setOnAction(event -> removeEntity(obj));
   });
}
```

Deleting .settings folder

Checklist:

- .gitignore: .settings/
- Delete .settings/ folder

SellerList

- Clone SellerService
 - o Replace: Department -> Seller
- Clone SellerListController
 - o Replace: Department -> Seller
 - o Comment createDialogForm
- Clone SellerList.fxml
 - o Replace: Department -> Seller
- Update MainViewController.onMenuItemSellerAction

Seller TableView

References:

https://stackoverflow.com/questions/47484280/format-of-date-in-the-javafx-tableview

- gui.utils.Util.java
 - o formatTableColumnDate method
 - o formatTableColumnDouble method
- SellerListController
 - o TableColumn attributes (Email, BirthDate, BaseSalary)
 - Update initializeNodes
- SellerListView
 - o TableColumn (Email, BirthDate, BaseSalary)
 - Associate fx:id

```
public static <T> void formatTableColumnDate(TableColumn<T, Date> tableColumn, String format) {
        tableColumn.setCellFactory(column -> {
                TableCell<T, Date> cell = new TableCell<T, Date>() {
                         private SimpleDateFormat sdf = new SimpleDateFormat(format);
                         @Override
                         protected void updateItem(Date item, boolean empty) {
                                 super.updateItem(item, empty);
                                 if (empty) {
                                         setText(null);
                                 } else {
                                         setText(sdf.format(item));
                                 }
                         }
                };
                return cell;
        });
}
public static <T> void formatTableColumnDouble(TableColumn<T, Double> tableColumn, int decimalPlaces) {
        tableColumn.setCellFactory(column -> {
                TableCell<T, Double> cell = new TableCell<T, Double>() {
                         protected void updateItem(Double item, boolean empty) {
                                 super.updateItem(item, empty);
                                 if (empty) {
                                         setText(null);
                                 } else {
                                         Locale.setDefault(Locale.US);
                                         setText(String.format("%."+decimalPlaces+"f", item));
                                 }
                         }
                };
                return cell;
        });
}
```

SellerForm

Checklist:

- Clone SellerFormController
 - o Replace: Department -> Seller
- Clone SellerForm view
 - o Replace: Department -> Seller
- SellerListController
 - o Uncomment createDialogForm

TextField & DatePicker

References:

https://stackoverflow.com/questions/26831978/javafx-datepicker-getvalue-in-a-specific-format

- gui.utils.Util.java
 - o formatDatePicker method
- TextField & DatePicker attributes (Email, BirthDate, BaseSalary)
- Label error attributes (Email, BirthDate, BaseSalary)
- Edit SellerFormView
- Bugfix: SellerDaoJDBC.instantiateSeller
 obj.setBirthDate(new java.util.Date(rs.getTimestamp("BirthDate").getTime()));
- Update: initializeNodes
- Update: updateFormData

```
public static void formatDatePicker(DatePicker datePicker, String format) {
        datePicker.setConverter(new StringConverter<LocalDate>() {
                DateTimeFormatter dateFormatter = DateTimeFormatter.ofPattern(format);
                        datePicker.setPromptText(format.toLowerCase());
                @Override
                public String toString(LocalDate date) {
                        if (date != null) {
                                 return dateFormatter.format(date);
                        } else {
                                 return "";
                        }
                }
                @Override
                public LocalDate fromString(String string) {
                        if (string != null && !string.isEmpty()) {
                                 return LocalDate.parse(string, dateFormatter);
                                 return null;
                        }
        });
}
```

Department ComboBox

Checklist:

- Update controller:
 - o DepartmentService dependency
 - attribute
 - set method
 - o ComboBox<Department> comboBoxDepartment
 - ObservableList<Department> obsList
 - loadAssociatedObjects
 - initializeComboBoxDepartment
 - o updateFormData
- Update view:
 - o ComboBox
 - o fx:id

Saving Seller

Checklist:

Update: getFormData

• Update: setErrorMessages