

Module IV - Basic Analysis

Drew Conway — Department of Politics



NEW YORK UNIVERSITY

June 29, 2010

Agenda for Module IV

Loading data from multiple sources

- ▶ Local network data files
- ▶ Connecting to a database
- ▶ Building directly from the Internet

Agenda for Module IV

Loading data from multiple sources

- ▶ Local network data files
- ▶ Connecting to a database
- ▶ Building directly from the Internet

Brief review of Python dict data type

- ▶ Why it is so useful
- ▶ How NetworkX utilizes it

Agenda for Module IV

Loading data from multiple sources

- ▶ Local network data files
- ▶ Connecting to a database
- ▶ Building directly from the Internet

Brief review of Python dict data type

- ▶ Why it is so useful
- ▶ How NetworkX utilizes it

Running basic centralities

- ▶ Degree, Closeness, Betweenness Eigenvector
- ▶ Calculating degree distribution
- ▶ Plotting statistics using matplotlib
- ▶ Calculating cliques, clustering and transitivity

Agenda for Module IV

Loading data from multiple sources

- ▶ Local network data files
- ▶ Connecting to a database
- ▶ Building directly from the Internet

Brief review of Python dict data type

- ▶ Why it is so useful
- ▶ How NetworkX utilizes it

Running basic centralities

- ▶ Degree, Closeness, Betweenness Eigenvector
- ▶ Calculating degree distribution
- ▶ Plotting statistics using matplotlib
- ▶ Calculating cliques, clustering and transitivity

Outputting data into multiple formats

- ▶ Writing network data
- ▶ Saving network analysis statistics

Agenda for Module IV

Loading data from multiple sources

- ▶ Local network data files
- ▶ Connecting to a database
- ▶ Building directly from the Internet

Brief review of Python dict data type

- ▶ Why it is so useful
- ▶ How NetworkX utilizes it

Running basic centralities

- ▶ Degree, Closeness, Betweenness Eigenvector
- ▶ Calculating degree distribution
- ▶ Plotting statistics using matplotlib
- ▶ Calculating cliques, clustering and transitivity

Outputting data into multiple formats

- ▶ Writing network data
- ▶ Saving network analysis statistics

Basic visualization

- ▶ Review of NetworkX's plotting algorithms
- ▶ Adding analysis to visualization

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- ▶ For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

```
>>> G = read_format("path/to/file.txt", ...options...)
      ↑           ↑                               ↑
Net variable   NX function, file directory path   Graph type, nodes type, etc.
```

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

<code>>>> G</code>	<code>=</code>	<code>read_format("path/to/file.txt",</code>	<code>...options...)</code>
↑		↑	↑
Net variable		NX function, file directory path	Graph type, nodes type, etc.

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- ▶ For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

`>>> G = read_format("path/to/file.txt", ...options...)`

↑ ↑ ↑

Net variable NX function, file directory path Graph type, nodes type, etc.

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

```
>>> G = read_format("path/to/file.txt", ...options...)
```

↑ ↑ ↑

Net variable NX function, file directory path Graph type, nodes type, etc.

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

```
>>> G = read_format("path/to/file.txt", ...options...)
      ↑           ↑                               ↑
Net variable   NX function, file directory path   Graph type, nodes type, etc.
```

Let's try!

- ▶ We will load the edge list of Hartford drug users network
- ▶ Specify that the network be a directed graph, and the nodes be integers
- ▶ Use `info()` to check that data has been loaded correctly

Loading a network file

As we have seen, one of the main advantages of working with NetworkX is that it can read many different network formats

- ▶ For those that are unfamiliar with working at the **command-line**, however, the process can be confusing

NX syntax for loading a file

```
>>> G = read_format("path/to/file.txt", ...options...)
      ↑           ↑                               ↑
Net variable   NX function, file directory path   Graph type, nodes type, etc.
```

Let's try!

- ▶ We will load the edge list of Hartford drug users network
- ▶ Specify that the network be a directed graph, and the nodes be integers
- ▶ Use `info()` to check that data has been loaded correctly

It's time to fire up your console and load Python!

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)
>>> info(hartford)
Name:
Type:          DiGraph
Number of nodes: 212
Number of edges: 337
Average in degree: 1.5896
Average out degree: 1.5896
```

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *  
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)  
>>> info(hartford)  
Name:  
Type:          DiGraph  
Number of nodes: 212  
Number of edges: 337  
Average in degree: 1.5896  
Average out degree: 1.5896
```

What did we just do?

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *  
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)  
>>> info(hartford)  
Name:  
Type:          DiGraph  
Number of nodes: 212  
Number of edges: 337  
Average in degree: 1.5896  
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *  
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)  
>>> info(hartford)  
Name:  
Type:          DiGraph  
Number of nodes: 212  
Number of edges: 337  
Average in degree: 1.5896  
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file
- ▶ Specified path to Hartford drug users file

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)
>>> info(hartford)
Name:
Type:          DiGraph
Number of nodes: 212
Number of edges: 337
Average in degree: 1.5896
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file
- ▶ Specified path to Hartford drug users file
- ▶ Used the `create_using` option to force NX to create as a directed graph

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)
>>> info(hartford)
Name:
Type:          DiGraph
Number of nodes: 212
Number of edges: 337
Average in degree: 1.5896
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file
- ▶ Specified path to Hartford drug users file
- ▶ Used the `create_using` option to force NX to create as a directed graph
- ▶ Used the `nodetype` option to force NX to store nodes as integers

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *  
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)  
>>> info(hartford)  
Name:  
Type:          DiGraph  
Number of nodes: 212  
Number of edges: 337  
Average in degree: 1.5896  
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file
- ▶ Specified path to Hartford drug users file
- ▶ Used the `create_using` option to force NX to create as a directed graph
- ▶ Used the `nodetype` option to force NX to store nodes as integers
- ▶ Used the `info` function to check that it all worked

Loading the Hartford drug users network

Starting NetworkX and loading data

```
>>> from networkx import *
>>> hartford=read_edgelist("../data/hartford_drug.txt",create_using=DiGraph(),nodetype=int)
>>> info(hartford)
Name:
Type:          DiGraph
Number of nodes: 212
Number of edges: 337
Average in degree: 1.5896
Average out degree: 1.5896
```

What did we just do?

- ▶ Used the `read_edgelist` function to load EL file
- ▶ Specified path to Hartford drug users file
- ▶ Used the `create_using` option to force NX to create as a directed graph
- ▶ Used the `nodetype` option to force NX to store nodes as integers
- ▶ Used the `info` function to check that it all worked


Some formats may have more or less options, **always check the documentations!**

Building a network from a database

As data sets become larger and persistently changing, it may make more sense to store them in a database rather than a single file


- ▶ As we have seen, Python provides binding to many modern database frameworks

Building the social network among LiveJournal users



Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data


Building the social network among LiveJournal users



Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data

- In Python, use NetworkX, cjson and a other standard scientific libraries to parse Google's SocialGraph data


Building the social network among LiveJournal users



Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data

- ▶ In Python, use NetworkX, cjson and a other standard scientific libraries to parse Google's SocialGraph data
- ▶ Using a "seed" user, we will build out a network


Building the social network among LiveJournal users



Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data

- ▶ In Python, use NetworkX, cjson and a other standard scientific libraries to parse Google's SocialGraph data
- ▶ Using a "seed" user, we will build out a network
- ▶ Through a process called "k-snowball searching"
 $seed \rightarrow friend \rightarrow \dots \rightarrow friend_k$

Building the social network among LiveJournal users




Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data

- ▶ In Python, use NetworkX, cjson and a other standard scientific libraries to parse Google's SocialGraph data
- ▶ Using a "seed" user, we will build out a network
- ▶ Through a process called "k-snowball searching"

$$\text{seed} \rightarrow \text{friend} \rightarrow \dots \rightarrow \text{friend}_k$$
 - ▶ Seed: imichaeldotorg.livejournal.com
 - ▶ $k = 3$

Building the social network among LiveJournal users



Perhaps the most powerful aspect of NetworkX is its ability to work in Python to generate networks from live-streaming data

- ▶ In Python, use NetworkX, cjson and a other standard scientific libraries to parse Google's SocialGraph data
- ▶ Using a "seed" user, we will build out a network
- ▶ Through a process called "k-snowball searching"

$$\text{seed} \rightarrow \text{friend} \rightarrow \dots \rightarrow \text{friend}_k$$
 - ▶ Seed: imichaeldotorg.livejournal.com
 - ▶ $k = 3$
- ▶ Note the low value of k

The code, part 1

Loading the libraries and setting things up

```
from cjson import *
from urllib import *
from networkx import *
from time import *
from scipy import array,unique
...
if __name__ == "__main__":
    seed_url='http://imichaeldotorg.livejournal.com'
    sg=get_sg(seed_url)
    net,newnodes=create_egonet(sg)
    info(net)
```

Get the JSON from SocialGraph

```
def get_sg(seed_url):
    sgapi_url="http://socialgraph.apis.google.com/lookup?q="+seed_url+"&edo=1&edi=1&fme=1&pretty=0"
    try:
        furl=urlopen(sgapi_url)
        fr=furl.read()
        furl.close()
        return fr
    except IOError:
        print "Could not connect to website"
        print sgapi_url
        return
```

The code, part 1

Loading the libraries and setting things up

```
from cjson import *
from urllib import *
from networkx import *
from time import *
from scipy import array, unique
...
if __name__ == "__main__":
    seed_url='http://imichaeldotorg.livejournal.com'
    sg=get_sg(seed_url)
    net,newnodes=create_egonet(sg)
    info(net)
```

```
Name: ['http://imichaeldotorg.livejournal.com/']
Type: DiGraph
Number of nodes: 5
Number of edges: 5
Average in degree: 1.0
Average out degree: 1.0
```

Get the JSON from SocialGraph

```
def get_sg(seed_url):
    sgapi_url="http://socialgraph.apis.google.com/lookup?q="+seed_url+"&edo=1&edi=1&fme=1&pretty=0"
    try:
        furl=urlopen(sgapi_url)
        fr=furl.read()
        furl.close()
        return fr
    except IOError:
        print "Could not connect to website"
        print sgapi_url
        return
```

Build egonet and snowball

Creating the egonet

```
def create_egonet(s):
    try:
        raw=decode(s)
        G=DiGraph()
        pendants=[]
        n=raw['nodes']
        nk=n.keys()
        G.name=str(nk)
        pendants=[]
        for a in range(0,len(nk)):
            for b in range(0,len(nk)):
                if a!=b:
                    G.add_edge(nk[a],nk[b])
        for k in nk:
            ego=n[k]
            ego_out=ego['nodes_referenced']
            for o in ego_out:
                G.add_edge(k,o)
                pendants.append(o)
            ego_in=ego['nodes_referenced_by']
            for i in ego_in:
                G.add_edge(i,k)
                pendants.append(i)
        pendants=array(pendants, dtype=str)
        pendants.flatten()
        pendants=unique(pendants)
        return G, pendants
    except DecodeError:
        ...
    except KeyError:
```

Rolling the snowball

```
def snowball_round(G, seeds, myspace=False):
    t0=time()
    if myspace:
        seeds=get_myspace_url(seeds)
    sb_data=[]
    for s in range(0,len(seeds)):
        s_sg=get_sg(seeds[s])
        new_ego, pen=create_egonet(s_sg)
        for p in pen:
            sb_data.append(p)
    if s<1:
        sb_net=compose(G, new_ego)
    else:
        sb_net=compose(new_ego, sb_net)
    del new_ego
    if s==round(len(seeds)*0.2):
        sb_net.name='20% complete'
        sb_net.info()
        print 'AT: ' +strtime('%m/%d/%Y, %H:%M:%S', gmtime())
        print ''
    ...
    # More time keeping, probably a MUCH better way to do this
    sb_data=array(sb_data)
    sb_data.flatten()
    sb_data=unique(sb_data)
    sb_net.info()
    return sb_net, sb_data
```

Build the whole network

Step	Nodes	Edges	Mean Degree	Density
Seed	5	5	2.0	0.25
$k = 2$	75	115	3.0	0.02
$k = 3$	4,938	8,659	3.5	$3.6(10^{-4})$

Build the whole network


Step	Nodes	Edges	Mean Degree	Density
Seed	5	5	2.0	0.25
$k = 2$	75	115	3.0	0.02
$k = 3$	4,938	8,659	3.5	$3.6(10^{-4})$

- Our seed is abnormally isolated, with only four neighbors

Build the whole network

Step	Nodes	Edges	Mean Degree	Density
Seed	5	5	2.0	0.25
$k = 2$	75	115	3.0	0.02
$k = 3$	4,938	8,659	3.5	$3.6(10^{-4})$


- ▶ Our seed is abnormally isolated, with only four neighbors
- ▶ Large jump after first snowball



Build the whole network

Step	Nodes	Edges	Mean Degree	Density
Seed	5	5	2.0	0.25
$k = 2$	75	115	3.0	0.02
$k = 3$	4,938	8,659	3.5	$3.6(10^{-4})$

- ▶ Our seed is abnormally isolated, with only four neighbors
- ▶ Large jump after first snowball
- ▶ Massive structural leap at $k = 3$



The full network

To get a feeling for the size of the full network...

