

BALESHOP DATABASE DISCOVERY

SUMMARY

Baleshop / Yenkasa Store is not stored in MongoDB. It is a Spring Boot service backed by a local MySQL database on the DigitalOcean droplet.

The database is currently local-only and cannot be reached directly from Cloud Run.

SERVER

- Public IP: 134.209.182.39
- Private IP observed on server: 10.16.0.5
- App directory: /root/triciabales
- PM2 app name: tricia-bales-api
- Spring Boot artifact: target/baleshop-0.0.1-SNAPSHOT.jar
- YenkasaChat proxy file:
/Users/kofibright/yenkasaChat/yenkasaChatBackend/RegLoginBackend/store/yenkasa-store-server.js
- Proxy upstream env var: TRICIABALES_API_BASE
- Proxy fallback: http://134.209.182.39:8080

SPRING DATASOURCE

Confirmed datasource in /root/triciabales/src/main/resources/application.properties:

- JDBC URL: jdbc:mysql://localhost:3306/bale_shop
- Driver: com.mysql.cj.jdbc.Driver
- Database user: balesuser
- Database name: bale_shop

Sensitive values are intentionally not recorded in this document.

MYSQL SERVER

- Server version: MySQL 8.0.46-0ubuntu0.24.04.2
- bind_address: 127.0.0.1

Because MySQL is bound to 127.0.0.1, only processes on the Baleshop droplet can connect to it. Cloud Run cannot connect directly to this MySQL server.

DATABASES

Confirmed databases:

- bale_shop
- information_schema
- performance_schema

TABLE INVENTORY

Database: bale_shop

Table	Approx. Rows
app_notifications	134
bale_images	101
bales	44
order_items	12
order_refunds	2
orders	12
user_tokens	35
users	20

APPLICATION STORAGE MODEL

Based on Spring entities and live tables:

- Users: users
- User sessions/tokens: user_tokens
- Store products/bales: bales
- Product images: bale_images
- Orders: orders
- Order line items: order_items
- Refunds: order_refunds
- Notifications: app_notifications

DATABASEAGENT INTEGRATION STATUS

YenkasaCode Agent now has optional read-only SQL support for Baleshop:

- Env var: BALESHOP_DATABASE_URL
- Display label: yenkasa_store
- Expected URL format: mysql://<user>:<password>@<host>:3306/<database>

Current production state:

- Secret Manager placeholder BALESHOP_DATABASE_URL exists.
- No usable production secret version has been attached.
- Cloud Run cannot use mysql://...@localhost:3306/bale_shop because localhost would mean the Cloud Run container, not the DigitalOcean droplet.
- Cloud Run cannot use 134.209.182.39:3306 while MySQL is bound to 127.0.0.1.

RECOMMENDED PRODUCTION OPTIONS

Option 1: Move Baleshop MySQL to a managed database.

- Recommended for production.
- Create a read-only DatabaseAgent user.
- Add BALESHOP_DATABASE_URL in Secret Manager.
- Attach the secret to Cloud Run.

Option 2: Expose MySQL securely from the droplet.

- Bind MySQL to a reachable private or public interface.
- Restrict firewall access.
- Create a read-only MySQL user for YenkaCode Agent.
- Prefer static egress from Cloud Run before allowlisting.

Option 3: Add a read-only internal inventory endpoint to Baleshop API.

- Avoids exposing MySQL directly.
- DatabaseAgent would call the Baleshop API instead of MySQL.
- Requires Baleshop code changes and authentication.

Option 4: Use an SSH tunnel.

- Useful for local debugging.
- Not recommended for Cloud Run production runtime.

CLOUD SQL PREPARATION BEFORE PAUSE

The migration was paused before any live application switch.

Completed before pause:

- Created a new separate Cloud SQL instance:
 - Instance name: yenkasa-store-mysql
 - Database engine: MySQL 8
 - Region: europe-west1
 - Status: RUNNABLE
 - Public IP: 34.78.8.96
- Stored generated root password in Secret Manager:
 - BALESHOP_CLOUDSQL_ROOT_PASSWORD

Not done before pause:

- Did not migrate data.
- Did not create app/read-only users.
- Did not change Baleshop Spring Boot config.
- Did not affect live store signups.

Recommended next move:

- Keep the live Baleshop droplet using localhost:3306/bale_shop until a planned migration window.
- Use YenkaCode Agent later to plan the Cloud SQL migration, create read-only/app users, import the dump, validate row counts, and switch the Spring Boot datasource only after successful validation.

SAFE FUTURE TRACE COMMANDS

Run on the Baleshop droplet:

```
bash
cd /root/triciabales
grep -RInE 'spring.datasource[jakarta.persistence.jdbc]jdbc:mysql|MYSQL|DB_|DATABASE' .
--exclude-dir=target 2>/dev/null
ss -lntp | grep 3306 || true
mysql -u balesuser -p bale_shop
```

Inside MySQL:

```
sql
SHOW DATABASES;
USE bale_shop;
SHOW TABLES;
SELECT table_name, table_rows
FROM information_schema.tables
WHERE table_schema = 'bale_shop'
ORDER BY table_name;
SHOW VARIABLES LIKE 'bind_address';
EXIT;
```

Schema-only dump from the shell, not from inside the MySQL prompt:

```
bash
mysqldump -u balesuser -p --no-data bale_shop > /tmp/baleshop_schema.sql
head -n 120 /tmp/baleshop_schema.sql
```

SECURITY NOTES

- The local Spring datasource password appeared in command output during manual discovery. Rotate the Baleshop MySQL password before treating this environment as production-safe.
- Prefer creating a dedicated read-only database user for YenkaCode Agent.
- Do not store live SQL credentials in repo files.