

Notification Client Handling

Overview

Yenkasa uses OneSignal for push transport, custom Android notification channels for sound selection, and app-specific routing logic to land the user on the correct screen when a notification is opened.

Current implementation

- `MyApplication`
 - initializes Firebase and OneSignal
 - creates message notification channels
 - intercepts foreground notifications
 - suppresses active-chat duplicates through `ChatNotificationState`
 - builds custom foreground notifications using user-selected sound
- `NotificationSoundManager`
 - stores sound preference
 - creates per-sound channel ids
 - supports preview playback from settings
- `NotificationNavigation`
 - converts notification payloads into explicit intents
 - handles chat, group chat, comments, wallet, profile, ads, communities, approval, and call flows
- `SettingsActivity`
 - exposes notification toggles and sound selection UI

```mermaid

flowchart TD

```
 OneSignal --> MyApplication
 MyApplication --> Sound[NotificationSoundManager]
 MyApplication --> Routing[NotificationNavigation]
 Routing --> Chat
 Routing --> Group
 Routing --> Comments
 Routing --> Wallet
 Routing --> Profile
```

```

Important payload types

- chat message notifications
- reward notifications
- community post notifications
- call invites
- post/comment activity
- moderation and approval-related events

Known issues

- push handling logic is spread across app bootstrap, settings, routing, and chat suppression helpers
- OneSignal configuration is still source-coded rather than fully environment-scoped
- channel migration logic can become brittle when sound ids or channel ids change

Scaling concerns

- notification type growth increases routing complexity quickly
- payload mismatch between backend and Android can silently route users to the wrong surface

- multiple notification preference sources must remain aligned with backend expectations

Future improvements

1. centralize notification payload schema validation
2. reduce notification-specific branching inside `MyApplication`
3. add stronger analytics around push delivery, suppression, and open routing