

CMSC 141 Automata and Language Theory

Regular Languages

Mark Froilan B. Tandoc

August 22, 2014

DFA NFA Comparison

DFA

States has exactly one exiting transition for each input symbol

Transition function:

$$\delta(Q, a) \rightarrow Q$$

e.g.

$$\delta(q_0, a) = q_1$$

$$\delta(q_0, b) = q_2$$

NFA

States can have zero, one, or many exiting transition for each input symbol

Transition function:

$$\delta(Q, a) \rightarrow P(Q)$$

e.g.

$$\delta(q_0, a) = \{q_1, q_2\}$$

$$\delta(q_0, b) = \emptyset$$

Quiz :)

Quiz :)

Create automata for

$$L_1 = \{w \mid w \text{ have a substring } aa \text{ or } bb\}$$

$$L_1 = \{aa, bb, aaa, baa, aab, bbb, abb, bba, abba, \dots\}$$

Quiz :)

Create automata for


$$L_1 = \{w \mid w \text{ have a substring aa or bb}\}$$

$$L_1 = \{aa, bb, aaa, baa, aab, bbb, abb, bba, abba, \dots\}$$

$$L_2 = \{w \mid w \text{ have all a's or all b's}\}$$


$$L_2 = \{a, b, aa, bb, aaa, bbb, aaaa, bbbb, \dots\}$$

Answers



$$L_1 = \{w \mid w \text{ have a substring aa or bb}\}$$

Answers



$$L_2 = \{w \mid w \text{ all a's or all b's}\}$$