

# CMSC 141 AUTOMATA AND LANGUAGE THEORY


## CONTEXT-FREE LANGUAGES

Mark Froilan B. Tandoc

October 3, 2014


# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aa**b**b



# PDA FOR $\{a^n b^n : n > 0\}$


aa**b**b






# PDA FOR $\{a^n b^n : n > 0\}$

aab**b**




# PDA FOR $\{a^n b^n : n > 0\}$

aab**b**




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aabb




# PDA FOR $\{a^n b^n : n > 0\}$

aab




# PDA FOR $\{a^n b^n : n > 0\}$

aab



# PDA FOR $\{a^n b^n : n > 0\}$


aab






# PDA FOR $\{a^n b^n : n > 0\}$

aab




# PDA FOR $\{a^n b^n : n > 0\}$

aab




# PDA FOR $\{a^n b^n : n > 0\}$

aa**b**




# PDA FOR $\{a^n b^n : n > 0\}$

aa**b**



# PDA FOR $\{a^n b^n : n > 0\}$

aab



# CONTEXT-FREE GRAMMARS (CFG)

# CONTEXT-FREE GRAMMARS (CFG)

- A grammar is a set of *string substitution rules* for producing a set of strings.

# CONTEXT-FREE GRAMMARS (CFG)

- A grammar is a set of *string substitution rules* for producing a set of strings.
- Example: The context-free grammar that generates the language  $\{a^n b^n : n > 0\} = \{ab, aabb, aaabbb, \dots\}$  is shown below:



# CONTEXT-FREE GRAMMARS (CFG)

- A grammar is a set of *string substitution rules* for producing a set of strings.
- Example: The context-free grammar that generates the language  $\{a^n b^n : n > 0\} = \{ab, aabb, aaabbb, \dots\}$  is shown below:

$$S \rightarrow ab \quad (\text{base case})$$

$$S \rightarrow aSb \quad (\text{recursive rule})$$

# CONTEXT-FREE GRAMMARS (CFG)

- A grammar is a set of *string substitution rules* for producing a set of strings.
- Example: The context-free grammar that generates the language  $\{a^n b^n : n > 0\} = \{ab, aabb, aaabbb, \dots\}$  is shown below:

$$S \rightarrow ab \quad (\text{base case})$$

$$S \rightarrow aSb \quad (\text{recursive rule})$$

- The grammar can also be shortened by combining rules with the same left-hand side and using " | "  
 $S \rightarrow ab \mid aSb$

# DERIVATION

# DERIVATION

A string  $x$  can be derived from a grammar if  $x$  can be generated by successive applications of the production rules starting from the start symbol.

## EXAMPLE

# DERIVATION

A string  $x$  can be derived from a grammar if  $x$  can be generated by successive applications of the production rules starting from the start symbol.

## EXAMPLE

Grammar:

$S \rightarrow ab$  (base case)

$S \rightarrow aSb$  (recursive rule)

# DERIVATION

A string  $x$  can be derived from a grammar if  $x$  can be generated by successive applications of the production rules starting from the start symbol.

## EXAMPLE

Grammar:

$S \rightarrow ab$  (base case)

$S \rightarrow aSb$  (recursive rule)

Derive: aaabbb

# DERIVATION

A string  $x$  can be derived from a grammar if  $x$  can be generated by successive applications of the production rules starting from the start symbol.

## EXAMPLE

Grammar:

$S \rightarrow ab$  (base case)

$S \rightarrow aSb$  (recursive rule)

Derive:  $aaabbb$

$S \Rightarrow aSb \Rightarrow aaSbb \Rightarrow aaabbb$

# PARSE TREES (DERIVATION TREE)



# PARSE TREES (DERIVATION TREE)

A parse tree is a tree with the *start symbol as the root*, and the *target string forming the leaves* of the tree

# PARSE TREES (DERIVATION TREE)

A parse tree is a tree with the *start symbol as the root*, and the *target string forming the leaves* of the tree

Grammar:  $S \rightarrow ab \mid aSb$

# PARSE TREES (DERIVATION TREE)

A parse tree is a tree with the *start symbol as the root*, and the *target string forming the leaves* of the tree

Grammar:  $S \rightarrow ab \mid aSb$


Derive: aaabbbb

# PARSE TREES (DERIVATION TREE)

A parse tree is a tree with the *start symbol as the root*, and the *target string forming the leaves* of the tree

Grammar:  $S \rightarrow ab \mid aSb$

Derive: aaabbbb



# CONTEXT-FREE LANGUAGES

# CONTEXT-FREE LANGUAGES

- All strings that can be generated constitute the *language of the grammar*

# CONTEXT-FREE LANGUAGES

- All strings that can be generated constitute the *language of the grammar*
- We write  $L(G)$  for the language of grammar  $G$

# CONTEXT-FREE LANGUAGES

- All strings that can be generated constitute the *language of the grammar*
- We write  $L(G)$  for the language of grammar  $G$
- Any language that can be generated by some context-free grammar is called a *context-free language*



# ENGLISH LANGUAGE EXAMPLE

SENTENCE	→ NOUN-PHRASE VERB-PHRASE
NOUN-PHRASE	→ CMPLX-NOUN
	→ CMPLX-NOUN PREP-PHRASE
VERB-PHRASE	→ CMPLX-VERB
	→ CMPLX-VERB PREP-PHRASE
PREP-PHRASE	→ PREP CMPLX-NOUN
CMPLX-NOUN	→ ARTICLE NOUN
CMPLX-VERB	→ VERB   VERB NOUN PHRASE
ARTICLE	→ a   the
NOUN	→ boy   girl   flower
VERB	→ touches   likes   sees
PREP	→ with

# ENGLISH LANGUAGE EXAMPLE

# ENGLISH LANGUAGE EXAMPLE

Sample strings we can derive from the grammar are:

- a boy sees
- the boy sees a flower
- a girl with a flower likes the boy

# ENGLISH LANGUAGE EXAMPLE

Sample strings we can derive from the grammar are:

- a boy sees
- the boy sees a flower
- a girl with a flower likes the boy

Try deriving them using the grammar

# ENGLISH LANGUAGE EXAMPLE

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE  $\Rightarrow$  NOUN-PHRASE VERB-PHRASE

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE  $\Rightarrow$  NOUN-PHRASE VERB-PHRASE  
 $\Rightarrow$  CMPLX-NOUN VERB-PHRASE



# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE  $\Rightarrow$  NOUN-PHRASE VERB-PHRASE  
 $\Rightarrow$  CMPLX-NOUN VERB-PHRASE  
 $\Rightarrow$  ARTICLE NOUN VERB-PHRASE

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE ⇒ NOUN-PHRASE VERB-PHRASE  
⇒ CMPLX-NOUN VERB-PHRASE  
⇒ ARTICLE NOUN VERB-PHRASE  
⇒ a NOUN VERB-PHRASE

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE ⇒ NOUN-PHRASE VERB-PHRASE  
⇒ CMPLX-NOUN VERB-PHRASE  
⇒ ARTICLE NOUN VERB-PHRASE  
⇒ a NOUN VERB-PHRASE  
⇒ a boy VERB-PHRASE

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE ⇒ NOUN-PHRASE VERB-PHRASE  
⇒ CMPLX-NOUN VERB-PHRASE  
⇒ ARTICLE NOUN VERB-PHRASE  
⇒ a NOUN VERB-PHRASE  
⇒ a boy VERB-PHRASE  
⇒ a boy CMPLX-VERB

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE ⇒ NOUN-PHRASE VERB-PHRASE  
⇒ CMPLX-NOUN VERB-PHRASE  
⇒ ARTICLE NOUN VERB-PHRASE  
⇒ a NOUN VERB-PHRASE  
⇒ a boy VERB-PHRASE  
⇒ a boy CMPLX-VERB  
⇒ a boy VERB

# ENGLISH LANGUAGE EXAMPLE

Derive: a boy sees

SENTENCE ⇒ NOUN-PHRASE VERB-PHRASE  
⇒ CMPLX-NOUN VERB-PHRASE  
⇒ ARTICLE NOUN VERB-PHRASE  
⇒ a NOUN VERB-PHRASE  
⇒ a boy VERB-PHRASE  
⇒ a boy CMPLX-VERB  
⇒ a boy VERB  
⇒ a boy sees

# FORMAL DEFINITION OF CFG

# FORMAL DEFINITION OF CFG

- A *context-free grammar* is a 4-tuple  $(V, \Sigma, R, S)$ , where
  - $V$  is a finite set of *variables* (or non-terminals)
  - $\Sigma$  is a finite set of *terminals*
  - $R$  is a finite set of *rules*
  - $S \in V$  is the start variable.



# FORMAL DEFINITION OF CFG

- A *context-free grammar* is a 4-tuple  $(V, \Sigma, R, S)$ , where
  - $V$  is a finite set of *variables* (or non-terminals)
  - $\Sigma$  is a finite set of *terminals*
  - $R$  is a finite set of *rules*
  - $S \in V$  is the start variable.
- The rule for the *rules* is  $V \rightarrow (V + T)^*$

# FORMAL DEFINITION OF CFG

- A *context-free grammar* is a 4-tuple  $(V, \Sigma, R, S)$ , where
  - $V$  is a finite set of *variables* (or non-terminals)
  - $\Sigma$  is a finite set of *terminals*
  - $R$  is a finite set of *rules*
  - $S \in V$  is the start variable.
- The rule for the *rules* is  $V \rightarrow (V + T)^*$
- Previous grammar is more formally defined as  $G = (\{S\}, \{a, b\}), \{S \rightarrow ab, S \rightarrow aSb\}, S$

# CHOMSKY HIERARCHY

by Noam Chomsky

# CHOMSKY HIERARCHY

by Noam Chomsky

Containment hierarchy of classes of formal grammars

# CHOMSKY HIERARCHY

by Noam Chomsky

Containment hierarchy of classes of formal grammars

- Regular grammars  
(simplest, weakest)

- $V \rightarrow T^*(V + \varepsilon)$

# CHOMSKY HIERARCHY

by Noam Chomsky

Containment hierarchy of classes of formal grammars

- Regular grammars  
(simplest, weakest)
  - $V \rightarrow T^*(V + \varepsilon)$
- Context-free grammars
  - $V \rightarrow (V + T)^*$

# CHOMSKY HIERARCHY

by Noam Chomsky

Containment hierarchy of classes of formal grammars

- Regular grammars  
(simplest, weakest)
  - $V \rightarrow T^*(V + \varepsilon)$
- Context-free grammars
  - $V \rightarrow (V + T)^*$
- Context-sensitive grammars

# CHOMSKY HIERARCHY

by Noam Chomsky


Containment hierarchy of classes of formal grammars

- Regular grammars  
(simplest, weakest)
  - $V \rightarrow T^*(V + \varepsilon)$
- Context-free grammars
  - $V \rightarrow (V + T)^*$
- Context-sensitive grammars
- Unrestricted grammars/Recursively enumerable grammars  
(most expressive)



# CHOMSKY HIERARCHY

# CHOMSKY HIERARCHY



# REFERENCES

- Previous slides on CMSC 141
- M. Sipser. Introduction to the Theory of Computation. Thomson, 2007.
- J.E. Hopcroft, R. Motwani and J.D. Ullman. Introduction to Automata Theory, Languages and Computation. 2nd ed, Addison-Wesley, 2001.
- E.A. Albacea. Automata, Formal Languages and Computations, UPLB Foundation, Inc. 2005
- JFLAP, [www.jflap.org](http://www.jflap.org)
- Various online  $\text{\LaTeX}$  and Beamer tutorials