


CMSC 141 AUTOMATA AND LANGUAGE THEORY

CONTEXT-FREE LANGUAGES


Mark Froilan B. Tandoc

October 8, 2014


CHOMSKY HIERARCHY



CHOMSKY HIERARCHY



CHOMSKY HIERARCHY




■ Regular Languages $V \rightarrow T^*(V + \varepsilon)$

■ $S \rightarrow abS \mid a \mid \varepsilon$

■ $S \rightarrow 0S \mid 1S \mid 11T$

$T \rightarrow 0T \mid 1T \mid \varepsilon$

CHOMSKY HIERARCHY



- Regular Languages $V \rightarrow T^*(V + \varepsilon)$
 - $S \rightarrow abS \mid a \mid \varepsilon$
 - $S \rightarrow 0S \mid 1S \mid 11T$
 $T \rightarrow 0T \mid 1T \mid \varepsilon$
- Context-Free Languages $V \rightarrow (V + T)^*$
 - $S \rightarrow ab \mid aSb$
 - $S \rightarrow () \mid SS \mid (S) \mid \varepsilon$

AMBIGUOUS GRAMMARS

AMBIGUOUS GRAMMARS

- A grammar is *ambiguous* if there is more than one parse tree for any string x in the language

AMBIGUOUS GRAMMARS

- A grammar is *ambiguous* if there is more than one parse tree for any string x in the language
- A grammar is *non-ambiguous* if every string in a language has a unique parse tree

AMBIGUOUS GRAMMARS

- A grammar is *ambiguous* if there is more than one parse tree for any string x in the language
- A grammar is *non-ambiguous* if every string in a language has a unique parse tree
- $S \rightarrow ab \mid aSb$ is non-ambiguous

AMBIGUOUS GRAMMARS

- A grammar is *ambiguous* if there is more than one parse tree for any string x in the language
- A grammar is *non-ambiguous* if every string in a language has a unique parse tree
- $S \rightarrow ab \mid aSb$ is non-ambiguous
- $S \rightarrow a \mid S + S$ is ambiguous

AMBIGUOUS GRAMMARS


Grammar: $S \rightarrow a \mid S + S$

Derive: $a + a + a$

AMBIGUOUS GRAMMARS

Grammar: $S \rightarrow a \mid S + S$



Derive: $a + a + a$



AMBIGUOUS GRAMMARS

Grammar: $S \rightarrow a \mid S + S$

Derive: $a + a + a$



AMBIGUITY IN NATURAL LANGUAGES

- The man on the hill saw the boy with a telescope.

- The man on the hill saw the boy with a telescope.
- Look at the dog with one eye.

REMOVING AMBIGUITY

REMOVING AMBIGUITY

- $G_1 : S \rightarrow a \mid S + S$ is ambiguous

REMOVING AMBIGUITY

- $G_1 : S \rightarrow a \mid S + S$ is ambiguous
- $G_2 : S \rightarrow a \mid S + a$ is non-ambiguous

REMOVING AMBIGUITY

- $G_1 : S \rightarrow a \mid S + S$ is ambiguous
- $G_2 : S \rightarrow a \mid S + a$ is non-ambiguous
- The two grammars generate the same language
 $L(G_1) = L(G_2)$

REMOVING AMBIGUITY

- $G_1 : S \rightarrow a \mid S + S$ is ambiguous
- $G_2 : S \rightarrow a \mid S + a$ is non-ambiguous
- The two grammars generate the same language
 $L(G_1) = L(G_2)$
- G_2 is better because it is non-ambiguous by forcing the rule on left-associativity

REMOVING AMBIGUITY

REMOVING AMBIGUITY


- Consider: $S \rightarrow 0 \mid 1 \mid S + S \mid S^*S \mid (S)$

REMOVING AMBIGUITY

- Consider: $S \rightarrow 0 \mid 1 \mid S + S \mid S^*S \mid (S)$
- How many ways can we parse $1 + 1^*0$



REMOVING AMBIGUITY

- Consider: $S \rightarrow 0 \mid 1 \mid S + S \mid S^*S \mid (S)$
- How many ways can we parse $1 + 1^*0$



REMOVING AMBIGUITY

- Consider: $S \rightarrow 0 \mid 1 \mid S + S \mid S^*S \mid (S)$
- How many ways can we parse $1 + 1^*0$



REMOVING AMBIGUITY

A non-ambiguous grammar

REMOVING AMBIGUITY

A non-ambiguous grammar
(enforcing operator precedence)

REMOVING AMBIGUITY

A non-ambiguous grammar
(enforcing operator precedence)

$$S \rightarrow E$$

$$E \rightarrow E + T \mid T \quad (\text{expressions})$$

$$T \rightarrow T * F \mid F \quad (\text{terms})$$

$$F \rightarrow 0 \mid 1 \mid (E) \quad (\text{factors})$$

REMOVING AMBIGUITY

A non-ambiguous grammar
(enforcing operator precedence)

$$S \rightarrow E$$

$$E \rightarrow E + T \mid T \quad (\text{expressions})$$

$$T \rightarrow T * F \mid F \quad (\text{terms})$$

$$F \rightarrow 0 \mid 1 \mid (E) \quad (\text{factors})$$

Exercise: Try parsing strings like $1 + 1 * 0$ and $(1 + 1) * 0$

DANGLING-ELSE PROBLEM

DANGLING-ELSE PROBLEM

Consider:

$S \rightarrow B \mid \text{if } C \text{ then } S \mid \text{if } C \text{ then } S \text{ else } S$

$B \rightarrow \textit{block}$

$C \rightarrow (\textit{cond})$

DANGLING-ELSE PROBLEM

Consider:

$S \rightarrow B \mid \text{if } C \text{ then } S \mid \text{if } C \text{ then } S \text{ else } S$

$B \rightarrow \text{block}$

$C \rightarrow (\text{cond})$

```
if (cond1) then
  if (cond2) then block1
else block2
```

DANGLING-ELSE PROBLEM

Consider:

$S \rightarrow B \mid \text{if } C \text{ then } S \mid \text{if } C \text{ then } S \text{ else } S$

$B \rightarrow \text{block}$

$C \rightarrow (\text{cond})$

```
if (cond1) then
  if (cond2) then block1
else block2
```

```
if (cond1) then
  if (cond2) then block1
  else block2
```

DANGLING-ELSE PROBLEM

Consider:

$S \rightarrow B \mid \text{if } C \text{ then } S \mid \text{if } C \text{ then } S \text{ else } S$

$B \rightarrow \text{block}$

$C \rightarrow (\text{cond})$

```
if (cond1) then
  if (cond2) then block1
else block2
```

```
if (cond1) then
  if (cond2) then block1
  else block2
```

Exercise: Design/Create a non-ambiguous version of the grammar that associates an else-clause to the nearest if

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous
- Example: $L = \{a^m b^m c^n\} \cup \{a^m b^n c^n\}; m, n > 0$

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous
- Example: $L = \{a^m b^m c^n\} \cup \{a^m b^n c^n\}; m, n > 0$
- Sample strings are aabbccccc, abbbccc, abc

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous
- Example: $L = \{a^m b^m c^n\} \cup \{a^m b^n c^n\}; m, n > 0$
- Sample strings are aabbccccc, abbbcccc, abc
- A CFG for L is given by
$$\begin{aligned} S &\rightarrow XC \mid AY \\ X &\rightarrow ab \mid aXb \\ A &\rightarrow a \mid aA \\ C &\rightarrow c \mid cC \\ Y &\rightarrow bc \mid bYc \end{aligned}$$

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous
- Example: $L = \{a^m b^m c^n\} \cup \{a^m b^n c^n\}; m, n > 0$
- Sample strings are aabbccccc, abbbcccc, abc
- A CFG for L is given by
$$\begin{aligned} S &\rightarrow XC \mid AY \\ X &\rightarrow ab \mid aXb \\ A &\rightarrow a \mid aA \\ C &\rightarrow c \mid cC \\ Y &\rightarrow bc \mid bYc \end{aligned}$$
- Show that aabbcc has 2 different parse trees

INHERENTLY-AMBIGUOUS LANGUAGES

- A language L is inherently ambiguous if every grammar for L is ambiguous
- Example: $L = \{a^m b^m c^n\} \cup \{a^m b^n c^n\}; m, n > 0$
- Sample strings are aabbccccc, abbbcccc, abc
- A CFG for L is given by
$$\begin{aligned} S &\rightarrow XC \mid AY \\ X &\rightarrow ab \mid aXb \\ A &\rightarrow a \mid aA \\ C &\rightarrow c \mid cC \\ Y &\rightarrow bc \mid bYc \end{aligned}$$
- Show that aabbcc has 2 different parse trees
- Why?

REFERENCES

- Previous slides on CMSC 141
- M. Sipser. Introduction to the Theory of Computation. Thomson, 2007.
- J.E. Hopcroft, R. Motwani and J.D. Ullman. Introduction to Automata Theory, Languages and Computation. 2nd ed, Addison-Wesley, 2001.
- E.A. Albacea. Automata, Formal Languages and Computations, UPLB Foundation, Inc. 2005
- JFLAP, www.jflap.org
- Various online \LaTeX and Beamer tutorials