# CMSC 141 Automata and Language Theory Context-Free Languages

Mark Froilan B. Tandoc

October 15, 2014

■ Chomsky Normal Form

- Chomsky Normal Form
  - $V \rightarrow (T + VV)$

- Chomsky Normal Form
  - $V \rightarrow (T + VV)$
- Greibach Normal Form

- Chomsky Normal Form
  - $V \rightarrow (T + VV)$
- Greibach Normal Form
  - V → TV\*

- Chomsky Normal Form
  - $V \rightarrow (T + VV)$
- Greibach Normal Form
  - $V \rightarrow TV^*$
- Elimination of unit productions  $(V \to W)$ , and empty productions  $(V \to \varepsilon)$  except for the start state

A context-free grammar in Chomsky Normal Form (CNF) have rules of the form:

A context-free grammar in Chomsky Normal Form (CNF) have rules of the form:

$$A \rightarrow BC$$
  
 $A \rightarrow a$ 

### Chomsky Normal Form

A context-free grammar in Chomsky Normal Form (CNF) have rules of the form:

$$A \rightarrow BC$$
  
 $A \rightarrow a$ 

where a is any terminal and A, B, C are any variables - except that B and C may not be the start variable. Also, only the start variable (say S), can have the rule  $S \to \varepsilon$ 

Convert the grammar to CNF

Convert the grammar to CNF

#### Grammar

 $B \rightarrow b \mid \varepsilon$ 

$$S \rightarrow ASA \mid aB$$
  
 $A \rightarrow B \mid S$ 

Add a new start variable (say  $S_0$ ) and have the rule  $S_0 \to S$  where S is the original start state

$$\begin{array}{ccc} S & \rightarrow ASA \mid aB \\ A & \rightarrow B \mid S \\ B & \rightarrow b \mid \varepsilon \end{array}$$

Add a new start variable (say  $S_0$ ) and have the rule  $S_0 \to S$  where S is the original start state

$$S_0 \rightarrow S$$
  
 $S \rightarrow ASA \mid aB$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b \mid \varepsilon$ 

Remove the  $\varepsilon$  rules.  $B \to \varepsilon$ 

$$S_0 \rightarrow S$$

$$S \rightarrow ASA \mid aB$$

$$A \rightarrow B \mid S$$

$$B \rightarrow b \mid \varepsilon$$

Remove the  $\varepsilon$  rules.  $B \to \varepsilon$ 

$$S_0 \rightarrow S$$

$$S \rightarrow ASA \mid aB \mid a$$

$$A \rightarrow B \mid S \mid \varepsilon$$

$$B \rightarrow b$$

Remove the  $\varepsilon$  rules.  $A \to \varepsilon$ 

$$S_0 \rightarrow S$$

$$S \rightarrow ASA \mid aB \mid a$$

$$A \rightarrow B \mid S \mid \varepsilon$$

$$B \rightarrow b$$

Remove the  $\varepsilon$  rules.  $A \to \varepsilon$ 

```
S_0 \rightarrow S

S \rightarrow ASA \mid aB \mid a \mid SA \mid AS \mid S

A \rightarrow B \mid S

B \rightarrow b
```

Remove unit rules.  $S \rightarrow S$ 

$$S_0 \rightarrow S$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS \mid S$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b$ 

Remove unit rules.  $S \rightarrow S$ 

$$S_0 \rightarrow S$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b$ 

Remove unit rules.  $S_0 \rightarrow S$ 

$$S_0 \rightarrow S$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b$ 

Remove unit rules.  $S_0 \rightarrow S$ 

$$S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b$ 

Remove unit rules.  $A \rightarrow B$ 

$$S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow B \mid S$   
 $B \rightarrow b$ 

Remove unit rules.  $A \rightarrow B$ 

$$S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow S \mid b$   
 $B \rightarrow b$ 

Remove unit rules.  $A \rightarrow S$ 

$$S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow S \mid b$   
 $B \rightarrow b$ 

Remove unit rules.  $A \rightarrow S$ 

$$S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS$$
  
 $S \rightarrow ASA \mid aB \mid a \mid SA \mid AS$   
 $A \rightarrow b \mid ASA \mid aB \mid a \mid SA \mid AS$   
 $B \rightarrow b$ 

Convert the remaining rules into proper form by adding additional variables and rules

#### Gramm<u>ar</u>

```
S_0 \rightarrow ASA \mid aB \mid a \mid SA \mid AS

S \rightarrow ASA \mid aB \mid a \mid SA \mid AS

A \rightarrow b \mid ASA \mid aB \mid a \mid SA \mid AS

B \rightarrow b
```

Convert the remaining rules into proper form by adding additional variables and rules

#### CONVERT TO CNF

 $S \rightarrow ab$ 

 $S \rightarrow aSb$ 

#### CONVERT TO CNF

 $S \rightarrow ab$  $S \rightarrow aSb$ 

 $B \rightarrow b$ 

#### CNF

 $S \rightarrow AB \mid XB$   $X \rightarrow AY$   $Y \rightarrow AB \mid XB$   $A \rightarrow a$ 

A context-free grammar in Greibach Normal Form (GNF) have rules of the form:

A context-free grammar in Greibach Normal Form (GNF) have rules of the form:

$$V \rightarrow TV^*$$

A context-free grammar in Greibach Normal Form (GNF) have rules of the form:

$$V \rightarrow TV^*$$

where V can be any variable and T can be any terminal. Only the start variable (say S), can have the rule  $S \to \varepsilon$ 

#### CONVERT THE GRAMMAR TO GNF

$$S \rightarrow a \mid S + S$$

#### CONVERT THE GRAMMAR TO GNF

$$S \rightarrow a \mid S + S$$

#### GNF

$$egin{array}{ll} S & 
ightarrow a \ S & 
ightarrow a PS \end{array}$$
 (this makes  $+$  right-associative)  $P & 
ightarrow +$ 

#### CONVERT THE GRAMMAR TO GNF

$$S \rightarrow a \mid S + S$$

#### **GNF**

$$\begin{array}{ccc} S & \rightarrow a \\ S & \rightarrow aPS \end{array}$$
 (this makes + right-associative)

$$P \rightarrow +$$

When in GNF, an input string of length n can always be derived in n steps

# EQUIVALENCE OF PDAs AND CFGs

# EQUIVALENCE OF PDAS AND CFGS

#### THEOREM

Every CFG can be converted into an equivalent PDA, and vice versa

# EQUIVALENCE OF PDAS AND CFGS

#### THEOREM

Every CFG can be converted into an equivalent PDA, and vice versa

Note that we are referring to non-deterministic PDA (NPDA) because deterministic PDA are weaker than NPDA

#### Idea:

■ Use a single state q, with stack alphabet  $\Gamma = V \cup T$ , and the PDA is accepting by empty stack

- Use a single state q, with stack alphabet  $\Gamma = V \cup T$ , and the PDA is accepting by empty stack
- Initial stack symbol is the start variable

- Use a single state q, with stack alphabet  $\Gamma = V \cup T$ , and the PDA is accepting by empty stack
- Initial stack symbol is the start variable
- For every terminal symbol a in  $\Sigma$ , add the transition  $\delta(q, a, a) = (q, pop)$

- Use a single state q, with stack alphabet  $\Gamma = V \cup T$ , and the PDA is accepting by empty stack
- Initial stack symbol is the start variable
- For every terminal symbol a in  $\Sigma$ , add the transition  $\delta(q, a, a) = (q, pop)$
- For every empty production  $A \to \varepsilon$ , add the transition  $\delta(q, \varepsilon, A) = (q, pop)$

- Use a single state q, with stack alphabet  $\Gamma = V \cup T$ , and the PDA is accepting by empty stack
- Initial stack symbol is the start variable
- For every terminal symbol a in  $\Sigma$ , add the transition  $\delta(q, a, a) = (q, pop)$
- For every empty production  $A \to \varepsilon$ , add the transition  $\delta(q, \varepsilon, A) = (q, pop)$
- For every rule  $A \to B_1 B_2 \dots B_n$ , add the transition  $\delta(q, \varepsilon, A) = (q, \{pop; pushB_n; pushB_{n-1}; \dots; pushB_1\})$

$$S \rightarrow \varepsilon \mid aSb$$

$$S \to \varepsilon \mid aSb \Longrightarrow L(G) = \{a^nb^n : n \ge 0\}$$

$$S \to \varepsilon \mid aSb \Longrightarrow L(G) = \{a^nb^n : n \ge 0\}$$

Stack alphabet:

$$\Gamma = \{S, a, b\}$$

Initial stack symbol: S

$$S \to \varepsilon \mid aSb \Longrightarrow L(G) = \{a^nb^n : n \ge 0\}$$

Stack alphabet:

$$\Gamma = \{S, a, b\}$$

Initial stack symbol: S




$$S \to \varepsilon \mid aSb \Longrightarrow L(G) = \{a^nb^n : n \ge 0\}$$


Stack alphabet:

$$\Gamma = \{S, a, b\}$$


Initial stack symbol: S

start 
$$\longrightarrow$$
  $q$   $\varepsilon$ ,  $S$ ,  $pop$   $\varepsilon$ ,  $S$ ,  $pop$   $\varepsilon$ ,  $S$ ,  $pop$ ,  $push b$ ,  $push S$ ,  $push a$ 








































### REFERENCES

- Previous slides on CMSC 141
- M. Sipser. Introduction to the Theory of Computation. Thomson, 2007.
- J.E. Hopcroft, R. Motwani and J.D. Ullman. Introduction to Automata Theory, Languages and Computation. 2nd ed, Addison-Wesley, 2001.
- E.A. Albacea. Automata, Formal Languages and Computations, UPLB Foundation, Inc. 2005
- JFLAP, www.jflap.org
- Various online LATEX and Beamer tutorials