J-LINK INPUT HEADER



SWD/JTAG OUTPUT HEADERS



SWD/JTAG BREAKOUT HEADER



HEADER REFERENCES FOR TARGET BOARD



DC-DC CONVERTER HEADER



(not plugged in = disabled)

SWD/JTAG MODE SELECTION



Both jumpers:
1-2 = SWD-mode
2-3 = JTAG-mode

DC-DC CONVERTER PINOUT SELECTION



INLINE CURRENT MEASURING JUMPER



BEST PRACTICES

Use the 0.05" pinheader for 'regular' development and the TagConnect header for fast on-location reprogramming.

GNDdetect can be used by the target board to detect if a debugger is present. (pin 9 in SWD mode connected to GND)

Put a 100 kΩ pullup resitor on the SWDIO line and a 10 kΩ pullup resistor on the RXD line on the target board.

If RTCK is not available on the target board it should be connected to GND.

J-Link 20-pin SWD + VCOM



J-Link 20-pin JTAG



DBGRQ = NC inside J-Link

TagConnect 2050



open source hardware

adapter.brechtve.be
Brecht Van Eeckhoudt

H1 M3 H2 M3 H3 M3 H4 M3

Sheet: /
File: jlink-tagConnect-adapter-v2.sch

Title: J-Link / Tag-Connect adapter board

Size: A4	Date: 2019-11-25	**Rev: v2.0**
KiCad E.D.A.	kicad 5.1.5-52549c584ubuntu19.04.1	Id: 1/1