




池州华宇电子科技股份有限公司 CHI ZHOU HISEMI ELECTRONICS TECHNOLOGY CO.,LTD				客户代码 Customer No.	008	线号 Drawing No.	HY-PX-008-797 A	
焊线图纸 Bonding Diagram				产品名称 Product Type	HS2241P		封装外型 PKG Type	SOP8L (12R)
焊线种类 Wire Type	焊线直径(um) Wire Diameter	焊线根数 NO. of wire	焊线总长(um) Total wire length	最长线长(um) Longest wire length	最短线长(um) Shortest wire length	塑封料型号(绿色环保) Compound Type (Green)		LF载体尺寸 LF Pad Size
合金丝 Ag	20	8	12730	1395	1184	首选(Preferred): EMG-600-2 备选(Optional): CEL-1702HF		SOP8L-12R (90*90mil) 2286*2286um <sup>2</sup>
客户图号 Customer drawing NO.								



推荐传送方向 (装片):  
L/F Direction (D/A): 椭圆孔



实物图:  
Chip photo:



特殊说明 Special Instructions:

DB注意:  
1. 芯片居中放置并逆时针旋转30°;  
HY-PX-008-797 A由HY-PX-008-242 A升级, 优化胶水

注意: 基岛全镀银

说明 Instructions	粘片胶类型 Epoxy type	芯片名称 Die name	芯片尺寸 Die Size	最小焊盘尺寸 Min BPO (um <sup>2</sup> )	最小焊盘间距 Min BPP(um)	铝垫厚度(um) Pad Thickness	焊盘下是否有电路 Circuit under Pad	划片道宽度 Street line (um)	晶圆尺寸 Wafer Size	是否是 Low-β If low-β?	减薄厚度 (um) Wafer Thickness
A芯: DIE A	导电胶 (conductivity) S210	HS5029	626*600(um <sup>2</sup> ) 24.65*23.62(mil <sup>2</sup> )	70*70	102	0.8	否/NO	NA	NA	否/NO	300
B芯: DIE B											
C芯: DIE C											
拟制 Prepared by	周世杰 2024.9.19		制图日期 Create Date	2024/9/19		生效日期 Effective Date	客户确认签字/盖章: Customer Signature				
研发审核 R&D Check	王强 2024.9.19		产品工程审核 PE Check			批准 Approved by					

\*温馨提示: 图纸为产品下线生产的唯一依据, 请您认真确认, 我司依据您回签后的图纸生产, 如因图纸错误会产生不可估量损失, 谢谢!

\*warm tips: the drawing is the only basis for the production of the product. Please confirm it carefully. Our company will produce the drawings according to the drawings you have signed back, such as drawing mistakes, which will produce incalculable loss. Thank you

页码 Page

1 / 1