

 池州华宇电子科技股份有限公司 CHI ZHOU HISEMI ELECTRONICS TECHNOLOGY CO.,LTD				客户代码 Customer No.	008	线号 Drawing No.	HY-PX-008-737 A			
焊线图纸 Bonding Diagram				产品名称 Product Type	HS4456		封装外型 PKG Type	SOT26 (14R)		
焊线种类 Wire Type	焊线直径(μm) Wire Diameter	焊线根数 NO. of wire	焊线总长(μm) Total wire length	最长线长(μm) Longest wire length	最短线长(μm) Shortest wire length	塑封料型号(绿色环保) Compound Type (Green)		LP载体尺寸 LF Pad Size		
合金丝 Ag	20	7	8195	1668	470	首选(Preferred): CEL-1702HF 备选(Optional): EME-C630AY		SOT23-6L-14R (42×72mil) [1060×1820μm]		
客户图号 Customer drawing NO.										



传输方向(装片): L/F Direction (D/A): 椭圆孔				实物图: Chip photo:		特殊说明 Special Instructions:					
						DB注意: 控制溢胶, 为WB预留焊线位置。 WB注意: 数字为不打线pad点个数。					
说明 Instructions	贴片胶类型 Epoxy type	芯片名称 Die name	芯片尺寸 Die Size	最小焊盘尺寸 Min BPP(μm)	最小焊盘间距 Min BPP(μm)	铝垫厚度(μm) Pad Thickness	焊盘下是否有电路 Circuit under Pad	划片线宽度 Street line (μm)	晶圆尺寸 Wafer Size	是否过 Lead-in	减薄厚度 (μm) Grinding Thickness
A芯: DIE A	导电胶 (conductivity) S210N	HS5151	755*595(μm) 29.72*23.42(mil)	70*70	95	1	是/Yes	60	8	否/NO	230
B芯: DIE B											
C芯: DIE C											
拟制 Prepared by	制图日期 Create Date		2024/2/29		生效日期 Effective Date		客户确认签字/盖章: Customer Signature				
研发审核 R&D Check	产品工程审核 PE Check				批准 Approved by		2024.3.1				

温馨提示: 图纸为产品下线生产的唯一依据, 请认真确认, 我司依据您签后的图纸生产, 如图纸错误会产生不可估量损失, 谢谢!
warm tips: the drawing is the only basis for the production of the product. Please confirm it carefully. Our company will produce the drawings according to the drawings you have signed back, such as drawing mistakes, which will produce inestimable loss. Thank you

页码 Page: 1 / 1