


AJAX


Asynchronous JavaScript and XML

- A technology based on:
 - JavaScript
 - DOM
 - Server side script
- Concept: **Client-Driven Communication, Server-Side Processing**

Classical case



Ajax case



Client-Side Communication

- Achieved by
 - XMLHttpRequest Object
 - XMLHttpRequest Object Methods

Method	Description
<code>abort()</code>	Cancels the current request
<code>getAllResponseHeaders()</code>	Returns all HTTP headers as a String type variable
<code>getResponseHeader()</code>	Returns the value of the HTTP header specified in the method
<code>open()</code>	Specifies the different attributes necessary to make a connection to the server; allows you to make selections such as GET or POST (more on that later), whether to connect asynchronously, and which URL to connect to
<code>setRequestHeader()</code>	Adds a label/value pair to the header when sent
<code>send()</code>	Sends the current request

- XMLHttpRequest Object Properties

Property	Description
onreadystatechange	Used as an event handler for events that trigger upon state changes
readyState	Contains the current state of the object (0: uninitialized, 1: loading, 2: loaded, 3: interactive, 4: complete)
responseText	Returns the response in string format
responseXML	Returns the response in proper XML format
status	Returns the status of the request in numerical format (regular page errors are returned, such as the number 404, which refers to a not found error)
statusText	Returns the status of the request, but in string format (e.g., a 404 error would return the string Not Found)

- Cross Browser Usage
 - IE and non-IE

```
var xmlhttp = false;

try {
    xmlhttp = new ActiveXObject("Msxml2.XMLHTTP");
    alert ("You are using Microsoft Internet Explorer.");
} catch (e) {
    xmlhttp = false;
}

if (!xmlhttp && typeof XMLHttpRequest != 'undefined') {
    xmlhttp = new XMLHttpRequest();
    alert ("You are not using Microsoft Internet Explorer");
}
```

```
var xmlhttp;

if (window.ActiveXObject) {
    xmlhttp = new ActiveXObject("Microsoft.XMLHTTP");
} else {
    xmlhttp = new XMLHttpRequest();
}
```


- Sending a request to Server

```
function makerequest(serverPage, objID) {  
    var obj = document.getElementById(objID);  
    xmlhttp.open("GET", serverPage);  
    xmlhttp.onreadystatechange = function() {  
        if (xmlhttp.readyState == 4 && xmlhttp.status == 200)  
        {  
            obj.innerHTML = xmlhttp.responseText;  
        }  
    }  
    xmlhttp.send(null);  
}
```

The .innerHTML is useful for returning or replacing the content of HTML elements

****innerHTML is not part of W3C DOM but it is supported by all major browser****

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml">
```

```
<head>
```

```
<title>Sample 2_1</title>
```

```
<meta http-equiv="Content-Type"
```

```
content="text/html; charset=iso-8859-1" />
```

```
<script type="text/javascript">
```

```
<!--
```

```
var xmlhttp = false;
```

```
try {
```

```
    xmlhttp = new ActiveXObject("Msxml2.XMLHTTP");
```

```
    alert ("You are using MS IE.");
```

```
} catch (e) {
```

```
    xmlhttp = false;
```

```
}
```

```
if (!xmlhttp && typeof XMLHttpRequest != 'undefined') {
```


```
    xmlhttp = new XMLHttpRequest();
```

```
    alert ("You are not using MS IE");
```

```
}
```

```
function makerequest(serverPage, objID) {  
    var obj = document.getElementById(objID);  
    xmlhttp.open("GET", serverPage);  
    xmlhttp.onreadystatechange = function() {  
        if (xmlhttp.readyState == 4 && xmlhttp.status == 200)  
        {  
            obj.innerHTML = xmlhttp.responseText;  
        }  
    }  
    xmlhttp.send(null);  
}  
//-->  
</script>  
</head>
```

```
<body onload="makerequest ('content1.html','hw')">
  <div align="center">
    <h1>My Webpage</h1>
    <a href="content1.html" onclick=
      "makerequest('content1.html','hw');
      return false;"> Page 1</a> |
    <a href="content2.html" onclick=
      "makerequest('content2.html','hw');
      return false;">Page 2</a> |
    <a href="content3.html" onclick=
      "makerequest('content3.html','hw');
      return false;">Page 3</a> |
    <a href="content4.html" onclick=
      "makerequest('content4.html','hw');
      return false;">Page 4</a>
    <div id="hw"></div>
  </div>
</body>
</html>
```



My Webpage

[Page 1](#) | [Page 2](#) | [Page 3](#) | [Page 4](#)

Page 3

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

ASP.Net Core MVC & Ajax Example

Controller

```
0 references
public IActionResult Index()
{
    return View();
}

0 references
public IActionResult Message01()
{
    string msg = "Hello,This is a test Ajax message";
    return Content(msg, "text/html", Encoding.UTF8);
}

2
0 references
public IActionResult Message02()
{
    string msg = "<ul><li>topic01</li><li>topic02</li><li>topic03</li><li>topic04</li><li>topic05</li></ul>";
    return Content(msg, "text/plain", Encoding.UTF8);
}
```

ASP.Net Core MVC & Ajax Example

View

```
<html>
<head>
  <meta name="viewport" content="width=device-width" />
  <title>Ajax testing</title>
  <script>
    var xmlhttp = new XMLHttpRequest();
    ...
    function MakeReq(serverpage, objID) {
      let obj = document.getElementById(objID);
      xmlhttp.open("GET", serverpage);
      xmlhttp.onreadystatechange = function () {
        if (xmlhttp.readyState == 4 && xmlhttp.status == 200) {
          obj.innerHTML = xmlhttp.responseText;
        }
      }
      xmlhttp.send(null);
    }
  </script>
</head>
<body>
  <div>
    <h2>Part I</h2>
    click here ==>
    <a href="" onclick="MakeReq('https://localhost:5001/Ajax/Message01', 'p01'); return false;">Hello</a>
    <div id="p01"></div>
  </div>
  <div>
    <h2>Part II</h2>
    click here ==>
    <a href="" onclick="MakeReq('https://localhost:5001/Ajax/Message02', 'p02'); return false;">Test</a>
    <div id="p02"></div>
  </div>
</body>
</html>
```