

Repository: Field-of-Dream-Studio/hotaru PR number: #38

#25

1. Module or symbol: hotaru-lib::compression - decompress-gzip/decompress-deflate/decompress-brotli/decompress-zstd
Change type: ☐ New module ☒ Fix ☐ Redesign ☐ No functional change

Design approach

在4个解压函数加入 max_size: usize 参数。使用 Read::take(max_size + 1) as u64
在解压中途强制截断解压炸弹

Justification of the approach

在解压过程中可以及时中断解压炸弹

2. Module or symbol: hotaru-http::util::encoding - ~~ContentCoding::decode_compressed/~~ ContentCoding::decode_compressed
Change type: ☐ New module ☒ Fix ☐ Redesign ☐ No functional change

Design approach

加 max_size: usize 参数, 透传给4个 decompress

Justification of the approach

修复 compression 和 HTTP 层间的桥接3. Module or symbol: hotaru-http::message::body::parse - parse-bufferChange type: ☐ New module ☒ Fix ☐ Redesign ☐ No functional change

Design approach

调用 decode_compressed 时传入 safety.effective-body-size(), 且解压错误以
map_err(1, BodyError::InvalidEncoding) 返回

Justification of the approach

在 HTTP body 解析入口 (parse-buffer) 使用已定义过的 HttpSafety 配置

#27

4. Module or symbol: hotaru-core::connection::io::rw_traits::read - ~~HotaruBufRead::~~ read-until/read-line
Change type: ☐ New module ☒ Fix ☐ Redesign ☐ No functional change

Design approach

在2个函数加入 max_size: usize 参数, 返回值加入 bool 变为 Result<usize, bool>, Self::Error
超出 read 长度限制时返回 Ok((read, true))

Justification of the approach

因 Self::Error 是 trait 关联类型, 无法构造所以用 bool 值传出截断信息5. Module or symbol: hotaru-http::message::meta + hotaru-http::message::body + ~~trunc~~
Change type: ☐ New module ☒ Fix ☐ Redesign ☐ No functional change

Design approach

chunk-size 行读取加上 max_size 参数和检查 truncated, 超长被截断时
返回 InvalidData. meta.rs 传入 effective-line-length() 并解构 (bytes_read, truncated)

Justification of the approach

meta 改前 trunc 的检查是在 OOM 发生后才确认, 改后截断在 saturating 处生效
内存分配前就停止.