

M3 Submachine Gun (“Grease Gun”)

PAGES FROM THE ORIGINAL MANUAL

TM 9-2200, Small Arms, Light Field Mortars and 20-mm Aircraft Guns (War Department, 1943)

WHAT'S INSIDE

The M3 submachine gun: drawings of both sides, with weights, measurements and technical data.

3 pages from the original follow: the manual's cover, then the section about this weapon. Original US Government publication (public domain). Scans courtesy of the Internet Archive and Wikimedia Commons.

ADVANCE COPY FOR USE IN
ORDNANCE OFFICE ONLY.
REGULAR DISTRIBUTION WILL
BE MADE BY YOUR LOCAL
ADJUTANT GENERAL OR
POST ADJUTANT.

TM 9-2200

WAR DEPARTMENT TECHNICAL MANUAL

Small Arms, Light Field Mortars and 20-mm Aircraft Guns

WAR DEPARTMENT, 11 OCTOBER 1943

★ RESTRICTED

★ *Dissemination of restricted matter.*—The information contained in restricted documents and the essential characteristics of restricted materiel may be given to any person known to be in the service of the United States and to persons of undoubted loyalty and discretion who are cooperating in Government work, but will not be communicated to the public or to the press except by authorized military public relations agencies. (See also par. 18 b, AR 380-5, 28 Sep 1942.)

SMALL ARMS, LIGHT FIELD MORTARS, AND 20-MM AIRCRAFT GUNS



RA PD 66765

Left Side View



RA PD 66764

Right Side View

Figure 26—Gun, Submachine, Cal. .45, M3

WEAPONS

28. GUN, SUBMACHINE, CAL. .45, M3.

Weight less magazine, oiler, and sling	8.1 lb
Weight, complete with magazine, oiler, and sling	8.9 lb
Weight of magazine (empty)	0.8 lb
Length (over-all):	
Stock extended	29.8 in.
Stock closed	22.8 in.
Weight of recoiling parts	2.0 lb
Weight of barrel	0.62 lb
Weight of barrel assembly	1.43 lb
Length of barrel	8 in.
Length of rifling	7.2 in.
Rifling:	
Number of grooves	4
Right-hand twist: 1 turn in	16 in. (15 in. alternate)
Depth of grooves	0.0035 in.
Cross-sectional area of bore	0.1581 sq in.
Type of mechanism	Straight blowback, fully automatic
Feeding device	Magazine
Capacity of feeding device	30 rounds
Rate of fire	350 to 450 rounds per min
Cooling system	Air
Mean sight radius	10.8 in.
Type of sights	Fixed peep, 100-yd
Trigger pull	5 to 7 lb
• Pull required to retract bolt	18 to 23 lb
Ammunition type	Ball

References

SNL A-58

Drawing No. 51-123-1A

Specification No. AXS-872