

Workshop 1

Creación de una máquina virtual con Vagrant

Pasos a seguir

1. Descarga e instalación de VirtualBox

1. Descarga VirtualBox desde [la página oficial](#).
2. Sigue las instrucciones de instalación para tu sistema operativo.

2. Descarga e instalación de Vagrant

1. Descarga Vagrant desde [la página oficial](#).
2. Sigue las instrucciones de instalación para tu sistema operativo.

3. Creando el entorno de trabajo

1. Crear una carpeta llamada **Workshop 1**:

```
mkdir Workshop1  
cd Workshop1
```

2. Dentro de esta carpeta, crea un archivo README (este archivo que estás leyendo).

3. **Ejemplo de estructura de carpetas:**

```
e\Workshops\Workshop I
```

4. Creando el archivo de configuración de la máquina virtual

1. Inicializa un nuevo proyecto de Vagrant:

```
vagrant init debian/bookworm64
```

2. Esto creará un archivo **Vagrantfile** en tu directorio de trabajo.

3. **Ejemplo de archivo Vagrantfile inicial:**

```
1 # -*- mode: ruby -*-  
2 # vi: set ft=ruby :  
3  
4 # All Vagrant configuration is done below. The "2" in Vagrant.configure  
5 # configures the configuration version (we support older styles for  
6 # backwards compatibility). Please don't change it unless you know what  
7 # you're doing.
```

```


1 # You're doing:
2 Vagrant.configure("2") do |config|
3   # The most common configuration options are documented and commented below.
4   # For a complete reference, please see the online documentation at
5   # https://docs.vagrantup.com.
6
7   # Every Vagrant development environment requires a box. You can search for
8   # boxes at https://vagrantcloud.com/search.
9   config.vm.box = "debian/bookworm64"
10
11   # Disable automatic box update checking. If you disable this, then
12   # boxes will only be checked for updates when the user runs
13   # `vagrant box outdated`. This is not recommended.
14   # config.vm.box_check_update = false
15
16   # Create a forwarded port mapping which allows access to a specific port
17   # within the machine from a port on the host machine. In the example below,
18   # accessing "localhost:8080" will access port 80 on the guest machine.
19   # NOTE: This will enable public access to the opened port
20   # config.vm.network "forwarded_port", guest: 80, host: 8080
21
22   # Create a forwarded port mapping which allows access to a specific port
23   # within the machine from a port on the host machine and only allow access
24   # via 127.0.0.1 to disable public access
25   # config.vm.network "forwarded_port", guest: 80, host: 8080, host_ip: "127.0.0.1"
26
27   # Create a private network, which allows host-only access to the machine
28   # using a specific IP.
29   # config.vm.network "private_network", ip: "192.168.33.10"
30
31   # Create a public network, which generally matched to bridged network.
32   # Bridged networks make the machine appear as another physical device on
33   # your network.
34   # config.vm.network "public_network"
35
36   # Share an additional folder to the guest VM. The first argument is
37   # the path on the host to the actual folder. The second argument is
38   # the path on the guest to mount the folder. And the optional third
39   # argument is a set of non-required options.
40   # config.vm.synced_folder "../data", "/vagrant_data"
41
42   # Disable the default share of the current code directory. Doing this
43   # provides improved isolation between the vagrant box and your host
44   # by making sure your Vagrantfile isn't accessible to the vagrant box.
45   # If you use this you may want to enable additional shared subfolders as
46   # shown above.
47   # config.vm.synced_folder ".", "/vagrant", disabled: true
48
49   # Provider-specific configuration so you can fine-tune various
50   # backing providers for Vagrant. These expose provider-specific options.
51   # Example for VirtualBox:
52   #
53   # config.vm.provider "virtualbox" do |vb|
54   #   # Display the VirtualBox GUI when booting the machine
55   #   vb.gui = true
56   #
57   #   # Customize the amount of memory on the VM:
58   #   vb.memory = "1024"
59   # end
60
61   # View the documentation for the provider you are using for more
62   # information on available options.
63
64   # Enable provisioning with a shell script. Additional provisioners such as
65   # Ansible, Chef, Docker, Puppet and Salt are also available. Please see the
66   # documentation for more information about their specific syntax and use.
67   # config.vm.provision "shell", inline: <←SHELL
68   # apt-get update
69   # apt-get install -y apache2
70   # SHELL
71 end
72

```

5. Buscar la IP de red en VirtualBox

1. Abre VirtualBox y busca la IP que tiene por defecto para conectarse a internet.

2. **Ejemplo de configuración de red en VirtualBox:**



6. Configurando la máquina virtual

1. Abre **Vagrantfile** en Visual Studio Code:

```
code Vagrantfile
```

2. Configura la red de la máquina virtual. Busca la sección de configuración de red y añade la siguiente línea:

```
config.vm.network "private_network", ip: "192.168.56.1"
```

3. Ejemplo de configuración de red en Vagrantfile:

```
1 # via 127.0.0.1 to disable public access
2 # config.vm.network "forwarded_port", guest: 80, host: 8080, host_ip: "127.0.0.1"
3
4 # Create a private network, which allows host-only access to the machine
5 # using a specific IP.
6 config.vm.network "private_network", ip: "192.168.56.1"
7
8 # Create a public network, which generally matched to bridged network.
9 # Bridged networks make the machine appear as another physical device on
10 # your network.
11 # config.vm.network "public_network"
```

7. Iniciando la máquina virtual

1. En tu terminal, dentro del directorio **Workshop1**, ejecuta:

```
vagrant up
```

2. Una vez la máquina esté en funcionamiento, conéctate a ella:

```
vagrant ssh
```

3. Ejemplo de conexión exitosa a la máquina virtual:

```
Admin@FierceSpectrum MINGW64 ~/Documents/Cursos/Software Libre/Workshops/Worksho
p I/maquinas
$ vagrant ssh
Linux bookworm 6.1.0-18-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.1.76-1 (2024-02-01) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
vagrant@bookworm:~$
```

8. Instalando paquetes básicos

1. Actualiza la lista de paquetes y el sistema:

```
sudo apt-get update
sudo apt-get upgrade
```

2. Instala algunos paquetes básicos. Por ejemplo:

```
sudo apt-get install -y git
```

3. Verifica que los paquetes se han instalado correctamente:

```
git --version
```

4. Ejemplo de instalación y verificación de paquetes:

```
vagrant@bookworm:~$ sudo apt-get install -y git
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  git-man liberror-perl patch
Suggested packages:
  git-daemon-run | git-daemon-sysvinit git-doc git-email git-gui gitk gitweb git-cvs git-mediawiki git-svn ed
  diffutils-doc
The following NEW packages will be installed:
  git git-man liberror-perl patch
0 upgraded, 4 newly installed, 0 to remove and 1 not upgraded.
Need to get 9377 kB of archives.
After this operation, 48.0 MB of additional disk space will be used.
Get:1 https://deb.debian.org/debian bookworm/main amd64 liberror-perl all 0.17029-2 [29.0 kB]
Get:2 https://deb.debian.org/debian bookworm/main amd64 git-man all 1:2.39.2-1.1 [2049 kB]
Get:3 https://deb.debian.org/debian bookworm/main amd64 git amd64 1:2.39.2-1.1 [7171 kB]
Get:4 https://deb.debian.org/debian bookworm/main amd64 patch amd64 2.7.6-7 [128 kB]
Fetched 9377 kB in 1s (6564 kB/s)
Selecting previously unselected package liberror-perl.
(Reading database ... 25485 files and directories currently installed.)
Preparing to unpack .../liberror-perl_0.17029-2_all.deb ...
Unpacking liberror-perl (0.17029-2) ...
Selecting previously unselected package git-man.
Preparing to unpack .../git-man_1%3a2.39.2-1.1_all.deb ...
Unpacking git-man (1:2.39.2-1.1) ...
Selecting previously unselected package git.
Preparing to unpack .../git_1%3a2.39.2-1.1_amd64.deb ...
Unpacking git (1:2.39.2-1.1) ...
Selecting previously unselected package patch.
Preparing to unpack .../patch_2.7.6-7_amd64.deb ...
Unpacking patch (2.7.6-7) ...
Setting up liberror-perl (0.17029-2) ...
Setting up patch (2.7.6-7) ...
Setting up git-man (1:2.39.2-1.1) ...
Setting up git (1:2.39.2-1.1) ...
Processing triggers for man-db (2.11.2-2) ...
vagrant@bookworm:~$ git --version
git version 2.39.2
vagrant@bookworm:~$
```

9. Finalizando

1. Para salir de la máquina virtual:

```
exit
```

2. Para detener la máquina virtual:

```
vagrant halt
```

3. Ejemplo de comandos para finalizar la máquina virtual:

```
Admin@FierceSpectrum MINGW64 ~/Documents/Cursos/Software Libre/Workshops/Workshop I/maquinas
$ vagrant halt
==> default: Attempting graceful shutdown of VM...
```

¡Y eso es todo! Ahora has configurado y trabajado con una máquina virtual Debian usando Vagrant.

[My GitHub](#)