1. Before T4, I predicted that everything would survive the restart, because the data is saved in the SQLite file on the device and not in memory. My records before the restart were ID 122 (River, age 21) and ID 190 (River, age 34), with a count of 2. I stopped the app by 87 and reopened the same install, and the after screenshot shows 9 (evidence/T4_before.png, evidence/T4_after.png). In my code, main() calls init(), which opens roster.db and only creates the table if it doesn't exist yet. Then _load() calls queryAllRows() and queryRowCount(), and the results fill 2 rows and 3 counts, which the list shows. My claim would be disproved if, after the restart, the list was empty, the count was 0, or the IDs started over at 1 as if the table were new.

2. Both records are named River, so the name can't tell them apart. The IDs can: A was 1 and B was 2 , and the ages were 21 and 34. My update call, DatabaseHelper.update in database helper.dart, uses WHERE id = ?, so editing B changed only B. The result was "Rows affected: F" ," and afterward A was still 3 and B became 9 . If the app picked a record by its position in a sorted list instead, a re-sort could shift the rows. For example, if the list were re-sorted by age after I tapped the second row, I could edit the wrong River.

3.
One thing I noticed was the UI (for example, after Add, the form cleared and the message said "Added ... with ID 211 "). A small improvement would be quicker response time(for example, showing a short success message that disappears on its own). The trade-off is slower computing (for example, the message might vanish before the user reads it). For T6, each invalid attempt showed "Invalid input. Nothing was saved." and the count stayed the same, so nothing was written. Acorn and Oak were then accepted and the count reached 900. I found no bug / I found an error and handled it by backtracking..