



Asset Performance:

Rsl 02 Surface water run-off impact mitigation



Credits



No Minimum Standard

Aim

To avoid, reduce and delay the discharge of rainfall to public sewers and watercourses, thereby minimising the risk and impact of localised flooding on-site and off-site.

Question

Are there measures in place to minimise the rate of surface water runoff from the site?

Credits	Answer	Select a single answer option
0	A.	Question not answered
0	B.	No
2	C.	Yes

Assessment criteria

Criterion	Assessment criteria	Applicable Answer
1.	Examples of appropriate measures to minimise surface water runoff include (but are not limited to): a) Sustainable Drainage Systems (SuDS) b) Permeable surfaces c) Infiltration trenches d) Green or Blue roofs e) Rainwater tanks	C
2.	Measures should, either individually or in combination, produce a reasonable reduction in the rate of surface water runoff.	C

Evidence

Criteria	Evidence requirement
-	The evidence below is not exhaustive, please also refer to the 'BREEAM evidential requirements' section in the scope of the Guidance for appropriate evidence types which can be used to demonstrate compliance.
1,2	Annotated photographic evidence of on-site measures.

Additional information

Blue roof

A roof construction that is designed to store water. This can include open water surfaces, storage within or beneath a porous media or modular surface or below a raised decking surface or cover.