

Assignment 3

Filipe Pires [85122], João Alegria [85048]

Information Retrieval

Department of Electronics, Telecommunications and Informatics

University of Aveiro

December 10, 2019

1 Introduction

This report was written for the discipline of 'Information Retrieval' and describes the implementation and evaluation of a ranked retrieval method that uses the indexes created with the solutions developed for the previous assignments.

We include the correction of design flaws of the delivery done prior to this one and the updates applied both to the text corpus indexation and to our class diagram. We also provide the instructions on how to run our code.

Along with the description of the solution, we also present the results of our calculations to evaluate the solution and determine its efficiency according to the metrics proposed for this last assignment (*I*). All code and documentation is present in our public GitHub project at <https://github.com/joao-alegria/RI>.

2 Re-Indexing the Corpus

In order to make query searches flexible, it was proposed to us the reindexation of the text corpus considering not only the document titles but also their abstracts. This turned out to be quite challenging due to its computational weight, as the abstracts were considerably larger than the titles. The initial index occupied about 500Mb in disk, whereas the reindexation turned out to be over 3Gb large.

There were 2 approaches when adding the abstract processing to our indexing process. The first one would consist in dealing with titles and abstracts separately, creating independent index entries for both. This approach has the advantage of simplifying the process of verification of appearance of a given term in titles, abstracts or both, since they would be stored in different structures. It has however the clear disadvantage of requiring far more disk space to store all the information and introducing redundancy and unnecessary repetitions.

With this in mind, we went for another strategy, consisting of concatenating both fields and processing the resulting text as a whole. This approach's advantage and disadvantage are inverted when compared to the previous, since the redundancy no longer exists but it becomes impossible to distinguish the field a term appears at. Our choice was based on the analysis of the requirements for the ranked retriever we wanted to implement, as there seemed to be no need to keep the notion of where each term appeared at in each document. This also made the code adaptations to the indexing pipeline more straightforward and, as we previously mentioned, the final size in disk of the index smaller. The execution time of this pipeline thankfully did not evolve as fast as the disk space, passing from 20 minutes without the abstract to approximately 1 hour and 20 minutes with it.

3 Ranked Retrieval of Relevant Documents

With an entirely functional index creator and a folder of generated indexes from the corpus of text documents, it was now time to develop a program capable of interpreting queries and returning the index entries most relevant to them. In this chapter we describe our implementation of a query results ranked retriever - that we called `Searcher`. We also explain how we prepared it for memory limitations and present the updates done to our class diagram.

3.1 Document Ranked Scores

The file `Searcher.py` contains an abstract class called `Searcher` that serves as a template for the implementations of results retriever classes. For our purposes, we developed `IndexSearcher`, a class that extends from the abstract template and is capable of selecting which index files will be required to answer a given query, assigning scores to documents from the index and returning the documents considered most relevant to the query according to these scores.

The step of determining which index files will be needed to answer the query is done through the function `retrieveRequiredFiles()` and is basically a comparison of each query term with the name of each index file. As each index file is named after the first and last terms it contains (separated by an underscore) and as the entire index is alphabetically ordered, the function simply determines where each term will be present and returns those index files.

Calculating the score of each document regarding a query is not as easy to explain. explain `calculateScores()`

Once the scores are found, `sortAndWriteResults()` does what its name suggests: sorts the documents by score and writes to a results file the first K documents, where K is passed as argument by the user.

3.2 Relevance Feedback

We knew `IndexSearcher` was a very limited solution, as it considers documents as relevant only for the presence of query terms in their titles and / or abstracts. So the idea of attempting to expand queries was introduced through feeding back to the `Searcher` information that would help it fine tune its results.

The aim of relevance feedback is to transform query vectors (consisting in the weights of each query term in the query) into new vectors closer to the actually relevant documents and further away from the remainder. The way we implemented this form of attempting to improve results was through a well known algorithm named Rocchio algorithm.

..... explain roocchio




Figure 1: Program’s class diagram.

4 Evaluation and Results Discussion

In order to evaluate the quality of our solutions, with and without relevance feedback, we calculate an assortment of performance metrics. The chosen metrics were: Precision, Recall, F-Measure, Mean Precision at rank 10, Mean Precision, Normalized Discounted Cumulative Gain, and all the averages in between the queries performed for all the previous metrics. The implementation of the calculations was done in `QueryAnalyzer.py`. Time related metrics were also considered, such as: Query Throughput and Median Query Latency, but for these we chose to use an auxiliary linux command line program called `time` which is able to summarize the system resources used in a program’s execution.

In this chapter we explain the metrics used to evaluate the implemented ranked retrieval,

present the results of our evaluation and our discussion regarding them and attempt to understand what exactly are the solutions limitations.

4.1 Evaluation Metrics

Precision and recall are one of the most used metrics in information retrieval. The first is characterized by dividing the correct retrieved documents by the totality of retrieved documents. This metric provides the percentage of the retrieved documents that are really relevant for the user. The second consists of dividing the correct retrieved documents by the totality of ideal correct documents. The result is the percentage of correct documents the system can present.

F-Measure (or F-Score) is a metric many times used to represent the system performance with only one value. This is accomplished by the combination of the two previous metrics, performing the harmonic mean between the two metrics through the following equation:

$$Fs = \frac{2 \times P \times R}{P + R} \quad (1)$$

Mean Precision is a variation of the Precision metric. Its formula is similar, the difference is that in this case the precision is calculated in the various ranks, i.e. it is calculated for every newly retrieved document and then the average of all the intermediate precisions is achieved, resulting in the mean of the precisions of the query result (hence the name). Mean Precision at rank 10 is described as the Mean Precision calculated just until rank 10 (until the 10th value).

Normalized Discounted Cumulative Gain is a more complex metric that uses a graded relevance scale of documents to evaluate usefulness/gain of the returned results. The core idea with this metric is that relevant documents that are lower in the list should be penalized, since the important documents should be the first results provided. This is accomplished by the formula:

$$DCG = \sum_{i=1}^p \frac{rel_i}{\log_2(i + 1)} \quad (2)$$

The normalization is then achieved by dividing this value by the ideal one, i.e. having the relevances in order, the first documents considered the most relevant and so on.

Query Throughput is a time related metric that indicates how many queries can be processed in one second. It's obvious that it's ideal that the information gathering and ordering should take the least amount of time possible, so the higher the query throughput the better.

Finally, the Median Query Latency, as the name suggests, is the average time it takes to process a query. Following the same logical line of thought of the previous metric, the lower this number is the better, since it means that more queries can be processed in less time.

4.2 Results

The tests phase of the project was conducted with the help of `QueryIndex` to execute the ranked retrievals and `QueryAnalyzer` to evaluate the results. They considered the original dataset indexed with the updates mentioned in chapter 1 and all 50 given queries.

`QueryIndex.py` works as the script that creates an instance of the `IndexSearcher` and, for each query, tells it to retrieve the best results. The command works as follows:

```
$ python3 QueryIndex.py [-h] [-p] [-o outputFile] [-t tokenizer]
  [-r limitRAM] [-f feedback] [-n n] [-k k] [-l limit] queryFile
  indexFolder [a b g]
```

Here, `-h` is the option that presents the manual for the command usage. Option `-p`, if present, tell the program that the index has the positions of each term in each document along with the weights. Option `-o` allows the definition of the output folder's name where the results will be stored. Option `-t` makes possible for the user to choose the type of tokenizer to be used, and the alternatives are: 'simple' for the use of the `SimpleTokenizer` class, and 'complex' for the `ComplexTokenizer` class. The chosen tokenizer must be the same used when indexing the text corpus. Option `-r` allows the user to define the maximum amount of memory that can be used by the process running the program. Option `-f` makes possible for the user to choose a form of relevance feedback, so that there is a greater assurance that the returned documents are actually relevant to the query. The alternatives are: 'pseudo' and 'user'. Options `-n`, `-k` and `-l` allow the definition of the number of retrieved documents considered for the Rocchio algorithm (applied in the relevance feedback), the size of the champions list and the number of scores to return (to store in the output files). The previous arguments are all optional and the actual values for these arguments must appear right after the respective options. `QueryFile` and `indexFolder` are the only obligatory parameters, as they tell the program where are the queries and the index files. `A`, `b` and `g` are optional parameters that must be defined if the relevance feedback is activated (if `-f` and `-n` are also defined), as they correspond to the Rocchio algorithm's parameters alpha, beta and gamma.

We executed `QueryIndex.py` for different combinations of parameters to ensure its correct functioning and to search for the configuration with highest performances. It was initially tested with indexes with positions and both types of tokenizers, although the remaining tests were all using only weights to reduce execution times and only the complex tokenizer to remove noise and increase precision. Then we tested the program with and without champions list (although this was not done through the command's parameters) and for champions lists of different sizes. Following we also varied the number of documents the program returned. And finally we tested the program with relevance feedback, with both pseudo and simulated user feedbacks, and with different Rocchio parameters values.

The presence of the champions list seemed to have no relevant impact on the overall performance, with the tests at the time rounding the 19% of precision (with a champions list of size 10 000). This feature was important for the execution times, as it reduced the search space of the program for each query without losing valuable information. What we later understood was that, if its size was reduced, the loss of useful information and relevant documents started to have a big impact on the performance, as for a list of size 1000 the precision dropped to about 16%.

With the champions list at size 10 000, we tried to reduce the number of results returned from 100 to 50, 20 and 10. The later reached a precision of 26%, which was good news to us.

Although pseudo feedback was also part of our tests, we knew *a priori* that this would not influence the results at all, since it assumed that the first results the program already considered more relevant were in fact relevant and increased their final scores. User feedback, on the other hand, proved to have great value when tested.

4.3 Discussion

Lorem ipsum ...

+ champions list = + precision user feedback = + precision + results returned = - precision

low recall is normal since we return X and X can be a very small group compared to the entire universe of documents

4.4 Implementation Limitations

Lorem ipsum ...

5 Conclusions

After completing the assignment, we drew a few conclusions regarding our solutions and the whole concept of

The biggest challenge we faced was

From this assignment, we take

The overall perspective of our performance regarding the project is

References

1. S. Matos, *IR: Assignment 3*, University of Aveiro, 2019/20.