

# Working with a single data frame

Filippo Chiarello, Ph.D.

*We...*

**have** *a single data frame*

**want** *to slice it, and dice it, and juice it, and process it*

# Data: Hotel bookings

- Data from two hotels: one resort and one city hotel
- Observations: Each row represents a hotel booking

```
hotels <- read_csv("data/hotels.csv")
```

R STUDIO CLOUD LINK

# select, arrange, and slice

# select to keep variables

```
hotels %>%  
  select(hotel, lead_time)
```

```
## # A tibble: 119,390 × 2  
##   hotel      lead_time  
##   <chr>      <dbl>  
## 1 Resort Hotel      342  
## 2 Resort Hotel      737  
## 3 Resort Hotel        7  
## 4 Resort Hotel      13  
## 5 Resort Hotel      14  
## 6 Resort Hotel      14  
## # ... with 119,384 more rows
```

# select to exclude variables

```
hotels %>%  
  select(-agent)
```

```
## # A tibble: 119,390 × 31  
##   hotel    is_canceled lead_time arrival_date_ye... arrival_date_mo...  
##   <chr>      <dbl>      <dbl>      <dbl> <chr>  
## 1 Resort...      0        342        2015 July  
## 2 Resort...      0        737        2015 July  
## 3 Resort...      0         7        2015 July  
## 4 Resort...      0        13        2015 July  
## 5 Resort...      0        14        2015 July  
## 6 Resort...      0        14        2015 July  
## # ... with 119,384 more rows, and 26 more variables:  
## #   arrival_date_week_number <dbl>,  
## #   arrival_date_day_of_month <dbl>,  
## #   stays_in_weekend_nights <dbl>, stays_in_week_nights <dbl>,  
## #   adults <dbl>, children <dbl>, babies <dbl>, meal <chr>,  
## #   country <chr>, market_segment <chr>,  
## #   distribution_channel <chr>, is_repeated_guest <dbl>, ...
```

# select a range of variables

```
hotels %>%  
  select(hotel:arrival_date_month)
```

```
## # A tibble: 119,390 × 5  
##   hotel    is_canceled lead_time arrival_date_ye... arrival_date_mo...  
##   <chr>          <dbl>    <dbl>          <dbl> <chr>  
## 1 Resort...          0      342          2015 July  
## 2 Resort...          0      737          2015 July  
## 3 Resort...          0        7          2015 July  
## 4 Resort...          0       13          2015 July  
## 5 Resort...          0       14          2015 July  
## 6 Resort...          0       14          2015 July  
## # ... with 119,384 more rows
```

# select variables with certain characteristics

```
hotels %>%  
  select(starts_with("arrival"))
```

```
## # A tibble: 119,390 × 4  
##   arrival_date_year arrival_date_month arrival_date_week_number  
##           <dbl> <chr>                <dbl>  
## 1           2015 July                    27  
## 2           2015 July                    27  
## 3           2015 July                    27  
## 4           2015 July                    27  
## 5           2015 July                    27  
## 6           2015 July                    27  
## # ... with 119,384 more rows, and 1 more variable:  
## #   arrival_date_day_of_month <dbl>
```



# select variables with certain characteristics

```
hotels %>%  
  select(ends_with("type"))
```

```
## # A tibble: 119,390 × 4  
##   reserved_room_type assigned_room_ty... deposit_type customer_type  
##   <chr>              <chr>              <chr>      <chr>  
## 1 C                  C                  No Deposit Transient  
## 2 C                  C                  No Deposit Transient  
## 3 A                  C                  No Deposit Transient  
## 4 A                  A                  No Deposit Transient  
## 5 A                  A                  No Deposit Transient  
## 6 A                  A                  No Deposit Transient  
## # ... with 119,384 more rows
```

# Select helpers

- `starts_with( )`: Starts with a prefix
- `ends_with( )`: Ends with a suffix
- `contains( )`: Contains a literal string
- `num_range( )`: Matches a numerical range like x01, x02, x03
- `one_of( )`: Matches variable names in a character vector
- `everything( )`: Matches all variables
- `last_col( )`: Select last variable, possibly with an offset
- `matches( )`: Matches a regular expression (a sequence of symbols/characters expressing a string/pattern to be searched for within text)

See help for any of these functions for more info, e.g. `?everything`.

# arrange in ascending / descending order

```
hotels %>%  
  select(adults, children, babies) %>%  
  arrange(babies)
```

```
## # A tibble: 119,390 × 3  
##   adults children babies  
##   <dbl>   <dbl>   <dbl>  
## 1      2       0       0  
## 2      2       0       0  
## 3      1       0       0  
## 4      1       0       0  
## 5      2       0       0  
## 6      2       0       0  
## # ... with 119,384 more rows
```

```
hotels %>%  
  select(adults, children, babies) %>%  
  arrange(desc(babies))
```

```
## # A tibble: 119,390 × 3  
##   adults children babies  
##   <dbl>   <dbl>   <dbl>  
## 1      2       0     10  
## 2      1       0      9  
## 3      2       0      2  
## 4      2       0      2  
## 5      2       0      2  
## 6      2       0      2  
## # ... with 119,384 more rows
```

# slice for certain row numbers

```
# first five  
hotels %>%  
  slice(1:5)
```

```
## # A tibble: 5 × 32  
##   hotel    is_canceled lead_time arrival_date_ye... arrival_date_mo...  
##   <chr>      <dbl>      <dbl>          <dbl> <chr>  
## 1 Resort...      0        342          2015 July  
## 2 Resort...      0        737          2015 July  
## 3 Resort...      0         7          2015 July  
## 4 Resort...      0        13          2015 July  
## 5 Resort...      0        14          2015 July  
## # ... with 27 more variables: arrival_date_week_number <dbl>,  
## #   arrival_date_day_of_month <dbl>,  
## #   stays_in_weekend_nights <dbl>, stays_in_week_nights <dbl>,  
## #   adults <dbl>, children <dbl>, babies <dbl>, meal <chr>,  
## #   country <chr>, market_segment <chr>,  
## #   distribution_channel <chr>, is_repeated_guest <dbl>,  
## #   previous_cancellations <dbl>, ...
```

In R, you can use the `#` for adding comments to your code. Any text following `#` will be printed as is, and won't be run as R code. This is useful for leaving comments in your code and for temporarily disabling certain lines of code while debugging.

```
hotels %>%  
  # slice the first five rows # this line is a comment  
  #select(hotel) %>%         # this one doesn't run  
  slice(1:5)                 # this line runs
```

```
## # A tibble: 5 × 32  
##   hotel    is_canceled lead_time arrival_date_ye... arrival_date_mo...  
##   <chr>      <dbl>      <dbl>      <dbl> <chr>  
## 1 Resort...      0      342      2015 July  
## 2 Resort...      0      737      2015 July  
## 3 Resort...      0       7      2015 July  
## 4 Resort...      0      13      2015 July  
## 5 Resort...      0      14      2015 July  
## # ... with 27 more variables: arrival_date_week_number <dbl>,  
## #   arrival_date_day_of_month <dbl>,  
## ...
```

# filter

# filter to select a subset of rows

```
# bookings in City Hotels
hotels %>%
  filter(hotel == "City Hotel")
```

```
## # A tibble: 79,330 × 32
##   hotel    is_canceled lead_time arrival_date_ye... arrival_date_mo...
##   <chr>      <dbl>      <dbl>          <dbl> <chr>
## 1 City H...          0          6            2015 July
## 2 City H...          1         88            2015 July
## 3 City H...          1         65            2015 July
## 4 City H...          1         92            2015 July
## 5 City H...          1        100            2015 July
## 6 City H...          1         79            2015 July
## # ... with 79,324 more rows, and 27 more variables:
## #   arrival_date_week_number <dbl>,
## #   arrival_date_day_of_month <dbl>,
## #   stays_in_weekend_nights <dbl>, stays_in_week_nights <dbl>,
## #   adults <dbl>, children <dbl>, babies <dbl>, meal <chr>,
## #   country <chr>, market_segment <chr>,
## #   distribution_channel <chr>, is_repeated_guest <dbl>, ...
```

# filter for many conditions at once

```
hotels %>%  
  filter(  
    adults == 0,  
    children >= 1  
  ) %>%  
  select(adults, babies, children)
```

```
## # A tibble: 223 × 3  
##   adults babies children  
##   <dbl>   <dbl>   <dbl>  
## 1      0      0       3  
## 2      0      0       2  
## 3      0      0       2  
## 4      0      0       2  
## 5      0      0       2  
## 6      0      0       3  
## # ... with 217 more rows
```



# filter for more complex conditions

```
# bookings with no adults and some children or babies in the room
hotels %>%
  filter(
    adults == 0,
    children >= 1 | babies >= 1    # | means or
  ) %>%
  select(adults, babies, children)
```

```
## # A tibble: 223 × 3
##   adults babies children
##   <dbl>   <dbl>   <dbl>
## 1      0      0       3
## 2      0      0       2
## 3      0      0       2
## 4      0      0       2
## 5      0      0       2
## 6      0      0       3
## # ... with 217 more rows
```

# Logical operators in R

operator	definition	operator	definition
<	less than	<code>x   y</code>	<code>x OR y</code>
<=	less than or equal to	<code>is.na(x)</code>	test if x is NA
>	greater than	<code>!is.na(x)</code>	test if x is not NA
>=	greater than or equal to	<code>x %in% y</code>	test if x is in y
==	exactly equal to	<code>!(x %in% y)</code>	test if x is not in y
!=	not equal to	<code>!x</code>	not x
<code>x &amp; y</code>	<code>x AND y</code>		

# Your turn!

Time to actually play around with the Hotels dataset!

- Go to RStudio Cloud and start `AE 04 – Hotels + Data wrangling`.
- Open the R Markdown document and complete Exercises 1 - 4.

# distinct and count

# distinct to filter for unique rows

... and arrange to order alphabetically

```
hotels %>%  
  distinct(market_segment) %>%  
  arrange(market_segment)
```

```
## # A tibble: 8 × 1  
##   market_segment  
##   <chr>  
## 1 Aviation  
## 2 Complementary  
## 3 Corporate  
## 4 Direct  
## 5 Groups  
## 6 Offline TA/T0  
## 7 Online TA  
## 8 Undefined
```

```
hotels %>%  
  distinct(hotel, market_segment) %>%  
  arrange(hotel, market_segment)
```

```
## # A tibble: 14 × 2  
##   hotel      market_segment  
##   <chr>      <chr>  
## 1 City Hotel Aviation  
## 2 City Hotel Complementary  
## 3 City Hotel Corporate  
## 4 City Hotel Direct  
## 5 City Hotel Groups  
## 6 City Hotel Offline TA/T0  
## 7 City Hotel Online TA  
## 8 City Hotel Undefined  
## 9 Resort Hotel Complementary  
## 10 Resort Hotel Corporate  
## ...
```

# count to create frequency tables

```
# alphabetical order by default
hotels %>%
  count(market_segment)
```

```
## # A tibble: 8 × 2
##   market_segment      n
##   <chr>          <int>
## 1 Aviation         237
## 2 Complementary     743
## 3 Corporate        5295
## 4 Direct          12606
## 5 Groups           19811
## 6 Offline TA/T0    24219
## 7 Online TA        56477
## 8 Undefined         2
```

```
# descending frequency order
hotels %>%
  count(market_segment, sort = TRUE)
```

```
## # A tibble: 8 × 2
##   market_segment      n
##   <chr>          <int>
## 1 Online TA        56477
## 2 Offline TA/T0    24219
## 3 Groups           19811
## 4 Direct          12606
## 5 Corporate        5295
## 6 Complementary     743
## 7 Aviation         237
## 8 Undefined         2
```

# count and arrange

```
# ascending frequency order
hotels %>%
  count(market_segment) %>%
  arrange(n)
```

```
## # A tibble: 8 × 2
##   market_segment      n
##   <chr>          <int>
## 1 Undefined           2
## 2 Aviation          237
## 3 Complementary      743
## 4 Corporate          5295
## 5 Direct            12606
## 6 Groups             19811
## 7 Offline TA/T0      24219
## 8 Online TA          56477
```

```
# descending frequency order
# just like adding sort = TRUE
hotels %>%
  count(market_segment) %>%
  arrange(desc(n))
```

```
## # A tibble: 8 × 2
##   market_segment      n
##   <chr>          <int>
## 1 Online TA          56477
## 2 Offline TA/T0      24219
## 3 Groups             19811
## 4 Direct            12606
## 5 Corporate          5295
## 6 Complementary      743
## 7 Aviation           237
## 8 Undefined           2
```

# count for multiple variables

```
hotels %>%  
  count(hotel, market_segment)
```

```
## # A tibble: 14 × 3  
##   hotel      market_segment     n  
##   <chr>      <chr>         <int>  
## 1 City Hotel Aviation         237  
## 2 City Hotel Complementary     542  
## 3 City Hotel Corporate       2986  
## 4 City Hotel Direct         6093  
## 5 City Hotel Groups       13975  
## 6 City Hotel Offline TA/T0  16747  
## 7 City Hotel Online TA      38748  
## 8 City Hotel Undefined         2  
## 9 Resort Hotel Complementary    201  
## 10 Resort Hotel Corporate      2309  
## 11 Resort Hotel Direct         6513  
## 12 Resort Hotel Groups        5836  
## 13 Resort Hotel Offline TA/T0   7472  
## 14 Resort Hotel Online TA     17729
```



# order matters when you count

```
# hotel type first  
hotels %>%
```

```
  count(hotel, market_segment)
```

```
## # A tibble: 14 × 3  
##   hotel      market_segment      n  
##   <chr>      <chr>          <int>  
## 1 City Hotel Aviation           237  
## 2 City Hotel Complementary       542  
## 3 City Hotel Corporate        2986  
## 4 City Hotel Direct          6093  
## 5 City Hotel Groups         13975  
## 6 City Hotel Offline TA/T0    16747  
## 7 City Hotel Online TA       38748  
## 8 City Hotel Undefined           2  
## 9 Resort Hotel Complementary     201  
## 10 Resort Hotel Corporate       2309  
## 11 Resort Hotel Direct         6513  
## 12 Resort Hotel Groups         5836  
## 13 Resort Hotel Offline TA/T0   7472  
## 14 Resort Hotel Online TA      17729
```

```
# market segment first  
hotels %>%
```

```
  count(market_segment, hotel)
```

```
## # A tibble: 14 × 3  
##   market_segment hotel      n  
##   <chr>      <chr>          <int>  
## 1 Aviation    City Hotel       237  
## 2 Complementary City Hotel       542  
## 3 Complementary Resort Hotel     201  
## 4 Corporate    City Hotel      2986  
## 5 Corporate    Resort Hotel    2309  
## 6 Direct       City Hotel      6093  
## 7 Direct       Resort Hotel    6513  
## 8 Groups       City Hotel     13975  
## 9 Groups       Resort Hotel    5836  
## 10 Offline TA/T0 City Hotel     16747  
## 11 Offline TA/T0 Resort Hotel    7472  
## 12 Online TA    City Hotel     38748  
## 13 Online TA    Resort Hotel   17729  
## 14 Undefined    City Hotel        2
```

# Your turn!

- Go back to RStudio Cloud and continue AE 04 – Hotels + Data wrangling.
- Open the R Markdown document and complete Exercises 5 and 6.

# mutate

# mutate to add a new variable

```
hotels %>%  
  mutate(little_ones = children + babies) %>%  
  select(children, babies, little_ones) %>%  
  arrange(desc(little_ones))
```

```
## # A tibble: 119,390 × 3  
##   children babies little_ones  
##   <dbl>   <dbl>   <dbl>  
## 1      10      0         10  
## 2       0     10         10  
## 3       0      9          9  
## 4       2      1          3  
## 5       2      1          3  
## 6       2      1          3  
## # ... with 119,384 more rows
```

# Little ones in resort and city hotels

```
# Resort Hotel
hotels %>%
  mutate(little_ones = children + babies)
  filter(
    little_ones >= 1,
    hotel == "Resort Hotel"
  ) %>%
  select(hotel, little_ones)
```

```
## # A tibble: 3,929 × 2
##   hotel      little_ones
##   <chr>         <dbl>
## 1 Resort Hotel         1
## 2 Resort Hotel         2
## 3 Resort Hotel         2
## 4 Resort Hotel         2
## 5 Resort Hotel         1
## 6 Resort Hotel         1
## # ... with 3,923 more rows
```

```
# City Hotel
hotels %>%
  mutate(little_ones = children + babies)
  filter(
    little_ones >= 1,
    hotel == "City Hotel"
  ) %>%
  select(hotel, little_ones)
```

```
## # A tibble: 5,403 × 2
##   hotel      little_ones
##   <chr>         <dbl>
## 1 City Hotel         1
## 2 City Hotel         1
## 3 City Hotel         2
## 4 City Hotel         1
## 5 City Hotel         1
## 6 City Hotel         1
## # ... with 5,397 more rows
```

## What is happening in the following chunk?

```
hotels %>%  
  mutate(little_ones = children + babies) %>%  
  count(hotel, little_ones) %>%  
  mutate(prop = n / sum(n))
```

```
## # A tibble: 12 × 4  
##   hotel      little_ones      n      prop  
##   <chr>      <dbl> <int>    <dbl>  
## 1 City Hotel      0 73923 0.619  
## 2 City Hotel      1  3263 0.0273  
## 3 City Hotel      2  2056 0.0172  
## 4 City Hotel      3    82 0.000687  
## 5 City Hotel      9     1 0.00000838  
## 6 City Hotel     10     1 0.00000838  
## 7 City Hotel     NA     4 0.0000335  
## 8 Resort Hotel    0 36131 0.303  
## 9 Resort Hotel    1  2183 0.0183  
## 10 Resort Hotel   2  1716 0.0144  
## 11 Resort Hotel   3    29 0.000243  
## 12 Resort Hotel  10     1 0.00000838
```

# summarise and group\_by

# summarise for summary stats

```
# mean average daily rate for all bookings
hotels %>%
  summarise(mean_adr = mean(adr))
```

```
## # A tibble: 1 × 1
##   mean_adr
##   <dbl>
## 1      102.
```

`summarise()` changes the data frame entirely, it collapses rows down to a single summary statistic, and removes all columns that are irrelevant to the calculation.



`summarise()` also lets you get away with being sloppy and not naming your new column, but that's not recommended!



```
hotels %>%  
  summarise(mean(adr))
```

```
## # A tibble: 1 × 1  
##   `mean(adr)`  
##   <dbl>  
## 1      102.
```



```
hotels %>%  
  summarise(mean_adr = mean(adr))
```

```
## # A tibble: 1 × 1  
##   mean_adr  
##   <dbl>  
## 1      102.
```

# group\_by for grouped operations

```
# mean average daily rate for all booking at city and resort hotels
hotels %>%
  group_by(hotel) %>%
  summarise(mean_adr = mean(adr))
```

```
## # A tibble: 2 × 2
##   hotel      mean_adr
##   <chr>      <dbl>
## 1 City Hotel    105.
## 2 Resort Hotel   95.0
```

# Calculating frequencies

The following two give the same result, so `count` is simply short for `group_by` then determine frequencies

```
hotels %>%  
  group_by(hotel) %>%  
  summarise(n = n())
```

```
## # A tibble: 2 × 2  
##   hotel      n  
##   <chr>    <int>  
## 1 City Hotel 79330  
## 2 Resort Hotel 40060
```

```
hotels %>%  
  count(hotel)
```

```
## # A tibble: 2 × 2  
##   hotel      n  
##   <chr>    <int>  
## 1 City Hotel 79330  
## 2 Resort Hotel 40060
```

# Multiple summary statistics

`summarise` can be used for multiple summary statistics as well

```
hotels %>%  
  summarise(  
    min_adr = min(adr),  
    mean_adr = mean(adr),  
    median_adr = median(adr),  
    max_adr = max(adr)  
  )
```

```
## # A tibble: 1 × 4  
##   min_adr mean_adr median_adr max_adr  
##   <dbl>   <dbl>     <dbl>   <dbl>  
## 1    -6.38    102.      94.6    5400
```

# Your turn!

Time to actually play around with the Hotels dataset!

- Go to RStudio Cloud and start `AE 04 – Hotels + Data wrangling`.
- Open the R Markdown document and complete Exercises 7 and 8.