

# Principles of Programming Languages, 2017.07.05

## Notes

- Total available time: 2h.
- You may use any written material you need, and write in Italian, if you prefer.
- You cannot use electronic devices during the exam.

## Exercise 1, Scheme (10 pts)

- 1) Define a mutable binary tree data structure, using structs.
- 2) Define a destructive map operation for binary trees, called tmap!.  
E.g. `(define t1 (branch (branch (leaf 1)(leaf 2))(leaf 3)))`; after `(map! (lambda (x) (+ x 1)) t1)`, t1 becomes `(branch (branch (leaf 2)(leaf 3))(leaf 4))`
- 3) Define a destructive reverse, called reverse!, which takes a binary tree and keeps its structure, but “reversing” all the values in the leaves. E.g. `(reverse! t1)` makes t1 the tree `(branch (branch (leaf 3)(leaf 2))(leaf 1))`.

## Exercise 2, Haskell (12 pts)

Consider the following binary tree data structure:

**data Tree a = Nil | Leaf a | Branch (Tree a)(Tree a) deriving (Show, Eq)**

- 1) Define a **tcompose** operation, which takes a function **f** and two trees, **t1** and **t2**, and returns a tree with the same structure as **t1**, but with leaves replaced by subtrees having the same structure of **t2**: each leaf is obtained by applying **f** to the value stored in the previous leaf, and the corresponding value in **t2**.

E.g. `t1 = Branch (Branch (Leaf 1) (Leaf 2)) (Leaf 3)`, `t2 = Branch (Leaf 6) (Leaf 7)`

**tcompose (+) t1 t2** is

**Branch (Branch (Branch (Leaf 7) (Leaf 8)) (Branch (Leaf 8) (Leaf 9))) (Branch (Leaf 9) (Leaf 10))**

- 2) Define a purely functional (i.e. non destructive) version of the reverse presented in Es. 1.3.

E.g. `revtree t1` is **Branch (Branch (Leaf 3) (Leaf 2)) (Leaf 1)**.

## Exercise 3, Erlang (10 pts)

Consider a binary tree stored with tuples, e.g. `{branch, {branch, {leaf, 1}, {leaf, 2}}, {leaf, 3}}`.

Define an **activate** function, which takes a binary tree and a binary function **f** and creates a network of actors having the same structure of the given tree. Actors corresponding to leaves run a function called **leafy**, that must be defined, which answer to the message `{ask, P}` by sending to process **P** the pair `{self(), V}`, where **V** is the value stored in the leaf, then terminate.

Actors for the branches run a function called **branchy**, that must be also defined: if they receive an `{ask, P}` request like that of leaves, they ask both their sons; when they receive the answers, they call **f** on the obtained values, then send the result **V** to **P** as `{self(), V}` and terminate.

E.g. running the following code:

`test() ->`

`T1 = {branch, {branch, {leaf, 1}, {leaf, 2}}, {leaf, 3}},`

`A1 = activate(T1, fun min/2),`

`A1 ! {ask, self()},`

`receive`

`{A1, V} -> V`

`end.`

should return 1.



Es 3

```
leafy(V) ->
  receive
    {ask, Pid} -> Pid ! {self(), V}
  end.
```

```
branchy(L, R, Fun, Ready, Dad) ->
  receive
    {ask, Pid} ->
      L ! {ask, self()},
      R ! {ask, self()},
      branchy(L, R, Fun, Ready, Pid);
    {L, V1} ->
      case Ready of
        true -> Dad ! {self(), Fun(V1, R)};
        false -> branchy(V1, R, Fun, true, Dad)
      end;
    {R, V1} ->
      case Ready of
        true -> Dad ! {self(), Fun(L, V1)};
        false -> branchy(L, V1, Fun, true, Dad)
      end
  end
end.
```

```
activate({leaf, X}, _) ->
  spawn(?MODULE, leafy, [X]);
activate({branch, L, R}, Fun) ->
  spawn(?MODULE, branchy, [activate(L, Fun), activate(R, Fun), Fun, false, none]).
```