Ubiquity API

Product Overview

Endpoint guide generated from the OpenAPI 3.0.3 specification, v1.7.0

What is in this document

A guided tour of the Ubiquity API: how to authenticate, how the core workflow runs, and a reference of all 56 operations across 10 functional areas.

Overview

Ubiquity discovers open-source signals, geotags and verifies them, and turns them into live feeds you can monitor, query and route into existing workflows. The API covers the full lifecycle of that platform: discover, stream and understand.

56	10	46	JWT
operations	resource areas	unique paths	bearer auth

Servers

Base URL	Purpose
`https://ubiquity.filterlabs.ai/api`	Reverse-proxied backend (locations / orchestrator / understand services)
`https://auth.filterlabs.ai`	Keycloak auth server (realm filter-labs-web, client web-app)
`https://agents.ubiquity.filterlabs.ai`	Trial / preview signup site ('Ubiquity for Agents'): signup and health check only

Authentication

All endpoints except the token call and the two signup-site calls require a JWT, sent as `Authorization: Bearer ***`. Tokens come from the Keycloak token endpoint (realm filter-labs-web, client web-app) using the password grant, and are renewed with the refresh_token grant. Access tokens last about 30 minutes; refresh tokens last about 8 hours and rotate on use.

Service families

Prefix	Service	Handles
`/locations`	Locations	Pipelines, feeds, entities, jobs, saved searches, sharing, media, direct data stream.
`/orchestrator`	Orchestrator	Query parsing, discovery job launch, dataset-upload workflow.
`/understand`	Understand	Ubi chat, artifacts, metric previews.
`/api/v1/signup, /health`	Signup site	Trial account signup and health check (separate base URL, no token).

Conventions

Paging. List endpoints take `limit` and `offset`. The feed stream is different: it pages with an opaque cursor (returned as `next_cursor`) and has no offset.

Core workflow: creating a pipeline

Pipeline creation is three ordered calls, each returning an id the next one needs. Launching a discovery job is a separate, optional fourth step.

Step	Method	Endpoint	What it does
1	POST	`/locations/api/v1/saved-searches`	Save the parsed query and filters.
2	POST	`/locations/api/v1/feeds`	Create the feed that will hold collected content.
3	POST	`/locations/v1/pipelines`	Link the saved search and feed into a new pipeline.
4	POST	`/orchestrator/api/v1/jobs/create`	Optional. Start discovery; poll with GET /locations/api/v1/jobs/{job_id}.

Where the inputs come from

The query is first parsed by `POST /search/unified`. Its `location.id` becomes the saved search's `search_filters.location_uuid`, its parsed locations, topics and entity types are flattened into `search_filters.entities`, and its `session_id` is passed to `POST /pipelines`.

Importing your own sources

Add URLs with `POST /feeds/{feed_id}/sources/upload` (returns 202), or upload a behavioral dataset with `POST /orchestrator/workflows/dataset-upload/trigger` and poll its status endpoint until it completes.

Endpoint reference

Methods: GET POST PUT PATCH DELETE

01 Authentication

1 endpoint

Keycloak-issued JWTs, sent as a Bearer token on every other call.

#	Method	Path	Description
1.1	POST	`/realms/filter-labs-web/protocol/openid-connect/token`	Log in or refresh a token (Keycloak password and refresh_token grants).

02 Trial Signup & Health

2 endpoints

Create a trial account and check service health. Both calls are served by the signup site (a separate base URL) and need no token.

#	Method	Path	Description
2.1	POST	`/api/v1/signup`	Create a trial / preview account. No token needed; served by the signup site.
2.2	GET	`/health`	Health check for the signup site's backend. No token needed.

03 Search & Locations

3 endpoints

Turn a free-text query into structured entities and look up places.

#	Method	Path	Description
3.1	POST	`/orchestrator/search/unified`	Parse a free-text query into location, topic and entity-type entities. Also the refine loop for the Discover chat.
3.2	GET	`/locations/v1/locations`	Search locations already in Ubiquity by name (not a geocoder). Pages with limit and offset.
3.3	GET	`/locations/v1/locations/{location_uuid}`	Get a location object (may be a synthesized COMBINED-location).

04 Pipelines & Routing

8 endpoints

Pipelines tie a saved search to a feed; routes pass results between pipelines.

#	Method	Path	Description
4.1	GET	`/locations/v1/pipelines`	List pipelines.
4.2	POST	`/locations/v1/pipelines`	Create a pipeline from an existing saved search and feed (step 3 of creation).
4.3	GET	`/locations/v1/pipelines/{pipeline_id}`	Get a pipeline: feed_id, agent_config, discovery_config, search_filters.
4.4	PUT	`/locations/v1/pipelines/{pipeline_id}`	Full update, for example a rename.
4.5	PATCH	`/locations/v1/pipelines/{pipeline_id}`	Update metadata.agent_config and discovery_config. This is the Agent Settings save call; resend the whole metadata object.
4.6	GET	`/locations/v1/pipelines/{pipeline_id}/routes`	List routes (fan-in / fan-out) for a pipeline.
4.7	POST	`/locations/v1/pipelines/{pipeline_id}/routes`	Create a route from this pipeline to a destination pipeline.
4.8	DELETE	`/locations/v1/pipelines/{pipeline_id}/routes/{route_id}`	Delete a route.

05 Sharing & Permissions

4 endpoints

Find who a pipeline can be shared with, and manage who has access.

#	Method	Path	Description
5.1	GET	`/locations/v1/organizations`	List the organizations the current user belongs to.
5.2	GET	`/locations/v1/permissions/organization/{org_uuid}`	List members of an organization: the only valid pipeline-sharing targets.
5.3	GET	`/locations/v1/permissions/pipeline/{pipeline_id}`	List current sharing grants for a pipeline.
5.4	PUT	`/locations/v1/permissions/pipeline/{pipeline_id}/{email}`	Grant an organization member access to a pipeline.

06 Saved Searches & Feeds

11 endpoints

Feeds hold the stream of collected content and its media; metric generators score it.

#	Method	Path	Description
6.1	POST	`/locations/api/v1/feeds`	Create the feed resource (step 2 of pipeline creation).
6.2	GET	`/locations/api/v1/feeds/{feed_id}`	Get a feed, including its refresh interval.
6.3	PUT	`/locations/api/v1/feeds/{feed_id}`	Full update: rename, refresh and detection intervals, review settings. GET first and resend unchanged fields.
6.4	GET	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	List metric generators for a feed.
6.5	POST	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	Create a metric generator.
6.6	PUT	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Edit a metric generator (full PUT only).
6.7	DELETE	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Delete a metric generator.
6.8	GET	`/locations/api/v1/feeds/{feed_id}/stream`	Direct Data Feed API: raw content items for the full corpus, with date, text, entity and URL filters, plus media asset metadata.
6.9	GET	`/locations/api/v1/feeds/{feed_id}/media/{artifact_uuid}/{asset_id}`	Resolve a stored media asset from a stream item to a short-lived presigned download URL.
6.10	POST	`/locations/api/v1/saved-searches`	Persist the parsed query and filters (step 1 of pipeline creation).
6.11	PUT	`/locations/api/v1/saved-searches/{saved_search_id}`	Re-save a pipeline's search query and filters.

07 Entities & Review

8 endpoints

Review, vote on, split and remove the sources and datasets Ubiquity discovers.

#	Method	Path	Description
7.1	POST	`/locations/v1/entity-votes/toggle`	Like, dislike or flag an entity. Repeating the same vote type removes it.
7.2	GET	`/locations/v1/entity-votes/pipeline/{pipeline_id}`	List current votes for a pipeline.
7.3	GET	`/locations/api/v1/feeds/{feed_id}/entities`	List discovered entities (sources and datasets) for a feed, with search, sort and type filters.
7.4	DELETE	`/locations/api/v1/feeds/{feed_id}/entities/{entity_id}`	Remove an entity from a feed (hard delete).
7.5	GET	`/locations/api/v1/entities/{entity_id}/split-preview`	AI-cluster an entity's source URLs by topic, as a preview before splitting. Slow.
7.6	POST	`/locations/api/v1/entities/{entity_id}/split`	Commit a previewed split. Destructive and cross-feed.
7.7	GET	`/locations/api/v1/entities/{entity_id}`	Get a single entity's raw record.
7.8	GET	`/locations/api/v1/source-evaluation-logs/by-url`	Full AI evaluation reasoning for a discovered source, keyed by URL.

08 Import Sources

3 endpoints

Bring your own URLs or behavioral datasets into a feed.

#	Method	Path	Description
8.1	POST	`/locations/api/v1/feeds/{feed_id}/sources/upload`	Import a list of source URLs (plain text or CSV flows). Async, returns 202.
8.2	POST	`/orchestrator/workflows/dataset-upload/trigger`	Import a behavioral dataset (multipart: jsonl, csv or xlsx, up to 25 MB).
8.3	GET	`/orchestrator/workflows/dataset-upload/{job_id}/status`	Poll a dataset upload job: pending, running, completed.

09 Discovery Jobs

7 endpoints

Launch, monitor and cancel agentic discovery work.

#	Method	Path	Description
9.1	POST	`/orchestrator/api/v1/jobs/create`	Launch a discovery job. The only call that actually starts agentic work; optional relative to pipeline creation.
9.2	GET	`/locations/api/v1/jobs/{job_id}`	Poll a job's status and progress.
9.3	PUT	`/locations/api/v1/jobs/{job_id}/status`	Cancel a job (only status=cancelled exercised).
9.4	GET	`/locations/api/v1/jobs`	List jobs across the account.
9.5	GET	`/locations/api/v1/jobs/count`	Total job count.
9.6	GET	`/locations/api/v1/jobs/count/status/{status}`	Job count by status.
9.7	GET	`/orchestrator/jobs/{job_id}/async-status`	Async sub-task progress for a job.

10 Understand

9 endpoints

Per-feed chat with Ubi, plus artifact and metric data for the Data Browser.

#	Method	Path	Description
10.1	GET	`/understand/chat/sessions`	List Ubi chat sessions for a user and feed.
10.2	POST	`/understand/chat/sessions`	Create a chat session (created lazily on first message).
10.3	GET	`/understand/chat/sessions/{session_id}`	Get one session's metadata.
10.4	DELETE	`/understand/chat/sessions/{session_id}`	Delete a chat session.
10.5	GET	`/understand/chat/sessions/{session_id}/messages`	Read a session's message history.
10.6	POST	`/understand/chat/sessions/{session_id}/messages`	Send a message to Ubi. Synchronous: the reply is in the same response. Required field: message.
10.7	GET	`/understand/artifacts/count/{feed_id}`	Count ingested artifacts for a feed. Preferred fast ingestion-progress check.
10.8	POST	`/understand/artifacts/preview`	Fetch artifacts for the Data Browser. Capped at 1000 items regardless of limit.
10.9	POST	`/understand/metrics/preview`	Custom metric time series and per-artifact scores. Slow and uncapped; always scope by date range.