FILTER LABS

Ubiquity API

Detailed Reference

Requests, parameters and response structures from the OpenAPI 3.0.3 specification, v1.7.0

What is in this document

The detailed edition of the Ubiquity API guide: for all 56 operations, the parameters, request body fields, example payloads and response structures, grouped across 6 functional areas.

Overview

The Ubiquity API lets you build discovery pipelines that find and curate sources and entities for a topic and location, then track and refine the resulting feed over time.

56	6	46	3
operations	resource areas	unique paths	service families

Servers

Base URL	Purpose
`https://ubiquity.filterlabs.ai/api`	Main reverse-proxied backend for pipelines, feeds, jobs and search.
`https://auth.filterlabs.ai`	Keycloak authentication server used to obtain and refresh access tokens.
`https://agents.ubiquity.filterlabs.ai`	Self-serve trial signup service.

Authentication

Clients authenticate against the Keycloak server to obtain a Bearer access token, which is sent as an `Authorization: Bearer <token>` header on every request. Access tokens are short-lived and must be refreshed periodically using the refresh token issued at login.

Service families

Prefix	Service	Handles
`/locations`	Locations service	Pipelines, feeds, saved searches, jobs, entities, permissions and organizations.
`/orchestrator`	Orchestrator service	Parses search queries and launches discovery jobs.
`/understand`	Understand service	Conversational chat sessions and generated artifacts.

Conventions

All list endpoints support `limit` and `offset` query parameters for pagination.

Resource identifiers are UUIDs unless otherwise noted.

Status codes in use

Code	Meaning in this API
200	Request succeeded.
201	Resource created.
400	Invalid request or resource not found by a business-logic check.
401	Missing or expired access token.
404	Resource not found.
500	Unexpected server error.

Core workflow

A typical integration parses a query into a saved search, creates a pipeline and feed from it, launches a discovery job, and then polls the job until sources are ready for review.

Step	Method	Endpoint	What it does	Returns	Used by
1	POST	`/orchestrator/search/unified`	Parse a free-text query into entities and a location.	Parsed query	Search setup
2	POST	`/locations/api/v1/saved-searches`	Persist the parsed query and filters.	Saved search id	Pipeline creation
3	POST	`/locations/v1/pipelines`	Create a pipeline from a saved search.	Pipeline object	Pipeline creation
4	POST	`/orchestrator/api/v1/jobs/create`	Launch a discovery job for the pipeline.	Job id	Discovery
5	GET	`/locations/api/v1/jobs/{job_id}`	Poll job status until completion.	Job status/progress	Discovery

Endpoint reference

Methods: GET POST PUT PATCH DELETE. Endpoints are grouped by service below.

01 api

1 endpoint

#	Method	Path	Description
1.1	POST	`/api/v1/signup`	Create a new trial/preview account (agents.ubiquity.filterlabs.ai server only, not the main backend).

1.1 POST `/api/v1/signup`

Create a new trial/preview account (agents.ubiquity.filterlabs.ai server only, not the main backend).

Request body `application/json`

Field	Type	Req	Notes
`email`	string (email)	Yes	
`first_name`	string		optional -- omitted from the request body entirely when left blank, not sent as an empty string
`last_name`	string		optional, same omit-if-blank behavior as first_name

Example

```
{
  "email": "<email>",
  "first_name": "<first_name>",
  "last_name": "<last_name>"
}
```

Responses

200 Not documented yet.

02 health

1 endpoint

#	Method	Path	Description
2.1	GET	`/health`	Health check for the signup site's backend (agents.ubiquity.filterlabs.ai server only).

2.1 GET `/health`

Health check for the signup site's backend (agents.ubiquity.filterlabs.ai server only).

Responses

200 Not documented yet.

03 realms

1 endpoint

#	Method	Path	Description
3.1	POST	`/realms/filter-labs-web/protocol/openid-connect/token`	Login / token refresh (Keycloak ROPC + refresh_token grants)

3.1 POST `/realms/filter-labs-web/protocol/openid-connect/token`

Login / token refresh (Keycloak ROPC + refresh_token grants)

Request body `application/x-www-form-urlencoded`

Field	Type	Req	Notes
`grant_type`	string		One of: `password`, `refresh_token`.
`client_id`	string		
`username`	string		
`password`	string		
`refresh_token`	string		

Example

```
grant_type=<grant_type>
client_id=<client_id>
username=<username>
password=<password>
refresh_token=<refresh_token>
```

Responses

200 access_token (~30min TTL) + refresh_token (~8hr TTL, rotates)

04 orchestrator

5 endpoints

#	Method	Path	Description
4.1	POST	`/orchestrator/search/unified`	Parse a free-text query into LOCATION/TOPIC/entity-type entities.
4.2	POST	`/orchestrator/workflows/dataset-upload/trigger`	Import Sources -- Behavioral Dataset sub-flow.
4.3	GET	`/orchestrator/workflows/dataset-upload/{job_id}/status`	Poll a Behavioral Dataset upload job.
4.4	POST	`/orchestrator/api/v1/jobs/create`	Not documented yet.
4.5	GET	`/orchestrator/jobs/{job_id}/async-status`	Async sub-task progress for a job

4.1 POST `/orchestrator/search/unified`

Parse a free-text query into LOCATION/TOPIC/entity-type entities.

Request body `application/json`

Field	Type	Req	Notes
`query`	string		
`limit`	integer		
`max_new_sources`	integer		
`include_suggestions`	boolean		
`prior_query`	string		REFINE TURNS ONLY: previous turn's query string, verbatim
`prior_entities`	object		REFINE TURNS ONLY: previous turn's parsed_entities object, verbatim
`prior_context`	string		REFINE TURNS ONLY: previous turn's context_report string, verbatim
`session_id`	string		REFINE TURNS ONLY: previous turn's response session_id, verbatim

Example

```
{
  "query": "<query>",
  "limit": 20,
  "max_new_sources": 100,
  "include_suggestions": true,
  "prior_query": "<prior_query>",
  "prior_entities": {},
  "prior_context": "<prior_context>",
  "session_id": "<session_id>"
}
```

Responses

200 existing_sources[], discovery_job_id, parsed_entities{locations,topics,entity_types,persons,organizations,events}, context_report, suggestions[], stats, location{id,name,country,coordinates,bounding_box,is_multi_location,component_locations}, entity_changes{added,removed,modified}, confidence, reasoning, query, session_id

4.2 POST `/orchestrator/workflows/dataset-upload/trigger`

Import Sources -- Behavioral Dataset sub-flow.

Request body `multipart/form-data`

Field	Type	Req	Notes
`dataset_title`	string	Yes	required
`dataset_behavior`	string		optional free-text tag, e.g. 'consumer-spending'
`dataset_unit`	string		optional, e.g. 'Percent of 2019'
`dataset_source_url`	string (uri)		optional
`dataset_description`	string		optional, free text for analysts/Ubi
`dataset_external_id`	string		optional, defaults to auto-generated-from-filename if omitted

Example

```
dataset_title=<dataset_title>
dataset_behavior=<dataset_behavior>
dataset_unit=<dataset_unit>
dataset_source_url=<dataset_source_url>
dataset_description=<dataset_description>
dataset_external_id=<dataset_external_id>
```

Responses

200 job object: {job_id, status: pending, progress: 0.0, dataset_id: null, series_names: [], observations_stored: 0, skipped_rows: 0, warnings: [], error: null, created_at, updated_at, completed_at: null}

4.3 GET `/orchestrator/workflows/dataset-upload/{job_id}/status`

Poll a Behavioral Dataset upload job.

Parameters

Name	In	Type	Req	Notes
`job_id`	path	string	Yes	

Responses

200 same shape as trigger's response; on completion: dataset_id populated, series_names derived from the file's non-date column header(s), observations_stored/skipped_rows/warnings populated

4.4 POST `/orchestrator/api/v1/jobs/create`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`location_uuid`	string		
`job_type`	string		
`parameters`	object		
`parameters.search_query`	string		
`parameters.parsed_entities`	array of object		
`parameters.feed_id`	integer		
`parameters.pipeline_id`	string		
`parameters.vote_context`	object		
`parameters.vote_context.liked_entities`	array of object		
`parameters.vote_context.liked_entities[].name`	string		
`parameters.vote_context.liked_entities[].type`	string		
`parameters.vote_context.disliked_entities`	array of object		
`max_queries`	integer		
`max_sources`	integer		
`min_sources`	integer		

Example

```
{
  "location_uuid": "<location_uuid>",
  "job_type": "discovery",
  "parameters": {
    "search_query": "<search_query>",
    "parsed_entities": [
      {}
    ],
    "feed_id": 0,
    "pipeline_id": "<pipeline_id>",
    "vote_context": {
      "liked_entities": [
        {
          "name": "<name>",
          "type": "<type>"
        }
      ],
      "disliked_entities": [
        {}
      ]
    }
  },
  "max_queries": 0,
  "max_sources": 0,
  "min_sources": 0
}
```

Responses

200 job object: id, status=pending, progress=0

4.5 GET `/orchestrator/jobs/{job_id}/async-status`

Async sub-task progress for a job

Parameters

Name	In	Type	Req	Notes
`job_id`	path	string	Yes	

Responses

200 {job_id, pending_count, processed_count, failed_count, total_count, all_complete, has_async_work, snapshots}

05 locations

39 endpoints

#	Method	Path	Description
5.1	GET	`/locations/v1/pipelines`	List pipelines
5.2	POST	`/locations/v1/pipelines`	Not documented yet.
5.3	GET	`/locations/v1/pipelines/{pipeline_id}`	Get a pipeline (feed_id, agent_config, discovery_config, search_filters)
5.4	PUT	`/locations/v1/pipelines/{pipeline_id}`	Full update, e.g.
5.5	PATCH	`/locations/v1/pipelines/{pipeline_id}`	Not documented yet.
5.6	GET	`/locations/v1/pipelines/{pipeline_id}/routes`	List pipeline routes (fan-in/fan-out)
5.7	POST	`/locations/v1/pipelines/{pipeline_id}/routes`	Create a route from this (source) pipeline to a destination pipeline
5.8	DELETE	`/locations/v1/pipelines/{pipeline_id}/routes/{route_id}`	Delete a route
5.9	POST	`/locations/v1/entity-votes/toggle`	Like / dislike / flag an entity (true toggle -- repeating the same vote_type un-votes it)
5.10	GET	`/locations/v1/entity-votes/pipeline/{pipeline_id}`	List current votes for a pipeline
5.11	GET	`/locations/api/v1/feeds/{feed_id}/entities`	List discovered entities (sources/datasets) for a feed.
5.12	DELETE	`/locations/api/v1/feeds/{feed_id}/entities/{entity_id}`	Remove an entity from a feed (hard delete)
5.13	GET	`/locations/api/v1/entities/{entity_id}/split-preview`	AI-cluster an entity's source URLs by apparent topic, as a preview before splitting.
5.14	POST	`/locations/api/v1/entities/{entity_id}/split`	DESTRUCTIVE, cross-feed: commit a split previewed above.
5.15	GET	`/locations/api/v1/entities/{entity_id}`	Get a single entity's raw record (location, metadata as base64, timestamps)
5.16	GET	`/locations/api/v1/source-evaluation-logs/by-url`	Full free-text AI evaluation reasoning for a discovered source, keyed by its URL
5.17	POST	`/locations/api/v1/feeds/{feed_id}/sources/upload`	Import Sources -- Plain Text and CSV Upload sub-flows (both hit this one endpoint, differing only in payload shape).
5.18	GET	`/locations/api/v1/jobs/{job_id}`	Poll a job's status/progress
5.19	PUT	`/locations/api/v1/jobs/{job_id}/status`	Cancel a job (only status=cancelled exercised)

#	Method	Path	Description
5.20	GET	`/locations/api/v1/jobs`	List jobs across the account
5.21	GET	`/locations/api/v1/jobs/count`	Total job count
5.22	GET	`/locations/api/v1/jobs/count/status/{status}`	Job count by status
5.23	POST	`/locations/api/v1/feeds`	Not documented yet.
5.24	GET	`/locations/api/v1/feeds/{feed_id}`	Get feed (refresh_interval as human string, e.g.
5.25	PUT	`/locations/api/v1/feeds/{feed_id}`	Not documented yet.
5.26	GET	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	List metric generators for a feed (null if none)
5.27	POST	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	Not documented yet.
5.28	PUT	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Not documented yet.
5.29	DELETE	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Delete a metric generator
5.30	GET	`/locations/api/v1/feeds/{feed_id}/stream`	Not documented yet.
5.31	GET	`/locations/api/v1/feeds/{feed_id}/media/{artifact_uuid}/{asset_id}`	Media retrieval -- resolves a stream item's media_assets entry (status=stored only) to a short-lived presigned download URL.
5.32	GET	`/locations/v1/locations`	Free-text location/POI search over EXISTING locations in Ubiquity's own database only (not a geocoder, not a curated country/region list; won't surface a place that hasn't been added via the unifie...
5.33	GET	`/locations/v1/locations/{location_uuid}`	Get a (possibly synthesized COMBINED-) location object
5.34	POST	`/locations/api/v1/saved-searches`	Not documented yet.
5.35	PUT	`/locations/api/v1/saved-searches/{saved_search_id}`	Re-save the pipeline's saved search_query/search_filters (fired as part of the coverage-level launch sequence)
5.36	GET	`/locations/v1/organizations`	List organizations the current user belongs to.
5.37	GET	`/locations/v1/permissions/organization/{org_uuid}`	List members of an organization, i.e.
5.38	GET	`/locations/v1/permissions/pipeline/{pipeline_id}`	List current sharing grants for a pipeline.
5.39	PUT	`/locations/v1/permissions/pipeline/{pipeline_id}/{email}`	Grant a specific org member access to a pipeline.

5.1 GET `/locations/v1/pipelines`

List pipelines

Parameters

Name	In	Type	Req	Notes
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.
`order_by`	query	string		
`order`	query	string		One of: `ASC`, `DESC`.
`saved_search_id`	query	string		

Responses

200 array of pipeline objects

5.2 POST `/locations/v1/pipelines`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`name`	string		
`saved_search_id`	string		id from the preceding saved-searches POST
`feed_id`	integer		id from the preceding feeds POST
`auto_sync_enabled`	boolean		Default: `true`.
`sync_on_job_completion`	boolean		Default: `true`.
`sync_on_map_change`	boolean		Default: `false`.
`session_id`	string		session_id from the originating /search/unified response

Example

```
{
  "name": "<name>",
  "saved_search_id": "<saved_search_id>",
  "feed_id": 0,
  "auto_sync_enabled": true,
  "sync_on_job_completion": true,
  "sync_on_map_change": false,
  "session_id": "<session_id>"
}
```

Responses

201 pipeline object: id, feed_id, saved_search_id, session_id, auto_sync_enabled, sync_on_job_completion, sync_on_map_change, metadata (empty {} until the discovery_config PATCH below), created_at, updated_at

5.3 GET `/locations/v1/pipelines/{pipeline_id}`

Get a pipeline (feed_id, agent_config, discovery_config, search_filters)

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Responses

200 pipeline object

5.4 PUT `/locations/v1/pipelines/{pipeline_id}`

Full update, e.g.

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Responses

200 updated pipeline

5.5 PATCH `/locations/v1/pipelines/{pipeline_id}`

Not documented yet.

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Request body `application/json`

Field	Type	Req	Notes
`metadata`	object		
`metadata.agent_config`	object		
`metadata.agent_config.search_generation`	object		
`metadata.agent_config.search_generation.max_queries`	integer		Range 5 to 50.
`metadata.agent_config.search_generation.creativity_level`	string		One of: `low`, `medium`, `high`.
`metadata.agent_config.search_generation.focus_types`	array of string		
`metadata.agent_config.search_generation.language_preference`	string		One of: `native_first`, `mixed`, `english_first`.
`metadata.agent_config.search_generation.custom_instructions`	string		Not documented yet.
`metadata.agent_config.evaluation`	object		
`metadata.agent_config.evaluation.credibility_threshold`	number		Range 0 to 1.
`metadata.agent_config.evaluation.local_focus_priority`	string		One of: `low`, `medium`, `high`.
`metadata.agent_config.evaluation.quality_standards`	string		One of: `lenient`, `moderate`, `strict`.
`metadata.agent_config.evaluation.topic_relevance_weight`	number		Range 0 to 1.
`metadata.agent_config.datasets_discovery`	object		
`metadata.agent_config.datasets_discovery.enable_dataset_hunting`	boolean		
`metadata.agent_config.datasets_discovery.providers`	array of string		
`metadata.discovery_config`	object		
`metadata.discovery_config.max_queries`	integer		
`metadata.discovery_config.max_sources`	integer		
`metadata.discovery_config.min_sources`	integer		

Example


```
{
  "metadata": {
    "agent_config": {
      "search_generation": {
        "max_queries": 0,
        "creativity_level": "low",
        "focus_types": [
          "news"
        ],
        "language_preference": "native_first",
        "custom_instructions": "<custom_instructions>"
      },
      "evaluation": {
        "credibility_threshold": 0.5,
        "local_focus_priority": "low",
        "quality_standards": "lenient",
        "topic_relevance_weight": 0.5
      },
      "datasets_discovery": {
        "enable_dataset_hunting": true,
        "providers": [
          "fred"
        ]
      }
    },
    "discovery_config": {
      "max_queries": 0,
      "max_sources": 0,
      "min_sources": 0
    }
  }
}
```


Responses

200 full updated pipeline object

5.6 GET `/locations/v1/pipelines/{pipeline_id}/routes`

List pipeline routes (fan-in/fan-out)

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Responses

200 array, each with source/destination_pipeline_name + feed_id denormalized

5.7 POST `/locations/v1/pipelines/{pipeline_id}/routes`

Create a route from this (source) pipeline to a destination pipeline

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Request body `application/json`

Field	Type	Req	Notes
`destination_pipeline_id`	string		
`filter_mode`	string		Not documented yet. Default: `all`.
`filter_config`	object		Not documented yet. Default: `{}`.

Example

```
{
  "destination_pipeline_id": "<destination_pipeline_id>",
  "filter_mode": "all",
  "filter_config": {}
}
```

Responses

201 route object: id, source_pipeline_id, destination_pipeline_id, enabled, filter_mode, filter_config

5.8 DELETE `/locations/v1/pipelines/{pipeline_id}/routes/{route_id}`

Delete a route

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	
`route_id`	path	string	Yes	

Responses

204 empty

5.9 POST `/locations/v1/entity-votes/toggle`

Like / dislike / flag an entity (true toggle -- repeating the same vote_type un-votes it)

Request body `application/json`

Field	Type	Req	Notes
`entity_id`	integer		
`pipeline_id`	string		
`keycloak_user_id`	string		Keycloak user UUID (JWT 'sub' claim), NOT the email
`vote_type`	string		One of: `like`, `dislike`, `flag`.

Example

```
{
  "entity_id": 0,
  "pipeline_id": "<pipeline_id>",
  "keycloak_user_id": "<keycloak_user_id>",
  "vote_type": "like"
}
```

Responses

200 {action: created|removed, vote: {...}}

201 {action: created, vote: {...}}

5.10 GET `/locations/v1/entity-votes/pipeline/{pipeline_id}`

List current votes for a pipeline

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	
`limit`	query	integer		Page size for list results.

Responses

200 array of vote objects, [] if none

5.11 GET `/locations/api/v1/feeds/{feed_id}/entities`

List discovered entities (sources/datasets) for a feed.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.
`q`	query	string		
`order_by`	query	string		One of: `vote`, `name`, `type`, `created_at`.
`order`	query	string		One of: `asc`, `desc`.
`type`	query	string		One of: `all`, `sources`, `datasets`.

Responses

200 {entities[], total, dataset_count, source_count}

5.12 DELETE `/locations/api/v1/feeds/{feed_id}/entities/{entity_id}`

Remove an entity from a feed (hard delete)

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	
`entity_id`	path	integer	Yes	

Responses

200 {message: 'Entity removed from feed successfully'}

5.13 GET `/locations/api/v1/entities/{entity_id}/split-preview`

AI-cluster an entity's source URLs by apparent topic, as a preview before splitting.

Parameters

Name	In	Type	Req	Notes
`entity_id`	path	integer	Yes	

Responses

200 {entity_id, entity_name, total_sources, groups: [{group_name, source_count, source_ids[], urls[], is_keeper}], discarded_urls[], feeds_affected[]}. is_keeper does NOT reliably land on the semantically-matching group -- inspect per call.

5.14 POST `/locations/api/v1/entities/{entity_id}/split`

DESTRUCTIVE, cross-feed: commit a split previewed above.

Parameters

Name	In	Type	Req	Notes
`entity_id`	path	integer	Yes	

Request body `application/json`

Field	Type	Req	Notes
`groups`	array of object		same groups the preview returned, trimmed to just group_name+source_ids
`groups[].group_name`	string		
`groups[].source_ids`	array of integer		

Example

```
{
  "groups": [
    {
      "group_name": "<group_name>",
      "source_ids": [
        0
      ]
    }
  ]
}
```

Responses

200 {original_entity_id, original_entity_sources_kept, new_entities: [{id, uuid, name, source_count}], discarded_urls[], feeds_linked[]}

5.15 GET `/locations/api/v1/entities/{entity_id}`

Get a single entity's raw record (location, metadata as base64, timestamps)

Parameters

Name	In	Type	Req	Notes
`entity_id`	path	integer	Yes	

Responses

200 entity object

5.16 GET `/locations/api/v1/source-evaluation-logs/by-url`

Full free-text AI evaluation reasoning for a discovered source, keyed by its URL

Parameters

Name	In	Type	Req	Notes
`url`	query	string	Yes	

Responses

200 {id, credibility_score, local_focus, quality, evaluation_details:{type,title,evaluation_notes,...}}

5.17 POST `/locations/api/v1/feeds/{feed_id}/sources/upload`

Import Sources -- Plain Text and CSV Upload sub-flows (both hit this one endpoint, differing only in payload shape).

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	

Request body `application/json`

Field	Type	Req	Notes
`skip_validation`	boolean		
`location_uuid`	string		
`urls`	array of string		Plain Text sub-flow: array of raw URL strings
`urls_with_metadata`	array of object		CSV Upload sub-flow: array of {url, name?} objects, mutually exclusive with urls
`urls_with_metadata[].url`	string		
`urls_with_metadata[].name`	string		

Example

```
{
  "skip_validation": true,
  "location_uuid": "<location_uuid>",
  "urls": [
    "<urls>"
  ],
  "urls_with_metadata": [
    {
      "url": "<url>",
      "name": "<name>"
    }
  ]
}
```

Responses

202 {job_id, feed_id, url_count, valid_urls, invalid_urls, status: processing, message}

5.18 GET `/locations/api/v1/jobs/{job_id}`

Poll a job's status/progress

Parameters

Name	In	Type	Req	Notes
`job_id`	path	string	Yes	

Responses

200 {id, status: pending|running|completed|failed|cancelled, progress (0-100), job_type, result_data, pipeline_id}

5.19 PUT `/locations/api/v1/jobs/{job_id}/status`

Cancel a job (only status=cancelled exercised)

Parameters

Name	In	Type	Req	Notes
`job_id`	path	string	Yes	

Request body `application/json`

Field	Type	Req	Notes
`status`	string		

Example

```
{
  "status": "cancelled"
}
```

Responses

200 job echoed with status=cancelled, completed_at set

5.20 GET `/locations/api/v1/jobs`

List jobs across the account

Parameters

Name	In	Type	Req	Notes
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.

Responses

200 array of job objects

5.21 GET /locations/api/v1/jobs/count

Total job count

Responses

200 {count}

5.22 GET /locations/api/v1/jobs/count/status/{status}

Job count by status

Parameters

Name	In	Type	Req	Notes
`status`	path	string	Yes	One of: `pending`, `running`, `completed`, `failed`, `cancelled`.

Responses

200 {count}

5.23 POST /locations/api/v1/feeds

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`name`	string		
`metadata`	object		
`metadata.description`	string		
`metadata.search_query`	string		

Example

```
{
  "name": "<name>",
  "metadata": {
    "description": "Feed for search: <query text>",
    "search_query": "<search_query>"
  }
}
```

Responses

201 feed object: id (numeric, this is feed_id for the pipelines POST), uuid, name, refresh_interval{Microseconds,Days,Months,Valid=false until set}, metadata (base64), keycloak_user_id, created_at, updated_at

5.24 GET /locations/api/v1/feeds/{feed_id}

Get feed (refresh_interval as human string, e.g.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	

Responses

200 feed object

5.25 PUT `/locations/api/v1/feeds/{feed_id}`

Not documented yet.

Parameters

Name	In	Type	Req	Notes
feed_id	path	integer	Yes	

Request body `application/json`

Field	Type	Req	Notes
name	string		must be re-sent, this is a full PUT not a partial PATCH
refresh_interval_minutes	integer		0=Do Not Update, 720=12h, 1440=Daily, 2880=Every 2 Days, 10080=Weekly, ~43200=Monthly
deletion_detection_interval_minutes	integer		Not documented yet.
engagement_detection_interval_minutes	integer		Not documented yet.
automatic_entity_rediscovery_interval_minutes	integer		Not documented yet.
force_review_for_auto_discover	boolean		Not documented yet.
backdate_limit	integer		Not documented yet.

Example

```
{
  "name": "<name>",
  "refresh_interval_minutes": 0,
  "deletion_detection_interval_minutes": 0,
  "engagement_detection_interval_minutes": 0,
  "automatic_entity_rediscovery_interval_minutes": 0,
  "force_review_for_auto_discover": true,
  "backdate_limit": 0
}
```

Responses

200 feed with refresh_interval{Microseconds,Days,Months,Valid} struct (same struct shape for every *_interval field above), refreshed_at

5.26 GET `/locations/api/v1/feeds/{feed_id}/metric_prompts`

List metric generators for a feed (null if none)

Parameters

Name	In	Type	Req	Notes
feed_id	path	integer	Yes	

Responses

200 array or null

5.27 POST `/locations/api/v1/feeds/{feed_id}/metric_prompts`

Not documented yet.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	

Request body `application/json`

Field	Type	Req	Notes
`feed_id`	integer		
`name`	string		
`metric_name`	string		client-generated slug of name
`prompt`	string		
`active`	boolean		
`filter_prompt`	string		Not documented yet. May be null.
`filter_distance`	number		Not documented yet. May be null.

Example

```
{
  "feed_id": 0,
  "name": "<name>",
  "metric_name": "<metric_name>",
  "prompt": "<prompt>",
  "active": true,
  "filter_prompt": "<filter_prompt>",
  "filter_distance": 0.5
}
```

Responses

200 metric prompt object: id, feed_id, name, metric_name, prompt, filter_prompt, filter_distance, active, created_at, updated_at

5.28 PUT `/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`

Not documented yet.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	
`metric_id`	path	string	Yes	

Responses

200 updated metric prompt object

5.29 DELETE /locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}

Delete a metric generator

Parameters

Name	In	Type	Req	Notes
feed_id	path	integer	Yes	
metric_id	path	string	Yes	

Responses

204 empty

5.30 GET /locations/api/v1/feeds/{feed_id}/stream

Not documented yet.

Parameters

Name	In	Type	Req	Notes
feed_id	path	integer	Yes	feed_id
limit	query	integer		Page size for list results. Range 1 to 1000. Default: 100.
cursor	query	string		Opaque cursor for cursor-based pagination: base64-encoded JSON payload, returned as 'next_cursor' in the response's pagination object. Pass back verbatim to fetch the next page -- do not decode/construct it yourself.
order_by	query	string		published_at can be null (no usable date on the artifact, or unparseable); items with a null published_at are silently skipped by default ordering. scraped_at is set by the scraper at ingest time and is never null. Use order_by=scraped_at to retrieve every artifact in the feed; the default published_at ordering does not guarantee completeness. One of: published_at, scraped_at. Default: published_at.
content_max_length	query	integer		Range 0 to 10000. Default: 500.
include_vectors	query	string		
date_from	query	string		Start date filter -- exclusive (RFC3339 or YYYY-MM-DD)
date_to	query	string		End date filter -- inclusive (RFC3339 or YYYY-MM-DD)
text_search	query	string		
entity_ids	query	string		
entity_types	query	string		
urls	query	string		

Responses

200 Not documented yet.

5.31 GET `/locations/api/v1/feeds/{feed_id}/media/{artifact_uuid}/{asset_id}`

Media retrieval -- resolves a stream item's media_assets entry (status=stored only) to a short-lived presigned download URL.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	feed_id (required -- validates the artifact belongs to this feed; wrong feed_id 404s with 'Artifact not found', nonexistent feed_id 400s with 'Feed not found')
`artifact_uuid`	path	string	Yes	the stream item's own uuid field (NOT entity_id)
`asset_id`	path	string	Yes	the media_assets entry's asset_id

Responses

200 {asset_id, kind, mime, bytes, url (presigned S3 GET URL, ~5 min TTL per X-Amz-Expires), expires_at}. The returned url requires no further auth and serves the raw file bytes directly.

404 {error: 'Media not found'} when the asset's status is failed/unavailable_logged_out (only status=stored is servable), or {error: 'Artifact not found'} when the artifact_uuid doesn't belong to the given feed_id

400 {error: 'Feed not found'} when feed_id doesn't exist

5.32 GET `/locations/v1/locations`

Free-text location/POI search over EXISTING locations in Ubiquity's own database only (not a geocoder, not a curated country/region list; won't surface a place that hasn't been added via the unifie...

Parameters

Name	In	Type	Req	Notes
`q`	query	string	Yes	
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.

Responses

200 double-nested envelope: {data: {data: [...]}}, array of location matches

5.33 GET `/locations/v1/locations/{location_uuid}`

Get a (possibly synthesized COMBINED-) location object

Parameters

Name	In	Type	Req	Notes
`location_uuid`	path	string	Yes	

Responses

200 {id, name, abbreviation, country, coordinates, bounding_box}

5.34 POST `/locations/api/v1/saved-searches`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`name`	string		query text, used as the default pipeline name
`search_query`	string		same query text
`search_filters`	object		
`search_filters.entities`	array of object		flattened parsed_entities.locations + .topics + .entity_types from the preceding /search/unified response, each entry's value/type/confidence/normalized_value/aliases/metadata/languages kept verbatim
`search_filters.location_uuid`	string		location.id from /search/unified

Example

```
{
  "name": "<name>",
  "search_query": "<search_query>",
  "search_filters": {
    "entities": [
      {}
    ],
    "location_uuid": "<location_uuid>"
  }
}
```

Responses

201 saved-search object: id (this is saved_search_id for the pipelines POST), name, search_query, search_filters, is_default, created_at, updated_at

5.35 PUT `/locations/api/v1/saved-searches/{saved_search_id}`

Re-save the pipeline's saved search_query/search_filters (fired as part of the coverage-level launch sequence)

Parameters

Name	In	Type	Req	Notes
`saved_search_id`	path	string	Yes	

Responses

200 updated saved-search object

5.36 GET `/locations/v1/organizations`

List organizations the current user belongs to.

Responses

200 array of {name, uuid, licensed_seats} -- most accounts see exactly one org

5.37 GET `/locations/v1/permissions/organization/{org_uuid}`

List members of an organization, i.e.

Parameters

Name	In	Type	Req	Notes
`org_uuid`	path	string	Yes	

Responses

200 array of {ability, keycloak_user_id} -- despite the key name, keycloak_user_id here is the member's EMAIL, not a UUID; ability reflects an org-level default/baseline, not per-pipeline access

5.38 GET `/locations/v1/permissions/pipeline/{pipeline_id}`

List current sharing grants for a pipeline.

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	

Responses

200 array of {ability, keycloak_user_id} (email), same shape as the organization members endpoint

5.39 PUT `/locations/v1/permissions/pipeline/{pipeline_id}/{email}`

Grant a specific org member access to a pipeline.

Parameters

Name	In	Type	Req	Notes
`pipeline_id`	path	string	Yes	
`email`	path	string	Yes	target user's email, sent as a plain (not URL-encoded) path segment

Request body `application/json`

Field	Type	Req	Notes
`ability`	string		Not documented yet.

Example

```
{
  "ability": "write"
}
```

Responses

200 OK

06 understand

9 endpoints

#	Method	Path	Description
6.1	GET	`/understand/chat/sessions`	List Ubi chat sessions for a user+feed
6.2	POST	`/understand/chat/sessions`	Create a chat session (fires lazily on first message, not on 'New Chat' click)
6.3	GET	`/understand/chat/sessions/{session_id}`	Get one session's metadata
6.4	DELETE	`/understand/chat/sessions/{session_id}`	Not documented yet.
6.5	GET	`/understand/chat/sessions/{session_id}/messages`	Read message history for a session
6.6	POST	`/understand/chat/sessions/{session_id}/messages`	Not documented yet.
6.7	GET	`/understand/artifacts/count/{feed_id}`	Count ingested artifacts for a feed.
6.8	POST	`/understand/artifacts/preview`	Not documented yet.
6.9	POST	`/understand/metrics/preview`	Not documented yet.

6.1 GET `/understand/chat/sessions`

List Ubi chat sessions for a user+feed

Parameters

Name	In	Type	Req	Notes
`keycloak_user_id`	query	string	Yes	the account EMAIL here, not the Keycloak UUID -- opposite convention from entity-votes/toggle
`feed_id`	query	integer	Yes	
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.

Responses

200 [] or array of session objects with filter_state auto-derived from the first message

6.2 POST `/understand/chat/sessions`

Create a chat session (fires lazily on first message, not on 'New Chat' click)

Responses

200 session object: id, feed_id, title, filter_state{topics,entities,dateRange,siteTypes,metricName,textSearch,entityTypes}

6.3 GET `/understand/chat/sessions/{session_id}`

Get one session's metadata

Parameters

Name	In	Type	Req	Notes
`session_id`	path	string	Yes	
`keycloak_user_id`	query	string	Yes	

Responses

200 session object

6.4 DELETE `/understand/chat/sessions/{session_id}`

Not documented yet.

Parameters

Name	In	Type	Req	Notes
`session_id`	path	string	Yes	

Responses

200 {status: 'deleted', session_id}

6.5 GET `/understand/chat/sessions/{session_id}/messages`

Read message history for a session

Parameters

Name	In	Type	Req	Notes
`session_id`	path	string	Yes	
`keycloak_user_id`	query	string	Yes	
`limit`	query	integer		Page size for list results.
`offset`	query	integer		Number of results to skip, for pagination.

Responses

200 array: {id, session_id, role, content, citations[{id,url,score,title}], chart{type,title,config}, created_at}

6.6 POST `/understand/chat/sessions/{session_id}/messages`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`message`	string	Yes	Not documented yet.

Example

```
{
  "message": "<message>"
}
```

Responses

200 Not documented yet.

6.7 GET `/understand/artifacts/count/{feed_id}`

Count ingested artifacts for a feed.

Parameters

Name	In	Type	Req	Notes
`feed_id`	path	integer	Yes	

Responses

200 {count, feed_id}

6.8 POST `/understand/artifacts/preview`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`feed_id`	integer		
`filter_state`	object		
`filter_state.dateRange`	object		
`filter_state.dateRange.start`	string (date)		
`filter_state.dateRange.end`	string (date)		
`filter_state.topics`	array		May be null.
`filter_state.entities`	array		May be null.
`filter_state.siteTypes`	array of string		
`filter_state.metricName`	string		May be null.
`filter_state.textSearch`	string		May be null.
`filter_state.entityTypes`	array		May be null.
`limit`	integer		Not documented yet.

Example

```
{
  "feed_id": 0,
  "filter_state": {
    "dateRange": {
      "start": "YYYY-MM-DD",
      "end": "YYYY-MM-DD"
    },
    "topics": [],
    "entities": [],
    "siteTypes": [
      "<siteTypes>"
    ],
    "metricName": "<metricName>",
    "textSearch": "<textSearch>",
    "entityTypes": []
  },
  "limit": 0
}
```

Responses

200 {artifacts: [{id, headline, url, site_type, published_at, content_sample, score}], total_count}

500 'Collection <email> doesn't exist' -- normal/expected before any artifacts have been ingested yet, not a real error

6.9 POST `/understand/metrics/preview`

Not documented yet.

Request body `application/json`

Field	Type	Req	Notes
`feed_id`	integer		
`filter_state`	object		
`filter_state.metricName`	string		
`filter_state.dateRange`	object		
`filter_state.dateRange.start`	string (date)		
`filter_state.dateRange.end`	string (date)		

Example

```
{
  "feed_id": 0,
  "filter_state": {
    "metricName": "<metricName>",
    "dateRange": {
      "start": "YYYY-MM-DD",
      "end": "YYYY-MM-DD"
    }
  }
}
```

Responses

200 {data: [{artifact_uuid, score, list}], series: [{bucket, score}], total_count, filter_applied}