Ubiquity API

Product Overview

Endpoint guide generated from the OpenAPI 3.0.3 specification, v1.7.0

What is in this document

A guided tour of the Ubiquity API: how to authenticate, how the core workflow runs, and a reference of all 56 operations across 6 functional areas.

Overview

The Ubiquity API lets you build discovery pipelines that find and curate sources and entities for a topic and location, then track and refine the resulting feed over time.

56	6	46	3
operations	resource areas	unique paths	service families

Servers

Base URL	Purpose
`https://ubiquity.filterlabs.ai/api`	Main reverse-proxied backend for pipelines, feeds, jobs and search.
`https://auth.filterlabs.ai`	Keycloak authentication server used to obtain and refresh access tokens.
`https://agents.ubiquity.filterlabs.ai`	Self-serve trial signup service.

Authentication

Clients authenticate against the Keycloak server to obtain a Bearer access token, which is sent as an `Authorization: Bearer <token>` header on every request. Access tokens are short-lived and must be refreshed periodically using the refresh token issued at login.

Service families

Prefix	Service	Handles
`/locations`	Locations service	Pipelines, feeds, saved searches, jobs, entities, permissions and organizations.
`/orchestrator`	Orchestrator service	Parses search queries and launches discovery jobs.
`/understand`	Understand service	Conversational chat sessions and generated artifacts.

Conventions

All list endpoints support `limit` and `offset` query parameters for pagination.

Core workflow

A typical integration parses a query into a saved search, creates a pipeline and feed from it, launches a discovery job, and then polls the job until sources are ready for review.

Step	Method	Endpoint	What it does
1	POST	`/orchestrator/search/unified`	Parse a free-text query into entities and a location.
2	POST	`/locations/api/v1/saved-searches`	Persist the parsed query and filters.
3	POST	`/locations/v1/pipelines`	Create a pipeline from a saved search.
4	POST	`/orchestrator/api/v1/jobs/create`	Launch a discovery job for the pipeline.
5	GET	`/locations/api/v1/jobs/{job_id}`	Poll job status until completion.

Endpoint reference

Methods: GET POST PUT PATCH DELETE

01 api

1 endpoint

#	Method	Path	Description
1.1	POST	`/api/v1/signup`	Create a new trial/preview account (agents.ubiquity.filterlabs.ai server only, not the main backend).

02 health

1 endpoint

#	Method	Path	Description
2.1	GET	`/health`	Health check for the signup site's backend (agents.ubiquity.filterlabs.ai server only).

03 realms

1 endpoint

#	Method	Path	Description
3.1	POST	`/realms/filter-labs-web/protocol/openid-connect/token`	Login / token refresh (Keycloak ROPC + refresh_token grants)

04 orchestrator

5 endpoints

#	Method	Path	Description
4.1	POST	`/orchestrator/search/unified`	Parse a free-text query into LOCATION/TOPIC/entity-type entities.
4.2	POST	`/orchestrator/workflows/dataset-upload/trigger`	Import Sources -- Behavioral Dataset sub-flow.
4.3	GET	`/orchestrator/workflows/dataset-upload/{job_id}/status`	Poll a Behavioral Dataset upload job.
4.4	POST	`/orchestrator/api/v1/jobs/create`	Not documented yet.
4.5	GET	`/orchestrator/jobs/{job_id}/async-status`	Async sub-task progress for a job

05 locations

39 endpoints

#	Method	Path	Description
5.1	GET	`/locations/v1/pipelines`	List pipelines
5.2	POST	`/locations/v1/pipelines`	Not documented yet.
5.3	GET	`/locations/v1/pipelines/{pipeline_id}`	Get a pipeline (feed_id, agent_config, discovery_config, search_filters)
5.4	PUT	`/locations/v1/pipelines/{pipeline_id}`	Full update, e.g.
5.5	PATCH	`/locations/v1/pipelines/{pipeline_id}`	Not documented yet.
5.6	GET	`/locations/v1/pipelines/{pipeline_id}/routes`	List pipeline routes (fan-in/fan-out)
5.7	POST	`/locations/v1/pipelines/{pipeline_id}/routes`	Create a route from this (source) pipeline to a destination pipeline
5.8	DELETE	`/locations/v1/pipelines/{pipeline_id}/routes/{route_id}`	Delete a route
5.9	POST	`/locations/v1/entity-votes/toggle`	Like / dislike / flag an entity (true toggle -- repeating the same vote_type un-votes it)
5.10	GET	`/locations/v1/entity-votes/pipeline/{pipeline_id}`	List current votes for a pipeline
5.11	GET	`/locations/api/v1/feeds/{feed_id}/entities`	List discovered entities (sources/datasets) for a feed.
5.12	DELETE	`/locations/api/v1/feeds/{feed_id}/entities/{entity_id}`	Remove an entity from a feed (hard delete)
5.13	GET	`/locations/api/v1/entities/{entity_id}/split-preview`	AI-cluster an entity's source URLs by apparent topic, as a preview before splitting.
5.14	POST	`/locations/api/v1/entities/{entity_id}/split`	DESTRUCTIVE, cross-feed: commit a split previewed above.
5.15	GET	`/locations/api/v1/entities/{entity_id}`	Get a single entity's raw record (location, metadata as base64, timestamps)
5.16	GET	`/locations/api/v1/source-evaluation-logs/by-url`	Full free-text AI evaluation reasoning for a discovered source, keyed by its URL
5.17	POST	`/locations/api/v1/feeds/{feed_id}/sources/upload`	Import Sources -- Plain Text and CSV Upload sub-flows (both hit this one endpoint, differing only in payload shape).
5.18	GET	`/locations/api/v1/jobs/{job_id}`	Poll a job's status/progress
5.19	PUT	`/locations/api/v1/jobs/{job_id}/status`	Cancel a job (only status=cancelled exercised)
5.20	GET	`/locations/api/v1/jobs`	List jobs across the account
5.21	GET	`/locations/api/v1/jobs/count`	Total job count
5.22	GET	`/locations/api/v1/jobs/count/status/{status}`	Job count by status
5.23	POST	`/locations/api/v1/feeds`	Not documented yet.
5.24	GET	`/locations/api/v1/feeds/{feed_id}`	Get feed (refresh_interval as human string, e.g.
5.25	PUT	`/locations/api/v1/feeds/{feed_id}`	Not documented yet.
5.26	GET	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	List metric generators for a feed (null if none)
5.27	POST	`/locations/api/v1/feeds/{feed_id}/metric_prompts`	Not documented yet.
5.28	PUT	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Not documented yet.

5.29	DELETE	`/locations/api/v1/feeds/{feed_id}/metric_prompts/{metric_id}`	Delete a metric generator
5.30	GET	`/locations/api/v1/feeds/{feed_id}/stream`	Not documented yet.
5.31	GET	`/locations/api/v1/feeds/{feed_id}/media/{artifact_uuid}/{asset_id}`	Media retrieval -- resolves a stream item's media_assets entry (status=stored only) to a short-lived presigned download URL.
5.32	GET	`/locations/v1/locations`	Free-text location/POI search over EXISTING locations in Ubiquity's own database only (not a geocoder, not a curated country/region list; won't surface a place that hasn't been added via the unifie...
5.33	GET	`/locations/v1/locations/{location_uuid}`	Get a (possibly synthesized COMBINED-) location object
5.34	POST	`/locations/api/v1/saved-searches`	Not documented yet.
5.35	PUT	`/locations/api/v1/saved-searches/{saved_search_id}`	Re-save the pipeline's saved search_query/search_filters (fired as part of the coverage-level launch sequence)
5.36	GET	`/locations/v1/organizations`	List organizations the current user belongs to.
5.37	GET	`/locations/v1/permissions/organization/{org_uuid}`	List members of an organization, i.e.
5.38	GET	`/locations/v1/permissions/pipeline/{pipeline_id}`	List current sharing grants for a pipeline.
5.39	PUT	`/locations/v1/permissions/pipeline/{pipeline_id}/{email}`	Grant a specific org member access to a pipeline.

06 understand

9 endpoints

#	Method	Path	Description
6.1	GET	`/understand/chat/sessions`	List Ubi chat sessions for a user+feed
6.2	POST	`/understand/chat/sessions`	Create a chat session (fires lazily on first message, not on 'New Chat' click)
6.3	GET	`/understand/chat/sessions/{session_id}`	Get one session's metadata
6.4	DELETE	`/understand/chat/sessions/{session_id}`	Not documented yet.
6.5	GET	`/understand/chat/sessions/{session_id}/messages`	Read message history for a session
6.6	POST	`/understand/chat/sessions/{session_id}/messages`	Not documented yet.
6.7	GET	`/understand/artifacts/count/{feed_id}`	Count ingested artifacts for a feed.
6.8	POST	`/understand/artifacts/preview`	Not documented yet.
6.9	POST	`/understand/metrics/preview`	Not documented yet.