Distilling Large Language Models into Tiny and Effective Students using pQRNN

Prabhu Kaliamoorthi, Aditya Siddhant, Edward Li, Melvin Johnson

Google

{prabhumk, adisid, gavinbelson, melvinp}@google.com

Abstract

Large pre-trained multilingual models like mBERT, XLM-R achieve state of the art results on language understanding tasks. However, they are not well suited for latency critical applications on both servers and edge devices. It's important to reduce the memory and compute resources required by these models. To this end, we propose pQRNN, a projectionbased embedding-free neural encoder that is tiny and effective for natural language processing tasks. Without pre-training, pORNNs significantly outperform LSTM models with pre-trained embeddings despite being 140x smaller. With the same number of parameters, they outperform transformer baselines thereby showcasing their parameter efficiency. Additionally, we show that pQRNNs are effective student architectures for distilling large pretrained language models. We perform careful ablations which study the effect of pQRNN parameters, data augmentation, and distillation settings. On MTOP, a challenging multilingual semantic parsing dataset, pQRNN students achieve 95.9% of the performance of an mBERT teacher while being 350x smaller. On mATIS, a popular parsing task, pQRNN students on average are able to get to 97.1% of the teacher while again being 350x smaller. Our strong results suggest that our approach is great for latency-sensitive applications while being able to leverage large mBERT-like models.

1 Introduction

Large pre-trained language models (Devlin et al., 2018; Lan et al., 2020; Liu et al., 2019; Yang et al., 2019; Raffel et al., 2019) have demonstrated state-of-the-art results in many natural language processing (NLP) tasks (e.g. the GLUE benchmark (Wang et al., 2018)). Multilingual variants of these models covering 100+ languages (Conneau et al., 2020; Arivazhagan et al., 2019; Fang

et al., 2020; Siddhant et al.; Xue et al., 2020; Chung et al., 2020) have shown tremendous crosslingual transfer learning capability on the challenging XTREME benchmark (Hu et al., 2020). However, these models require millions of parameters and several GigaFLOPS making them take up significant compute resources for applications on servers and impractical for those on the edge such as mobile platforms.

Reducing the memory and compute requirements of these models while maintaining accuracy has been an active field of research. The most commonly used techniques are quantization (Gong et al., 2014; Han et al., 2015a), weight pruning (Han et al., 2015b), and knowledge distillation (Hinton et al., 2015). In this work, we will focus on knowledge distillation (KD), which aims to transfer knowledge from a teacher model to a student model, as an approach to model compression. KD has been widely studied in the context of pre-trained language models (Tang et al., 2019; Turc et al., 2019; Sun et al., 2020). These methods can be broadly classified into two categories: taskagnostic and task-specific distillation (Sun et al., 2020). Task-agnostic methods aim to perform distillation on the pre-training objective like masked language modeling (MLM) in order to obtain a smaller pre-trained model. However, many tasks of practical interest to the NLP community are not as complex as the MLM task solved by task-agnostic approaches. This results in complexity inversion — i.e., in order to solve a specific relatively easy problem the models learn to solve a general much harder problem which entails language understanding. Task-specific methods on the other hand distill the knowledge needed to solve a specific task onto a student model thereby making the student very efficient at the task that it aims to solve. This allows for decoupled evolution of both the teacher and student models.

In task-specific distillation, the most important requirement is that the student model architectures are efficient in terms of the number of training samples, number of parameters, and number of FLOPS. To address this need we propose pQRNN (projection Quasi-RNN), an embedding-free neural encoder for NLP tasks. Unlike embedding-based model architectures used in NLP (Wu et al., 2016; Vaswani et al., 2017), pQRNN learns the tokens relevant for solving a task directly from the text input similar to Kaliamoorthi et al. (2019). Specifically, they overcome a significant bottleneck of multilingual pre-trained language models where embeddings take up anywhere between 47% and 71% of the total parameters due to large vocabularies (Chung et al., 2020). This results in many advantages such as not requiring pre-processing before training a model and having orders of magnitude fewer parameters.

Our main contributions in this paper are as follows

- 1. We propose pQRNN a tiny, efficient, and embedding-free neural encoder for NLP tasks.
- 2. We demonstrate the effectiveness of pQRNNs as a student architecture for task-specific distillation of large pre-trained language models.
- 3. We propose a simple and effective strategy for data augmentation which further improves quality and perform careful ablations on pQRNN parameters and distillation settings.
- 4. We show in experiments on two semantic-parsing datasets, that our pQRNN student is able to achieve >95% of the teacher performance while being 350x smaller than the teacher.

2 Related Work

Distillation of pre-trained models In task-specific distillation, the pre-trained model is first fine-tuned for the task and then distilled. Tang et al. (2019) distill BERT into a simple LSTM-based model for sentence classification. In Sun et al. (2019), they also extract information from the intermediate layers of the teacher. Chatterjee (2019) distills a BERT model fine-tuned on SQUAD into a smaller transformer model that's initialized from BERT. Tsai et al. (2019) distills mBERT into a single multilingual student model which is 6x smaller

on sequence-labeling tasks. In task-agnostic distillation, the distillation is performed at the pre-training stage. Some examples of this strategy are: MobileBERT (Sun et al., 2020) which distills BERT into a slimmer version and MiniLM (Wang et al., 2020) distills the self-attention component during pre-training. In TinyBERT (Jiao et al., 2020) and Turc et al. (2019), the authors perform a combination of the above two strategies where they perform distillation both at the pre-training and fine-tuning stages.

Model Compression Apart from knowledge distillation, there has been an extensive body of work around compressing large language models. Some of the most prominent methods include: low-rank approximation (Lan et al., 2020), weight-sharing (Lan et al., 2020; Dehghani et al., 2019), pruning (Cui et al., 2019; Gordon et al., 2020; Hou et al., 2020), and quantization (Shen et al., 2019; Zafrir et al., 2019).

3 Proposed Approach

3.1 Overview

We perform distillation from a pre-trained mBERT teacher fine-tuned for the semantic parsing task. We propose a projection-based architecture for the student. We hypothesise that since the student is task-specific, using projection would allow the model to learn the relevant tokens needed to replicate the decision surface learnt by the teacher. This allows us to significantly reduce the number of parameters that are context invariant, such as those in the embeddings, and increase the number of parameters that are useful to learn a contextual representation. We further use a multilingual teacher that helps improve the performance of low-resource languages through cross-lingual transfer learning. We propose input paraphrasing as a strategy for data augmentation which further improves the final quality.

3.2 Data augmentation strategy

Large pre-trained language models generalize well beyond the supervised data on which they are fine-tuned. However we show that the use of supervised data alone is not effective at knowledge transfer during distillation. Most industry scale problems have access to a large corpus of unlabeled data that can augment the supervised data during distillation. However, this is not true for public datasets. We leverage query paraphrasing through bilingual




Figure 1: The pQRNN model architecture

pivoting (Mallinson et al., 2017) as a strategy to overcome this problem. This is achieved by using a in-house neural machine translation system (Wu et al., 2016; Johnson et al., 2017) to translate a query in the source language S to a foreign language T and then back-translating it into the original source language S, producing a paraphrase. We show that this introduces sufficient variation and novelty in the input text and helps improve knowledge transfer between the teacher and the student.

3.3 Teacher Model Architecture: mBERT

We used mBERT (Devlin et al., 2018), a transformer model that has been pretrained on the Wikipedia corpus of 104 languages using MLM and Next Sentence Prediction (NSP) tasks, as our teacher. The model architecture has 12 layers of transformer encoder (Vaswani et al., 2017) with a model dimension of 768 and 12 attention heads. It uses an embedding table with a wordpiece (Schuster and Nakajima, 2012) vocabulary of 110K resulting in approximately 162 million parameters. The mBERT teacher is then fine-tuned on the multilingual training data for the relevant downstream task. This results in a single multilingual task-specific teacher model for each dataset.

3.4 Student Model Architectures: pQRNN

The pQRNN model architecture, shown in Figure 1, consists of three distinct layers which we describe below.

3.4.1 Projection Layer

We use the projection operator proposed in (Kaliamoorthi et al., 2019) for this work. The operator takes a sequence of tokens and turns it into a sequence of ternary vectors $\in \mathbb{P}^N$, where \mathbb{P} is the set $\{-1,0,1\}$ and N is a hyper-parameter. This is achieved by generating a fingerprint for each token

with 2N bits and using a surjective function to map every two bits to \mathbb{P} . The surjective function maps the binary values $\{00,01,10,11\}$ to $\{-1,0,0,1\}$ and has a few useful properties. 1) Since the value 0 is twice as likely as the non-zero values and the non-zero values are equally likely, the representation has a symmetric distribution. 2) For any two non-identical tokens the resulting vectors are orthogonal if the fingerprints are truly random. This can be proved by performing a dot product of the vectors $\in \mathbb{P}^N$ and showing that the positive and negative values are equally likely, and hence the expected value of the dot product is 0.3) The norm of the vectors are expected to be $\sqrt{N/2}$ since N/2 values are expected to be non zero.

3.4.2 Bottleneck Layer

The result of the projection layer is a sequence of vectors $\mathbf{X} \in \mathbb{P}^{T \times N}$, where T is the number of tokens in the input sequence. Though this is a unique representation for the sequence of tokens, the network has no influence on the representation and the representation does not have semantic similarity. So we combine it with a fully connected layer to allow the network to learn a representation useful for our task.

$$ReLU(BatchNorm(\mathbf{XW} + b))$$

where $\mathbf{W} \in \mathbb{R}^{N \times B}$ and B is the bottleneck dimension.

3.4.3 Contextual Encoder

The result of the bottleneck layer is invariant to the context. We learn a contextual representation by feeding the result of the bottleneck layer to a stack of sequence encoders. In this study we used a stack of bidirectional QRNN (Bradbury et al., 2016) encoders and we refer to the resulting model as **pQRNN**. We make a couple of modifications to the QRNN encoder.

- 1. We use batch normalization (Ioffe and Szegedy, 2015) before applying *sigmoid* and *tanh* to the Z/F/O gates. This is not straightforward since the inputs are zero padded sequences during training. We circumvented this issue by excluding the padded region when calculating the batch statistics.
- 2. We use quantization-aware training (Jacob et al., 2017) to construct the model.

The hyper-parameters of the model are the state size S, the kernel width k and the number of layers L. As described in (Bradbury et al., 2016), we use zoneout for regularization. However, we use a decaying form of zoneout which sets the zoneout probability in layer $l \in [1, ..., L]$ as b^l , where b is a base zoneout probability. This is done based on the observation that regularization in higher layers makes it harder for the network to learn a good representation since it has fewer parameters to compensate for it, while this is not the case in lower layers.

4 Experimental Setup

4.1 Model Configuration: pQRNN

We configure the pQRNN encoder to predict both intent and arguments as done in (Li et al., 2020). But we decompose the probabilities using chain rule, as follows

$$P(i, a_{1:T}|q) = P(a_{1:T}|i, q)P(i|q)$$

where i, $a_{1:T}$, and q are the intent, arguments and query respectively. The first term in the decomposition is trained with teacher forcing (Williams and Zipser, 1989) for the intent values. The arguments are derived from the pQRNN outputs as follows

$$P(a_{1:T}|i,q) = Softmax(Linear(O) + W\delta_i)$$

where $O \in \mathbb{R}^{T \times 2S}$ are the outputs of the bidirectional pQRNN encoder with state size $S, W \in \mathbb{R}^{A \times I}$ is a trainable parameter, where I and A are the number of intents and arguments respectively, $\delta_i \in \mathbb{R}^I$ is a one hot distribution on the intent label during training and most likely intent prediction during inference. The intent prediction from the query is derived using attention pooling as follows

$$P(i|q) = Softmax(Softmax(W_{pool}O^T)O)$$

where $W_{pool} \in \mathbb{R}^{2S}$ is a trainable parameter.

Training Setup: Using this model configuration we construct an optimization objective using crossentropy loss on the intent and arguments. The objective includes an L2 decay with scale $1e^{-5}$ on the trainable parameters of the network. The training loss is optimized using Adam optimizer (Kingma and Ba, 2017) with a base learning rate of $1e^{-3}$ and an exponential learning rate decay with decay rate of 0.9 and decay steps of 1000. Training is performed for 60,000 steps with a batch size

of 4096 and synchronous gradient updates (Chen et al., 2016). We evaluate the model continuously on the development set during training and the best model is later evaluated on the test set to obtain the metrics reported in this paper.

Model Hyper-parameters: The pQRNN model configuration we use in the experiments have a projection feature dimension N=1024, bottleneck dimension B=256, a stack of bidirectional QRNN encoder with number of layers L=4, state size S=128 and convolution kernel width k=2. We used an open source projection operator 1 that preserves information on suffixes and prefixes. For regularization we use zoneout (Krueger et al., 2016) with a layer-wise decaying probability of 0.5. We also used dropout on the projection features with a probability of 0.8.

4.2 Datasets

We run our experiments on two multilingual semantic-parsing datasets: multilingual ATIS and MTOP. Both datasets have one intent and some slots associated with a query. Given a query, both intent and slots have to be predicted jointly.

Languaga	Ех	kample	Intents	Slots	
Language	train	dev	test	ments	Siois
English	4488	490	893	18	84
Spanish	4488	490	893	18	84
Portuguese	4488	490	893	18	84
German	4488	490	893	18	84
French	4488	490	893	18	84
Chinese	4488	490	893	18	84
Japanese	4488	490	893	18	84
Hindi	1440	160	893	17	75
Turkish	578	60	715	17	71

Table 1: Data statistics for the MultiATIS++ corpus.

Multilingual ATIS: It is a multilingual version of the classic goal oriented dialogue dataset ATIS (Price, 1990). ATIS contains queries related to single domain i.e. air travel. ATIS was expanded to multilingual ATIS by translating to 8 additional languages (Xu et al., 2020a). Overall, it has 18 intents and 84 slots. Table 1 shows the summary of the statistics of this dataset.

MTOP: It is a multilingual task-oriented semantic parsing dataset covering 6 languages (Li et al.,

¹https://github.com/tensorflow/models/tree/master/research/seq_flow_lite

Languaga	Е	xamples	Intente	Slots	
Language	train	152 1878 3757 1 610 1658 3317 1 821 1546 3092 1 327 1618 3236 1	ments	Siois	
English	13152	1878	3757	113	75
German	11610	1658	3317	113	75
French	10821	1546	3092	110	74
Spanish	11327	1618	3236	104	71
Hindi	10637	1520	3039	113	73
Thai	13152	1879	3758	110	73

Table 2: Data statistics for the MTOP corpus.

2020). It contains a mix of both simple as well as compositional nested queries across 11 domains, 117 intents and 78 slots. Similar to multilingual ATIS, this dataset was also created by translating from English to five other target languages. The dataset provides both flat and hierarchical representations but for the purpose of our work, we only use the former. Table 2 shows a summary of the MTOP dataset.

4.3 Data Augmentation

It has been shown (Das et al., 2020) that generalization performance of deep learning models can be improved significantly by simple data augmentation strategies. It is particularly useful for our case since we are trying to replicate a function learnt by a teacher model that has been trained on much more data than the student.

Our method for data augmentation uses round-trip translation through a pivot language which is different from that of the original query. To get a new utterances/queries, we take the original query from the dataset and first translate it to the pivot language using our in-house translation system. The query in the pivot language is then translated back to the original language. The round-trip translated queries are now slightly different from the original query. This increases the effective data size. The round-trip translated queries sometimes also have some noise which has an added advantage as it would make the model, which uses this data, robust to noise.

Once we get the queries, we obtain the intent and argument labels for these new queries by doing a forward pass through the teacher model that was trained on original queries. For our experiments in this paper, we run 3 variations: one where the number of augmented queries is equal to the size of the original data and two other variations where the augmented data is 4x or 8x the size of the original

data.

5 Results & Ablations

5.1 MTOP Results

Table 3 presents our results on the MTOP dataset. The Reference subsection presents results from prior work. XLU refers to a bidirectional LSTMbased intent slot model as proposed in Liu and Lane (2016); Zhang and Wang (2016) using pre-trained XLU embeddings. XLM-R (Conneau et al., 2020) refers to a large multilingual pre-trained model with 550M parameters. From the *Baselines* subsection, we can see that the pQRNN baseline trained just on the supervised data significantly outperforms a comparable transformer baseline by 9.1% on average. Our pQRNN baseline also significantly beats the XLU biLSTM pre-trained model by 3% on average despite being 140x smaller. In the Distillation subsection, we present our mBERT teacher results which are slightly worse than the XLM-R reference system since mBERT has far fewer parameters compared to XLM-R. For building the student, we experimented with distillation on just the supervised data and with using 4x or 8x additional paraphrased data. The best result from these three configurations is presented as *pQRNN student*. It can be observed that on average our distillation recipe improves the exact match accuracy by close to 3% when compared to the pQRNN baseline. Furthermore, our student achieves 95.9% of the teacher performance despite being 340x smaller.

5.2 Multilingual ATIS Results

Table 4 showcases the results for Multilingual ATIS dataset. For simplicity, we report just the intent accuracy metric in Table 4 and show the argument F1 metric in Table 7 in the Appendix. The Reference subsection has LSTM-based results presented in (Xu et al., 2020b) and our own mBERT baseline. As expected, our mBERT system is significantly better than the LSTM system presented in (Xu et al., 2020b). We see similar trends as seen in section 5.1 on this dataset as well. Our pQRNN baseline significantly outperforms a comparable transformer baseline by avg. 4.3% intent accuracy. Furthermore, the pQRNN baseline performs significantly better than the LSTM reference system by avg. 2.9%. It should be noted that the pQRNN baseline outperforms the mBERT reference system by avg. 1.4% on intent accuracy. This is significant since pQRNN has 85x fewer parameters. In the

	Exact Match Accuracy									
	#Params	en	es	fr	de	hi	th	avg		
Reference										
XLU	70M (float)	78.2	70.8	68.9	65.1	62.6	68.0	68.9		
XLM-R	550M (float)	85.3	81.6	79.4	76.9	76.8	73.8	79.0		
Baselines										
Transformer	2M (float)	71.7	68.2	65.1	64.1	59.1	48.4	62.8		
pQRNN	2M (8bit)	78.8	75.1	71.9	68.2	69.3	68.4	71.9		
Distillation										
mBERT* teacher	170M (float)	84.4	81.8	79.7	76.5	73.8	72.0	78.0		
pQRNN student	2M (8bit)	81.8	79.1	75.8	70.8	72.1	69.5	74.8		
Student/Tead	cher (%)	96.9	96.7	95.1	92.5	97.7	96.5	95.9		

Table 3: References, Baselines, Teacher and Student for MTOP dataset. Reference numbers have been taken from (Li et al., 2020). We use exact match accuracy as metric to compare w/references.

			Intent Accuracy								
	#Params	en	de	es	fr	hi	ja	pt	tr	zh	avg
			R	eferenc	ce						
LSTM		96.1	94.0	93.0	94.7	84.5	91.2	92.7	81.1	92.5	91.1
mBERT	170M (float)	95.5	95.1	94.1	94.8	87.8	92.9	94.0	85.4	93.4	92.6
Baselines											
Transformer	2M (float)	96.8	93.2	92.1	93.1	79.6	90.7	92.1	78.3	88.1	89.3
pQRNN	2M (8bit)	98.0	96.6	97.0	97.9	90.7	88.7	97.2	86.2	93.5	94.0
			D	istillati	on						
mBERT* teacher	170M (float)	98.3	98.5	97.4	98.6	94.5	98.6	97.4	91.2	97.5	96.9
pQRNN student	2M (8bit)		97.3			91.0			88.5		
Student/Teac	cher (%)		98.0			96.3			97.0		

Table 4: References, Baselines, Teacher and Student for multilingual ATIS dataset. Reference numbers have been taken from (Xu et al., 2020a). We report both intent accuracy and argument f1 metrics to compare w/references.

Distillation subsection, we present the results of our multilingual mBERT teacher which serves as the quality upper-bound. We can see that the headroom between the teacher and the pQRNN baseline is low for the following languages: en, es, fr, and pt. Note that ja and zh are not space-separated languages, thereby requiring access to the original segmenter used in the multilingual ATIS dataset to segment our paraphrased data and distill them using the teacher. Since this is not publicly available, we skip distillation on these two languages. This leaves us with distillation results on de, hi and tr. From the Table, we can see that we obtain on average 97.1% of the teacher performance while being dramatically smaller.

5.3 pQRNN Ablation

In this section, we study the impact of various hyper-parameters on the pQRNN model performance. We use the German MTOP dataset for this study. We report intent accuracy, slot F1 and exact match accuracy metrics for the baseline configuration in Table 5.

We first studied the impact quantization had on the results while keeping all other parameters unchanged. From the Table, we can observe that quantization acts as a regularizer and helps improve the performance albeit marginally. Furthermore, it can be observed that disabling batch normalization results in a very significant degradation of the model performance. Next, we studied the impact of the mapping function. Instead of using a bal-

	D	1	2	3	4	5	6	7
Quantized	Yes	No						
Batch Norm	Yes		No					
Balanced	Yes			No				
Zoneout Probability	0.5				0.0			
State Size	128					96		
Bottleneck	256						128	
Feature Size	1024							512
Intent Accuracy	92.7	92.6	90.8	91.7	89.2	92.2	91.3	92.1
Argument F1	81.9	81.9	79.1	80.5	77.9	80.4	80.6	81.0
Exact Match	68.2	68.2	64.3	67.1	61.1	66.4	66.8	67.9

Table 5: The table shows the impact of various hyper-parameters on the pQRNN model performance evaluated on the de language in MTOP dataset. D is the default setting and in each of the ablations, we change exactly one hyper-parameter.

anced map that results in symmetric and orthogonal projections, we created projection that had positive value twice as likely as the non-positive values; this degrades the performance noticeably. Setting the zoneout probability to 0.0, has the most significant impact on the model performance. We believe that due to the small dataset size, regularization is essential to prevent over-fitting. Finally, we study the impact of the hyper-parameters such as N,B,S defined in Section 4.1 on the model performance by halving them. It can be observed that of the three parameters halving S degrades the model performance the most especially for slot tagging. This is followed by B and then N.

5.4 Effect of Data Augmentation

	en	de	es	fr	hi	th
teacher	84.4	76.5	81.8	79.7	73.8	72.0
1x data 4x data 8x data	79.4 81.2 81.8	68.6 70.6 70.8	75.4 78.5 79.1	73.0 75.8 74.9	70.2 72.1 71.2	69.5 63.9 62.7

Table 6: Effect of data augmentation on student's performance on MTOP. The metric used is exact match accuracy.

Table 6 captures the effect of the data size on distillation. It shows the exact match accuracy for all languages on the MTOP dataset when we perform distillation on just the supervised training data as well as when we augment the training data with four times and eight times the data using the paraphrasing strategy. The paraphrasing strategy uses different pivot languages to generate the samples hence noise in the data is not uniform across all

augmented samples. It can be observed that for all languages except Thai, when we use four times the data, the model performance improves. We believe the main reason for this is that the paraphrasing technique results in utterances that include different ways to express the same queries using novel words not part of the training set. The student pQRNN model learns to predict the classes with these novel words and hence generalizes better. For Hindi and French, as we increase the size further to eight times the original dataset we observe a slight drop in performance. We believe this is mostly due to noise introduced in the paraphrased data such as punctuation that affects the generalization of the BERT teacher. However for Thai, the distillation performs worse as we augment data. Further analysis revealed that the paraphrased data was segmented differently since we didn't have access to the segmenter used to create the original dataset. This introduces a mismatch between the supervised and the paraphrased data which results in poor distillation performance. These findings indicate that one could achieve even better performance if they have access to a large corpus of unlabeled data from the input domain and have full control over the segmenters used during supervised data creation.

5.5 Effect of scaling the teacher logits

In this section, we study the effect of scaling the teacher logits on the MTOP Spanish dataset. This is not the same as distillation temperature discussed in (Hinton et al., 2015), since we change the temperature of just the teacher model. We plot the eval and train loss for training runs using differ-




Figure 2: The effect of changing the scale of the teacher logits on the training and evaluation loss. The figure shows the training and eval loss in vertical axis against the training steps in horizontal axis.




Figure 3: The effect of changing the scale of teacher logits on the exact matching accuracy on the test set.

ent scales in Figure 2. Scaling the logits with a multiplier greater than 1.0 results in a more peaky distribution whereas using a multiplier less than 1.0 result in a softer distribution for the intent and slot prediction probabilities from the teacher. It can be observed that as the scalar multiple is reduced the eval loss reduces and remains low as the training progresses. However, with higher temperatures (e.g., T=1,2) the eval loss first reduces and then increases indicating over-fitting. From these observations, we conclude that the exact match accuracy on the test set improves as the scale of the logits is reduced. This is further demonstrated in Figure 3.

6 Conclusion

We present pQRNN: a tiny, efficient, embeddingfree neural encoder for NLP tasks. We show that pQRNNs outperform LSTM models with pretrained embeddings despite being 140x smaller. They are also parameter efficient which is proven by their gain over a comparable transformer baseline. We then show that pQRNNs are ideal student architectures for distilling large pre-trained language models (i.e., mBERT). On MTOP, a multilingual task-oriented semantic parsing dataset, pQRNN students reach 95.9% of the mBERT teacher performance. Similarly, on mATIS, a popular semantic parsing task, our pQRNN students achieve 97.1% of the teacher performance. In both cases, the student pQRNN is a staggering 350x smaller than the teacher. Finally, we carefully ablate the effect of pQRNN parameters, the amount of pivot-based paraphrasing data, and the effect of teacher logit scaling. Our results prove that it's possible to leverage large pre-trained language models into dramatically smaller pQRNN students without any significant loss in quality. Our approach has been shown to work reliably at Google-scale for latency-critical applications.

Acknowledgments

We would like to thank our colleagues Catherine Wah, Edgar Gonzàlez i Pellicer, Evgeny Livshits, James Kuczmarski, Jason Riesa and Milan Lee for helpful discussions related to this work. We would also like to thank Amarnag Subramanya, Andrew Tomkins, Macduff Hughes and Rushin Shah for their leadership and support.

References

Naveen Arivazhagan, Ankur Bapna, Orhan Firat, Dmitry Lepikhin, Melvin Johnson, Maxim Krikun, Mia Xu Chen, Yuan Cao, George Foster, Colin Cherry, Wolfgang Macherey, Zhifeng Chen, and Yonghui Wu. 2019. Massively multilingual neural

- machine translation in the wild: Findings and challenges.
- James Bradbury, Stephen Merity, Caiming Xiong, and Richard Socher. 2016. Quasi-recurrent neural networks.
- Debajyoti Chatterjee. 2019. Making neural machine reading comprehension faster.
- Jianmin Chen, Rajat Monga, Samy Bengio, and Rafal Józefowicz. 2016. Revisiting distributed synchronous SGD. CoRR, abs/1604.00981.
- Hyung Won Chung, Thibault Févry, Henry Tsai, Melvin Johnson, and Sebastian Ruder. 2020. Rethinking embedding coupling in pre-trained language models.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.
- Baiyun Cui, Yingming Li, Ming Chen, and Zhongfei Zhang. 2019. Fine-tune BERT with sparse self-attention mechanism. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3548–3553, Hong Kong, China. Association for Computational Linguistics.
- Deepan Das, Haley Massa, Abhimanyu Kulkarni, and Theodoros Rekatsinas. 2020. An empirical analysis of the impact of data augmentation on knowledge distillation.
- Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Lukasz Kaiser. 2019. Universal transformers. In *International Conference on Learning Representations*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805.
- Yuwei Fang, Shuohang Wang, Zhe Gan, Siqi Sun, and Jingjing Liu. 2020. Filter: An enhanced fusion method for cross-lingual language understanding.
- Yunchao Gong, Liu Liu, Ming Yang, and Lubomir Bourdev. 2014. Compressing deep convolutional networks using vector quantization.
- Mitchell A. Gordon, Kevin Duh, and Nicholas Andrews. 2020. Compressing bert: Studying the effects of weight pruning on transfer learning.

- Song Han, Huizi Mao, and William J Dally. 2015a. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv* preprint arXiv:1510.00149.
- Song Han, Jeff Pool, John Tran, and William J. Dally. 2015b. Learning both weights and connections for efficient neural networks. In *Proceedings of the 28th International Conference on Neural Information Processing Systems Volume 1*, NIPS'15, page 1135–1143, Cambridge, MA, USA. MIT Press.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network.
- Lu Hou, Zhiqi Huang, Lifeng Shang, Xin Jiang, Xiao Chen, and Qun Liu. 2020. Dynabert: Dynamic bert with adaptive width and depth.
- Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. 2020. Xtreme: A massively multilingual multi-task benchmark for evaluating cross-lingual generalization. arXiv preprint arXiv:2003.11080.
- Sergey Ioffe and Christian Szegedy. 2015. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *CoRR*, abs/1502.03167.
- Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew G. Howard, Hartwig Adam, and Dmitry Kalenichenko. 2017. Quantization and training of neural networks for efficient integer-arithmetic-only inference. *CoRR*, abs/1712.05877.
- Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. 2020. Tinybert: Distilling bert for natural language understanding.
- Melvin Johnson, Mike Schuster, Quoc V. Le, Maxim Krikun, Yonghui Wu, Zhifeng Chen, Nikhil Thorat, Fernanda Viégas, Martin Wattenberg, Greg Corrado, Macduff Hughes, and Jeffrey Dean. 2017. Google's multilingual neural machine translation system: Enabling zero-shot translation. *Transactions of the Association for Computational Linguistics*, 5:339–351.
- Prabhu Kaliamoorthi, Sujith Ravi, and Zornitsa Kozareva. 2019. PRADO: Projection attention networks for document classification on-device. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 5012–5021, Hong Kong, China. Association for Computational Linguistics.
- Diederik P. Kingma and Jimmy Ba. 2017. Adam: A method for stochastic optimization.
- David Krueger, Tegan Maharaj, János Kramár, Mohammad Pezeshki, Nicolas Ballas, Nan Rosemary Ke, Anirudh Goyal, Yoshua Bengio, Hugo Larochelle,

- Aaron C. Courville, and Chris Pal. 2016. Zoneout: Regularizing rnns by randomly preserving hidden activations. *CoRR*, abs/1606.01305.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman,Kevin Gimpel, Piyush Sharma, and Radu Soricut.2020. Albert: A lite bert for self-supervised learning of language representations.
- Haoran Li, Abhinav Arora, Shuohui Chen, Anchit Gupta, Sonal Gupta, and Yashar Mehdad. 2020. Mtop: A comprehensive multilingual task-oriented semantic parsing benchmark. *arXiv preprint arXiv:2008.09335*.
- Bing Liu and Ian Lane. 2016. Attention-based recurrent neural network models for joint intent detection and slot filling. In *Interspeech 2016*, pages 685–689.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692.
- Jonathan Mallinson, Rico Sennrich, and Mirella Lapata. 2017. Paraphrasing revisited with neural machine translation. In *Proceedings of the 15th Con*ference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers, pages 881–893, Valencia, Spain. Association for Computational Linguistics.
- Patti Price. 1990. Evaluation of spoken language systems: The atis domain. In *Speech and Natural Language: Proceedings of a Workshop Held at Hidden Valley, Pennsylvania, June 24-27, 1990.*
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2019. Exploring the limits of transfer learning with a unified text-to-text transformer. arXiv preprint arXiv:1910.10683.
- Mike Schuster and Kaisuke Nakajima. 2012. Japanese and korean voice search. In 2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 5149–5152. IEEE.
- Sheng Shen, Zhen Dong, Jiayu Ye, Linjian Ma, Zhewei Yao, Amir Gholami, Michael W. Mahoney, and Kurt Keutzer. 2019. Q-bert: Hessian based ultra low precision quantization of bert.
- Aditya Siddhant, Melvin Johnson, Henry Tsai, Naveen Ari, Jason Riesa, Ankur Bapna, Orhan Firat, and Karthik Raman. Evaluating the cross-lingual effectiveness of massively multilingual neural machine translation.
- Siqi Sun, Yu Cheng, Zhe Gan, and Jingjing Liu. 2019. Patient knowledge distillation for BERT model compression. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages

- 4323–4332, Hong Kong, China. Association for Computational Linguistics.
- Zhiqing Sun, Hongkun Yu, Xiaodan Song, Renjie Liu, Yiming Yang, and Denny Zhou. 2020. MobileBERT: a compact task-agnostic BERT for resource-limited devices. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 2158–2170, Online. Association for Computational Linguistics.
- Raphael Tang, Yao Lu, Linqing Liu, Lili Mou, Olga Vechtomova, and Jimmy Lin. 2019. Distilling task-specific knowledge from BERT into simple neural networks. *CoRR*, abs/1903.12136.
- Henry Tsai, Jason Riesa, Melvin Johnson, Naveen Arivazhagan, Xin Li, and Amelia Archer. 2019. Small and practical bert models for sequence labeling.
- Iulia Turc, Ming-Wei Chang, Kenton Lee, and KristinaToutanova. 2019. Well-read students learn better:On the importance of pre-training compact models.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *CoRR*, abs/1706.03762.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. 2018. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP, pages 353–355, Brussels, Belgium. Association for Computational Linguistics.
- Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *arXiv preprint arXiv:2002.10957*.
- R. J. Williams and D. Zipser. 1989. A learning algorithm for continually running fully recurrent neural networks. *Neural Computation*, 1(2):270–280.
- Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V. Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, Jeff Klingner, Apurva Shah, Melvin Johnson, Xiaobing Liu, Lukasz Kaiser, Stephan Gouws, Yoshikiyo Kato, Taku Kudo, Hideto Kazawa, Keith Stevens, George Kurian, Nishant Patil, Wei Wang, Cliff Young, Jason Smith, Jason Riesa, Alex Rudnick, Oriol Vinyals, Greg Corrado, Macduff Hughes, and Jeffrey Dean. 2016. Google's neural machine translation system: Bridging the gap between human and machine translation. *CoRR*, abs/1609.08144.
- Weijia Xu, Batool Haider, and Saab Mansour. 2020a. End-to-end slot alignment and recognition for crosslingual nlu. *arXiv preprint arXiv:2004.14353*.

- Weijia Xu, Batool Haider, and Saab Mansour. 2020b. End-to-end slot alignment and recognition for crosslingual nlu.
- Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2020. mt5: A massively multilingual pre-trained text-to-text transformer. arXiv preprint arXiv:2010.11934.
- Zhilin Yang, Zihang Dai, Yiming Yang, Jaime G. Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. 2019.Xlnet: Generalized autoregressive pretraining for language understanding. *CoRR*, abs/1906.08237.
- Ofir Zafrir, Guy Boudoukh, Peter Izsak, and Moshe Wasserblat. 2019. Q8bert: Quantized 8bit bert.
- Xiaodong Zhang and Houfeng Wang. 2016. A joint model of intent determination and slot filling for spoken language understanding. In *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence*, IJCAI'16, page 2993–2999. AAAI Press.

A Appendix

For the multilingual ATIS dataset, we present Argument F1 metrics in table 7 below.

		Argument F1									
	#Params	en	de	es	fr	hi	ja	pt	tr	zh	avg
#Params en de es fr hi ja pt tr zh avg											
LSTM		94.7	91.4	75.9	85.9	74.9	88.8	88.4	64.4	90.8	83.9
mBERT	170M (float)	95.6	95.0	86.6	89.1	82.4	91.4	91.4	75.2	93.5	88.9
	Baselines										
Transformer	2M (float)	93.8	91.5	73.9	82.8	71.5	88.1	85.9	67.7	87.9	82.6
pQRNN	2M (8bit)	95.1	93.9	87.8	91.3	79.9	90.2	88.8	75.7	92.2	88.3
	Distillation										
mBERT* teacher	170M (float)	95.7	95.0	83.5	94.2	87.5	92.9	91.4	87.3	92.7	91.3
pQRNN student	2M (8bit)		94.8			84.5			77.7		
Student/Tea	cher (%)		99.7			96.6			89.0		

Table 7: References, Baselines, Teacher and Student argument F1 metrics for multilingual ATIS dataset. Reference numbers have been taken from (Xu et al., 2020a). Intent Accuracy metric is reported in 4