

SOCIAL API

Create Feed Token

CREATE FEED TOKEN

Reference Guide

Twitter column need to authenticate the account by using oauth, if you just create twitter column, you need process to create feed token.

After you created feed token, you will get respond about feed token information, if url_oauth is not blank, you should use that url to open new window for authentication. if it is blank and contain token and secret, that means the account is already authorized.

HOST : api.finfore.net / test.finfore.net

METHOD : POST

FORMAT : json,xml,fxml

PATH : /feed_tokens.format

PARAMETERS :

- **feed_account_id** : your column id (integer & required)
- **user_id** : your current user id (integer & required)
- **call_back**: return address after authenticated (optional)
 - if you add call_back in parameter, please look UPDATE FEED TOKEN
Suggestion: better you add feed_account_id in your callback parameter to handle multiple authorizations.

Show Feed Token

SHOW FEED TOKEN

Reference Guide

Show feed token is used to access authorized token and secret, that will be used for your widget or application.

HOST : api.finfore.net / test.finfore.net

METHOD : GET

FORMAT : json,xml,fxml

PATH : /feed_token/:id.format

PARAMETERS :

- **id** : feed token id

UPDATE FEED TOKEN

UPDATE FEED TOKEN

Reference Guide

You should update token to get authorized token and secret.

HOST : `api.finfore.net / test.finfore.net`

METHOD : PUT

FORMAT : `json,xml,fxml`

PATH : `/feed_tokens/:id.format`

PARAMETERS :

- **id** : your feed token id
- **oauth_verifier** : this pin is taken from call back url.

TweetFore

home timeline

HOME TIME LINE

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/home_timeline.format

PARAMETERS :

- feed_token_id : value is integer
- http://dev.twitter.com/doc/get/statuses/home_timeline

mentions

MENTIONS

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/mentions.format

PARAMETERS :

- feed_token_id : value is integer
- <http://dev.twitter.com/doc/get/statuses/mentions>

search

SEARCH

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required

parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/search.format

PARAMETERS :

- feed_token_id : value is integer
- <http://apiwiki.twitter.com/Twitter-Search-API-Method:-search>

message inbox

MESSAGE INBOX / DIRECT MESSAGE

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/message_inbox.format

PARAMETERS :

- feed_token_id : value is integer
- http://apiwiki.twitter.com/Twitter-REST-API-Method:-direct_messages

message sentbox

MESSAGE SENTBOX / DIRECT MESSAGE SENT

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/message_sentbox.format

PARAMETERS :

- feed_token_id : value is integer
- http://apiwiki.twitter.com/Twitter-REST-API-Method%3A-direct_messages%C2%A0sent

message destroy

MESSAGE DESTROY / DIRECT MESSAGE DESTROY

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/message_destroy.format

PARAMETERS :

- feed_token_id : value is integer
- http://apiwiki.twitter.com/Twitter-REST-API-Method%3A-direct_messages%C2%A0destroy

message post

MESSAGE POST / DIRECT MESSAGE NEW

Reference Guide

send message to twitter people

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/message_post.format

PARAMETERS :

- feed_token_id : value is integer
- user: could be id numeric or screen name
- text: your message

status update

UPDATE STATUS

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/status_update.format

PARAMETERS :

- feed_token_id : value is integer
- <http://dev.twitter.com/doc/post/statuses/update>

status destroy

DESTROY STATUS

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/status_destroy.format

PARAMETERS :

- feed_token_id : value is integer
- status_id : your status integer id

status retweet

RETWEET STATUS

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/status_retweet.format

PARAMETERS :

- feed_token_id : value is integer
- status_id : your status integer id

friends

LOAD FRIEND LIST

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/friends.format

PARAMETERS :

- feed_token_id : value is integer
- page : page number to show

followers

LOAD FOLLOWER LIST

Reference Guide

The general parameters are following twitter API documentation, you need to add feed_token_id as required parameter.

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json

PATH : /tweetfores/followers.format

PARAMETERS :

- feed_token_id : value is integer
- page : page number to show

LINKEDIN NETWORK STATUS

HOST : api.finfo.net / test.finfo.net

METHOD : GET & POST

FORMAT : json,xml,fxml (if json not work please use xml)

PATH : /linkedins/network_status.format

PARAMETERS :

- **tid** : it is feed token id
- **count**: total items perpage

Gmail

Inbox

LOAD GMAIL

HOST : api.finfo.net / test.finfo.net

METHOD : GET

FORMAT : json,xml,fxml (if json not work please use xml)

PATH : /mails.format

PARAMETERS :

- gid : feed_account_id for gmail or gmail column id

Compose

COMPOSE MESSAGE

HOST : api.finfo.net / test.finfo.net

METHOD : POST

FORMAT : json,xml,fxml (if json not work please use xml)

PATH : /mails.format

PARAMETERS :

- gid : feed_account_id for gmail or gmail column id (url parameter)
- subject: email subject, eg : params[:mail][:subject]
- receiver: receiver message
- message_html: text message.