

Malware Analysis Report For pe-cygwin-ls

Binary Type

PE (Portable Executable File) (Approved)

Analyzing File

- **File Name:** pe-cygwin-ls
 - **File Extension:** .exe
 - **File Type:** EXE (Executable File).
 - **MD5 Hash:** 9f93d89bc4bf0baf3858c186250c586d
 - **SHA256 Hash:** ce3e4fbeb2112467b89fe9c47d7c75e64e811135f1fef5bb799be8cd5cfa52c
-

File Identification

File detected as a valid Windows executable (DLL or EXE).

PE File Analysis

PE File Analysis: True

PE File Imports

- *_assertfunc*
- *_cxaatexit*
- *__errno*
- *__getreent*
- *_localectype_ptr*
- *_localembcумax*
- *__main*
- *dllcrt0@0*
- *_exit*
- *_fstat64*
- *_getgrgid32*
- *_getgrnam32*
- *_getpwuid32*
- *impureptr*
- *_lstat64*
- *_stat64*
- *abort*
- *aclextendedfile*
- *btowc*
- *calloc*
- *clock_gettime*
- *closedir*
- *cygwindetachdll*
- *cygwin_internal*

- `dirfd`
- `dll_dllcrt0`
- `error`
- `exit`
- `fclose`
- `fflush_unlocked`
- `fprintf`
- `fputs_unlocked`
- `free`
- `fstat`
- `fwrite`
- `fwrite_unlocked`
- `getenv`
- `getgrgid`
- `getgrnam`
- `getopt_long`
- `getpwnam`
- `getpwuid`
- `gettimeofday`
- `gmtime_r`
- `ioctl`
- `isatty`
- `iswcntrl`
- `iswctype`
- `iswprint`
- `localeconv`
- `localtime_r`
- `longjmp`
- `lstat`
- `malloc`
- `mbrtowc`
- `mbsinit`
- `mbsrtowcs`
- `mbstowcs`
- `memchr`
- `memcmp`
- `memcpy`
- `memmove`
- `mempcpy`
- `memset`
- `nl_langinfo`
- `opendir`
- `optarg`
- `optind`
- `posix_memalign`
- `printf`
- `program_invocation_name`
- `program_invocationshort_name`
- `putc_unlocked`
- `raise`
- `readdir`
- `readlink`

- realloc
- setenv
- setjmp
- setlocale
- sigaction
- sigaddset
- sigemptyset
- sigismember
- signal
- sigprocmask
- snprintf
- sprintf
- stat
- stpcpy
- stpncpy
- strcasecmp
- strcat
- strchr
- strcmp
- strcoll
- strcpy
- strdup
- strftime
- strlen
- strncmp
- strrchr
- strtoul
- strtoumax
- tcgetpgrp
- timegm
- tolower
- toupper
- tolower
- tzset
- unsetenv
- wcscat
- wcslen
- wcstombs
- wcswidth
- wctype
- wcwidth
- wmemchr
- wmemcpy
- libintl_bindtextdomain
- libintl_dcgettext
- libintl_gettext
- libintl_setlocale
- libintl_textdomain
- __divdi3
- __moddi3
- __udivdi3
- __umoddi3

- FreeLibrary
- GetACP
- GetModuleHandleA
- GetModuleHandleW
- GetProcAddress
- LoadLibraryA

PE File Exports

No Exported functions were found.

String Analysis

ASCII Strings

- !This program cannot be run in DOS mode.
- P`.data
- .rdata
- `@.buildid5
- 0@.bss
- .idata
- 9t\$ v"
- D\$, 1B
- F<+C
- t\$09t\$0
- D\$D????
- D\$H????f
- l\$\$9l\$,
- D\$\$+D\$,
- FL+CLu
- FD+CDu
- D\$,9D\$
- BL+ALu
- BL+ALu
- B<+A
- BD+ADu
- BD+ADu
- B<+A
- A<+B
- A<+B
- AL+BLu+
- AD+BDu+
- AL+BLu+
- AD+BDu+
- F<+C
- FL+CLu
- FD+CDu
- FD+CDu
- FL+CLu
- F<+C
- F<+C
- FD+CDu

- FL+CLu
-
- UWVSvi
- T\$,:T\$\$
- D\$88D\$-v\$9
- 8D\$-s49
- 8D\$-s49
- 8T\$-s(9
- T\$@8T\$.
- :D\$/v%
- T\$4+T\$(
-
- T\$4+T\$(9
- T\$4+T\$(9
- |\$4+|\$ (9
- D\$@8\ \$@
- d9T\$,u#
- L\$,+L\$d
- +D\$,9D\$\
- D\$4+D\$(9
- D\$T;(tG
- 9t\$,r5
- ;t\$(w3
- ;t\$,w2
- ;t\$,w2
- ;t\$\$w1
- ;t\$,w5
- 9L\$ t#
- ;D\$(t*
- <^t*<]
- uk<[t\$
- <:tb<=
- tKUWVS
- cyggcc_s-1.dll
- __registerframe_info
- __deregisterframe_info
- cyggcj-16.dll
- JvRegisterClasses
- %.*s%s%s
- *sorttype* != *sortversion*
- /usr/src/coreutils-8.26-2.i686/src/coreutils-8.26/src/lis.c
- %s %*s
- %s, %s
- cannot compare file names %s and %s
- cannot access %s
- cannot read symbolic link %s
- cannot open directory %s
- cannot determine device and inode of %s
- %s: not listing already-listed directory
- reading directory %s
- closing directory %s
- invocation

- Try '%s --help' for more information.
- Usage: %s [OPTION]... [FILE]...
- List information about the FILES (the current directory by default).
- Sort entries alphabetically if none of -cftuvSUX nor --sort is specified.
- Mandatory arguments to long options are mandatory for short options too.
- -a, --all do not ignore entries starting with .
- -A, --almost-all do not list implied . and ..
- --author with -l, print the author of each file
- -b, --escape print C-style escapes for nongraphic characters
- --block-size=SIZE scale sizes by SIZE before printing them; e.g.,
- '--block-size=M' prints sizes in units of
- 1,048,576 bytes; see SIZE format below
- -B, --ignore-backups do not list implied entries ending with ~
- -c with -lt: sort by, and show, ctime (time of last
- modification of file status information);
- with -l: show ctime and sort by name;
- otherwise: sort by ctime, newest first
- -C list entries by columns
- --color[=WHEN] colorize the output; WHEN can be 'always' (default
- if omitted), 'auto', or 'never'; more info below
- -d, --directory list directories themselves, not their contents
- -D, --dired generate output designed for Emacs' dired mode
- -f do not sort, enable -aU, disable -ls --color
- -F, --classify append indicator (one of */=>@|) to entries
- --file-type likewise, except do not append '**'
- --format=WORD across -x, commas -m, horizontal -x, long -l,
- single-column -1, verbose -l, vertical -C
- --full-time like -l --time-style=full-iso
- -g like -l, but do not list owner
- --group-directories-first
- group directories before files;
- can be augmented with a --sort option, but any
- use of --sort=none (-U) disables grouping
- -G, --no-group in a long listing, don't print group names
- -h, --human-readable with -l and/or -s, print human readable sizes
- (e.g., 1K 234M 2G)
- --si likewise, but use powers of 1000 not 1024
- -H, --dereference-command-line
- follow symbolic links listed on the command line
- --dereference-command-line-symlink-to-dir
- follow each command line symbolic link
- that points to a directory
- --hide=PATTERN do not list implied entries matching shell PATTERN
- (overridden by -a or -A)
- --indicator-style=WORD append indicator with style WORD to entry names:
- none (default), slash (-p),
- file-type (--file-type), classify (-F)
- -i, --inode print the index number of each file
- -I, --ignore=PATTERN do not list implied entries matching shell PATTERN
- -k, --kibibytes default to 1024-byte blocks for disk usage
- -l use a long listing format
- -L, --dereference when showing file information for a symbolic

- link, show information for the file the link
- references rather than for the link itself
- -m fill width with a comma separated list of entries
- -n, --numeric-uid-gid like -l, but list numeric user and group IDs
- -N, --literal print entry names without quoting
- -o like -l, but do not list group information
- -p, --indicator-style=slash
- append / indicator to directories
- -q, --hide-control-chars print ? instead of nongraphic characters
- --show-control-chars show nongraphic characters as-is (the default, unless program is 'ls' and output is a terminal)
- -Q, --quote-name enclose entry names in double quotes
- --quoting-style=WORD use quoting style WORD for entry names:
 - literal, locale, shell, shell-always,
 - shell-escape, shell-escape-always, c, escape
- -r, --reverse reverse order while sorting
- -R, --recursive list subdirectories recursively
- -s, --size print the allocated size of each file, in blocks
- -S sort by file size, largest first
- --sort=WORD sort by WORD instead of name: none (-U), size (-S),
 - time (-t), version (-v), extension (-X)
- --time=WORD with -l, show time as WORD instead of default
 - modification time: atime or access or use (-u);
 - ctime or status (-c); also use specified time
- as sort key if --sort=time (newest first)
- --time-style=STYLE with -l, show times using style STYLE:
 - full-iso, long-iso, iso, locale, or +FORMAT;
 - FORMAT is interpreted like in 'date'; if FORMAT
 - is FORMAT1FORMAT2, then FORMAT1 applies
 - to non-recent files and FORMAT2 to recent files;
 - if STYLE is prefixed with 'posix-', STYLE
 - takes effect only outside the POSIX locale
- -t sort by modification time, newest first
- -T, --tabsize=COLS assume tab stops at each COLS instead of 8
- -u with -lt: sort by, and show, access time;
- with -l: show access time and sort by name;
- otherwise: sort by access time, newest first
- -U do not sort; list entries in directory order
- -v natural sort of (version) numbers within text
- -w, --width=COLS set output width to COLS. 0 means no limit
- -x list entries by lines instead of by columns
- -X sort alphabetically by entry extension
- -Z, --context print any security context of each file
- -1 list one file per line. Avoid '\n' with -q or -b
- --append-exe append .exe if cygwin magic was needed
- --help display this help and exit
- --version output version information and exit
- The SIZE argument is an integer and optional unit (example: 10K is 10*1024).
- Units are K,M,G,T,P,E,Z,Y (powers of 1024) or KB,MB,... (powers of 1000).
- Using color to distinguish file types is disabled both by default and
- with --color=never. With --color=auto, ls emits color codes only when
- standard output is connected to a terminal. The LS_COLORS environment

- variable can change the settings. Use the `dircolors` command to set it.
- Exit status:
- 0 if OK,
- 1 if minor problems (e.g., cannot access subdirectory),
- 2 if serious trouble (e.g., cannot access command-line argument).
- test invocation
- `coreutils`
- Multi-call invocation
- `sha224sum`
- `sha2` utilities
- `sha256sum`
- `sha384sum`
- `sha512sum`
- `%s` online help: `<%s>`
- <http://www.gnu.org/software/coreutils/>
- GNU `coreutils`
- Report `%s` translation bugs to <http://translationproject.org/team/>
- Full documentation at: `<%s%s>`
- or available locally via: `info '(coreutils) %s%s'`
- `full-iso`
- `locale`
- `/usr/share/locale`
- `QUOTING_STYLE`
- ignoring invalid value of environment variable `QUOTING_STYLE`: `%s`
- `COLUMNS`
- ignoring invalid width in environment variable `COLUMNS`: `%s`
- `TABSIZE`
- ignoring invalid tab size in environment variable `TABSIZE`: `%s`
- `abcdefghijklmnopqrstuvwxyz:ABCDEFGHI:LNQRST:UXZ1`
- invalid line width
- `%s: %s`
- invalid tab size
- `--sort`
- `--time`
- `--format`
- `--color`
- `--indicator-style`
- `--quoting-style`
- David MacKenzie
- Richard M. Stallman
- `LSBLOCKSIZE`
- `BLOCK_SIZE`
- `TIME_STYLE`
- invalid time style format `%s`
- time style
- Valid arguments are:
- - `[posix-]%s`
- - `+FORMAT` (e.g., `+%H:%M`) for a 'date'-style format
- `%Y-%m-%d %H:%M:%S.%N %z`

- %Y-%m-%d %H:%M
- %Y-%m-%d
- %m-%d %H:%M
- LSCOLORS
- COLORTERM
- *target*
- *devino*size <= *obstack*objectsiz (&devinoobstack)
- //DIRED//
- //SUBDIRED//
- //DIRED-OPTIONS// --quoting-style=%s
- *hashgetnentries* (*activedirset*) == 0
- unrecognized prefix: %s
- unparsable value for LSCOLORS *environment variable*
- *devinopop*
- *sortfiles*
- posix-
- always
- if-tty
- access
- status
- extension
- version
- verbose
- commas
- horizontal
- across
- vertical
- single-column
- escape
- directory
- full-time
- group-directories-first
- human-readable
- kibibytes
- numeric-uid-gid
- no-group
- hide-control-chars
- reverse
- almost-all
- ignore-backups
- classify
- file-type
- dereference-command-line
- dereference-command-line-symlink-to-dir
- ignore
- indicator-style
- dereference
- literal
- quote-name
- quoting-style
- recursive
- format

- show-control-chars
- tabsize
- time-style
- block-size
- context
- author
- append-exe
- %b %e %Y
- %b %e %H:%M
- long-iso
- ?pcdb-lswd
- # Configuration file for dircolors, a utility to help you set the
- # LSCOLORS environment variable used by GNU ls with the --color option.
- # Copyright (C) 1996-2016 Free Software Foundation, Inc.
- # Copying and distribution of this file, with or without modification,
- # are permitted provided the copyright notice and this notice are preserved.
- # The keywords COLOR, OPTIONS, and EIGHTBIT (honored by the
- # slackware version of dircolors) are recognized but ignored.
- # Below are TERM entries, which can be a glob patterns, to match
- # against the TERM environment variable to determine if it is colorizable.
- TERM Eterm
- TERM ansi
- TERM color
- TERM con[0-9]x[0-9]
- TERM cons25
- TERM console
- TERM cygwin
- TERM dtterm
- TERM gnome
- TERM hurd
- TERM jfbterm
- TERM konsole
- TERM kterm
- TERM linux
- TERM linux-c
- TERM mlterm
- TERM putty
- TERM rxvt*
- TERM screen*
- TERM st
- TERM terminator
- TERM tmux*
- TERM vt100
- TERM xterm*
- # Below are the color init strings for the basic file types. A color init
- # string consists of one or more of the following numeric codes:
- # Attribute codes:
- # 00=none 01=bold 04=underscore 05=blink 07=reverse 08=concealed
- # Text color codes:
- # 30=black 31=red 32=green 33=yellow 34=blue 35=magenta 36=cyan 37=white
- # Background color codes:
- # 40=black 41=red 42=green 43=yellow 44=blue 45=magenta 46=cyan 47=white

- *#NORMAL 00 # no color code at all*
- *#FILE 00 # regular file: use no color at all*
- *RESET 0 # reset to "normal" color*
- *DIR 01;34 # directory*
- *LINK 01;36 # symbolic link. (If you set this to 'target' instead of a*
- *# numerical value, the color is as for the file pointed to.)*
- *MULTIHARDLINK 00 # regular file with more than one link*
- *FIFO 40;33 # pipe*
- *SOCK 01;35 # socket*
- *DOOR 01;35 # door*
- *BLK 40;33;01 # block device driver*
- *CHR 40;33;01 # character device driver*
- *ORPHAN 40;31;01 # symlink to nonexistent file, or non-stat'able file ...*
- *MISSING 00 # ... and the files they point to*
- *SETUID 37;41 # file that is setuid (u+s)*
- *SETGID 30;43 # file that is setgid (g+s)*
- *CAPABILITY 30;41 # file with capability*
- *STICKYOTHERWRITABLE 30;42 # dir that is sticky and other-writable (+t,o+w)*
- *OTHERWRITABLE 34;42 # dir that is other-writable (o+w) and not sticky*
- *STICKY 37;44 # dir with the sticky bit set (+t) and not other-writable*
- *# This is for files with execute permission:*
- *EXEC 01;32*
- *# List any file extensions like '.gz' or '.tar' that you would like ls*
- *# to colorize below. Put the extension, a space, and the color init string.*
- *# (and any comments you want to add after a '#')*
- *# If you use DOS-style suffixes, you may want to uncomment the following:*
- *#.cmd 01;32 # executables (bright green)*
- *#.exe 01;32*
- *#.com 01;32*
- *#.btm 01;32*
- *#.bat 01;32*
- *# Or if you want to colorize scripts even if they do not have the*
- *# executable bit actually set.*
- *#.sh 01;32*
- *#.csh 01;32*
- *# archives or compressed (bright red)*
- *.tar 01;31*
- *.tgz 01;31*
- *.arc 01;31*
- *.arj 01;31*
- *.taz 01;31*
- *.lha 01;31*
- *.lz4 01;31*
- *.lzh 01;31*
- *.lzma 01;31*
- *.tlz 01;31*
- *.txz 01;31*
- *.tzo 01;31*
- *.t7z 01;31*
- *.zip 01;31*
- *.z 01;31*
- *.Z 01;31*

- .dz 01;31
- .gz 01;31
- .lrz 01;31
- .lz 01;31
- .lzo 01;31
- .xz 01;31
- .zst 01;31
- .tzst 01;31
- .bz2 01;31
- .bz 01;31
- .tbz 01;31
- .tbz2 01;31
- .tz 01;31
- .deb 01;31
- .rpm 01;31
- .jar 01;31
- .war 01;31
- .ear 01;31
- .sar 01;31
- .rar 01;31
- .alz 01;31
- .ace 01;31
- .zoo 01;31
- .cpio 01;31
- .7z 01;31
- .rz 01;31
- .cab 01;31
- # image formats
- .jpg 01;35
- .jpeg 01;35
- .mjpg 01;35
- .mjpeg 01;35
- .gif 01;35
- .bmp 01;35
- .pbm 01;35
- .pgm 01;35
- .ppm 01;35
- .tga 01;35
- .xbm 01;35
- .xpm 01;35
- .tif 01;35
- .tiff 01;35
- .png 01;35
- .svg 01;35
- .svgz 01;35
- .mng 01;35
- .pcx 01;35
- .mov 01;35
- .mpg 01;35
- .mpeg 01;35
- .m2v 01;35
- .mkv 01;35

- .webm 01;35
- .ogm 01;35
- .mp4 01;35
- .m4v 01;35
- .mp4v 01;35
- .vob 01;35
- .qt 01;35
- .nuv 01;35
- .wmv 01;35
- .asf 01;35
- .rm 01;35
- .rmvb 01;35
- .flc 01;35
- .avi 01;35
- .fli 01;35
- .flv 01;35
- .gl 01;35
- .dl 01;35
- .xcf 01;35
- .xwd 01;35
- .yuv 01;35
- .cgm 01;35
- .emf 01;35
- # [http://wiki.xiph.org/index.php/MIME TypesandFileExtensions](http://wiki.xiph.org/index.php/MIME%20TypesandFileExtensions)
- .ogv 01;35
- .ogx 01;35
- # audio formats
- .aac 00;36
- .au 00;36
- .flac 00;36
- .m4a 00;36
- .mid 00;36
- .midi 00;36
- .mka 00;36
- .mp3 00;36
- .mpc 00;36
- .ogg 00;36
- .ra 00;36
- .wav 00;36
- # [http://wiki.xiph.org/index.php/MIME TypesandFileExtensions](http://wiki.xiph.org/index.php/MIME%20TypesandFileExtensions)
- .oga 00;36
- .opus 00;36
- .spx 00;36
- .xspf 00;36
- invalid argument %s for %s
- ambiguous argument %s for %s
- Valid arguments are:
- - %s
- write error
- %s: %s
- # entries: %lu

- # buckets: %lu
- # buckets used: %lu (%.2f%%)
- max bucket length: %lu
- BLOCKSIZE
- BLOCKSIZE
- POSIXLYCORRECT
- eEgGkKmMpPtTyYzZ0
- human-readable
- KMGTPPEZY
- A NULL argv[0] was passed through an exec system call.
- /.libs/
- literal
- shell-always
- shell-escape
- shell-escape-always
- c-maybe
- escape
- locale
- clocale
- %m/%d/%y
- %Y-%m-%d
- %H:%M:%S
- %s (%s) %s
- Packaged by %s (%s)
- 8.26-2
- Cygwin
- License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>.
- This is free software: you are free to change and redistribute it.
- There is NO WARRANTY, to the extent permitted by law.
- Written by %s.
- Written by %s and %s.
- Written by %s, %s, and %s.
- Written by %s, %s, %s,
- and %s.
- Written by %s, %s, %s,
- %s, and %s.
- Written by %s, %s, %s,
- %s, %s, and %s.
- Written by %s, %s, %s,
- %s, %s, %s, and %s.
- Written by %s, %s, %s,
- %s, %s, %s, %s,
- and %s.
- Written by %s, %s, %s,
- %s, %s, %s, %s,
- %s, and %s.
- Written by %s, %s, %s,
- %s, %s, %s, %s,
- %s, %s, and others.
- Report bugs to: %s
- bug-coreutils@gnu.org
- Report %s bugs to: %s

- cygwin@cygwin.com
- %s home page: <%s>
- <http://www.gnu.org/software/coreutils/>
- GNU coreutils
- General help using GNU software: <http://www.gnu.org/gethelp/>
- Copyright %s %d Free Software Foundation, Inc.
- memory exhausted
- %s: %s
- 0 <= strtolbase && strtolbase <= 36
- /usr/src/coreutils-8.26-2.i686/src/coreutils-8.26/lib/xstrtoul.c
- xstrtoul
- invalid %s%s argument '%s'
- invalid suffix in %s%s argument '%s'
- %s%s argument '%s' too large
- 0 <= strtolbase && strtolbase <= 36
- /usr/src/coreutils-8.26-2.i686/src/coreutils-8.26/lib/xstrtoul.c
- xstrtoulmax
- POSIXLYCORRECT
- list != NULL
- /usr/src/coreutils-8.26-2.i686/src/coreutils-8.26/lib/fnmatchloop.c
- p[-1] == L('(')
- ! "Invalid extended matching operator"
- mbsinit (&ps)
- /usr/src/coreutils-8.26-2.i686/src/coreutils-8.26/lib/fnmatch.c
- extmatch
- extwmatch
- gnufnmatch
- memory exhausted
- CP1361
- CP20127
- CP20866
- KOI8-R
- CP20936
- GB2312
- CP21866
- KOI8-RU
- CP28591
- ISO-8859-1
- CP28592
- ISO-8859-2
- CP28593
- ISO-8859-3
- CP28594
- ISO-8859-4
- CP28595
- ISO-8859-5
- CP28596
- ISO-8859-6
- CP28597
- ISO-8859-7
- CP28598
- ISO-8859-8

- [illegible]

- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0 20160603 (Fedora Cygwin 5.4.0-2)
- GCC: (GNU) 5.4.0
- GCC: (GNU) 5.4.0
- *assertfunc*
- *cxatexit*
- **errno**
- *getreent*
- *localectypeptr*
- *localembcurmax*
- **main**
- *dllcrt0@0*
- **fstat64**
- *getgrgid32*
- *getgrnam32*
- *getpwuid32*
- *impureptr*
- **lstat64**
- *stat64*
- *aclextendedfile*
- *calloc*
- *clock_gettime*
- *closedir*
- *cygwindetachdll*
- *cygwininternal*
- *dllcrt0*
- *fclose*
- *fflushunlocked*

- *fprintf*
- *fputsunlocked*
- *fwrite*
- *fwriteunlocked*
- *getenv*
- *getgrgid*
- *getgrnam*
- *getoptlong*
- *getpwnam*
- *getpwuid*
- *gettimeofday*
- *gmtime*
- *isatty*
- *iswcntrl*
- *iswctype*
- *iswprint*
- *localeconv*
- *localtime*
- *longjmp*
- *malloc*
- *mbrtowc*
- *mbsinit*
- *mbsrtowcs*
- *mbstowcs*
- *memchr*
- *memcmp*
- *memcpy*
- *memmove*
- *mempcpy*
- *memset*
- *nllanginfo*
- *opendir*
- *optarg*
- *optind*
- *posixmemalign*
- *printf*
- *programinvocationname*
- *programinvocationshortname*
- *putcunlocked*
- *readdir*
- *readlink*
- *realloc*
- *setenv*
- *setjmp*
- *setlocale*
- *sigaction*
- *sigaddset*
- *sigemptyset*
- *sigismember*
- *signal*
- *sigprocmask*
- *snprintf*

- **sprintf**
- **stpcpy**
- **stpncpy**
- **strcasecmp**
- **strcat**
- **strchr**
- **strcmp**
- **strcoll**
- **strcpy**
- **strdup**
- **strftime**
- **strlen**
- **strncmp**
- **strrchr**
- **strtoul**
- **strtoumax**
- **tcgetpgrp**
- **timegm**
- **tolower**
- **toupper**
- **towlower**
- **unsetenv**
- **wcscat**
- **wcslen**
- **wcstombs**
- **wcswidth**
- **wctype**
- **wcwidth**
- **wmemchr**
- **wmemcpy**
- **libintlbindtextdomain**
- **libintldcgettext**
- **libintlgettext**
- **libintlsetlocale**
- **libintltextdomain**
- *divdi3*
- **moddi3**
- *udivdi3*
- *umoddi3*
- *FreeLibrary*
- *GetACP*
- *GetModuleHandleA*
- *GetModuleHandleW*
- *GetProcAddress*
- *LoadLibraryA*
- *cygwin1.dll*
- *cygintl-8.dll*
- *cyggccs-1.dll*
- *KERNEL32.dll*
-
-
-

- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .
- .ls.exe.dbg
- .ehframe
- .gnudebuglink

UTF-8 Strings

No detected.

UTF-16LE Strings

No detected.

Extracted URLs

- <http://www.gnu.org/software/coreutils/>
- <http://translationproject.org/team/>
- [http://wiki.xiph.org/index.php/MIME *Types*and*File*Extensions](http://wiki.xiph.org/index.php/MIME%20TypesandFileExtensions)
- [http://wiki.xiph.org/index.php/MIME *Types*and*File*Extensions](http://wiki.xiph.org/index.php/MIME%20TypesandFileExtensions)
- <http://gnu.org/licenses/gpl.html>
- <http://www.gnu.org/software/coreutils/>
- <http://www.gnu.org/gethelp/>

Base64 Strings

No valid Base64-encoded strings found.

File Entropy Analysis

- **Entropy:** 6.36
- **Status:** This file is likely packed or encrypted.

VirusTotal Analysis

Scan Date: 2024-08-26 00:52:22

Scan Results

- Malicious: 0
- Suspicious: 0
- Undetected: 75
- Harmless: 0
- Timeout: 0
- Confirmed-timeout: 0
- Failure: 0
- Type-unsupported: 4

Community Votes

- Harmless: 0
- Malicious: 0

Virus Total Permalink

- No VirusTotal link available.

Detailed Engine Results

Engine Name	Detection Category	Detection
No results	No results	No results