

Malware Analysis Report For elf-Linux-Mips4-bash

Binary Type

ELF (Executable and Linkable Format). (Approved)

Analyzing File

- **File Name:** elf-Linux-Mips4-bash
 - **File Extension:**
 - **File Type:** ELF (Executable and Linkable Format).
 - **MD5 Hash:** 628f094cff8ec9d9e36c5b94460c7454
 - **SHA256 Hash:** 97157e2bc3a9726593edb9e517911d71255811fdd0f2a8a6be03389d8fb75927
-

File Identification

File detected as a valid Linux executable.

ELF File Analysis

ELF File Analysis: True

ELF File Imports

- libcurses.so.5
- libdl.so.2
- libc.so.6

ELF File Exports

No Exported functions were found.

String Analysis

ASCII Strings

- /lib/ld.so.1
- __libccsu_init
- __libccsu_fini
- __libcstart_main
- gmon_start
- JvRegisterClasses
- current_user
- getpwuid
- xmalloc
- strcpy
- endpwent
- dcgettext

- `closebufferedfd`
- `defaultbufferedinput`
- `remember_args`
- `pop_args`
- `setuid`
- `setgid`
- `base_pathname`
- `setvarread_only`
- `signalistrapped`
- `interactive_shell`
- `unlinkfifolist`
- `subshell_environment`
- `endjobcontrol`
- `sh_exit`
- `runexittrap`
- `maybesaveshell_history`
- `huponexit`
- `hangupalljobs`
- `bashhistoryreinit`
- `posixly_correct`
- `setjobcontrol`
- `expand_aliases`
- `nolineediting`
- `startup_state`
- `shell_name`
- `long_args`
- `xstrchr`
- `shellversionstring`
- `exitimmediatelyon_error`
- `maybeexecutefile`
- `functiontracemode`
- `expandstringunsplittostring`
- `privileged_mode`
- `commandexecutionstring`
- `find_variable`
- `getstringvalue`
- `fileno`
- `isnetconn`
- `__sigsetjmp`
- `lastcommandexit_value`
- `command_error`
- `withinputfrom_string`
- `parse_command`
- `global_command`
- `protected_mode`
- `expandwordsno_vars`
- `parseandexecute`
- `array_rshift`
- `isatty`
- `lseek64`
- `checkbinaryfile`

- `movetohigh_fd`
- `forced_interactive`
- `executinglinenumber`
- `_ermolocation`
- `absolute_program`
- `file_error`
- `findpathfile`
- `__fxstat64`
- `internal_error`
- `make_word`
- `makewordlist`
- `list_reverse`
- `push_args`
- `dispose_words`
- `checkdevtty`
- `debuggingloginshell`
- `setdefaultlocale`
- `getuid`
- `getgid`
- `geteuid`
- `getegid`
- `subshelltoplevel`
- `shell_initialized`
- `wantpendingcommand`
- `readfromstdin`
- `primary_prompt`
- `secondary_prompt`
- `currentcommandnumber`
- `executing`
- `deleteallcontexts`
- `deleteallvariables`
- `shellstarttime`
- `thiscommandname`
- `setloginshell`
- `dumppostrings`
- `dumptranslatablestrings`
- `readbutdont_execute`
- `disableprivmode`
- `cmd_init`
- `wordexp_only`
- `shopt_setopt`
- `stderr`
- `initializeshell/builtins`
- `currenthostname`
- `initialize_traps`
- `initialize_signals`
- `getcurrentuser_info`
- `tilde_initialize`
- `initializeshell/variables`
- `initializejobcontrol`
- `initializebashinput`

- initialize_flags
- initialize*shell*options
- set*default*locale_vars
- change_flag
- unbind_variable
- shell/isrestricted
- restricted_shell
- debugging_mode
- exit_shell
- report_error
- subshell_argc
- subshell_argv
- subshell_envp
- strstr
- running*under*emacs
- gnuerrorformat
- sv*strict*posix
- sh_setlinebuf
- stdout
- maybe*make*restricted
- set*minus*_option
- gethostname
- xrealloc
- list*minus*_opts
- shopt_listopt
- showshell/version
- shunsetnodelay_mode
- withinputfrom_stdin
- remembermaildates
- reader_loop
- withinputfrom_stream
- withinputfrombufferedstream
- resetmailtimer
- bashinitializehistory
- getttystate
- historylinesthis_session
- load_history
- echoinputat_read
- bash_logout
- jumptotop_level
- needheredoc
- runpendingtraps
- currentcommandline_count
- executepromptcommand
- yyparse
- gatherheredocuments
- getworkingdirectory
- setcurrentprompt_level
- interrupt_state
- throwtotop_level
- setsignalhandler

- `_strtolinternal`
- `indirection_level`
- `EOF_Reached`
- `signal/ignored`
- `disposeusedenv_vars`
- `read_command`
- `execute_command`
- `stdin_redir`
- `dispose_command`
- `justonecommand`
- `sigint_sighandler`
- `variable_context`
- `currentreadlineline_index`
- `currentreadlineline`
- `stream_list`
- `dstack`
- `currentpromptstring`
- `ps2_prompt`
- `ps1_prompt`
- `promptstringpointer`
- `pushedstringlist`
- `restoretokenstate`
- `eof_encountered`
- `rememberonhistory`
- `historyexpansioninhibited`
- `lastshellbuiltin`
- `thisshellbuiltin`
- `array_dispose`
- `savetokenstate`
- `array_copy`
- `wordtokenalist`
- `parser_error`
- `inityyio`
- `streamonstack`
- `findtokenin_alist`
- `othertokenalist`
- `yyval`
- `string/istinternal`
- `fflush`
- `mbrtowc`
- `reset_parser`
- `substring`
- `promptvars`
- `dequote_string`
- `expandpromptstring`
- `subappendstring`
- `history_number`
- `strncpy`
- `politedirectoryformat`
- `shbackslashquotefordouble_quotes`
- `patch_level`

- dist_version
- localtime
- ttyname
- countalljobs
- strftime
- read_octal
- strchr
- getcwd
- decodepromptstring
- currentreadlineprompt
- sigwinch_received
- getnewwindow_size
- notifyandcleanup
- preprocessline
- historydelimitingchars
- maybeaddhistory
- clearerr
- sh_syntaxtab
- extended_quote
- localeexpand
- sh_mkdoublequoted
- ansiexpand
- shsinglequote
- makeheredocument
- extended_glob
- builtinaddressinternal
- find_alias
- legal_number
- legal_identifier
- interactive_comments
- yyerror
- allocworddesc
- test_unop
- makecondnode
- dispose_word
- makewordfrom_token
- disposecondnode
- test_binop
- makecondcommand
- saveparserstate
- restoreparserstate
- bashinputfd_changed
- setbufferedstream
- xbcopy
- bashhistorydisable
- push_stream
- pop_stream
- ungetcwithrestart
- interrupt_immediately
- bashreadlineinitialized
- initialize_readline

- shell_pgrp
- giveterminalto
- yychar
- yynerrs
- memcpy
- makeforcommand
- timetocheck_mail
- makepatternlist
- command_connect
- makecasecommand
- makefunctiondef
- makesubshellcommand
- makeifcommand
- makegroupcommand
- makearithcommand
- eofencounteredlimit
- exit_builtin
- makesimplecommand
- make_redirection
- makearithfor_command
- makeselectcommand
- cleansimplecommand
- makewhilecommand
- makeuntilcommand
- connectasynclist
- sourceusespath
- sourcesearchescwd
- getmaxgroups
- getgroups
- tildeexpansionpreexpansion_hook
- strvec_create
- tildeadditionalprefixes
- tildeadditionalsuffixes
- getdirstackfrom_string
- strncmp
- sh_makepath
- bashtildeexpand
- __xstat64
- file_isdir
- test_eaccess
- _ctypeb_loc
- getdtablesize
- skipsubscript
- all_digits
- _strtol_internal
- __umoddi3
- __udivdi3
- make_command
- wlcache
- makebaresimple_command
- wdcache

- programming_error
- stringquoteremoval
- readsecondaryline
- _ctypegetmbcur_max
- makebareword
- makewordflags
- theprintedcommand
- theprintedcommand_size
- commandstringindex
- ansic_shouldquote
- ansic_quote
- copy_redirect
- dispose_redirects
- printcondcommand
- printarithcommand
- addunwindprotect
- copy_command
- removeunwindprotect
- printsimplecommand
- strlen
- indirectionlevel/string
- fwrite
- shcontainsshell_metas
- xtraceprintword_list
- vfprintf
- makecommandstring
- disposefunctiondef
- disposefunctiondef_contents
- sys_error
- executable_file
- deleteallaliases
- withoutjobcontrol
- setsigchldhandler
- initjobstats
- resetshellflags
- resetshelloptions
- resetshoptoptions
- clearunwindprotect_list
- returncatchflag
- setsiginthandler
- strvec_len
- strvec_resize
- unbind_args
- siglongjmp
- unsetbashinput
- setsignalignored
- execredirectionundo_list
- do_redirections
- eval_builtin
- source_builtin
- unset_builtin

- `return_builtin`
- `discardunwindframe`
- `rununwindframe`
- `beginunwindframe`
- `mergetemporaryenv`
- `push_scope`
- `pop_scope`
- `unwindprotectmem`
- `echocommandat_execute`
- `xtraceprintarith_cmd`
- `signalinprogress`
- `theprintedcommandexcepttrap`
- `rundebugtrap`
- `evalexp`
- `sigprocmask`
- `condexpandword`
- `sh_regmatch`
- `binary_test`
- `xtraceprintcond_term`
- `unary_test`
- `memset`
- `currentfdsto_close`
- `newfdbitmap`
- `disposefdbitmap`
- `executecommandinternal`
- `loop_level`
- `breaking`
- `continuing`
- `reapdeadjobs`
- `check_identifier`
- `xtraceprintselectcommandhead`
- `list_length`
- `read_builtin`
- `/Oputc`
- `xtraceprintforcommandhead`
- `make_child`
- `stop_pipeline`
- `describe_pid`
- `wait_for`
- `stdin_redirects`
- `copy_redirects`
- `xtraceprintcasecommandhead`
- `expandwordunsplit`
- `lastmadeqid`
- `alreadymakingchildren`
- `disposeexecredirects`
- `expandwordleave_quoted`
- `quotestringfor_globbing`
- `matchignorecase`
- `find_function`
- `sigemptyset`

- sigaddset
- closefdbitmap
- terminatecurrentpipeline
- killcurrentpipeline
- runerrortrap
- bind_function
- push_context
- pop_context
- return_catch
- thisshellfunction
- makefuncnamevisible
- errortracemode
- restoredefaultsignal
- findfunctiondef
- returncatchvalue
- runreturntrap
- array_shift
- arraydisposeelement
- trap_list
- setdebugtrap
- seterrortrap
- setreturntrap
- jobs_builtin
- maybeexport_env
- lastasynchronouspid
- lastcommandsubst_pid
- expand_words
- findspecialbuiltin
- tempenvassignerror
- setpipestatusfrom_exit
- restoreoriginalsignals
- setupasyncsignals
- subshell_level
- copywordlist
- exec_builtin
- ferror
- command_builtin
- searchforcommand
- putcommandnameintoenv
- builtin_address
- getjobby_name
- start_job
- findshellbuiltin
- strvecfromword_list
- shell_execve
- original_pgrp
- resetterminatingsignals
- gettimeofday
- getusage
- difftimeval
- timevaltosecs

- `addtimeval`
- `timevaltocpu`
- `setuphistoryignore`
- `setupglobignore`
- `freemailfiles`
- `phash_flush`
- `setdollarvars_unchanged`
- `listrestof_args`
- `hash_dispose`
- `global_variables`
- `disposevarcontext`
- `shellfunctiondefs`
- `expanding_redir`
- `var_lookup`
- `findvariableinternal`
- `posix_initialize`
- `posixreadlineinitialize`
- `set_shellopts`
- `historywritetimestamps`
- `clearhostnamelist`
- `hostnamelistinitialized`
- `rlcompleterwordbreakcharacters`
- `setifs`
- `popdollarvars`
- `popvarcontext`
- `sv_ifs`
- `arrayneedsmaking`
- `newvarcontext`
- `pushdollarvars`
- `pushvarcontext`
- `rlbasicwordbreakcharacters`
- `sort_variables`
- `mapoverfuncs`
- `map_over`
- `addorsupercedeexportedvar`
- `updateexportenv_inplace`
- `allvisiblevariables`
- `dispose_variable`
- `stupidlyhackspecial_variables`
- `makunbound`
- `setitemlistdirty`
- `it_functions`
- `xtraceprintassignment`
- `expandassignmentstringtostring`
- `err_readonly`
- `copyfunctiondef`
- `copyfunctiondef_contents`
- `markmodifiedvars`
- `array_create`
- `array_insert`
- `array_flush`

- `makenewarray_variable`
- `setpipestatusarray`
- `getvariablevalue`
- `makevariablevalue`
- `noinvisiblevars`
- `validarrayreference`
- `arrayvariablepart`
- `assignarrayelement`
- `fmtulong`
- `bindintvariable`
- `sh_readonly`
- `makelocalvariable`
- `setlocalevar`
- `set_lang`
- `sh_opterr`
- `historyexpansionchar`
- `historysubstchar`
- `historycommentchar`
- `extractcolonunit`
- `unstifle_history`
- `historytruncatefile`
- `historylinesin_file`
- `where_history`
- `rlresetterminal`
- `getpid`
- `getrandomnumber`
- `namedfunctionstring`
- `printvarfunction`
- `putchar`
- `printarrayassignment`
- `printvarvalue`
- `getppid`
- `same_file`
- `setworkingdirectory`
- `__divdi3`
- `__moddi3`
- `internal_warning`
- `set_pwd`
- `dollardollarpid`
- `setifnot`
- `adjustshelllevel`
- `set_ppid`
- `getopts_reset`
- `findusercommand`
- `full_pathname`
- `build_version`
- `release_status`
- `sv_histsize`
- `sv_ignoreeof`
- `svhistorycontrol`
- `sv_histignore`

- file_status
- make_absolute
- sh_canonpath
- shgethome_dir
- getgrouplist
- setdirstackelement
- getdirectorystack
- arrayfromword_list
- enablehostnamecompletion
- performhostnamecompletion
- _strtoulinternal
- strvec_flush
- svcompwordbreaks
- sv_globignore
- sv_histtimefmt
- sv_hostfile
- sv_locale
- sv_mail
- sv_opterr
- sv_optind
- sv_path
- sv_terminal
- sv_histchars
- copy_word
- lasthistoryline
- getnamefor_error
- yyinputname
- bashbadsuberrmsg
- unboundvarsis_error
- err_unboundvar
- arrayvariablename
- getarrayvalue
- __cmpdi2
- brace_expansion
- disallowfilenameglobbing
- placekeywordsin_env
- noclobber
- jobsmflag
- pipefail_opt
- nosymboliclinks
- hashing_enabled
- asynchronous_notification
- history_expansion
- optflags
- find_flag
- pipeline_pgrp
- waitforbackground_pids
- nohup_job
- strsignal
- thecurrentworking_directory
- signal_name

- waitpid
- maybecalltrap_handler
- lastcommandexit_signal
- substassignvarlist
- maybe_setsigchld_trap
- terminationunwindprotect
- traptosighandler
- bgpids
- shell_tty
- tcsetpgrp
- terminal_pgrp
- initializejobsignals
- getmaxchild
- killpg
- terminatestoppedjobs
- setpgid
- wait_builtin
- waitsignalreceived
- waitintrbuf
- tcsetattr
- tcgetattr
- checkwindow_size
- tcgetpgrp
- delete_job
- sourcelevel
- setttystate
- waitforsingle_pid
- stopmakingchildren
- cleanupthepipeline
- start_pipeline
- deletealljobs
- syncbufferedstream
- top/level/mask
- defaultttyjob_signals
- ignorettyjob_signals
- ifs_value
- ifs_cmap
- expand_string
- xdupmbstowcs
- wcsdup
- wcsmatch
- wcsrtombs
- ifs_var
- ifsfirstclen
- ifs_firstc
- wcslen
- resetsignalhandlers
- freepushedstring_input
- closepgrppipe
- currentcommandsubst_pid
- strip_trailing

- `mbtowc`
- `wcschr`
- `list_string`
- `word_split`
- `quote_escapes`
- `stringlistdollar_star`
- `expandstringassignment`
- `expandstringunsplit`
- `assignarrayfrom_string`
- `extractarrayassignment_list`
- `makeocalarray_variable`
- `assignarrayvarfromstring`
- `skiptodelim`
- `disposeworddesc`
- `expandarithstring`
- `numberofargs`
- `allvariablesmatching_prefix`
- `strvectoword_list`
- `stringlistdollar_at`
- `array_keys`
- `mbstrlen`
- `array_subrange`
- `arraytoword_list`
- `extractarithmeticsubst`
- `extractcommandsubst`
- `command_substitute`
- `whichsefflags`
- `extractprocesssubst`
- `de_backslash`
- `bashtildefind_word`
- `save_pipeline`
- `restore_pipeline`
- `dowordassignment`
- `wordlistremovequotednulls`
- `brace_expand`
- `assigninenv`
- `strvec_dispose`
- `unquotedglobpattern_p`
- `shellglobfilename`
- `globerrorreturn`
- `failglobexpansion`
- `allownullglob_expansion`
- `pat_subst`
- `array_patsub`
- `arrayexpandindex`
- `getdollarvar_value`
- `err_badarraysub`
- `phash_create`
- `hash_string`
- `mailstat`
- `mail_warning`

- `expandstringto_string`
- `makedefaultmailpath`
- `trapsavedexit_value`
- `running_trap`
- `initializeterminatingsignals`
- `set_signal`
- `signal_names`
- `runinterrupttrap`
- `strcasecmp`
- `freebufferedstream`
- `closebufferedstream`
- `fdtobuffered_stream`
- `buffered_getchar`
- `return_EOF`
- `buffered_ungetchar`
- `fdisbash_input`
- `savebashinput`
- `setupignorepatterns`
- `noglobdofilenames`
- `shouldignoreglob_matches`
- `strvec_sort`
- `sigaction`
- `sigwinch_sighandler`
- `parseandexecute_level`
- `parseandexecute_cleanup`
- `rununwindprotects`
- `bashline_reinitialize`
- `signal/sspecial`
- `sigdelset`
- `builtin_error`
- `strcat`
- `group_member`
- `__lxstat64`
- `minusoption_value`
- `it_aliases`
- `aliasexpandall`
- `initialize_aliases`
- `arraycreateelement`
- `arrayassignlist`
- `shdoublequote`
- `array_quote`
- `getifs`
- `arraytostring`
- `arraytoassign`
- `arraykeystowordlist`
- `array_remove`
- `parsestringtowordlist`
- `convertvarto_array`
- `findomakearrayvariable`
- `bindarrayvariable`
- `strvec_copy`

- braceargseparator
- rlfilenamequoting_desired
- rlcompletionentry_function
- rlfilenamecompletion_function
- rignoreosomecompletionsfunction
- rlattemptedcompletion_function
- rlfilenamequoting_function
- rlcompleteinternal
- shbackslashquote
- historyinhibitexpansion_function
- history_base
- hist/astline_added
- hist/astline_pushed
- commandorientedhistory
- literal_history
- replacehistoryentry
- bashaddhistory
- remove_history
- strcreplace
- currentcommandfirstlinesaved
- checkaddhistory
- bashreedit
- history_expand
- hist_verify
- history_reediting
- rl_done
- rl_dispatching
- forceappendhistory
- write_history
- historyquotesinhibit_expansion
- historysearchdelimiter_chars
- read_history
- force_ignore
- rlcompletionquote_character
- rlcompletionmatches
- rlgetkeymap
- rlgenericbind
- rlbindkeyseqinmap
- rlmakebare_keymap
- rlstartuphook
- rlexecutingkeymap
- rl_ding
- rl_crlf
- rlforcedupdate_display
- setgrent
- getgrent
- endgrent
- setservent
- getservent
- endservent
- rlvariablevalue

- `rlcompletionfound_quote`
- `allvisiblefunctions`
- `executableordirectory`
- `numshellbuiltins`
- `strncasecmp`
- `rldirectoryrewrite_hook`
- `rldirectorycompletion_hook`
- `noemptycommand_completion`
- `commandwordcompletion_function`
- `absolute_pathname`
- `rlcompletionsuppress_append`
- `rlfilenamecompletion_desired`
- `rlcompletiontype`
- `rlusernamecompletion_function`
- `rlexplicitarg`
- `rlcompletionsuppress_quote`
- `rlcompletionappend_character`
- `fopen64`
- `fclose`
- `rlinserttext`
- `unclosed_pair`
- `rllinebuffer`
- `bashdefaultcompletion`
- `progcompletionenabled`
- `progcomp_size`
- `charisquoted`
- `rlattemptedcompletion_over`
- `programmable_completions`
- `rlreadkey`
- `getaliasvalue`
- `rlpushmacro_input`
- `rl_newline`
- `rlreadlinestate`
- `rl_point`
- `rl_end`
- `rlastfunc`
- `history_list`
- `history_tokenize`
- `strvec_strcmp`
- `rleditingmode`
- `rlcompletionmode`
- `rlviend_word`
- `rlvibWord`
- `rl_complete`
- `rlvistart_inserting`
- `rl_outstream`
- `rlonnew_line`
- `rl_redisplay`
- `historyisstified`
- `history_length`
- `historymaxentries`

- `rlgetprevious_history`
- `rladdundo`
- `rldeletetext`
- `rl_mark`
- `rlforwardword`
- `alias_expand`
- `rl_insert`
- `rlspecialprefixes`
- `rladddefun`
- `rlterminalname`
- `rl_instream`
- `rlreadlinename`
- `rl_yanklast_arg`
- `bashbracecompletion`
- `rl_initialize`
- `rlbindkeyifunboundinmap`
- `emacsmetakeymap`
- `emacsstandardkeymap`
- `emacsctlxkeymap`
- `rlfunctionof_keyseq`
- `rlviediting_mode`
- `rlunbindkeyinmap`
- `vimovementkeymap`
- `rltildeexpand`
- `rltabinsert`
- `rlbindkeyinmap`
- `rlcompleterquote_characters`
- `rlfilenamequote_characters`
- `rlfilenamedequoting_function`
- `rlcharisquotedp`
- `rlvariablebind`
- `viinsertionkeymap`
- `quoteglobbingchars`
- `getlocalevar`
- `mk_msgstr`
- `localetrans`
- `sh_syntabsiz`
- `setlocale`
- `bindtextdomain`
- `dotfoundin_search`
- `is_directory`
- `phash_insert`
- `phash_search`
- `checkhashedfilenames`
- `phash_remove`
- `redirection_expand`
- `sh_mktmpfd`
- `unlink`
- `checkbashinput`
- `findstringin_alist`
- `duplicatebufferedstream`

- fdopen
- netopen
- redirection_error
- strlist_create
- *allexportedvariables*
- *allarrayvariables*
- strpbrk
- getshoptoptions
- getminuso_opts
- gethostnamelist
- *rfunmapnames*
- assignarrayvarfromword_list
- clean_itemlist
- initialize_itemlist
- bashdequotetext
- *rlcompletionmarksymlinkdirs*
- bashdirectorycompletion_matches
- completionstostringlist
- strlist_append
- strlist_dispose
- it_arrayvars
- it_bindings
- it_builtins
- it_disabled
- it_enabled
- it_exports
- it_hostnames
- it_jobs
- it_keywords
- it_running
- it_setopts
- it_shopts
- it_signals
- it_stopped
- it_variables
- bashgroupnamecompletion_function
- bashservicenamecompletion_function
- splitatdelims
- executeshellfunction
- filter_stringlist
- strlistprefixsuffix
- compspec_create
- compspec_dispose
- strlist_resize
- expandwordsshellexp
- arraytoargv
- progcomp_search
- compspec_copy
- gencompspeccompletions
- prog_completes
- hash_walk

- progcomp_create
- fatal_error
- unalias_builtin
- unalias_doc
- bind_builtin
- bind_doc
- break_builtin
- break_doc
- continue_builtin
- continue_doc
- builtin_builtin
- builtin_doc
- caller_builtin
- caller_doc
- cd_builtin
- cd_doc
- pwd_builtin
- pwd_doc
- colon_builtin
- colon_doc
- true_doc
- false_builtin
- false_doc
- command_doc
- declare_builtin
- declare_doc
- typeset_doc
- local_builtin
- local_doc
- echo_builtin
- echo_doc
- enable_builtin
- enable_doc
- eval_doc
- getopts_builtin
- getopts_doc
- exec_doc
- exit_doc
- logout_builtin
- logout_doc
- fc_builtin
- fc_doc
- fg_builtin
- fg_doc
- bg_builtin
- bg_doc
- hash_builtin
- hash_doc
- help_builtin
- history_builtin
- history_doc
- jobs_doc

- disown_builtin
- disown_doc
- kill_builtin
- kill_doc
- let_builtin
- let_doc
- read_doc
- return_doc
- unset_doc
- export_builtin
- export_doc
- readonly_builtin
- readonly_doc
- shift_builtin
- shift_doc
- source_doc
- dot_doc
- suspend_builtin
- suspend_doc
- test_builtin
- test_doc
- test*bracket*doc
- times_builtin
- times_doc
- trap_builtin
- trap_doc
- type_builtin
- type_doc
- ulimit_builtin
- ulimit_doc
- umask_builtin
- umask_doc
- wait_doc
- arith*for*doc
- select_doc
- time_doc
- case_doc
- if_doc
- while_doc
- until_doc
- function_doc
- grouping*braces*doc
- fg*percent*doc
- arith_doc
- conditional_doc
- variable*help*doc
- pushd_builtin
- pushd_doc
- popd_builtin
- popd_doc
- dirs_builtin
- dirs_doc

- shopt_builtin
- shopt_doc
- printf_builtin
- printf_doc
- complete_builtin
- complete_doc
- compgen_builtin
- compgen_doc
- staticshell/builtins
- resetinternal/getopt
- builtin_usage
- loptend
- remove_alias
- sh_notfound
- legalaliasname
- add_alias
- rl/istfunmap_names
- rfunctiondumper
- rmacrodumper
- rvariabledumper
- rreadinit_file
- rnamedfunction
- rinvokingkeyseqs
- rlunbindfunctioninmap
- rlsetkey
- bindkeyseqtounixcommand
- rlparseand_bind
- list_optarg
- rlgetkeymapbyname
- rlsetkeymap
- getnumericarg
- sh_erange
- no_options
- sh_notbuiltin
- sh_invalidnum
- sh_werror
- sh_physpath
- sh_restricted
- cdable_vars
- cdspelling
- spname
- describe_command
- confstr
- current_builtin
- bashgetcwderrstr
- setdollarvars_changed
- sh_invalidsig
- decode_signal
- sh_neednumarg
- no_args
- list_opttype

- `shownameattributes`
- `sh_invalidid`
- `findtempenvvariable`
- `setorshow_attributes`
- `bindvariablevalue`
- `xpg_echo`
- `ansicstr`
- `dlopen`
- `dLError`
- `dlclose`
- `getcurrentprompt_level`
- `zcatfd`
- `runtrapcleanup`
- `unfreezejobslist`
- `noexitonfailedexec`
- `restartjobcontrol`
- `get_exitstat`
- `lcurrent`
- `strsub`
- `delete/asthistory`
- `sh_mktmpfp`
- `fcexecuteFile`
- `getjobspec`
- `sh_badjob`
- `sh_nojobs`
- `sh_needarg`
- `history_get`
- `historysetpos`
- `clear_history`
- `historygettime`
- `readhistoryrange`
- `maybeappendhistory`
- `getjobby_pid`
- `nohupalljobs`
- `listonejob`
- `liststoppedjobs`
- `listalljobs`
- `listrunningjobs`
- `sh_badpid`
- `kill_pid`
- `displaysignallist`
- `sh_invalidopt`
- `sh_validfd`
- `rnumcharstoread`
- `zreadc`
- `zsyncfd`
- `ttsave`
- `ttcbreak`
- `ttrestore`
- `getwordfrom_string`
- `ttonechar`

- `striptrailingifs_whitespace`
- `ttnoecho`
- `bashhistoryenable`
- `unbindarrayelement`
- `unbind_func`
- `sh_invalidoptname`
- `parse_shellopts`
- `list_optopt`
- `allshellvariables`
- `printvarlist`
- `allshellfunctions`
- `printfunclist`
- `dontsavefunction_defs`
- `showvarattributes`
- `setvarattribute`
- `doassignmentno_expand`
- `printshiftererror`
- `source_file`
- `disposesaveddollar_vars`
- `suspend_continue`
- `makebuiltinargv`
- `test_command`
- `print_timeval`
- `ignore_signal`
- `findreservedword`
- `usercommandmatches`
- `getrlimit64`
- `print_rlimtype`
- `stringtorlimtype`
- `setrlimit64`
- `parsesymbolicmode`
- `waitforjob`
- `sh_optind`
- `sh_badopt`
- `shgetoptrestore_state`
- `sh_getopt`
- `sh_optarg`
- `sh_optopt`
- `globignorecase`
- `asprintf`
- `bindvarto_int`
- `_strtoullinternal`
- `_strtodinternal`
- `strlist_print`
- `progcomp_walk`
- `progcomp_insert`
- `progcomp_remove`
- `progcomp_flush`
- `sysconf`
- `setvbuf`
- `fmtumax`

- `tt_setonechar`
- `tt_setnoecho`
- `tt_setcbreak`
- `ttsetattr`
- `tt_setnocanon`
- `tt_seteightbit`
- `ttgetattr`
- `regcomp`
- `regexec`
- `regfree`
- `getpeername`
- `getaddrinfo`
- `socket`
- `freeaddrinfo`
- `gai_strerror`
- `readlink`
- `pathconf`
- `file_iswdir`
- `strvec_remove`
- `strlist_copy`
- `strcoll`
- `opendir`
- `readdir64`
- `closedir`
- `_ctypetoupper_loc`
- `_ctypetolower_loc`
- `zwrite`
- `shsetlinesandcolumns`
- `rllinebuffer_len`
- `rlinsertmode`
- `rlundolist`
- `rl_prompt`
- `rlkeymap`
- `rlkeysequence_length`
- `rlpendinginput`
- `rlcatchsignals`
- `rlexecutingmacro`
- `rlcatchsigwinch`
- `rlkscxt`
- `rlbindkeyseqifunbound`
- `rlgetnext_history`
- `rlforwardchar`
- `rlbackwardchar`
- `rlbegof_line`
- `rlendof_line`
- `rlin_stream`
- `rlout_stream`
- `rlinitterminalio`
- `rlbindsttychars`
- `rlinitializemap`
- `rlinit_eightbit`

- *rlhorizontalscrollmode*
- *rlterm_autowrap*
- *rlsetkeymapfromedit_mode*
- *rlenable_meta*
- *rlinitlinestate*
- *rlstartusinghistory*
- *rlresetline_state*
- *rlparsingconditionalizedout*
- *rlviinitializeline*
- *rlsetinsertmode*
- *rlscreenwidth*
- *rlscreenchars*
- *rlscreenheight*
- *rlttysetdefaultbindings*
- *rlenablemetakey*
- *shgetenv_value*
- *rlkeyseqcxtdispose*
- *rlconvertmetacharstoascii*
- *rltolowercase_version*
- *rlnumericarg*
- *rlargsign*
- *rldigitargument*
- *rladdmacrochar*
- *rldispatching_keymap*
- *rlkeyseqcxtdalloc*
- *rlwithmacroinput*
- *rldispatch*
- *rlinput_queued*
- *rlvitextmodcommand*
- *rlvisetlast*
- *rldispatch_subseq*
- *rlunget_char*
- *rlkeyseqchaindispose*
- *rlabort_internal*
- *rlvcheck*
- *rlredisplayfunction*
- *rleraseempty_line*
- *rlwant_redisplay*
- *rleraseentireline*
- *rllastcommandwas_kill*
- *readlinetoplevel*
- *rlreset_argument*
- *rlEOF_char*
- *rlinternalcharcleanup*
- *current_history*
- *rlrevertline*
- *rlfreehistoryentry*
- *rlfreeundo_list*
- *readlineechoingp*
- *rlalreadyprompted*

- *rlonewlinewith_prompt*
- *rlpreinput_hook*
- *rlviinsertion_mode*
- *rlstrip_prompt*
- *rldisplayprompt*
- *rlexpandprompt*
- *rlvisibleprompt_length*
- *rlsetprompt*
- *rlpreterm_function*
- *rlmeta_flag*
- *rlsetsignals*
- *readlineinternal/setup*
- *readlineinternal/char*
- *readlineinternal/teardown*
- *rldepreterm_function*
- *rlclearsignals*
- *rlclearpending_input*
- *rlvilastcommand*
- *rlcallback_func*
- *rlcallback_data*
- *rlvioverstrike*
- *rlvioverstrike_delete*
- *rlvimovement_mode*
- *rl_rubout*
- *rlundo*
- *rlundo_group*
- *rlbeginundo_group*
- *rloverwrite_char*
- *rlbyteoriented*
- *rlread_mbstring*
- *rlfindprevmbchar*
- *rlvibracktype*
- *rlfindnextmbchar*
- *rlcharchsearchinternal*
- *rlcallbackdataalloc*
- *rlread_mbchar*
- *rlvibacktoindent*
- *rlkilltext*
- *rlvdelete*
- *rlvirubout*
- *rlinsert_char*
- *rlvieWord*
- *rlviewword*
- *rlvinext_word*
- *rlvibword*
- *rlviprev_word*
- *rlvifWord*
- *rlvifword*
- *rluniversalargument*
- *rlarg_overflow*

- *rlarg_getchar*
- *rlclearmessage*
- *rlstuffchar*
- *rlvidomove*
- *rlvichange_to*
- *rlviappend_mode*
- *rl_yank*
- *rladjust_point*
- *iswupper*
- *towlower*
- *wcrtomb*
- *iswlower*
- *towupper*
- *rlundogrouplevel*
- *rlvidoneinserting*
- *rlfreesavedhistory_line*
- *rlnonincreverse_search*
- *rlnonincforward_search*
- *rlnonincforwardsearchagain*
- *rlnonincreversesearchagain*
- *rlbeginningof_history*
- *rl_yanknth_arg*
- *rlundocommand*
- *rladdfunmap_entry*
- *funmapprogramsspecificentrystart*
- *rlqsortstringcompare*
- *rl_abort*
- *rlarrowkeys*
- *rlbackwardbyte*
- *rlbackwardkill_line*
- *rlbackwardkill_word*
- *rlbackwardword*
- *rlcalllastkbmacro*
- *rlcapitalizeword*
- *rlcharesearch*
- *rlbackwardchar_search*
- *rlcopybackward_word*
- *rlcopyforward_word*
- *rlcopyregiontokill*
- *rl_delete*
- *rldeleteorshowcompletions*
- *rldeletehorizontal_space*
- *rldowncaseword*
- *rldumpfunctions*
- *rldumpmacros*
- *rldumpvariables*
- *rlmacsediting_mode*
- *rlendkbd_macro*
- *rlendof_history*
- *rlexchangeptandmark*

- `rlruboutor_delete`
- `rlforwardbyte`
- `rlforwardsearch_history`
- `rlhistorysearch_backward`
- `rlhistorysearch_forward`
- `rlinsertcomment`
- `rlinsertcompletions`
- `rlkillfull_line`
- `rlkillline`
- `rlkillregion`
- `rlkillword`
- `rlmenucomplete`
- `rloverwrite`
- `rlpossiblecompletions`
- `rlquotedinsert`
- `rlrereadinitfile`
- `rlrefreshline`
- `rlreversesearch_history`
- `rlsetmark`
- `rlstartkbd_macro`
- `rltransposechars`
- `rltransposewords`
- `rlttystatus`
- `rlunixfilename_rubout`
- `rlunixline_discard`
- `rlunixword_rubout`
- `rlupcaseword`
- `rlyankpop`
- `rlviappend_eol`
- `rlviarg_digit`
- `rlvichange_case`
- `rlvichange_char`
- `rlvichar_search`
- `rlvicolumn`
- `rlvicomplete`
- `rlvidelete_to`
- `rlvieof_maybe`
- `rlvifetch_history`
- `rlvifirst_print`
- `rlvigoto_mark`
- `rlvinsert_beg`
- `rlvimatch`
- `rlviput`
- `rlviredo`
- `rlvireplace`
- `rlvisearch`
- `rlvisearch_again`
- `rlviset_mark`
- `rlvisubst`
- `rlvitilde_expand`

- `rlviyank_arg`
- `rlviyank_to`
- `rldiscardkeymap`
- `rlviundo`
- `historysearchprefix`
- `history_search`
- `rlreplace_text`
- `rlsavedlinefor_history`
- `rlfix_point`
- `rlmaybesave_line`
- `rlmaybeunsave_line`
- `rlrestoreprompt`
- `rlrubout_char`
- `rlscxt_dispose`
- `rlnscxt`
- `rlsearch_getchar`
- `rlscxt_alloc`
- `rlmakepromptfor_search`
- `rl_message`
- `rlttysetdefault_bindings`
- `tcflow`
- `rlenable_keypad`
- `rlcontrol_keypad`
- `rlttyunsetdefaultbindings`
- `rlpreterminal`
- `rldepreterminal`
- `rlcompleteshowall`
- `rlcompleteshowunmodified`
- `rlcompletemarksymlink_dirs`
- `rlcompletioncasefold`
- `rlcompare_chars`
- `rlgetcharlen`
- `rlignorecompletion_duplicates`
- `rlcompletemarkdirectories`
- `rlmatchhiddenfiles`
- `rlcompletewithtildeexpansion`
- `setpwent`
- `getpwent`
- `wcwidth`
- `rlvisiblestats`
- `rlprintcompletionshorizontally`
- `rlpage_completions`
- `rlvis_botlin`
- `rlmove_vert`
- `rlcompletiondisplaymatcheshook`
- `rlcompletionquery_items`
- `rldisplaymatch_list`
- `rldisplayfixed`
- `rlcompletionwordbreakhook`
- `rlbasicquote_characters`

- *rfreematchlist*
- *rlcopytext*
- *rlfindcompletionword*
- *rlinhibitcompletion*
- *rlbindingkeymap*
- *rlbindkey*
- *rlcomment_begin*
- *rlbell_preference*
- *rlgetkeymap_name*
- *rlgetkeymapnamefromeditmode*
- *rlsearch_terminators*
- *rlinvokingkeyseqsinmap*
- *rlblinkmatching_paren*
- *rlenableparenmatching*
- *rlstrindex*
- *rltranslatekeyseq*
- *rlbindkeyseqifunboundinmap*
- *rlpossiblecontrolprefixes*
- *rlpossiblemetaprefixes*
- *rlmacrobind*
- *rlbindkeyseq*
- *rlhistorypreservepoint*
- *rlmarkmodifiedlines*
- *rloutputmetachars*
- *rliscxt*
- *rlinput_available*
- *rlexecutenext*
- *rlreplaceline*
- *rlchar_value*
- *rlwalphabetic*
- *rlsearch_dispatch*
- *rlmaybereplace_line*
- *rlsaveprompt*
- *rlastvpos*
- *rlastcpos*
- *rlterm_cr*
- *rloutputcharacterfunction*
- *rlterm_clrpag*
- *rlterm_cleol*
- *rlcleartoeol*
- *rlterm_up*
- *rlrestartoutput*
- *rlbackspace*
- *rlmovecursorrelative*
- *vsnprintf*
- *rloutputsomechars*
- *memcmp*
- *rlterminalcaninsert*
- *rlterm_IC*
- *rlterm_dc*

- *rterm_DC*
- *rterm_im*
- *rterm_ic*
- *rterm_ei*
- *memmove*
- *rkillkbmacro*
- *rlcleanupfor_exit*
- *rlresizeterminal*
- *rlcleanupafter_signal*
- *rlresetafter_signal*
- *rlfreeline_state*
- *rlsettheline*
- *rlpopexecutingmacro*
- *iswalnum*
- *rlallowpathnamealphanumeric_chars*
- *historyargextract*
- *rlsetmarkat_pos*
- *rldoinganundo*
- *rlpushexecutingmacro*
- *select*
- *rlsetkeyboardinputtimeout*
- *rlnextmacrokey*
- *rlventhook*
- *rlgetcfunction*
- *rl_getc*
- *rl_linefunc*
- *rlargcxt*
- *rlarg_callback*
- *rlisearch_callback*
- *rlnsearch_callback*
- *rlpushedinputavailable*
- *rldispatch_callback*
- *rlcallbackdatadispose*
- *rterm_backspace*
- *rlpreferenv_winsize*
- *tgetnum*
- *rlgetscreenize*
- *tgetent*
- *tgetstr*
- *rterm_pc*
- *tgetflag*
- *rlsetscreenize*
- *rlredisplayaftersigwinch*
- *rlismbchamatched*
- *rl_modifying*
- *rlhistorysavedpoint*
- *rlupdate_final*
- *rlviresetlast*
- *rlcurrentdisplayline*
- *rlclear_screen*

- *rlextendline_buffer*
- *rlcharacterlen*
- *rleraseatendofline*
- *rlany_typein*
- *rlinsert_typein*
- *rloverwrite_rubout*
- *rlrestoretty signals*
- *rldisabletty signals*
- *rlreplacefrom_history*
- *rlarg_dispatch*
- *rlarg_init*
- *history_offset*
- *maxinputhistory*
- *historyworddelimiters*
- *gethistoryevent*
- *historynoexpand_chars*
- *addhistorytime*
- *__mbrlen*
- *getpwnam*
- *tildeexpansionfailure_hook*
- *tildeexpandword*
- *rlinsertclose*
- *libncurses.so.5*
- *DYNAMICLINKING*
- *_RLDMAP*
- *gpdisp*
- *_DYNAMIC*
- *GLOBALOFFSETTABLE*
- *glob_vector*
- *internal_wstrmatch*
- *xstrmatch*
- *wcscoll*
- *wcsncmp*
- *wcscmp*
- *iswctype*
- *internal_strmatch*
- *mbsinit*
- *libdl.so.2*
- *_c_lztab*
- *libc.so.6*
- *unsetenv*
- *putenv*
- */Ostdin_used*
- *__environ*
- *_finiarray_start*
- *_finiarray_end*
- *_initarray_start*
- *_initarray_end*
- *_ftext*
- *_fdata*
- *_edata*

- `_bssstart`
- `rlrestorestate`
- `setbashinput_fd`
- `rluntranslatekeyseq`
- `ttocanon`
- `it_groups`
- `sccs_version`
- `rldiscardargument`
- `rlshowchar`
- `rldigit_value`
- `command_errstr`
- `zreadintr`
- `rlsetretained_kills`
- `historysethistory_state`
- `historytotalbytes`
- `stringrestof_args`
- `resetmailfiles`
- `findindexin_alist`
- `historygethistory_state`
- `it_files`
- `unbindfunctiondef`
- `rlterm_goto`
- `rlsavestring`
- `strlistfromword_list`
- `rlresetscreen_size`
- `strlist_sort`
- `hash_bucket`
- `rlunbindkey`
- `rlbindkeyifunbound`
- `it_services`
- `rllibraryversion`
- `rl_alphabetic`
- `rlgnureadline_p`
- `rl_forward`
- `sh_mktmpname`
- `uinttostr`
- `xmbsrtowcs`
- `unsetsigwinchhandler`
- `killalllocal_variables`
- `aliasexpandword`
- `rlstopoutput`
- `rlsavestate`
- `rlcallbackhandler_install`
- `rlterm_ip`
- `malloctraceat_exit`
- `historysearchpos`
- `__start`
- `rlcopykeymap`
- `rlset_cursor`
- `rlsetparenblinktimeout`
- `rlto_upper`

- `strlist_merge`
- `rlunbindcommandinmap`
- `rlcallbackhandler_remove`
- `strlist_flush`
- `strlisttoword_list`
- `arrayunshiftelement`
- `globalerrorlist`
- `r/to_lower`
- `r/lowercase_p`
- `r/pure_alphabetic`
- `rlmakekeymap`
- `hash_size`
- `arrayshiftelement`
- `openbufferedstream`
- `_getenv`
- `progcomp_dispose`
- `do_assignment`
- `ttattr`
- `it_directories`
- `rl_backward`
- `rlreadlineversion`
- `rlgettermcap`
- `shundouble_quote`
- `r/fixlastundoofype`
- `r/suppress_redisplay`
- `r/digit_p`
- `strlist_walk`
- `print_command`
- `localexportedvariables`
- `remove_backslashes`
- `getgrouparray`
- `strlist_remove`
- `array_walk`
- `thecurrentmaintainer`
- `sh_realpath`
- `it_users`
- `_datastart`
- `hash_copy`
- `zreset`
- `tteightbit`
- `rlcallbackread_char`
- `r/uppercase_p`
- `it_commands`
- `GLIBC_2.0`
- `GLIBC_2.2`
- `GLIBC_2.3`
- `GLIBC_2.3.4`
- `@!'9;l`
- ``0!'9x`
- `@@$B7l`
- `@(!$FE`

- @(!\$F;\$
- `8!'9
- `8!'9
- !\$Q4`\$s7 \$
- H('93`
- H('93`
- 0!&y4`
- ,&uC@\$w3`&
- \$c;0&94`\$B
- (&94 &04
- \$C;(&94`
- &bH(&G;\$
- 8!&fH(&C;\$
- !&G;\$&bH(
- 0!&gH(
- @!&C;\$
- @!4fg
- @\$G?X
- ff4jfg
- !'9i
- \$P;\$T@
- @ !'9h
- ` !'9h
- (!'9s
- ` !'9p
- @8!&\$A
- @ !\$BY
- @ !&9\
- %\$EH,\$
- @ !&eH
- (!'92`
- \$E;\$P`
- !'9lh
- ` !'9X
- `(!'9X
- @ !'9X
- @ !'9B\
- @(!'9B\
- !\$W P\$
- !'9lh
- `(!\$D#(
- (!\$D#(
- @ !\$ER
- 0!'9!0\$
- !'9%T
- @(!'9Y
- d]\\$c]\
- 8\$B_,\$
- !'9A\
- ` !'9A\
- @ !'9=
- !'9Ep

- (!\$Y|p
- @8!'9t,
- 8!'9rH
- !\$y|p
- !\$y|p
- 8!\$dP,
- `!'9AD
- @!'9Qh
- (!'9Qh
- /4Gfg'
- `(!\$Pdd
- (!\$Pd(
- 8#4BB@
- 8!4BB@
- `!\$E.
- `!\$E.
- `0!%e5p
- ff4cfg
- ff4cfg
- ff4cfg
- @!'9u
- @!'9u
- \$Bm<\$Q
- 0!&e?
- 8!\$F;\$
- 0!'9/8
- fD\ \$gD\
- FDh\$DDh
- @(!'9_\
- 0!'9zX
- 0\$SzX&
- Q0#'9x
- UU4cUV
- E0\$BE,
- `(!'9X
- !'9X`
- !'9X`
- /bin/sh
- I have no name!
- BASH_ENV
- GNU bash, version %s-(%s)
- mips-unknown-linux-gnu
- Usage:
- %s [GNU long option] [option] ...
- %s [GNU long option] [option] script-file ...
- GNU long options:
- Shell options:
- -irsD or -c command or -O shopt_option
- (invocation only)
- -%s or -o option
- Type `%s -c "help set"' for more information about shell options.
- Type `%s -c help' for more information about shell builtin commands.

- Use the `bashbug' command to report bugs.
- /usr/local/lib/bashdb/bashdb-main.inc
- SSH_CLIENT
- SSH2_CLIENT
- /etc/bash/bashrc
- /etc/profile
- ~/.profile
- ~/.bash_profile
- ~/.bash_login
- run_wordexp
- --wordexp
- runoncommand
- FUNCNAME
- BASH_SOURCE
- BASH_LINENO
- %s: is a directory
- %s: cannot execute binary file
- POSIXLY_CORRECT
- POSIX_PEDANTIC
- \s-\v\\$
- ~/.bashrc
- %s: option requires an argument
- %s: invalid option
- %c%c: invalid option
- ??host??
- debugger
- dump-po-strings
- dump-strings
- noediting
- noprofile
- protected
- rcfile
- verbose
- version
- timed out waiting for input: auto-logout
- PROMPT_COMMAND
- reader_loop
- PIPESTATUS
- readline stdin
- syntax error near unexpected token `%'
- syntax error near `%'
- syntax error: unexpected end of file
- syntax error
- %a %b %d
- %H:%M:%S
- %l:%M:%S
- %l:%M %p
- unexpected EOF while looking for matching `{'
- unexpected EOF while looking for `]'
- syntax error in conditional expression: unexpected token `%'
- syntax error in conditional expression
- unexpected EOF while looking for matching `{'

- [illegible]

- for ((
- print_command: bad connector '%d'
- function %s ()
- print_command
- case %s in
- %s=(%s)
- dispose_command
- cannot duplicate fd %d to fd %d
- %s: %s: bad interpreter
- /dev/null
- cannot redirect standard input from /dev/null: %s
- eval_builtin
- builtin_env
- returntempenv
- executecondnode
- execute-command
- COLUMNS
- %*d%s%s
- loop_redirections
- pipe error
- pipe-file-descriptors
- execute_connection
- %s: readonly function
- execute_command
- function_calling
- simple-command
- auto_resume
- substring
- saved_redirects
- saved_redirects
- %s: restricted: cannot specify '/' in command names
- %s: command not found
- execute-shell-function
- real %2R
- user %2U
- sys %2S
- TIMEFORMAT: '%c': invalid format character
- popvarcontext: head of shell_variables not a function context
- popvarcontext: no global_variables context
- popscope: *head of shell*variables not a temporary environment scope
- BASH_ARGV
- BASH_ARGC
- alllocalvariables: no function context at current scope
- makeocalvariable: no function context at current scope
- OPTERR
- ignorespace
- erasedups
- ignoredups
- ignoreboth
- HISTFILE
- shell-init
- shell level (%d) too high, resetting to 1

- error importing function definition for '%s'
- /usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin
- HOSTTYPE
- OSTYPE
- linux-gnu
- MACHTYPE
- HOSTNAME
- MAILCHECK
- OPTIND
- BASH_VERSION
- BASH_VERSINFO
- BASHEXECUTIONSTRING
- ~/.sh_history
- ~/.bash_history
- HISTSIZE
- IGNOREEOF
- ignoreeof
- HISTCONTROL
- HISTIGNORE
- SECONDS
- BASH_COMMAND
- BASH_SUBSHELL
- RANDOM
- LINENO
- HISTCMD
- COMP_WORDBREAKS
- DIRSTACK
- GROUPS
- GLOBIGNORE
- HISTFILESIZE
- HISTTIMEFORMAT
- HOSTFILE
- LC_ALL
- LC_COLLATE
- LC_CTYPE
- LC_MESSAGES
- LC_NUMERIC
- LC_TIME
- MAILPATH
- TERMCAP
- TERMINFO
- TEXTDOMAIN
- TEXTDOMAINDIR
- histchars
- line
- %s: %s:%s%d:
- last command: %s
- (null)
- Aborting...
- %s: %s: %d
- %s: warning:
- %s: readonly variable

- %s: unbound variable
- bash-maintainers@gnu.org
- unknown command error
- bad command type
- bad connector
- bad jump
- %s%s%s: %s (error token is "%s")
- expression recursion level exceeded
- syntax error in expression
- recursion stack underflow
- invalid arithmetic base
- value too great for base
- */%+-&^|
- identifier expected after pre-increment or pre-decrement
- missing `)'
- syntax error: operand expected
- exponent less than 0
- division by 0
- `:' expected for conditional expression
- attempted assignment to non-variable
- bug: bad expassign token
- (core dumped)
- (wd: %s)
- Signal %d
-
- [%d]%c
- Stopped
- Stopped(%s)
- Running
- Done(%d)
- Exit %d
- Unknown status
- %s: line %d:
- (core dumped)
- (wd now: %s)
- notifyofjob_status
- SIGCHLD trap
- [%d] %ld
- describe_pid: %ld: no such pid
- [%ld: %d] tcsetattr
- initializejobcontrol: getpgrp failed
- initializejobcontrol: setpgid
- no job control in this shell
- deleting stopped job %d with process group %ld
- wait_for: No record of process %ld
- %s: job has terminated
- %s: job %d already in background
- [%d]%s
- (wd: %s)
- waitforjob: job %d is stopped
- wait: pid %ld is not a child of this shell
- job-working-directory

- start_pipeline: pgrp pipe
- child setpgid (%ld to %ld)
- cannot make pipe for command substitution
- cannot make child for command substitution
- command_substitute: cannot duplicate pipe as fd 1
- command substitution
- %s: cannot assign list to array member
- bad substitution: no closing `%' in %s
- #%:.-=?+/}
- %s: substring expression < 0
- %s: bad substitution
- \$%s: cannot assign in this way
- %s: parameter null or not set
- cannot make pipe for process substitution
- /dev/fd/
- cannot make child for process substitution
- cannot duplicate named pipe %s as fd %d
- process substitution
- bad substitution: no closing "" in %s
- no match: %s
- You have mail in \$_
- You have new mail in \$_
- The mail in %s has been read
- interrupt trap
- return trap
- error trap
- debug trap
- exit trap
- invalid signal number
- runpendingtraps: bad value in trap_list[%d]: %p
- runpendingtraps: signal handler is SIG_DFL, resending %d (%s) to myself
- trap_handler: bad signal %d
- SIGHUP
- SIGINT
- SIGQUIT
- SIGILL
- SIGTRAP
- SIGABRT
- SIGEMT
- SIGFPE
- SIGKILL
- SIGBUS
- SIGSEGV
- SIGSYS
- SIGPIPE
- SIGALRM
- SIGTERM
- SIGUSR1
- SIGUSR2
- SIGCHLD
- SIGPWR
- SIGWINCH

- SIGURG
- SIGSTOP
- SIGTSTP
- SIGCONT
- SIGTTIN
- SIGTTOU
- SIGVTALRM
- SIGPROF
- SIGXCPU
- SIGXFSZ
- SIGJUNK(32)
- SIGJUNK(33)
- SIGJUNK(34)
- SIGRTMIN
- SIGRTMIN+1
- SIGRTMIN+2
- SIGRTMIN+3
- SIGRTMIN+4
- SIGRTMIN+5
- SIGRTMIN+6
- SIGRTMIN+7
- SIGRTMIN+8
- SIGRTMIN+9
- SIGRTMIN+10
- SIGRTMIN+11
- SIGRTMIN+12
- SIGRTMIN+13
- SIGRTMIN+14
- SIGRTMIN+15
- SIGRTMIN+16
- SIGRTMIN+17
- SIGRTMIN+18
- SIGRTMIN+19
- SIGRTMIN+20
- SIGRTMIN+21
- SIGRTMIN+22
- SIGRTMIN+23
- SIGRTMIN+24
- SIGRTMIN+25
- SIGRTMIN+26
- SIGRTMIN+27
- SIGRTMIN+28
- SIGRTMIN+29
- SIGRTMIN+30
- SIGRTMIN+31
- SIGRTMIN+32
- SIGRTMIN+33
- SIGRTMIN+34
- SIGRTMIN+35
- SIGRTMIN+36
- SIGRTMIN+37
- SIGRTMIN+38

- SIGRTMIN+39
- SIGRTMIN+40
- SIGRTMIN+41
- SIGRTMIN+42
- SIGRTMIN+43
- SIGRTMIN+44
- SIGRTMIN+45
- SIGRTMIN+46
- SIGRTMAX-45
- SIGRTMAX-44
- SIGRTMAX-43
- SIGRTMAX-42
- SIGRTMAX-41
- SIGRTMAX-40
- SIGRTMAX-39
- SIGRTMAX-38
- SIGRTMAX-37
- SIGRTMAX-36
- SIGRTMAX-35
- SIGRTMAX-34
- SIGRTMAX-33
- SIGRTMAX-32
- SIGRTMAX-31
- SIGRTMAX-30
- SIGRTMAX-29
- SIGRTMAX-28
- SIGRTMAX-27
- SIGRTMAX-26
- SIGRTMAX-25
- SIGRTMAX-24
- SIGRTMAX-23
- SIGRTMAX-22
- SIGRTMAX-21
- SIGRTMAX-20
- SIGRTMAX-19
- SIGRTMAX-18
- SIGRTMAX-17
- SIGRTMAX-16
- SIGRTMAX-15
- SIGRTMAX-14
- SIGRTMAX-13
- SIGRTMAX-12
- SIGRTMAX-11
- SIGRTMAX-10
- SIGRTMAX-9
- SIGRTMAX-8
- SIGRTMAX-7
- SIGRTMAX-6
- SIGRTMAX-5
- SIGRTMAX-4
- SIGRTMAX-3
- SIGRTMAX-2

- SIGRTMAX-1
- SIGRTMAX
- RETURN
- cannot allocate new file descriptor for bash input from fd %d
- save`bash`input: buffer already exists for new fd %d
- %s: integer expression expected
- argument expected
- %s: binary operator expected
- %s: unary operator expected
- `)' expected
- `)' expected, found %s
- missing `]'
- too many arguments
- %s.%d(%d)-%s
- %s.%d(%d)
- GNU bash, version %s (%s)
- Copyright (C) 2005 Free Software Foundation, Inc.
- release
- @(#)Bash version 3.1.17(1) release GNU
- %s[%s: %s
- [%s]: %s
- array assign
- %s: cannot assign to non-numeric index
- bad array subscript
- %s%s%s
- ;&()|<>
- %s: cannot create: %s
- %s: first non-whitespace character is not `"'
- no closing `%c' in %s
- %s: missing colon separator
- bash`executeunix_command`: cannot find keymap for command
- bash`executeunix_command`
- completion-ignore-case
- ;|&{(`
- \$include
- hostname`completionfile`
- /etc/hosts
- symlink-hook
- ()<>;&|
- C-xC-e
- fc -e "\${VISUAL:-\${EDITOR:-emacs}}"
- fc -e vi
- fc -e "\${VISUAL:-\${EDITOR:-vi}}"
- shell-expand-line
- history-expand-line
- magic-space
- history-and-alias-expand-line
- insert-last-argument
- operate-and-get-next
- display-shell-version
- edit-and-execute-command
- complete-into-braces

- complete-filename
- possible-filename-completions
- complete-username
- possible-username-completions
- complete-hostname
- possible-hostname-completions
- complete-variable
- possible-variable-completions
- complete-command
- possible-command-completions
- glob-complete-word
- glob-expand-word
- glob-list-expansions
- dynamic-complete-history
- \'"@<>=;|&()#\$`?\*`![:{
- comment-begin
- FIGNORE
- '"@><=;|&(:
- "'><=;|&(:
- #: %s:%d
- msgid %s%s
- msgstr ""
- /usr/share/locale
- redirection error: cannot duplicate fd
- sh-thd
- file descriptor out of range
- %s: ambiguous redirect
- %s: cannot overwrite existing file
- %s: restricted: cannot redirect output
- cannot create temp file for here document: %s
- /dev/tcp//
- /dev/udp//
- COMP_LINE
- COMP_POINT
- COMP_WORDS
- COMP_CWORD
- completion: function '%s' not found
- COMPREPLY
- progcomp_insert: %s: NULL COMPSPEC
- xrealloc: cannot reallocate %lu bytes (%lu bytes allocated)
- xmalloc: cannot allocate %lu bytes (%lu bytes allocated)
- alias [-p] [name[=value] ...]
- unalias
- unalias [-a] name [name ...]
- bind [-lpvsPVS] [-m keymap] [-f filename] [-q name] [-u name] [-r keyseq] [-x keyseq:shell-command]
- break [n]
- continue
- continue [n]
- builtin [shell-builtin [arg ...]]
- caller
- caller [EXPR]
- cd [-L|-P] [dir]

- pwd [-LP]
- command [-pVv] command [arg ...]
- declare
- declare [-afFirtx] [-p] [name[=value] ...]
- typeset
- typeset [-afFirtx] [-p] name[=value] ...
- local name[=value] ...
- echo [-neE] [arg ...]
- enable
- enable [-pnds] [-a] [-f filename] [name ...]
- eval [arg ...]
- getopts
- getopts optstring name [arg]
- exec [-cl] [-a name] file [redirection ...]
- exit [n]
- fc [-e ename] [-nlr] [first] [last] or fc -s [pat=rep] [cmd]
- fg [job_spec]
- bg [job_spec ...]
- hash [-lr] [-p pathname] [-dt] [name ...]
- help [-s] [pattern ...]
- history [-c] [-d offset] [n] or history -awrn [filename] or history -ps arg [arg...]
- jobs [-lnprs] [jobspec ...] or jobs -x command [args]
- disown
- disown [-h] [-ar] [jobspec ...]
- kill [-s sigspec | -n signum | -sigspec] pid | jobspec ... or kill -l [sigspec]
- let arg [arg ...]
- read [-ers] [-u fd] [-t timeout] [-p prompt] [-a array] [-n nchars] [-d delim] [name ...]
- return
- return [n]
- set [--abefhkmnptuvxBCHP] [-o option] [arg ...]
- unset [-f] [-v] [name ...]
- export
- export [-nf] [name[=value] ...] or export -p
- readonly
- readonly [-af] [name[=value] ...] or readonly -p
- shift [n]
- source
- source filename [arguments]
- . filename [arguments]
- suspend
- suspend [-f]
- test [expr]
- [arg...]
- trap [-lp] [arg signal_spec ...]
- type [-afptP] name [name ...]
- ulimit
- ulimit [-SHacdefilmnpqrstuvx] [limit]
- umask [-p] [-S] [mode]
- wait [n]
- for NAME [in WORDS ... ;] do COMMANDS; done
- for ((exp1; exp2; exp3)); do COMMANDS; done
- select NAME [in WORDS ... ;] do COMMANDS; done

- time [-p] PIPELINE
- case WORD in [PATTERN [| PATTERN]...] COMMANDS ;;]... esac
- if COMMANDS; then COMMANDS; [elif COMMANDS; then COMMANDS;]... [else COMMANDS;] fi
- while COMMANDS; do COMMANDS; done
- until COMMANDS; do COMMANDS; done
- function NAME { COMMANDS ; } or NAME () { COMMANDS ; }
- { ... }
- JOB_SPEC [&]
- ((...))
- ((expression))
- [[...]]
- [[expression]]
- variables
- variables - Some variable names and meanings
- pushd [dir | +N | -N] [-n]
- popd [+N | -N] [-n]
- dirs [-clpv] [+N] [-N]
- shopt [-pqsu] [-o long-option] optname [optname...]
- printf
- printf [-v var] format [arguments]
- complete [-abcdefgksuv] [-pr] [-o option] [-A action] [-G globpat] [-W wordlist] [-P prefix] [-S su
- compgen
- compgen [-abcdefgksuv] [-o option] [-A action] [-G globpat] [-W wordlist] [-P prefix] [-S suffix] [
- `alias' with no arguments or with the -p option prints the list
- of aliases in the form alias NAME=VALUE on standard output.
- Otherwise, an alias is defined for each NAME whose VALUE is given.
- A trailing space in VALUE causes the next word to be checked for
- alias substitution when the alias is expanded. Alias returns
- true unless a NAME is given for which no alias has been defined.
- Remove NAMEs from the list of defined aliases. If the -a option is given,
- then remove all alias definitions.
- Bind a key sequence to a Readline function or a macro, or set
- a Readline variable. The non-option argument syntax is equivalent
- to that found in ~/.inputrc, but must be passed as a single argument:
- bind ""\C-x\C-r": re-read-init-file'.
- bind accepts the following options:
- -m keymap Use `keymap' as the keymap for the duration of this
- command. Acceptable keymap names are emacs,
- emacs-standard, emacs-meta, emacs-ctlx, vi, vi-move,
- vi-command, and vi-insert.
- -l List names of functions.
- -P List function names and bindings.
- -p List functions and bindings in a form that can be
- reused as input.
- -r keyseq Remove the binding for KEYSEQ.
- -x keyseq:shell-command
- Cause SHELL-COMMAND to be executed when
- KEYSEQ is entered.
- -f filename Read key bindings from FILENAME.
- -q function-name Query about which keys invoke the named function.
- -u function-name Unbind all keys which are bound to the named function.
- -V List variable names and values

- -v List variable names and values in a form that can be reused as input.
- -S List key sequences that invoke macros and their values
- -s List key sequences that invoke macros and their values in a form that can be reused as input.
- Exit from within a FOR, WHILE or UNTIL loop. If N is specified, break N levels.
- Resume the next iteration of the enclosing FOR, WHILE or UNTIL loop.
- If N is specified, resume at the N-th enclosing loop.
- Run a shell builtin. This is useful when you wish to rename a shell builtin to be a function, but need the functionality of the builtin within the function itself.
- Returns the context of the current subroutine call.
- Without EXPR, returns returns "\$line \$filename". With EXPR, returns "\$line \$subroutine \$filename"; this extra information can be used used to provide a stack trace.
- The value of EXPR indicates how many call frames to go back before the current one; the top frame is frame 0.
- Change the current directory to DIR. The variable \$HOME is the default DIR. The variable CDPATH defines the search path for the directory containing DIR. Alternative directory names in CDPATH are separated by a colon (:). A null directory name is the same as the current directory, i.e. `.`. If DIR begins with a slash (/), then CDPATH is not used. If the directory is not found, and the shell option `cdable_vars' is set, then try the word as a variable name. If that variable has a value, then cd to the value of that variable. The -P option says to use the physical directory structure instead of following symbolic links; the -L option forces symbolic links to be followed.
- Print the current working directory. With the -P option, pwd prints the physical directory, without any symbolic links; the -L option makes pwd follow symbolic links.
- No effect; the command does nothing. A zero exit code is returned.
- Return a successful result.
- Return an unsuccessful result.
- Runs COMMAND with ARGS ignoring shell functions. If you have a shell function called `ls`, and you wish to call the command `ls`, you can say "command ls". If the -p option is given, a default value is used for PATH that is guaranteed to find all of the standard utilities. If the -V or -v option is given, a string is printed describing COMMAND.
- The -V option produces a more verbose description.
- Declare variables and/or give them attributes. If no NAMEs are given, then display the values of variables instead. The -p option will display the attributes and values of each NAME.
- The flags are:
 - -a
 - to make NAMEs arrays (if supported)
 - -f
 - to select from among function names only
 - -F
 - to display function names (and line number and source file name if debugging) without definitions

- -i
- to make NAMES have the 'integer' attribute
- -r
- to make NAMES readonly
- -t
- to make NAMES have the 'trace' attribute
- -x
- to make NAMES export
- Variables with the integer attribute have arithmetic evaluation (see 'let') done when the variable is assigned to.
- When displaying values of variables, -f displays a function's name and definition. The -F option restricts the display to function name only.
- Using '+' instead of '-' turns off the given attribute instead. When used in a function, makes NAMES local, as with the 'local' command.
- Obsolete. See 'declare'.
- Create a local variable called NAME, and give it VALUE. LOCAL can only be used within a function; it makes the variable NAME have a visible scope restricted to that function and its children.
- Output the ARGs. If -n is specified, the trailing newline is suppressed. If the -e option is given, interpretation of the following backslash-escaped characters is turned on:
 - alert (bell)
 - backspace
 - suppress trailing newline
 - escape character
 - form feed
 - new line
 - carriage return
 - horizontal tab
 - vertical tab
 - backslash
 - the character whose ASCII code is NUM (octal).
- You can explicitly turn off the interpretation of the above characters with the -E option.
- Enable and disable builtin shell commands. This allows you to use a disk command which has the same name as a shell builtin without specifying a full pathname. If -n is used, the NAMES become disabled; otherwise NAMES are enabled. For example, to use the 'test' found in \$PATH instead of the shell builtin version, type 'enable -n test'. On systems supporting dynamic loading, the -f option may be used to load new builtins from the shared object FILENAME. The -d option will delete a builtin previously loaded with -f. If no non-option names are given, or the -p option is supplied, a list of builtins is printed. The -a option means to print every builtin with an indication of whether or not it is enabled. The -s option restricts the output to the POSIX.2 'special' builtins. The -n option displays a list of all disabled builtins.
- Read ARGs as input to the shell and execute the resulting command(s).
- Getopts is used by shell procedures to parse positional parameters.
- OPTSTRING contains the option letters to be recognized; if a letter is followed by a colon, the option is expected to have an argument,

- which should be separated from it by white space.
- Each time it is invoked, getopt will place the next option in the
- shell variable \$name, initializing name if it does not exist, and
- the index of the next argument to be processed into the shell
- variable OPTIND. OPTIND is initialized to 1 each time the shell or
- a shell script is invoked. When an option requires an argument,
- getopt places that argument into the shell variable OPTARG.
- getopt reports errors in one of two ways. If the first character
- of OPTSTRING is a colon, getopt uses silent error reporting. In
- this mode, no error messages are printed. If an invalid option is
- seen, getopt places the option character found into OPTARG. If a
- required argument is not found, getopt places a ':' into NAME and
- sets OPTARG to the option character found. If getopt is not in
- silent mode, and an invalid option is seen, getopt places '?' into
- NAME and unsets OPTARG. If a required argument is not found, a '?'
- is placed in NAME, OPTARG is unset, and a diagnostic message is
- printed.
- If the shell variable OPTERR has the value 0, getopt disables the
- printing of error messages, even if the first character of
- OPTSTRING is not a colon. OPTERR has the value 1 by default.
- Getopt normally parses the positional parameters (\$0 - \$9), but if
- more arguments are given, they are parsed instead.
- Exec FILE, replacing this shell with the specified program.
- If FILE is not specified, the redirections take effect in this
- shell. If the first argument is '-l', then place a dash in the
- zeroth arg passed to FILE, as login does. If the '-c' option
- is supplied, FILE is executed with a null environment. The '-a'
- option means to make set argv[0] of the executed process to NAME.
- If the file cannot be executed and the shell is not interactive,
- then the shell exits, unless the shell option 'execfail' is set.
- Exit the shell with a status of N. If N is omitted, the exit status
- is that of the last command executed.
- Logout of a login shell.
- fc is used to list or edit and re-execute commands from the history list.
- FIRST and LAST can be numbers specifying the range, or FIRST can be a
- string, which means the most recent command beginning with that
- string.
- -e ENAME selects which editor to use. Default is FCEDIT, then EDITOR,
- then vi.
- -l means list lines instead of editing.
- -n means no line numbers listed.
- -r means reverse the order of the lines (making it newest listed first).
- With the 'fc -s [pat=rep ...] [command]' format, the command is
- re-executed after the substitution OLD=NEW is performed.
- A useful alias to use with this is r='fc -s', so that typing 'r cc'
- runs the last command beginning with `cc` and typing `r` re-executes
- the last command.
- Place JOB_SPEC in the foreground, and make it the current job. If
- JOB_SPEC is not present, the shell's notion of the current job is
- used.
- Place each JOB_SPEC in the background, as if it had been started with
- '&'. If JOB_SPEC is not present, the shell's notion of the current

- job is used.
- For each NAME, the full pathname of the command is determined and
- remembered. If the -p option is supplied, PATHNAME is used as the
- full pathname of NAME, and no path search is performed. The -r
- option causes the shell to forget all remembered locations. The -d
- option causes the shell to forget the remembered location of each NAME.
- If the -t option is supplied the full pathname to which each NAME
- corresponds is printed. If multiple NAME arguments are supplied with
- -t, the NAME is printed before the hashed full pathname. The -l option
- causes output to be displayed in a format that may be reused as input.
- If no arguments are given, information about remembered commands is displayed.
- Display helpful information about builtin commands. If PATTERN is
- specified, gives detailed help on all commands matching PATTERN,
- otherwise a list of the builtins is printed. The -s option
- restricts the output for each builtin command matching PATTERN to
- a short usage synopsis.
- Display the history list with line numbers. Lines listed with
- with a '*' have been modified. Argument of N says to list only
- the last N lines. The -c option causes the history list to be
- cleared by deleting all of the entries. The -d option deletes
- the history entry at offset OFFSET. The -w option writes out the
- current history to the history file; -r means to read the file and
- append the contents to the history list instead. -a means
- to append history lines from this session to the history file.
- Argument -n means to read all history lines not already read
- from the history file and append them to the history list.
- If FILENAME is given, then that is used as the history file else
- if \$HISTFILE has a value, that is used, else ~/.bash_history.
- If the -s option is supplied, the non-option ARGs are appended to
- the history list as a single entry. The -p option means to perform
- history expansion on each ARG and display the result, without storing
- anything in the history list.
- If the \$HISTTIMEFORMAT variable is set and not null, its value is used
- as a format string for strftime(3) to print the time stamp associated
- with each displayed history entry. No time stamps are printed otherwise.
- Lists the active jobs. The -l option lists process id's in addition
- to the normal information; the -p option lists process id's only.
- If -n is given, only processes that have changed status since the last
- notification are printed. JOBSPEC restricts output to that job. The
- -r and -s options restrict output to running and stopped jobs only,
- respectively. Without options, the status of all active jobs is
- printed. If -x is given, COMMAND is run after all job specifications
- that appear in ARGS have been replaced with the process ID of that job's
- process group leader.
- By default, removes each JOBSPEC argument from the table of active jobs.
- If the -h option is given, the job is not removed from the table, but is
- marked so that SIGHUP is not sent to the job if the shell receives a
- SIGHUP. The -a option, when JOBSPEC is not supplied, means to remove all
- jobs from the job table; the -r option means to remove only running jobs.
- Send the processes named by PID (or JOBSPEC) the signal SIGSPEC. If
- SIGSPEC is not present, then SIGTERM is assumed. An argument of -l
- lists the signal names; if arguments follow -l they are assumed to

- be signal numbers for which names should be listed. Kill is a shell
- builtin for two reasons: it allows job IDs to be used instead of
- process IDs, and, if you have reached the limit on processes that
- you can create, you don't have to start a process to kill another one.
- Each ARG is an arithmetic expression to be evaluated. Evaluation
- is done in fixed-width integers with no check for overflow, though
- division by 0 is trapped and flagged as an error. The following
- list of operators is grouped into levels of equal-precedence operators.
- The levels are listed in order of decreasing precedence.
- id++, id--
- variable post-increment, post-decrement
- ++id, --id
- variable pre-increment, pre-decrement
- unary minus, plus
- logical and bitwise negation
- exponentiation
- *, /, %
- multiplication, division, remainder
- addition, subtraction
- <<, >>
- left and right bitwise shifts
- <=, >=, <, >
- comparison
- ==, !=
- equality, inequality
- bitwise AND
- bitwise XOR
- bitwise OR
- logical AND
- logical OR
- expr ? expr : expr
- conditional operator
- =, *=, /=, %=,
- +=, -=, <<=, >>=,
- &=, ^=, |=
- assignment
- Shell variables are allowed as operands. The name of the variable
- is replaced by its value (coerced to a fixed-width integer) within
- an expression. The variable need not have its integer attribute
- turned on to be used in an expression.
- Operators are evaluated in order of precedence. Sub-expressions in
- parentheses are evaluated first and may override the precedence
- rules above.
- If the last ARG evaluates to 0, let returns 1; 0 is returned
- otherwise.
- One line is read from the standard input, or from file descriptor FD if the
- -u option is supplied, and the first word is assigned to the first NAME,
- the second word to the second NAME, and so on, with leftover words assigned
- to the last NAME. Only the characters found in \$IFS are recognized as word
- delimiters. If no NAMEs are supplied, the line read is stored in the REPLY
- variable. If the -r option is given, this signifies 'raw' input, and
- backslash escaping is disabled. The -d option causes read to continue

- until the first character of DELIM is read, rather than newline. If the -p
- option is supplied, the string PROMPT is output without a trailing newline
- before attempting to read. If -a is supplied, the words read are assigned
- to sequential indices of ARRAY, starting at zero. If -e is supplied and
- the shell is interactive, readline is used to obtain the line. If -n is
- supplied with a non-zero NCHARS argument, read returns after NCHARS
- characters have been read. The -s option causes input coming from a
- terminal to not be echoed.
- The -t option causes read to time out and return failure if a complete line
- of input is not read within TIMEOUT seconds. If the TMOUT variable is set,
- its value is the default timeout. The return code is zero, unless end-of-file
- is encountered, read times out, or an invalid file descriptor is supplied as
- the argument to -u.
- Causes a function to exit with the return value specified by N. If N
- is omitted, the return status is that of the last command.
- -a Mark variables which are modified or created for export.
- -b Notify of job termination immediately.
- -e Exit immediately if a command exits with a non-zero status.
- -f Disable file name generation (globbing).
- -h Remember the location of commands as they are looked up.
- -k All assignment arguments are placed in the environment for a
- command, not just those that precede the command name.
- -m Job control is enabled.
- -n Read commands but do not execute them.
- -o option-name
- Set the variable corresponding to option-name:
- allexport same as -a
- braceexpand same as -B
- emacs use an emacs-style line editing interface
- errexit same as -e
- errtrace same as -E
- functrace same as -T
- hashall same as -h
- histexpand same as -H
- history enable command history
- ignoreeof the shell will not exit upon reading EOF
- interactive-comments
- allow comments to appear in interactive commands
- keyword same as -k
- monitor same as -m
- noclobber same as -C
- noexec same as -n
- noglob same as -f
- nolog currently accepted but ignored
- notify same as -b
- nounset same as -u
- onecmd same as -t
- physical same as -P
- pipefail the return value of a pipeline is the status of
- the last command to exit with a non-zero status,
- or zero if no command exited with a non-zero status
- posix change the behavior of bash where the default

- operation differs from the 1003.2 standard to
- match the standard
- privileged same as -p
- verbose same as -v
- vi use a vi-style line editing interface
- xtrace same as -x
- -p Turned on whenever the real and effective user ids do not match.
- Disables processing of the \$ENV file and importing of shell
- functions. Turning this option off causes the effective uid and
- gid to be set to the real uid and gid.
- -t Exit after reading and executing one command.
- -u Treat unset variables as an error when substituting.
- -v Print shell input lines as they are read.
- -x Print commands and their arguments as they are executed.
- -B the shell will perform brace expansion
- -C If set, disallow existing regular files to be overwritten
- by redirection of output.
- -E If set, the ERR trap is inherited by shell functions.
- -H Enable ! style history substitution. This flag is on
- by default when the shell is interactive.
- -P If set, do not follow symbolic links when executing commands
- such as cd which change the current directory.
- -T If set, the DEBUG trap is inherited by shell functions.
- - Assign any remaining arguments to the positional parameters.
- The -x and -v options are turned off.
- Using + rather than - causes these flags to be turned off. The
- flags can also be used upon invocation of the shell. The current
- set of flags may be found in \$-. The remaining n ARGs are positional
- parameters and are assigned, in order, to \$1, \$2, .. \$n. If no
- ARGs are given, all shell variables are printed.
- For each NAME, remove the corresponding variable or function. Given
- the -v', unset will only act on variables. Given the -f flag,
- unset will only act on functions. With neither flag, unset first
- tries to unset a variable, and if that fails, then tries to unset a
- function. Some variables cannot be unset; also see readonly.
- NAMES are marked for automatic export to the environment of
- subsequently executed commands. If the -f option is given,
- the NAMES refer to functions. If no NAMES are given, or if -p' is given, a list of all names that are
- exported in this shell is printed. An argument of -n' says to remove the export property
- from subsequent NAMES. An argument of --' disables further option processing. The given
- NAMES are marked readonly and the values of these NAMES may not be changed by subsequent
- assignment. If the -f option is given, then functions corresponding to the NAMES are so marked.
- If no arguments are given, or if -p' is given, a list of all readonly names
- is printed. The -a' option means to treat each NAME as an array variable. An argument of --' disables
- further option
- processing.
- The positional parameters from \$N+1 ... are renamed to \$1 ... If N is
- not given, it is assumed to be 1.
- Read and execute commands from FILENAME and return. The pathnames
- in \$PATH are used to find the directory containing FILENAME. If any

- ARGUMENTS are supplied, they become the positional parameters when
- FILENAME is executed.
- Suspend the execution of this shell until it receives a SIGCONT
- **signal.** The `-f` if specified says not to complain about this being a login shell if it is; just suspend anyway.
- Exits with a status of 0 (true) or 1 (false) depending on the evaluation of EXPR. Expressions may be unary or binary. Unary expressions are often used to examine the status of a file. There are string operators as well, and numeric comparison operators.
- File operators:
 - `-a` FILE True if file exists.
 - `-b` FILE True if file is block special.
 - `-c` FILE True if file is character special.
 - `-d` FILE True if file is a directory.
 - `-e` FILE True if file exists.
 - `-f` FILE True if file exists and is a regular file.
 - `-g` FILE True if file is set-group-id.
 - `-h` FILE True if file is a symbolic link.
 - `-L` FILE True if file is a symbolic link.
 - `-k` FILE True if file has its **sticky** bit set.
- `-p` FILE True if file is a named pipe.
- `-r` FILE True if file is readable by you.
- `-s` FILE True if file exists and is not empty.
- `-S` FILE True if file is a socket.
- `-t` FD True if FD is opened on a terminal.
- `-u` FILE True if the file is set-user-id.
- `-w` FILE True if the file is writable by you.
- `-x` FILE True if the file is executable by you.
- `-O` FILE True if the file is effectively owned by you.
- `-G` FILE True if the file is effectively owned by your group.
- `-N` FILE True if the file has been modified since it was last read.
- FILE1 `-nt` FILE2 True if file1 is newer than file2 (according to modification date).
- FILE1 `-ot` FILE2 True if file1 is older than file2.
- FILE1 `-ef` FILE2 True if file1 is a hard link to file2.
- String operators:
 - `-z` STRING True if string is empty.
 - `-n` STRING
 - STRING True if string is not empty.
 - STRING1 = STRING2
 - True if the strings are equal.
 - STRING1 != STRING2
 - True if the strings are not equal.
 - STRING1 < STRING2
 - True if STRING1 sorts before STRING2 lexicographically.
 - STRING1 > STRING2
 - True if STRING1 sorts after STRING2 lexicographically.
- Other operators:
 - `-o` OPTION True if the shell option OPTION is enabled.
 - `! EXPR` True if expr is false.
 - EXPR1 `-a` EXPR2 True if both expr1 AND expr2 are true.
 - EXPR1 `-o` EXPR2 True if either expr1 OR expr2 is true.
 - arg1 OP arg2 Arithmetic tests. OP is one of `-eq`, `-ne`, `-lt`, `-le`, `-gt`, or `-ge`.
 - Arithmetic binary operators return true if ARG1 is equal, not-equal, less-than, less-than-or-equal, greater-than, or greater-than-or-equal than ARG2.
- This is a synonym for the "test" builtin, but the last argument must be a literal `]`, to match the opening `[`.
- Print the accumulated user and system times for processes run from

- the shell.
- The command ARG is to be read and executed when the shell receives
- signal(s) SIGNALSPEC. If ARG is absent (and a single SIGNALSPEC
- is supplied) or '-', each specified signal is reset to its original value. If ARG is the null string each SIGNAL_SPEC is ignored by the shell and by the commands it invokes. If a SIGNAL_SPEC is EXIT (0) the command ARG is executed on exit from the shell. If a SIGNAL_SPEC is DEBUG, ARG is executed after every simple command. If the -p option
- is supplied then the trap commands associated with each SIGNALSPEC are
- displayed. If no arguments are supplied or if only -p is given, trap prints the list of commands associated with each signal. Each SIGNAL_SPEC is either a signal name in <signal.h> or a signal number. Signal names are case insensitive and the SIG prefix is optional. trap -l prints
- a list of signal names and their corresponding numbers. Note that a
- signal can be sent to the shell with "kill -signal \$\$".
- For each NAME, indicate how it would be interpreted if used as a
- command name.
- If the -t option is used, type outputs a single word which is one of alias', keyword', function', builtin', file' or', if NAME is an alias, shell reserved word, shell function, shell builtin, disk file, or unfound, respectively. If the -p flag is used, type either returns the name of the disk
- file that would be executed, or nothing if type -t NAME' would not return file'.
- If the -a flag is used, type displays all of the places that contain an executable named file'. This includes aliases, builtins, and
- functions, if and only if the -p flag is not also used.
- The -f flag suppresses shell function lookup.
- The -P flag forces a PATH search for each NAME, even if it is an alias,
- builtin, or function, and returns the name of the disk file that would
- be executed.
- Ulimit provides control over the resources available to processes
- started by the shell, on systems that allow such control. If an
- option is given, it is interpreted as follows:
- -S
- use the soft' resource limit -H use the hard' resource limit
- -a
- all current limits are reported
- -c
- the maximum size of core files created
- -d
- the maximum size of a process's data segment
- -e
- the maximum scheduling priority (nice') -f the maximum size of files created by the shell -i the maximum number of pending signals -l the maximum size a process may lock into memory -m the maximum resident set size -n the maximum number of open file descriptors -p the pipe buffer size -q the maximum number of bytes in POSIX message queues -r the maximum rt priority -s the maximum stack size -t the maximum amount of cpu time in seconds -u the maximum number of user processes -v the size of virtual memory -x the maximum number of file locks - If LIMIT is given, it is the new value of the specified resource; the special LIMIT values soft', hard', and unlimited' stand for
- the current soft limit, the current hard limit, and no limit, respectively.
- Otherwise, the current value of the specified resource is printed.
- If no option is given, then -f is assumed. Values are in 1024-byte

- increments, except for `-t`, which is in seconds, `-p`, which is in
- increments of 512 bytes, and `-u`, which is an unscaled number of
- processes.
- The user file-creation mask is set to `MODE`. If `MODE` is omitted, or if
- `-S` is supplied, the current value of the mask is printed. The `-S`
- option makes the output symbolic; otherwise an octal number is output.
- If `-p` is supplied, and `MODE` is omitted, the output is in a form that may be used as input. If `MODE` begins with a digit, it is interpreted as an octal number, otherwise it is a symbolic mode string like that accepted by `chmod(1)`. Wait for the specified process and report its termination status. If `N` is not given, all currently active child processes are waited for, and the return code is zero. `N` may be a process ID or a job specification; if a job spec is given, all processes in the job's pipeline are waited for. The `for` loop executes a sequence of commands for each member in a
- list of items. If in `WORDS ...;` is not present, then in `"$@"` is
- assumed. For each element in `WORDS`, `NAME` is set to that element, and
- the `COMMANDS` are executed.
- Equivalent to
- `(( EXP1 ))`
- `while (( EXP2 )); do`
- `COMMANDS`
- `(( EXP3 ))`
- `EXP1`, `EXP2`, and `EXP3` are arithmetic expressions. If any expression is
- omitted, it behaves as if it evaluates to 1.
- The `WORDS` are expanded, generating a list of words. The
- set of expanded words is printed on the standard error, each
- preceded by a number. If in `WORDS'` is not present, in `"$@"`
- is assumed. The PS3 prompt is then displayed and a line read
- from the standard input. If the line consists of the number
- corresponding to one of the displayed words, then `NAME` is set
- to that word. If the line is empty, `WORDS` and the prompt are
- redisplayed. If EOF is read, the command completes. Any other
- value read causes `NAME` to be set to null. The line read is saved
- in the variable `REPLY`. `COMMANDS` are executed after each selection
- until a break command is executed.
- Execute `PIPELINE` and print a summary of the real time, user CPU time,
- and system CPU time spent executing `PIPELINE` when it terminates.
- The return status is the return status of `PIPELINE`. The `-p` option prints the timing summary in a slightly different format. This uses the value of the `TIMEFORMAT` variable as the output format. Selectively execute `COMMANDS` based upon WORD matching `PATTERN`. The `|` is used to separate multiple patterns.
- The `if` `COMMANDS'` list is executed. If its exit status is zero, then the `then` `COMMANDS'` list is executed. Otherwise, each `elif` `COMMANDS'` list is executed in turn, and if its exit status is zero, the corresponding `then` `COMMANDS'` list is executed and the `if` command completes. Otherwise,
- the `else` `COMMANDS'` list is executed, if present. The exit status of the entire construct is the exit status of the last command executed, or zero if no condition tested true. Expand and execute `COMMANDS` as long as the final command in the `while` `COMMANDS` has an exit status of zero.
- Expand and execute `COMMANDS` as long as the final command in the
- `until` `COMMANDS` has an exit status which is not zero. Create a simple command invoked by `NAME` which runs `COMMANDS`. Arguments on the command line along with `NAME` are passed to the function as `$0 .. $n`. Run a set of commands in a group. This is one way to redirect an

entire set of commands. Equivalent to the `JOB_SPEC` argument to the `fg` command. Resume a

- stopped or background job. `JOBSPEC` can specify either a job name
- or a job number. Following `JOBSPEC` with a `&` places the job in the background, as if the job specification had been supplied as an argument to `bg`.
- The `EXPRESSION` is evaluated according to the rules for arithmetic
- evaluation. Equivalent to "`let EXPRESSION`".
- Returns a status of 0 or 1 depending on the evaluation of the conditional
- expression `EXPRESSION`. Expressions are composed of the same primaries used
- by the `test` builtin, and may be combined using the following operators (`EXPRESSION`) Returns the value of `EXPRESSION` ! `EXPRESSION` True if `EXPRESSION` is false; else false `EXPR1 && EXPR2` True if both `EXPR1` and `EXPR2` are true; else false `EXPR1 || EXPR2` True if either `EXPR1` or `EXPR2` is true; else false When the `<code>==` and</code> `!=` operators are used, the string to the right of the operator is used as a pattern and pattern matching is performed. The `&&` and `||` operators do not evaluate `EXPR2` if `EXPR1` is sufficient to determine the expression's value. `BASH_VERSION` Version information for this Bash. `CDPATH` A colon-separated list of directories to search for directories given as arguments to `cd`.
- `GLOBIGNORE`
- A colon-separated list of patterns describing filenames to
- be ignored by pathname expansion.
- `HISTFILE` The name of the file where your command history is stored.
- `HISTFILESIZE` The maximum number of lines this file can contain.
- `HISTSIZE` The maximum number of history lines that a running
- shell can access.
- `HOME` The complete pathname to your login directory.
- `HOSTNAME`
- The name of the current host.
- `HOSTTYPE` The type of CPU this version of Bash is running under.
- `IGNOREEOF` Controls the action of the shell on receipt of an EOF
- character as the sole input. If set, then the value
- of it is the number of EOF characters that can be seen
- in a row on an empty line before the shell will exit
- (default 10). When unset, EOF signifies the end of input.
- `MACHTYPE`
- A string describing the current system Bash is running on.
- `MAILCHECK`
- How often, in seconds, Bash checks for newmail.
- `MAILPATH`
- A colon-separated list of filenames which Bash checks
- for newmail.
- `OSTYPE`
- The version of Unix this version of Bash is running on.
- `PATH` A colon-separated list of directories to search when
- looking for commands.
- `PROMPTCOMMAND` A command to be executed before the printing of each
- primary prompt.
- `PS1` The primary prompt string.
- `PS2` The secondary prompt string.
- `PWD`
- The full pathname of the current directory.
- `SHELLOPTS`
- A colon-separated list of enabled shell options.

- TERM The name of the current terminal type.
- TIMEFORMAT
- The output format for timing statistics displayed by the
- `time'` reserved word.
- `auto_resume` Non-null means a command word appearing on a line by itself is first looked for in the list of currently stopped jobs. If found there, that job is foregrounded.
- A value of **exact'** means that the command word must exactly match a command in the list of stopped jobs. A
- value of `substring'` means that the command word must match a substring of the job. Any other value means that the command must be a prefix of a stopped job.
- `histchars` Characters controlling history expansion and quick substitution. The first character is the history substitution character, usually `!`. The second is the quick substitution character, usually `^`. The third is the history comment character, usually `#`.
- HISTIGNORE
- A colon-separated list of patterns used to decide which commands should be saved on the history list.
- Adds a directory to the top of the directory stack, or rotates the stack, making the new top of the stack the current working directory. With no arguments, exchanges the top two directories.
- `+N`
- Rotates the stack so that the Nth directory (counting from the left of the list shown by `dirs'`, starting with zero) is at the top.
- `-N` Rotates the stack so that the Nth directory (counting from the right of the list shown by `dirs'`, starting with zero) is at the top.
- `-n`
- suppress the normal change of directory when adding directories to the stack, so only the stack is manipulated.
- `dir`
- adds DIR to the directory stack at the top, making it the new current working directory.
- You can see the directory stack with the `dirs'` command.
- Removes entries from the directory stack. With no arguments, removes the top directory from the stack, and `cd's` to the new top directory.
- `+N` removes the Nth entry counting from the left of the list shown by `dirs'`, starting with zero. For example: `popd +0'` removes the first directory, `popd +1'` the second.
- `-N`
- removes the Nth entry counting from the right of the list shown by `dirs'`, starting with zero. For example: `popd -0'`
- removes the last directory, `popd -1'` the next to last.
- `-n` suppress the normal change of directory when removing directories from the stack, so only the stack is manipulated.
- You can see the directory stack with the `dirs'` command.
- Display the list of currently remembered directories. Directories find their way onto the list with the `pushd'` command; you can get back up through the list with the `popd'` command.
- The `-l` flag specifies that `dirs'` should not print shorthand versions of directories which are relative to your home directory. This means that `~/bin'` might be displayed as `/homes/bfox/bin'`. The `-v` flag causes `dirs'` to print the directory stack with one entry per line, prepending the directory name with its position in the stack. The `-p` flag does the same thing, but the stack position is not prepended.
- The `-c` flag clears the directory stack by deleting all of the elements.
- `+N`

- displays the Nth entry counting from the left of the list shown by
- dirs when invoked without options, starting with zero.
- -N
- displays the Nth entry counting from the right of the list shown by
- dirs when invoked without options, starting with zero.
- Toggle the values of variables controlling optional behavior.
- The -s flag means to enable (set) each OPTNAME; the -u flag
- unsets each OPTNAME. The -q flag suppresses output; the exit
- status indicates whether each OPTNAME is set or unset. The -o
- option restricts the OPTNAMEs to those defined for use with
- set -o'. With no options, or with the -p option, a list of all settable options is displayed, with an indication of whether or not each is set. printf formats and prints ARGUMENTS under control of the FORMAT. FORMAT is a character string which contains three types of objects: plain characters, which are simply copied to standard output, character escape sequences which are converted and copied to the standard output, and format specifications, each of which causes printing of the next successive argument. In addition to the standard printf(1) formats, %b means to expand backslash escape sequences in the corresponding argument, and %q means to quote the argument in a way that can be reused as shell input. If the -v option is supplied, the output is placed into the value of the shell variable VAR rather than being sent to the standard output. For each NAME, specify how arguments are to be completed. If the -p option is supplied, or if no options are supplied, existing completion specifications are printed in a way that allows them to be reused as input. The -r option removes a completion specification for each NAME, or, if no NAMES are supplied, all completion specifications. Display the possible completions depending on the options. Intended to be used from within a shell function generating possible completions. If the optional WORD argument is supplied, matches against WORD are generated. alias %s': invalid alias name
- bindbuiltin
- lvpVPsSf:q:u:m:r:x:
- %s': invalid keymap name %s: cannot read: %s %s': unknown function name
- %s is not bound to any keys.
- %s can be invoked via
- "%s"%s
- %s': cannot unbind only meaningful in a <code>for',</code>while', or until' loop
- loop count
- %s %s %s
- OLDPWD=
- HOME not set
- OLDPWD not set
- CDPATH
- commandbuiltin
- /bin:/usr/bin:/sbin:/usr/sbin
- %s: error retrieving current directory: %s: %s
- %s: usage:
- %s: ambiguous job spec
- write error: %s
- %s: not a shell builtin
- %s: restricted
- %s: no job control
- %s: no such job
- %s: %s out of range
- %s': not a pid or valid job spec %s: invalid signal specification SIGJUNK

```
<li>Unknown</li> <li>%2d) %s</li> <li>%s: invalid number</li> <li>%s: invalid option name</li> <li>%s:
not found</li> <li>%s: numeric argument required</li> <li>cannot use -f to make functions
```

- %s %d %s
 - %s: cannot destroy array variables in this way
 - +afiprtxF
 - can only be used in a function
 - adnpsf:
 - enable %s
 - enable -n %s
 - cannot open shared object %s: %s
 - struct
 - cannot find %s in shared object %s: %s
 - %s: not dynamically loaded
 - %s: cannot delete: %s
 - %s: not a regular file
 - %s: file is too large
 - evalfile
 - parseandexecutetop
 - pedispose
 - parseandexecute
 - %s: cannot execute: %s
 - ~/.bashlogout
 - /etc/bash/bashlogout
 - There are stopped jobs.
 - not login shell: use `exit'` logout \${FCEDIT:-\${EDITOR:-ed}} \${FCEDIT:-\${EDITOR:-vi}} fc builtin :e:lnrs no command found history specification bash-fc %s: cannot open temp file: %s current job %d started without job control builtin hash -p %s %s hashing disabled dlp:rt command %s: hash table empty These shell commands are defined internally. Type `help'` to see this list.
- Type `help name'` to find out more about the function `name'`.
 - Use `info bash'` to find out more about the shell in general.Use `man -k'` or</code>`info'` to find out more about commands not in this list. A star (*) next to a name means that the command is disabled. Shell commands matching keywords
- Shell commands matching keyword %s: cannot open: %s no help topics match `<code>%s'`. Try</code>`help help'` or `<code>man -k %s'` or</code>`info %s'`. %5d%c %s% acd:npsrw cannot use more than one of -anrw %s: history expansion failed history position no other options allowed with -X'
- lpnxrs
 - jobsbuiltin
 - Unknown error
 - (%ld) - %s
 - %s: arguments must be process or job IDs
 -
 - %2d %s
 - %2d %s
 - dirstack
 - directory stack empty
 - directory stack index
 - no other directory
 - readbuiltin
 - read error: %d: %s
 - %s: invalid timeout specification

- %s: invalid file descriptor specification
- %d: invalid file descriptor: %s
- ersa:d:n:p:t:u:
- can only return' from a function or sourced script editing-mode cannot simultaneously unset a function and a variable %s: cannot unset %s: cannot unset: readonly %s %s: not an array variable SHELLOPTS set %co %s allexport braceexpand errexit errtrace functrace hashall histexpand interactive-comments keyword monitor noclobber noexec noglob notify nounset onecmd physical pipefail privileged xtrace declare -%s %s -%s %s: not a function shift count filename argument required %s: file not found cannot suspend cannot suspend a login shell unknown trap -- %s %d trap -- %s %s %s is aliased to %s'
- alias %s=%s
- %s is a shell keyword
- %s is a function
- %s is a shell builtin
- %s is %s
- %s is hashed (%s)
- (%s, -%c)
- (-%c)
- %-20s %16s
- unlimited
- %s: cannot get limit: %s
- %c': bad command %s: cannot modify limit: %s core file size blocks data seg size kbytes file size pending signals max locked memory max memory size open files pipe size 512 bytes POSIX message queues stack size cpu time seconds max user processes virtual memory file locks umask%s %c': invalid symbolic mode operator
- %c': invalid symbolic mode character u=%s,g=%s,o=%s octal number OPTARG %s: invalid shell option name shopt %s %s cannot set and unset shell options simultaneously cdable_vars cdspell checkhash checkwinsize cmdhist dotglob execfail expand_aliases extdebug extglob extquote failglob force_fignore gnu_errfmt histappend histreedit histverify hostcomplete huponexit interactive_comments lithist login_shell mailwarn noemptycmd_completion nocaseglob nocasematch >nullglob progcomp promptvars restricted_shell shift_verbos sourcepath xpg_echo missing hex digit for \x warning: %s: %s #'-+0 hjlLt %s': missing format character
- %s: illegal option -- %c
- %s: option requires an argument -- %c
- warning: -F option may not work as you expect
- warning: -C option may not work as you expect
- %s: invalid action name
- abcdefgjkoprsvA:G:W:P:S:X:F:C:
- complete
- -o %s
- bashdefault
- dirnames
- filenames
- nospace

- plusdirs
- -A %s
- arrayvar
- binding
- enabled
- helptopic
- hostname
- running
- setopt
- signal
- %s %s
- %s: no completion specification
- service
- BASHREMATCH
- %s: *bad network path specification*
- *socket*
- *connect*
- %ldm%d.%03ds
- shmakepath
- shrealpath
- TMPDIR
- /var/tmp
- /usr/tmp
- %s/%s-%lu
- %s/cur
- %s/tmp
- %s/new
- *invalid base*
- 0123456789ABCDEF
- 0123456789abcdef
- l|h^0%bB
- l|hWw^0bB
- l|h^0bB
- h|^\$0ftFT;,%wbeWBE]
- *AaIiCcDdPpYyRrSsXx~
- accept-line
- arrow-key-prefix
- backward-byte
- backward-char
- backward-kill-line
- backward-kill-word
- backward-word
- beginning-of-history
- beginning-of-line
- call-last-kbd-macro
- capitalize-word
- character-search
- character-search-backward
- clear-screen
- copy-backward-word
- copy-forward-word
- copy-region-as-kill

- delete-char
- delete-char-or-list
- delete-horizontal-space
- digit-argument
- do-lowercase-version
- downcase-word
- dump-functions
- dump-macros
- dump-variables
- emacs-editing-mode
- end-kbd-macro
- end-of-history
- end-of-line
- exchange-point-and-mark
- forward-backward-delete-char
- forward-byte
- forward-char
- forward-word
- history-search-backward
- history-search-forward
- insert-comment
- insert-completions
- kill-whole-line
- kill-line
- kill-region
- kill-word
- menu-complete
- next-history
- non-incremental-forward-search-history
- non-incremental-reverse-search-history
- non-incremental-forward-search-history-again
- non-incremental-reverse-search-history-again
- overwrite-mode
- possible-completions
- previous-history
- quoted-insert
- re-read-init-file
- redraw-current-line
- revert-line
- self-insert
- set-mark
- start-kbd-macro
- tab-insert
- tilde-expand
- transpose-chars
- transpose-words
- tty-status
- universal-argument
- unix-filename-rubout
- unix-line-discard
- unix-word-rubout
- upcase-word

- yank-last-arg
- yank-nth-arg
- yank-pop
- vi-append-eol
- vi-append-mode
- vi-arg-digit
- vi-back-to-indent
- vi-bWord
- vi-bword
- vi-change-case
- vi-change-char
- vi-change-to
- vi-char-search
- vi-column
- vi-complete
- vi-delete
- vi-delete-to
- vi-eWord
- vi-editing-mode
- vi-end-word
- vi-eof-maybe
- vi-eword
- vi-fWord
- vi-fetch-history
- vi-first-print
- vi-fword
- vi-goto-mark
- vi-insert-beg
- vi-insertion-mode
- vi-match
- vi-movement-mode
- vi-next-word
- vi-overstrike
- vi-overstrike-delete
- vi-prev-word
- vi-put
- vi-redo
- vi-replace
- vi-rubout
- vi-search
- vi-search-again
- vi-set-mark
- vi-subst
- vi-tilde-expand
- vi-yank-arg
- vi-yank-to
- --More--
- Display all %d possibilities? (y or n)
- readline: bad value %d for whattodo in rlcomplete
- "\ @\${>}<;=|&{("%s%s": "%s" %s outputs %s readline: %s: line %d: %s readline: %s \$endif without matching \$if \$else found without matching \$if audible visible bell-style completion-query-items

isearch-terminators keymap set %s %s %s is set to %s'

- *blink-matching-paren*
- *prefer-visible-bell*
- *# %s (not bound)*
- *"%s": %s*
- *%s is not bound to any keys*
- *%s can be found on*
- *unknown parser directive*
- *no closing "" in key binding prefix-meta INPUTRC ~/.inputrc /etc/inputrc Control- bind-tty-special-chars byte-oriented convert-meta disable-completion enable-keypad expand-tilde history-preserve-point horizontal-scroll-mode input-meta mark-directories mark-modified-lines mark-symlinked-directories match-hidden-files meta-flag output-meta page-completions print-completions-horizontally show-all-if-ambiguous show-all-if-unmodified visible-stats emacs-standard emacs-meta emacs-ctlx vi-move vi-command vi-insert include Escape Newline Return Rubout reverse- i-search)*
- *readline: debug: insertsomechars: count (%d) != col (%d)*
- */=~.#\$*
- *readline: readlinecallbackreadchar() called with no handler!*
- *(arg: %d)*
- *<>;&|\$*
- *no previous substitution*
- *unknown expansion error*
- *event not found*
- *bad word specifier*
- *substitution failed*
- *unrecognized history modifier*
- *;&()|<>*
- *.history*
- *xdigit*
- *backspace*
- *vertical-tab*
- *form-feed*
- *carriage-return*
- *exclamation-mark*
- *quotation-mark*
- *number-sign*
- *dollar-sign*
- *percent-sign*
- *ampersand*
- *apostrophe*
- *left-parenthesis*
- *right-parenthesis*
- *asterisk*
- *plus-sign*
- *hyphen*
- *hyphen-minus*
- *period*
- *full-stop*
- *semicolon*

- [illegible]

- [illegible]

- [illegible]

- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- GCC: (GNU) 4.1.1 (Gentoo 4.1.1)
- .shstrtab
- .interp
- .note.ABI-tag
- .reginfo
- .dynamic
- .dynsym
- .dynstr
- .gnu.version
- .gnu.versionr
- .MIPS.stubs
- .rodata
- .ehframehdr
- .ehframe
- .ctors
- .dtors
- .data.rel.ro
- .rldmap
- .comment
- .mdebug.abi32

UTF-8 Strings

No detected.

UTF-16LE Strings

- 244.,,
- &'()55
- " !"# \$%&'()
- /0<=@b1
-]^T9Uwy:~sz
- mnogh_

- !c"#\$\$%&'()
- 56tufp7/

Extracted URLs

No detected.

Base64 Strings

No valid Base64-encoded strings found.

File Entropy Analysis

- **Entropy:** 5.82
- **Status:** This file likely contains Standard Text or human-readable text.

VirusTotal Analysis

Scan Date: 2024-12-14 07:24:57

Scan Results

- Malicious: 0
- Suspicious: 0
- Undetected: 63
- Harmless: 0
- Timeout: 0
- Confirmed-timeout: 0
- Failure: 0
- Type-unsupported: 13

Community Votes

- Harmless: 0
- Malicious: 0

Detailed Engine Results

Engine Name	Detection Category	Detection
No results	No results	No results