

Malware Analysis Report For MachO-OSX-ppc-openssl-1.0

Binary Type

Mach-O (Mach Object). (Approved)

Analyzing File

- **File Name:** MachO-OSX-ppc-openssl-1.0
 - **File Extension:** .1h
 - **File Type:** Mach-O (Mach Object).
 - **MD5 Hash:** bae4089c1ed3d12c3529b513bb15a8b2
 - **SHA256 Hash:** 06b0515f7779a51a8362a32428d4f8de1bd30021ed2ab5092cb8f9a87a0fe4fd
-

File Identification

File detected as a valid macOS/iOS executable.

Mach-O File Analysis

Mach-O File Analysis: True

Mach-O File Imports

No Imported functions were found.

Mach-O File Exports

No Exported functions were found.

Linked Dynamic Libraries

No dynamically linked libraries found.

Mach-O Symbols

No additional symbols found.

String Analysis

ASCII Strings

- 8__PAGEZERO
- __TEXT
- __text
- __TEXT

- `__symbolstub1`
- `__TEXT`
- `__cstring`
- `__TEXT`
- `__const`
- `__TEXT`
- `__literal4`
- `__TEXT`
- `__literal8`
- `__TEXT`
- `__DATA`
- `__data`
- `__DATA`
- `__dyld`
- `__DATA`
- `__/asymbol_ptr`
- `__DATA`
- `__/n/symbol_ptr`
- `__DATA`
- `__const`
- `__DATA`
- `__DATA`
- `__common`
- `__DATA`
- `8__LINKEDIT`
- `/usr/lib/dyld`
- `/usr/local/Cellar/openssl/1.0.1h/lib/libssl.1.0.0.dylib`
- `/usr/local/Cellar/openssl/1.0.1h/lib/libcrypto.1.0.0.dylib`
- `/usr/lib/libgcc_s.1.dylib`
- `/usr/lib/libSystem.B.dylib`
- `V\;iVp<_`
- `8:BVh;)V<<_`
- `x:BR$<_`
- `9"Jh8!`
- `V1@>H`
- `V1@>H`
- `V1@>H`
- `X:BJ@<_`
- `Cx};Kx}YSx`
- `U" 6j``
- `Cx}2Kx}QSx`
- `x}%Kx8`
- `Cx}2Kx}QSx|v`
- `;BRh;)X`
- `;"@T<_`
- `4T@F>/`
- `H;B5t;`
- `;" ,,<_`
- `;b#@<_`
- `H:b#H<_`
- `kx8B6(`
- `x9)W@H`

- :B0H<_
- ;".l<_
- .}b[xH
- /)BSx@
- 8b#T=?
- = C0<_
- x}'KxH
- ;)gl;a
- ;i^d:a
- +p8cgdH
- :)^t=?
- A<@C0o
- 8:B^X<_
- x{q.@
- ~[H.=?
- @.U)@.T
- KxUk@.
- @.U)@.T
- KxUk@.
- @.U)@.T
- KxUk@.
- :lNx??
- wX,;b}4<_
- Cx};Kx}{Sx|y
- 3x}9Kx|z
- Cx}6Kx}USxH
- 3x}9Kx|z
- }"X.9)
- 9b`(9l
- 9b`89l
- 9b`L9l
- 9b``9l
- 9b`p9l
- Cx}i[x
- 9Bdt<_
- ;bWl<_
- p:bOP:.)O<>_
- U)@.lB
- :BDP~D
- :b6T:l6H>
- x9)-x8
- Cx};Kx}YSxH
- 0TB >|P
- 8TB >|P
-
- tTB >|P
- Cx};Kx}ZSx
- ;x};Kx}YSx;
-
- %s => %s
- list-standard-commands
- list-message-digest-commands

- list-message-digest-algorithms
- list-cipher-commands
- list-cipher-algorithms
- list-public-key-algorithms
- Name: %s
- Type: Alias to %s
- External
- Builtin
- Type: %s Algorithm
- OID: %s
- (none)
- PEM string: %s
- openssl:Error: '%s' is an invalid command.
- Standard commands
- Message Digest commands (see the `dgst' command for more details)
- Cipher commands (see the `enc' command for more details)
- OPENSSLDEBUGMEMORY
- OPENSSL_FIPS
- FIPS mode not supported.
- OPENSSL_CONF
- SSLEAY_CONF
- WARNING: can't open config file: %s
- OpenSSL>
- error in %s
- bad exit
- invalid mode
- type out of bounds
- already locked
- not locked
- CRYPTOunlock on write lock
- CRYPTOunlock on read lock
- openssl (lockdbgcb): %s (mode=%d, type=%d) at %s:%d
- verify
- asn1parse
- dhparam
- passwd
- errstr
- rsautl
- dsaparam
- ecparam
- genrsa
- gendsa
- genpkey
- s_server
- s_client
- s_time
- version
- crl2pkcs7
- sess_id
- ciphers
- pkcs12
- pkeyparam

- pkeyutil
- engine
- rmd160
- aes-128-cbc
- aes-128-ecb
- aes-192-cbc
- aes-192-ecb
- aes-256-cbc
- aes-256-ecb
- camellia-128-cbc
- camellia-128-ecb
- camellia-192-cbc
- camellia-192-ecb
- camellia-256-cbc
- camellia-256-ecb
- base64
- rc4-40
- des-ecb
- des-ede
- des-ede3
- des-cbc
- des-ede-cbc
- des-ede3-cbc
- des-cfb
- des-ede-cfb
- des-ede3-cfb
- des-ofb
- des-ede-ofb
- des-ede3-ofb
- idea-cbc
- idea-ecb
- idea-cfb
- idea-ofb
- seed-cbc
- seed-ecb
- seed-cfb
- seed-ofb
- rc2-cbc
- rc2-ecb
- rc2-cfb
- rc2-ofb
- rc2-64-cbc
- rc2-40-cbc
- bf-cbc
- bf-ecb
- bf-cfb
- bf-ofb
- cast5-cbc
- cast5-ecb
- cast5-cfb
- cast5-ofb
- cast-cbc

- certificate file
- -CApath
- -CAfile
- -untrusted
- -trusted
- -CRLfile
- -engine
- -verbose
- Error loading file %s
- Error loading directory %s
- untrusted certificates
- trusted certificates
- other CRLs
- usage: verify [-verbose] [-CApath path] [-CAfile file] [-purpose purpose] [-crl_check]
- [-atime timestamp]
- [-engine e]
- cert1 cert2 ...
- recognized usages:
- [CRL path]
- %error %d at %d depth lookup:%s
- Memory allocation failure
- -inform
- -noout
- -offset
- -length
- -dlimit
- -strparse
- -genstr
- -genconf
- unknown option %s
- %s [options]
- where options are
- -inform arg input format - one of DER PEM
- -in arg input file
- -out arg output file (output format is always DER
- -noout arg don't produce any output
- -offset arg offset into file
- -length arg length of section in file
- -i indent entries
- -dump dump unknown data in hex form
- -dlimit arg dump the first arg bytes of unknown data in hex form
- -oid file file of extra oid definitions
- -strparse offset
- a series of these can be used to 'dig' into multiple
- ASN1 blob wrappings
- -genstr str string to generate ASN1 structure from
- -genconf file file to generate ASN1 structure from
- problems opening %s
- default
- Can't find 'asn1' in '%s'
- Error on line %ld of config file '%s'
- Error loading config file '%s'

- '%s' is an invalid number
- Error parsing structure
- OBJECT
- Can't parse %s type
- Error: offset too large
- Error writing output
- string is too short, it needs to be at least %d bytes long
- string is too long, it needs to be less than %d bytes long
- parameter error "%s"
- param:
- Unknown algorithm %.*s
- Can't open parameter file %s
- Error reading parameter file %s
- Key Type does not match parameters
- Internal error: can't find key algorithm
- Error allocating keygen context
- Error initializing keygen context
- Error setting RSA keysize
- -outform
- -keygen_engine
- Can't find keygen engine %s
- -pubkey
- -config
- -keyform
- -keyout
- -passin
- -passout
- -newkey
- -pkeyopt
- -sigopt
- -batch
- -newhdr
- -modulus
- -verify
- -nodes
- -nameopt
- -reqopt
- -subject
- -asn1-kludge
- -no-asn1-kludge
- -multivalue-rdn
- -set_serial
- -extensions
- -reqexts
- %s [options]
- where options are
- -inform arg input format - DER or PEM
- -outform arg output format - DER or PEM
- -in arg input file
- -out arg output file
- -text text form of request
- -pubkey output public key

- -noout do not output REQ
- -verify verify signature on REQ
- -modulus RSA modulus
- -nodes don't encrypt the output key
- -engine e use engine e, possibly a hardware device
- -subject output the request's subject
- -passin private key password source
- -key file use the private key contained in file
- -keyform arg key file format
- -keyout arg file to send the key to
- -rand file%cfile%c...
- load the file (or the files in the directory) into
- the random number generator
- -newkey rsa:bits generate a new RSA key of 'bits' in size
- -newkey dsa:file generate a new DSA key, parameters taken from CA in 'file'
- -newkey ec:file generate a new EC key, parameters taken from CA in 'file'
- -[digest] Digest to sign with (md5, sha1, md2, mdc2, md4)
- -config file request template file.
- -subj arg set or modify request subject
- -multivalue-rdn enable support for multivalued RDNs
- -new new request.
- -batch do not ask anything during request generation
- -x509 output a x509 structure instead of a cert. req.
- -days number of days a certificate generated by -x509 is valid for.
- -set_serial serial number to use for a certificate generated by -x509.
- -newhdr output "NEW" in the header lines
- -asn1-kludge Output the 'request' in a format that is wrong but some CA's
- have been reported as requiring
- -extensions .. specify certificate extension section (override value in config file)
- -reqexts .. specify request extension section (override value in config file)
- -utf8 input characters are UTF8 (default ASCII)
- -nameopt arg - various certificate name options
- -reqopt arg - various request text options
- Error getting passwords
- Using configuration from %s
- error on line %ld of %s
- Unable to load config info from %s
- oid_file
- default_md
- x509_extensions
- Error Loading extension section %s
- input_password
- output_password
- string_mask
- Invalid global string mask setting %s
- req_extensions
- Error Loading request extension section %s
- Private Key
- RANDFILE
- default_bits
- private key length is too short,
- it needs to be at least %d bits, not %ld

- Generating a %ld bit %s private key
- Error Generating Key
- default_keyfile
- writing new private key to stdout
- writing new private key to '%s'
- encryptrsakey
- encrypt_key
- bad input format specified for X509 request
- unable to load X509 request
- you need to specify a private key
- prompt
- distinguished_name
- unable to find '%s' in config
- unable to get '%s' section
- attributes
- error, no objects specified in config file
- You are about to be asked to enter information that will be incorporated
- into your certificate request.
- What you are about to enter is what is called a Distinguished Name or a DN.
- There are quite a few fields but you can leave some blank
- For some fields there will be a default value,
- If you enter '.', the field will be left blank.
- _default
- _value
- %s_default
- Name '%s' too long
- %s_value
- %s_min
- %s_max
- %s [%s]:
- weird input :-(
- Please enter the following 'extra' attributes
- to be sent with your certificate request
- Error adding attribute
- No template, please set one up.
- problems making Certificate Request
- Cannot modify certificate subject
- Modifying Request's Subject
- old subject=
- ERROR: cannot modify subject
- new subject=
- verify failure
- verify OK
- Error getting public key
- subject=
- Modulus=unavailable
- Modulus=
- Wrong Algorithm type
- bad output format specified for outfile
- unable to write X509 request
- unable to write X509 certificate
- Read Error in %s

- Verified OK
- Verification Failure
- Error Verifying Data
- Error Signing Data
- %s-%s(%s)=
- %s(%s)=
- (%s)=
- dgst.c
- out of memory
- -prverify
- -signature
- -binary
- -fips-fingerprint
- etaonrshdlcupfm
- -non-fips-allow
- -macopt
- No signature to verify: use the -signature option
- unknown option '%s'
- options are
- -c to output the digest with separating colons
- -r to output the digest in coreutils format
- -d to output debug info
- -hex output as hex dump
- -binary output in binary form
- -sign file sign digest using private key in file
- -verify file verify a signature using public key in file
- -prverify file verify a signature using private key in file
- -keyform arg key file format (PEM or ENGINE)
- -out filename output to filename rather than stdout
- -signature file signature to verify
- -sigopt nm:v signature parameter
- -hmac key create hashed MAC with key
- -mac algorithm create MAC (not necessarily HMAC)
- -macopt nm:v MAC algorithm parameters or key
- -engine e use engine e, possibly a hardware device.
- Error getting password
- (stdout)
- Error opening output file %s
- MAC and Signing key cannot both be specified
- key file
- MAC parameter error "%s"
- Error generating key
- Error getting context
- Error setting context
- Error setting digest %s
- Error opening signature file %s
- Error reading signature file %s
- -%-14s to use the %s message digest algorithm
- -check
- -outform arg output format - one of DER PEM
- -out arg output file
- -check check the DH parameters

- -text print a text form of the DH parameters
- -C Output C code
- -noout no output
- -engine e use engine e, possibly a hardware device.
- bad input format specified
- unable to load DH parameters
- p value is not prime
- p value is not a safe prime
- unable to check the generator value
- the g value is not a generator
- DH parameters appear to be ok.
- OPENSSL_malloc
- static unsigned char dh%d_p[]={
- 0x%02X,
- static unsigned char dh%d_g[]={
- DH *get_dh%d()
- DH *dh;
- if ((dh=DH_new()) == NULL) return(NULL);
- dh->p=BNbin2bn(dh%dp,sizeof(dh%d_p),NULL);
- dh->g=BNbin2bn(dh%dg,sizeof(dh%d_g),NULL);
- if ((dh->p == NULL) || (dh->g == NULL))
- return(NULL);
- return(dh);
- unable to write DH parameters
- -dsaparam
- %s [options] [numbits]
- -dsaparam read or generate DSA parameters, convert to DH
- -2 generate parameters using 2 as the generator value
- -5 generate parameters using 5 as the generator value
- numbits number of bits in to generate (default 512)
- - load the file (or the files in the directory) into
- the random number generator
- generator may not be chosen for DSA parameters
- warning, not much extra random data, consider using the -rand option
- %ld semi-random bytes loaded
- Generating DSA parameters, %d bit long prime
- Generating DH parameters, %d bit long safe prime, generator %d
- This is going to take a long time
- unable to load DSA parameters
- dhparam.c
- #ifndef HEADERDHH
- #include
- #endif
- static unsigned char dh%dp[]={
- static unsigned char dh%dg[]={
- { DHfree(dh); return(NULL); }
- dh->length = %ld;
- hex string is too long
- non-hex digit
- %s is an unknown cipher

- *-nopad*
- *-nosalt*
- *-debug*
- *-base64*
- *-bufsize*
- *-kfile*
- *unable to read key from '%s'*
- *zero length password*
- *%-14s input file*
- *-in*
- *%-14s output file*
- *-out*
- *%-14s pass phrase source*
- *-pass*
- *%-14s encrypt*
- *%-14s decrypt*
- *%-14s base64 encode/decode, depending on encryption flag*
- *-a/-base64*
- *%-14s passphrase is the next argument*
- *%-14s passphrase is the first line of the file argument*
- *%-14s the next argument is the md to use to create a key*
- *%-14s from a passphrase. One of md2, md5, sha or sha1*
- *%-14s salt in hex is the next argument*
- *%-14s key/iv in hex is the next argument*
- *-K/-iv*
- *%-14s print the iv/key (then exit if -P)*
- *%-14s buffer size*
- *-bufsize*
- *%-14s disable standard block padding*
- *%-14s use engine e, possibly a hardware device.*
- *-engine e*
- *Cipher Types*
- *AEAD ciphers not supported by the enc utility*
- *%s is an unsupported message digest type*
- *invalid 'bufsize' specified.*
- *bufsize=%d*
- *OPENSSLmalloc failure %ld*
- *encryption*
- *decryption*
- *enter %s %s password:*
- *bad password read*
- *invalid hex salt value*
- *error writing output file*
- *error reading input file*
- *bad magic number*
- *invalid hex iv value*
- *iv undefined*
- *invalid hex key value*
- *Error setting cipher %s*
- *bad decrypt*
- *bytes read :%8ld*
- *bytes written:%8ld*

- `-%-25s`
- `Salted_`
- `passwd.c`
- `saltp != NULL`
- `saltmallocp != NULL`
- `salt_p != NULL`
- *Warning: truncating password to %u characters*
- `strlen(passwd) <= pw_maxlen`
- `strlen(magic) <= 4`
- `strlen(out_buf) <= 6 + 8`
- `salt_len <= 8`
- `output == outbuf + strlen(outbuf)`
- `strlen(outbuf) < sizeof(outbuf)`
- `hash != NULL`
- `-crypt`
- `-stdin`
- `-noverify`
- `-quiet`
- `-table`
- `-reverse`
- *Usage: passwd [options] [passwords]*
- *-crypt standard Unix password algorithm (default)*
- *-1 MD5-based password algorithm*
- *-apr1 MD5-based password algorithm, Apache variant*
- *-salt string use provided salt*
- *-in file read passwords from file*
- *-stdin read passwords from stdin*
- *-noverify never verify when reading password from terminal*
- *-quiet no warnings*
- *-table format output as table*
- *-reverse switch table columns*
- `in_stdin == 0`
- `in_stdin`
- *Password:*
- `passwd != NULL`
- `passwd != NULL`
- `passwdmain`
- `dopasswd`
- `md5crypt`
- `usage: gendh [args] [numbits]`
- `-out file` - output the key to 'file'
- `-2` - use 2 as the generator value
- `-5` - use 5 as the generator value
- `-engine e` - use engine e, possibly a hardware device.
- - load the file (or the files in the directory) into
- the random number generator
- `-stats`
- `%s`: bad error code
- `usage: errstr [-stats] ...`
- invalid revocation date `%s`
- missing hold instruction

- invalid object identifier %s
- missing compromised time
- invalid compromised time %s
- invalid reason code %s
- PRINTABLE:'
- T61STRING:'
- IA5STRING:'
- UNIVERSALSTRING:'
- ASN.1 %2d:'
- \0x%02X
- Unknown CRL reason %s
- holdInstruction
- Invalid object identifier %s
- Invalid time format %s. Need YYYYMMDDHHMMSSZ
- CAkeyTime
- keyTime
- malloc error
- The Subject's Distinguished Name is as follows
- emailAddress type needs to be of type IA5STRING
- The string contains characters that are illegal for the ASN.1 type
- %s:unknown object type in 'policy' configuration
- optional
- supplied
- The %s field needed to be supplied and was missing
- The mandatory %s field was missing
- The %s field does not exist in the CA certificate,
- the 'policy' is misconfigured
- The %s field needed to be the same in the
- CA certificate (%s) and the request (%s)
- %s:invalid type in 'policy' configuration
- The subject name appears to be ok, checking data base for clashes
- ERROR:There is already a certificate for %s
- ERROR:Serial number %s has already been issued,
- check the database/serialfile for corruption
- *The matching entry has the following details*
- *Expired*
- *Revoked*
- *invalid type, Data base error*
- *Was revoked on:%s*
- *Expires on :%s*
- *Serial Number :%s*
- *File name :%s*
- *Subject Name :%s*
- *Everything appears to be ok, creating and signing the certificate*
- *Extra configuration file found*
- *ERROR: adding extensions in section %s*
- *Successfully added extensions from file.*
- *Successfully added extensions from config*
- *ERROR: adding extensions from request*
- *Certificate Details:*
- *Certificate is to be certified until*
- *(%ld days)*

- *Sign the certificate? [y/n]:*
- *CERTIFICATE WILL NOT BE CERTIFIED: I/O error*
- *CERTIFICATE WILL NOT BE CERTIFIED*
- *unknown*
- *failed to update database*
- *TXTDB error number %ld*
- *Error reading certificate request in %s*
- *Check that the request matches the signature*
- *Certificate request and CA private key do not match*
- *error unpacking public key*
- *Signature verification problems....*
- *Signature did not match the certificate request*
- *Signature ok*
- *Adding Entry with serial number %s to DB for %s*
- *ERROR:name does not match %s*
- *ERROR:Already revoked, serial number %s*
- *Revoking Certificate %s.*
- *Error in revocation arguments*
- *-createserial*
- *-startdate*
- *-enddate*
- *-policy*
- *-keyfile*
- *-selfsign*
- *-outdir*
- *-notext*
- *-preserveDN*
- *-noemailDN*
- *-gencrl*
- *-msiehack*
- *-crl days*
- *-crl hours*
- *-crlsec*
- *-infile*
- *-sscert*
- *-spkac*
- *-revoke*
- *-extfile*
- *-status*
- *-updatedb*
- *-crl exts*
- *-crl reason*
- *-crl hold*
- *-crl compromise*
- *-crl CA compromise*
- *openssl.cnf*
- *error loading the config file '%s'*
- *error on line %ld of config file '%s'*
- *defaultca*
- *variable lookup failed for %s::%s*
- *uniquesubject*
- *database*

- Malloc failure
- Serial %s not present in db.
- %s=Valid (%c)
- %s=Revoked (%c)
- %s=Expired (%c)
- %s=Suspended (%c)
- %s=Unknown (%c).
- Error verifying serial %s!
- privatekey
- CA private key
- certificate
- CA certificate
- CA certificate and CA private key do not match
- preserve
- msiehack
- nameopt
- Invalid name options: "%s"
- certopt
- Invalid certificate options: "%s"
- copyextensions
- Invalid extension copy option: "%s"
- newcertsdir
- there needs to be defined a directory for newcertificate to be placed in
- I am unable to access the %s directory
- %s need to be a directory
- entry %d: not revoked yet, but has a revocation date
- in entry %d
- entry %d: invalid expiry date
- entry %d: bad serial number length (%d)
- entry %d: bad serial number characters, char pos %ld, char is '%c'
- %d entries loaded from the database
- generating index
- Updating %s ...
- %s=Expired
- No entries found to mark expired
- Done. %d entries marked as expired
- ERROR: loading the config file '%s'
- ERROR: on line %ld of config file '%s'
- Successfully loaded extensions file %s
- extensions
- no default digest
- emailindn
- message digest is %s
- policy
- policy is %s
- serial
- defaultstartdate
- start date is invalid, it should be YYMMDDHHMMSSZ or YYYYMMDDHHMMSSZ
- defaultenddate
- end date is invalid, it should be YYMMDDHHMMSSZ or YYYYMMDDHHMMSSZ
- defaultdays
- cannot lookup how many days to certify for

- error while loading serial number
- next serial number is 00
- next serial number is %s
- unable to find 'section' for %s
- no name/value pairs found in %s
- unable to load Netscape SPKAC structure
- Netscape SPKAC structure not found in %s
- Check that the SPKAC request matches the signature
- error unpacking SPKAC public key
- signature verification failed on SPKAC public key
- Signature did not match the certificate
- %d out of %d certificate requests certified, commit? [y/n]
- CERTIFICATION CANCELED: I/O error
- CERTIFICATION CANCELED
- Write out database with %d new entries
- writing new certificates
- certificate file name too long
- writing %s
- Data Base Updated
- *crlexensions*
- *Error Loading CRL extension section %s*
- *crlnumber*
- *error while loading CRL number*
- *defaultcrl days*
- *defaultcrl hours*
- *cannot lookup howlong until the next CRL is issued*
- *making CRL*
- *error setting CRL nextUpdate*
- *signing CRL*
- *no input files*
- *unspecified*
- *keyCompromise*
- *CACompromise*
- *affiliationChanged*
- *superseded*
- *cessationOfOperation*
- *certificateHold*
- *removeFromCRL*
- *usage: ca args*
- *-verbose - Talk alot while doing things*
- *-config file - A config file*
- *-name arg - The particular CA definition to use*
- *-gencrl - Generate a newCRL*
- *-crl days days - Days is when the next CRL is due*
- *-crl hours hours - Hours is when the next CRL is due*
- *-startdate YYMMDDHHMMSSZ - certificate validity notBefore*
- *-enddate YYMMDDHHMMSSZ - certificate validity notAfter (overrides -days)*
- *-days arg - number of days to certify the certificate for*
- *-md arg - md to use, one of md2, md5, sha or sha1*
- *-policy arg - The CA 'policy' to support*
- *-keyfile arg - private key file*
- *-keyform arg - private key file format (PEM or ENGINE)*

- *-key arg - key to decode the private key if it is encrypted*
- *-cert file - The CA certificate*
- *-selfsign - sign a certificate with the key associated with it*
- *-in file - The input PEM encoded certificate request(s)*
- *-out file - Where to put the output file(s)*
- *-outdir dir - Where to put output certificates*
- *-infile - The last argument, requests to process*
- *-spkac file - File contains DN and signed public key and challenge*
- *-sscert file - File contains a self signed cert to sign*
- *-preserveDN - Don't re-order the DN*
- *-noemailDN - Don't add the EMAIL field into certificate' subject*
- *-batch - Don't ask questions*
- *-msiehack - msie modifications to handle all those universal strings*
- *-revoke file - Revoke a certificate (given in file)*
- *-subj arg - Use arg instead of request's subject*
- *-utf8 - input characters are UTF8 (default ASCII)*
- *-multivalue-rdn - enable support for multivalued RDNs*
- *-extensions .. - Extension section (override value in config file)*
- *-extfile file - Configuration file with X509v3 extensions to add*
- *-crlxsts .. - CRL extension section (override value in config file)*
- *-engine e - use engine e, possibly a hardware device.*
- *-status serial - Shows certificate status given the serial number*
- *-updatedb - Updates db for expired certificates*
- *-print*
- *-printcerts*
- *-inform arg input format - DER or PEM*
- *-outform arg output format - DER or PEM*
- *-printcerts print any certs or crl in the input*
- *-text print full details of certificates*
- *-noout don't output encoded data*
- *bad input format specified for pkcs7 object*
- *unable to load PKCS7 object*
- *unable to write pkcs7 object*
- *-nocrl*
- *-certfile*
- *-certfile arg certificates file of chain to a trusted CA*
- *(can be used more than once)*
- *-nocrl no crl to load, just certs from '-certfile'*
- *bad input format specified for input crl*
- *unable to load CRL*
- *error opening the file, %s*
- *error reading the file, %s*
- *error loading certificates*
- *-hashold*
- *-issuer*
- *-lastupdate*
- *-nextupdate*
- *-fingerprint*
- *-crlnumber*
- *Error initialising X509 store*
- *Error getting CRL issuer certificate*
- *Error getting CRL issuer public key*

- issuer=
- crlNumber=
-
- lastUpdate=
- nextUpdate=
- %s Fingerprint=
- %02X%c
- unable to write CRL
- usage: crl args
- -inform arg - input format - default PEM (DER or PEM)
- -outform arg - output format - default PEM
- -text - print out a text format version
- -in arg - input file - default stdin
- -out arg - output file - default stdout
- -hash - print hash value
- -hashold - *print old-style (MD5) hash value*
- -fingerprint - *print the crl fingerprint*
- -issuer - *print issuer DN*
- -lastupdate - *lastUpdate field*
- -nextupdate - *nextUpdate field*
- -crlnumber - *print CRL number*
- -noout - *no CRL output*
- -CAfile name - *verify CRL using certificates in file "name"*
- -CApath dir - *verify CRL using certificates in "dir"*
- -sgckey
- -pubin
- -pubout
- -RSAPublicKeyin
- -RSAPublicKeyout
- -pvk-strong
- -pvk-weak
- -pvk-none
- -inform arg input format - *one of DER NET PEM*
- -outform arg output format - *one of DER NET PEM*
- -in arg input file
- -sgckey Use IIS SGC key format
- -passin arg input file pass phrase source
- -out arg output file
- -passout arg output file pass phrase source
- -des encrypt PEM output with cbc des
- -des3 encrypt PEM output with ede cbc des using 168 bit key
- -idea encrypt PEM output with cbc idea
- -seed encrypt PEM output with cbc seed
- -aes128, -aes192, -aes256
- encrypt PEM output with cbc aes
- -camellia128, -camellia192, -camellia256
- encrypt PEM output with cbc camellia
- -text print the key in text
- -noout don't print key out
- -modulus print the RSA key modulus
- -check verify key consistency
- -pubin expect a public key in input file

- *-pubout output a public key*
- *-engine e use engine e, possibly a hardware device.*
- *Only private keys can be checked*
- *Public Key*
- *RSA key ok*
- *RSA key error: %s*
- *writing RSA key*
- *unable to write key*
- *-inkey*
- *-certin*
- *-asn1parse*
- *-hexdump*
- *-encrypt*
- *-decrypt*
- *Usage: rsautl [options]*
- *-in file input file*
- *-out file output file*
- *-inkey file input key*
- *-keyform arg private key format - default PEM*
- *-pubin input is an RSA public*
- *-certin input is a certificate carrying an RSA public key*
- *-ssl use SSL v2 padding*
- *-rawuse no padding*
- *-pkcs use PKCS#1 v1.5 padding (default)*
- *-oaep use PKCS#1 OAEP*
- *-sign sign with private key*
- *-verify verify with public key*
- *-encrypt encrypt with public key*
- *-decrypt decrypt with private key*
- *-hexdump hex dump output*
- *-passin arg pass phrase source*
- *A private key is needed for this operation*
- *Certificate*
- *Error getting RSA key*
- *Error Reading Input File*
- *Error Reading Output File*
- *rsautl.c*
- *Error reading input Data*
- *RSA operation error*
- *-inform arg input format - DER or PEM*
- *-outform arg output format - DER or PEM*
- *-modulus print the DSA public value*
- *read DSA key*
- *unable to load Key*
- *Public Key=*
- *writing DSA key*
- *unable to write private key*
- *-genkey*
- *%s [options] [bits]*
- *-text print as text*
- *-genkey generate a DSA key*
- *-rand files to use for random number input*

- *number number of bits to use for generating private key*
- *dsaparam.c*
- *needrand*
- *Error allocating DSA object*
- *This could take some time*
- *Error, DSA key generation failed*
- *static unsigned char dsa%dp[]={*
- *static unsigned char dsa%dq[]={*
- *static unsigned char dsa%dg[]={*
- *DSA *getdsa%d()*
- *DSA dsa;*
- *if ((dsa=DSA_new()) == NULL) return(NULL);*
- *dsa->p=BNbin2bn(dsa%dp,sizeof(dsa%d_p),NULL);*
- *dsa->q=BNbin2bn(dsa%dq,sizeof(dsa%d_q),NULL);*
- *dsa->g=BNbin2bn(dsa%dg,sizeof(dsa%d_g),NULL);*
- *if ((dsa->p == NULL) || (dsa->q == NULL) || (dsa->g == NULL))*
- *{ DSA_free(dsa); return(NULL); }*
- *return(dsa);*
- *unable to write DSA parameters*
- *dsaparam_main*
- *-conv_form*
- *compressed*
- *uncompressed*
- *hybrid*
- *-param_enc*
- *named_curve*
- *explicit*
- *-param_out*
- *-des encrypt PEM output, instead of 'des' every other*
- *cipher supported by OpenSSL can be used*
- *-text print the key*
- *-param_out print the elliptic curve parameters*
- *-conv_form arg specifies the point conversion form*
- *possible values: compressed*
- *uncompressed (default)*
- *hybrid*
- *-param_enc arg specifies the way the ec parameters are encoded*
- *in the asn1 der encoding*
- *possible values: named_curve (default)*
- *explicit*
- *read EC key*
- *bad input format specified for key*
- *writing EC key*
- *static unsigned char %s_%d[] = {*
- *0x%02X*
- *-list_curves*
- *-no_seed*
- *-inform arg input format - default PEM (DER or PEM)*
- *-outform arg output format - default PEM*
- *-in arg input file - default stdin*
- *-out arg output file - default stdout*
- *-noout do not print the ec parameter*

- *-text* print the ec parameters in text form
- *-check* validate the ec parameters
- *-C* print a 'C' function creating the parameters
- *-name arg* use the ec parameters with 'short name' name
- *-list_curves* prints a list of all currently available curve 'short names'
- *-conv_form arg* specifies the point conversion form
- possible values: compressed
- uncompressed (default)
- hybrid
- *-param_enc arg* specifies the way the ec parameters are encoded
- in the asn1 der encoding
- possible values: named_curve (default)
- explicit
- *-no_seed* if 'explicit' parameters are chosen do not use the seed
- *-genkey* generate ec key
- *-rand file* files to use for random number input
- *-engine e* use engine e, possibly a hardware device
- *ecparam.c*
- CURVE DESCRIPTION NOT AVAILABLE
- %-10s:
- secp192r1
- using curve name prime192v1 instead of secp192r1
- secp256r1
- using curve name prime256v1 instead of secp256r1
- unknown curve name (%s)
- unable to create curve (%s)
- unable to load elliptic curve parameters
- checking elliptic curve parameters:
- failed
- *ec_gen*
- *ec_order*
- *ec_cofactor*
- *ECGROUP *getecgroup%d(void)*
- *int ok=0;*
- *EC_GROUP *group = NULL;*
- *EC_POINT *point = NULL;*
- *BIGNUM *tmp1 = NULL, *tmp2 = NULL, *tmp_3 = NULL;*
- *if ((tmp1 = BNbin2bn(ecp%d, sizeof(ecp%d), NULL)) == NULL)*
- *goto err;*
- *if ((tmp2 = BNbin2bn(eca%d, sizeof(eca%d), NULL)) == NULL)*
- *goto err;*
- *if ((tmp3 = BNbin2bn(ecb%d, sizeof(ecb%d), NULL)) == NULL)*
- *goto err;*
- *if ((group = ECGROUPnewcurveGFp(tmp1, tmp2, tmp_3, NULL)) == NULL)*
- *goto err;*
- */build generator /*
- *if ((tmp1 = BNbin2bn(ecgen%d, sizeof(ecgen%d), tmp_1)) == NULL)*
- *goto err;*
- *point = ECPOINTbn2point(group, tmp_1, NULL, NULL);*
- *if (point == NULL)*
- *goto err;*
- *if ((tmp2 = BNbin2bn(ecorder%d, sizeof(ecorder%d), tmp_2)) == NULL)*

- `goto err;`
- `if ((tmp3 = BNbin2bn(eccofactor%d, sizeof(eccofactor%d), tmp_3)) == NULL)`
- `goto err;`
- `if (!ECGROUPsetgenerator(group, point, tmp2, tmp_3))`
- `goto err;`
- `if (tmp_1)`
- `BNfree(tmp1);`
- `if (tmp_2)`
- `BNfree(tmp2);`
- `if (tmp_3)`
- `BNfree(tmp3);`
- `if (point)`
- `ECPOINTfree(point);`
- `if (!ok)`
- `ECGROUPfree(group);`
- `group = NULL;`
- `return(group);`
- *unable to write elliptic curve parameters*
- *ecparam_main*
- *-CAform*
- *-CAkeyform*
- *bad number of days*
- *-signkey*
- *-CAkey*
- *-CAserial*
- *-addtrust*
- *Invalid trust object value %s*
- *-addreject*
- *Invalid reject object value %s*
- *-setalias*
- *-certopt*
- *-email*
- *-ocsp_uri*
- *-serial*
- *-next_serial*
- *-x509toreq*
- *-subject_hash*
- *-subjecthashold*
- *-issuer_hash*
- *-issuerhashold*
- *-dates*
- *-purpose*
- *-checkend*
- *-trustout*
- *-clrtrust*
- *-clrreject*
- *-alias*
- *-CAcreateserial*
- *-clrext*
- *-crlex*
- *use -clrext instead of -crlex*
- *-ocspid*

- *need to specify a CAkey if using the CA command*
- *We need a private key to sign with*
- *The certificate request appears to corrupted*
- *It does not contain a public key*
- *Signature verification error*
- *CA Certificate*
- *2.99999.3*
- *SET.ex3*
- *SET x509v3 extension 3*
- *issuer=*
- *subject=*
- *serial=*
-
- *Certificate purposes:*
- *%s%s :*
- *Yes (WARNING code=%d)*
- */subject:%s /*
- */issuer :%s */*
- *x509.c*
- *unsigned char XXXsubjectname[%d]={*
- *unsigned char XXXpublickey[%d]={*
- *unsigned char XXXcertificate[%d]={*
- *notBefore=*
- *notAfter=*
- *Getting Private key*
- *Private key*
- *Getting CA Private Key*
- *CA Private Key*
- *out of mem*
- *addword failure*
- *Getting request Private Key*
- *no request key file specified*
- *request key*
- *Generating certificate request*
- *Certificate will expire*
- *Certificate will not expire*
- *unable to write certificate*
- *error with certificate to be certified - should be self signed*
- *error with certificate - error %d at depth %d*
- *usage: x509 args*
- *-inform arg - input format - default PEM (one of DER, NET or PEM)*
- *-outform arg - output format - default PEM (one of DER, NET or PEM)*
- *-keyform arg - private key format - default PEM*
- *-CAform arg - CA format - default PEM*
- *-CAkeyform arg - CA key format - default PEM*
- *-passin arg - private key password source*
- *-serial - print serial number value*
- *-subjecthash - print subject hash value*
- *-subjecthashold - print old-style (MD5) subject hash value*
- *-issuerhash - print issuer hash value*
- *-issuerhashold - print old-style (MD5) issuer hash value*
- *-hash - synonym for -subjecthash*

- *-subject - print subject DN*
- *-email - print email address(es)*
- *-startdate - notBefore field*
- *-enddate - notAfter field*
- *-purpose - print out certificate purposes*
- *-dates - both Before and After dates*
- *-modulus - print the RSA key modulus*
- *-pubkey - output the public key*
- *-fingerprint - print the certificate fingerprint*
- *-alias - output certificate alias*
- *-noout - no certificate output*
- *-ocspid - print OCSP hash values for the subject name and public key*
- *-ocspuri - print OCSP Responder URL(s)*
- *-trustout - output a "trusted" certificate*
- *-clrtrust - clear all trusted purposes*
- *-clrreject - clear all rejected purposes*
- *-addtrust arg - trust certificate for a given purpose*
- *-addreject arg - reject certificate for a given purpose*
- *-setalias arg - set certificate alias*
- *-days arg - How long till expiry of a signed certificate - def 30 days*
- *-checkend arg - check whether the cert expires in the next arg seconds*
- *exit 1 if so, 0 if not*
- *-signkey arg - self sign cert with arg*
- *-x509toreq - output a certification request object*
- *-req - input is a certificate request, sign and output.*
- *-CA arg - set the CA certificate, must be PEM format.*
- *-CAkey arg - set the CA key, must be PEM format*
- *missing, it is assumed to be in the CA file.*
- *-CAcreateserial - create serial number file if it does not exist*
- *-CAserial arg - serial file*
- *-setserial - serial number to use*
- *-text - print the certificate in text form*
- *-C - print out C code forms*
- *-md2/-md5/-sha1/-mdc2 - digest to use*
- *-extfile - configuration file with X509V3 extensions to add*
- *-extensions - section from config file with X509V3 extensions to add*
- *-clrext - delete extensions before signing and input certificate*
- *-certopt arg - various certificate text options*
- *x509main*
- *unable to create BIO for output*
- *-aes128*
- *-aes192*
- *-aes256*
- *-camellia128*
- *-camellia192*
- *-camellia256*
- *usage: genrsa [args] [numbits]*
- *-des encrypt the generated key with DES in cbc mode*
- *-des3 encrypt the generated key with DES in ede cbc mode (168 bit key)*
- *-idea encrypt the generated key with IDEA in cbc mode*
- *-seed*
- *encrypt PEM output with cbc seed*

- -out file output the key to 'file'
- -f4 use F4 (0x10001) for the E value
- -3 use 3 for the E value
- load the file (or the files in the directory) into
- the random number generator
- Generating RSA private key, %d bit long modulus
- e is %ld (0x%lX)
- usage: gendsa [args] dsaparam-file
- -out file - output the key to 'file'
- -des - encrypt the generated key with DES in cbc mode
- -des3 - encrypt the generated key with DES in ede cbc mode (168 bit key)
- -idea - encrypt the generated key with IDEA in cbc mode
- dsaparam-file
- - a DSA parameter file as generated by the dsaparam command
- unable to load DSA parameter file
- Generating DSA key, %d bits
- Algorithm already set!
- Algorithm %s not found
- Error initializing %s context
- -paramfile
- Parameters already set!
- Error initializing context
- -algorithm
- No keytype specified
- parameter setting error
- -genparam
- Unknown cipher %s
- Usage: genpkey [options]
- where options may be
- -out file output file
- -outform X output format (DER or PEM)
- -pass arg output file pass phrase source
- - use cipher to encrypt the key
- -engine e use engine e, possibly a hardware device.
- -paramfile file parameters file
- -algorithm alg the public key algorithm
- -pkeyopt opt:value set the public key algorithm option
- to value
- -genparam generate parameters, not key
- -text print the in text
- NB: options order may be important! See the manual page.
- Can't open output file %s
- Error generating parameters
- Bad format specified for key
- Error writing key
- Error printing key
- %4ld items in the session cache
- %4ld client connects (SSLconnect())
- %4ld client renegotiates (SSLconnect())
- %4ld client connects that finished
- %4ld server accepts (SSLaccept())

- *%4ld server renegotiates (SSLaccept())*
- *%4ld server accepts that finished*
- *%4ld session cache hits*
- *%4ld session cache misses*
- *%4ld session cache timeouts*
- *%4ld callback cache hits*
- *%4ld cache full overflows (%ld allowed)*
- *server.pem*
- *server2.pem*
- *-accept*
- *verify depth is %d*
- *-Verify*
- *verify depth is %d, must return a certificate*
- *-context*
- *-certform*
- *-dhparam*
- *-namedcurve*
- *-dcertform*
- *-dcert*
- *-dkeyform*
- *-dpass*
- *-nocert*
- *-nocache*
- *-verifyreturnerror*
- *-serverpref*
- *-legacyrenegotiation*
- *-cipher*
- *-nbio*
- *-tlsextdebug*
- *-statusverbose*
- *-statustimeout*
- *-statusurl*
- *Error parsing URL*
- *-state*
- *-notmpsa*
- *-nodhe*
- *-noecdhe*
- *-pskhint*
- *-srpfile*
- *-srpuserseed*
- *-noss/2*
- *-noss/3*
- *-notls1*
- *-notls11*
- *-notls12*
- *-nocomp*
- *-noticket*
- *-tls11*
- *-tls12*
- *-dtls1*
- *-timeout*

- *-chain*
- *-idprefix*
- *-servername*
- *-servernamefatal*
- *-cert2*
- *-nextprotoneg*
- *-usesrtp*
- *-keymatexport*
- *-keymatexportlen*
- *usage: sserver [args ...]*
- *-accept arg - port to accept on (default is %d)*
- *-context arg - set session ID context*
- *-verify arg - turn on peer certificate verification*
- *-Verify arg - turn on peer certificate verification, must have a cert.*
- *-cert arg - certificate file to use*
- *(default is %s)*
- *-crlcheck - check the peer certificate has not been revoked by its CA.*
- *The CRL(s) are appended to the certificate file*
- *-crlcheckall - check the peer certificate has not been revoked by its CA*
- *or any other CRL in the CA chain. CRL(s) are appened to the*
- *the certificate file.*
- *-certform arg - certificate format (PEM or DER) PEM default*
- *-key arg - Private Key file to use, in cert file if*
- *not specified (default is %s)*
- *-keyform arg - key format (PEM, DER or ENGINE) PEM default*
- *-pass arg - private key file pass phrase source*
- *-dcert arg - second certificate file to use (usually for DSA)*
- *-dcertform x - second certificate format (PEM or DER) PEM default*
- *-dkey arg - second private key file to use (usually for DSA)*
- *-dkeyform arg - second key format (PEM, DER or ENGINE) PEM default*
- *-dpass arg - second private key file pass phrase source*
- *-dhparam arg - DH parameter file to use, in cert file if not specified*
- *or a default set of parameters is used*
- *-namedcurve arg - Elliptic curve name to use for ephemeral ECDH keys.*
- *Use "openssl ecparam -listcurves" for all names*
- *(default is nistp256).*
- *-nbio - Run with non-blocking IO*
- *-nbio test - test with the non-blocking test bio*
- *-crlf - convert LF from terminal into CRLF*
- *-debug - Print more output*
- *-msg - Showprotocol messages*
- *-state - Print the SSL states*
- *-CApath arg - PEM format directory of CA's*
- *-CAfile arg - PEM format file of CA's*
- *-nocert - Don't use any certificates (Anon-DH)*
- *-cipher arg - play with 'openssl ciphers' to see what goes here*
- *-serverpref - Use server's cipher preferences*
- *-quiet - No server output*
- *-notmprsa - Do not generate a tmp RSA key*
- *-pskhint arg - PSK identity hint to use*
- *-psk arg - PSK in hex (without 0x)*
- *-srpfile file - The verifier file for SRP*

- -srpuserseed string - A seed string for a default user salt.
- -ssl2 - Just talk SSLv2
- -ssl3 - Just talk SSLv3
- -tls12 - *Just talk TLSv1.2*
- -tls11 - Just talk TLSv1.1
- -tls1 - Just talk TLSv1
- -dtls1 - Just talk DTLSv1
- -timeout - Enable timeouts
- -mtu - Set link layer MTU
- -chain - Read a certificate chain
- -nossl2 - *Just disable SSLv2*
- -nossl3 - Just disable SSLv3
- -notls1 - *Just disable TLSv1*
- -notls11 - *Just disable TLSv1.1*
- -notls12 - *Just disable TLSv1.2*
- -nodhe - Disable ephemeral DH
- -noecdhe - *Disable ephemeral ECDH*
- -bugs - *Turn on SSL bug compatibility*
- -www - Respond to a 'GET /' with a status page
- -WWW - Respond to a 'GET / HTTP/1.0' with file ./
- -HTTP - Respond to a 'GET / HTTP/1.0' with file ./
- *with the assumption it contains a complete HTTP response.*
- -engine id - *Initialise and use the specified engine*
- -idprefix arg - Generate SSL/TLS session IDs prefixed by 'arg'
- -servername host - servername for HostName TLS extension
- -servernamefatal - *on mismatch send fatal alert (default warning alert)*
- -cert2 arg - *certificate file to use for servername*
- -key2 arg - *Private Key file to use for servername, in cert file if*
- -tlsextdebug - *hex dump of all TLS extensions received*
- -noticket - disable use of RFC4507bis session tickets
- -legacyrenegotiation - *enable use of legacy renegotiation (dangerous)*
- -nextprotoneg arg - *set the advertised protocols for the NPN extension (comma-separated list)*
- -usesrtp profiles - Offer SRTP key management with a colon-separated profile list
- -keymatexport label - Export keying material using label
- -keymatexportlen len - Export len bytes of keying material (default 20)
- server certificate private key file
- server certificate file
- second server certificate private key file
- second server certificate file
- second certificate private key file
- warning: *idprefix is too long, only one newsession will be possible*
- warning: *idprefix is too long if you use SSLv2*
- error setting 'idprefix'
- *idprefix '%s' set.*
- Setting secondary ctx parameters
- Setting temp DH parameters
- Using default temp DH parameters
- Using default temp ECDH parameters
- unable to create curve (nistp256)
- PSK key given or JPAKE in use, setting server callback
- error setting PSK identity hint to context

- error setting cipher list
- Cannot initialize SRP verifier file "%s":ret=%d
- ACCEPT
- Not a hex number '%s'
- Setting temp ECDH parameters
- *certstatus: callback called*
- *certstatus: can't parse AIA URL*
- *certstatus: AIA URL: %s*
- *certstatus: no AIA and no default responder URL*
- *certstatus: Can't retrieve issuer certificate.*
- *certstatus: error querying responder*
- *certstatus: ocsp response sent:*
- sserver.c
- turning on non blocking io
- LOOKUP during accept %s
- LOOKUP done %s
- LOOKUP not successful
- read R BLOCK
- GET /stats
- HTTP/1.0 200 ok
- Content-type: text/html
-
- Secure Renegotiation IS%s supported
- Ciphers supported in sserver *binary*
- %-11s:%-25s
- *Ciphers common between both SSL end points:*
- *Reused,*
- *%s, Cipher is %s*
- *Client certificate*
- *no client certificate available*
-
- *'%s' is an invalid file name*
- *'%s' contains '..' reference*
- *'%s' is an invalid path*
- *'%s' is a directory*
- *Error opening '%s'*
- *FILE:%s*
- HTTP/1.0 200 ok
- Content-type: text/plain
- *write WBLOCK*
- *SRP username = "%s"*
- *User %s doesn't exist*
- *SRP parameters set: username = "%s" info="%s"*
- *Hostname in TLS extension: "%s"*
- *Switching server context.*
- *pskservercb*
- *Error: client did not send PSK identity*
- *identitylen=%d identity=%s*
- PSK error: client identity not found (got '%s' expected '%s')
- PSK client identity found
- Could not convert PSK key '%s' to BIGNUM
- psk buffer of callback is too small (%d) for key (%d)

- fetched PSK len=%d
- Error in PSK server callback
- Allocation error in generating RSA key
- Generating temp (%d bit) RSA key...
- CONNECTION CLOSED
- TIMEOUT occurred
- *lfnun == 0*
- *shutdown accept socket*
- *HEARTBEATING*
- *SSLdohandshake -> %d*
- *LOOKUP renegotio during write*
- *Write BLOCK*
- *verify error:%s*
- *subject=%s*
- *issuer=%s*
- *Shared ciphers:%s*
- *(NONE)*
- *CIPHER is %s*
- *NEXTPROTO is*
- *SRTP Extension negotiated, profile=%s*
- *Reused session-id*
- *Peer has incorrect TLSv1 block padding*
- *Keying material exporter:*
- *Label: '%s'*
- *Length: %i bytes*
- *Error*
- *Keying material:*
- *LOOKUP renegotio during read*
- *Read BLOCK*
- *shutting down SSL*
- *Lets print some clear text*
- *svbody*
-
- *Client_identity*
- Certificate chain
- *%2d s:%s*
- *i:%s*
- Server certificate
- no peer certificate available
- Acceptable client certificate CA names
- No client certificate CA names sent
- Ciphers common between both SSL endpoints:
- SSL handshake has read %ld bytes and written %ld bytes
- Server public key is %d bit
- Compression: %s
- Expansion: %s
- Next protocol: (%d)
- *s_client.c*
- OCSP response:
- no response sent
- response parse error

- =====
- =====
- SRP parameters:
- SRP param N and g are not known params, going to check deeper.
- SRP param N and g rejected.
- SRP user
- Can't read Password
- Can't use SSL~~get~~servername
- Protocols advertised by server:
- psk~~client~~cb
- NULL received PSK identity hint, continuing anyway
- Received PSK identity hint '%s'
- created identity '%s' len=%d
- created PSK len=%d
- Error in PSK client callback
- localhost
- -connect
- -sess_out
- -sess_in
- -prexit
- -ign_eof
- -noignoreof
- -pause
- -showcerts
- -psk_identity
- -srpuser
- -srppass
- -srp_strength
- SRP minimal length for N is %d
- -srp_lateuser
- -srp_moregroups
- -reconnect
- -legacyserverconnect
- -nolegacyserver_connect
- -starttls
- -sslclientengine
- usage: s_client args
- -host host - use -connect instead
- -port port - use -connect instead
- -connect host:port - who to connect to (default is %s:%s)
- -cert arg - certificate file to use, PEM format assumed
- -key arg - Private key file to use, in cert file if
- not specified but cert file is.
- -keyform arg - key format (PEM or DER) PEM default
- -reconnect - Drop and re-make the connection with the same Session-ID
- -pause - sleep(1) after each read(2) and write(2) system call
- -showcerts - show all certificates in the chain
- -debug - extra output
- -nbio_test - more ssl protocol testing
- -state - print the 'ssl' states
- -quiet - no s_client output
- -ign_eof - ignore input eof (default when -quiet)

- -noignoreeof - don't ignore input eof
- -psk_identity arg - PSK identity
- -srpuser user - SRP authentication for 'user'
- -srppass arg - password for 'user'
- -srp_lateuser - SRP username into second ClientHello message
- -srp_moregroups - Tolerate other than the known g N values.
- -srp_strength int - minimal length in bits for N (default %d).
- -ssl2 - just use SSLv2
- -ssl3 - just use SSLv3
- -tls1_2 - just use TLSv1.2
- -tls1_1 - just use TLSv1.1
- -tls1 - just use TLSv1
- -dtls1 - just use DTLSv1
- -mtu - set the link layer MTU
- -notls12/-notls11/-notls1/-noSSL3/-no_ssl2 - turn off that protocol
- -bugs - Switch on all SSL implementation bug workarounds
- -serverpref - Use server's cipher preferences (only SSLv2)
- -cipher - preferred cipher to use, use the 'openssl ciphers' command to see what is available
- -starttls prot - use the STARTTLS command before starting TLS
- for those protocols that support it, where
- 'prot' defines which one to assume. Currently,
- only "smtp", "pop3", "imap", "ftp" and "xmpp"
- are supported.
- -sess_out arg - file to write SSL session to
- -sess_in arg - file to read SSL session from
- -servername host - Set TLS extension servername in ClientHello
- -tlsextdebug - hex dump of all TLS extensions received
- -status - request certificate status from server
- -no_ticket - disable use of RFC4507bis session tickets
- -nextprotoneg arg - enable NPN extension, considering named protocols supported (comma-separated list)
- Error parsing -nextprotoneg argument
- Error getting client auth engine
- client certificate private key file
- client certificate file
- Error setting client auth engine
- PSK key given or JPAKE in use, setting client callback
- Unable to set SRP username
- Can't open session file %s
- Unable to set TLS servername extension.
- connect:errno=%d
- CONNECTED(%08X)
- getsockname:errno=%d
- EHLO openssl.client.net
- STARTTLS
- didn't found starttls in server response, try anyway...
- STARTTLS
- . CAPABILITY
- didn't found STARTTLS in server response, try anyway...
- . STARTTLS
- AUTH TLS
-

- /stream:features>
-
-
-
- Error writing session file %s
- drop connection and then reconnect
- bad select %d
- write W BLOCK
- write R BLOCK
- write X BLOCK
- shutdown
- write:errno=%d
- read W BLOCK
- read X BLOCK
- read:errno=%d
- closed
- RENEGOTIATING
- *sclient*main
- - +R:%d:%s:%f
- %d %s's in %.2fs
- +DTP:%d:%s:%s:%d
- Doing %d bit %s %s's for %ds:
- +DT:%s:%d:%d
- Doing %s for %ds on %d size blocks:
- speed.c
- -elapsed
- no EVP given
- %s is an unknown cipher or digest
- no engine given
- -multi
- no multi count given
- bad multi count
- sha256
- sha512
- whirlpool
- ripemd
- ripemd160
- aes-128-ige
- aes-192-ige
- aes-256-ige
- openssl
- dsa512
- dsa1024
- dsa2048
- rsa512
- rsa1024
- rsa2048
- rsa4096
- blowfish
- camellia
- ecdsap160

- ecdsap192
- ecdsap224
- ecdsap256
- ecdsap384
- ecdsap521
- ecdsak163
- ecdsak233
- ecdsak283
- ecdsak409
- ecdsak571
- ecdsab163
- ecdsab233
- ecdsab283
- ecdsab409
- ecdsab571
- ecdhp160
- ecdhp192
- ecdhp224
- ecdhp256
- ecdhp384
- ecdhp521
- ecdhk163
- ecdhk233
- ecdhk283
- ecdhk409
- ecdhk571
- ecdhb163
- ecdhb233
- ecdhb283
- ecdhb409
- ecdhb571
- Error: bad option or value
- Available values:
- mdc2
- md4
- md5
- hmac
- sha1
- sha256
- sha512
- idea-cbc
- seed-cbc
- rc2-cbc
- des-cbc des-ede3
- aes-128-cbc aes-192-cbc aes-256-cbc
- aes-128-ige aes-192-ige aes-256-ige
- camellia-128-cbc camellia-192-cbc camellia-256-cbc
- rsa512 rsa1024 rsa2048 rsa4096
- dsa512 dsa1024 dsa2048
- ecdsap160 ecdsap192 ecdsap224 ecdsap256 ecdsap384 ecdsap521
- ecdsak163 ecdsak233 ecdsak283 ecdsak409 ecdsak571
- ecdsab163 ecdsab233 ecdsab283 ecdsab409 ecdsab571

- ecdhp160 ecdhp192 ecdhp224 ecdhp256 ecdhp384 ecdhp521
- ecdhk163 ecdhk233 ecdhk283 ecdhk409 ecdhk571
- ecdhb163 ecdhb233 ecdhb283 ecdhb409 ecdhb571
- idea
- seed
- rc2
- des
- aes
- camellia
- rsa
- Available options:
- -evp e use EVP e.
- -decrypt time decryption instead of encryption (only EVP).
- -mr produce machine readable output.
- -multi n run n benchmarks in parallel.
- pipe failure
- Forked child %d
- dup failed
- Don't understand line '%s' from child %d
- Got: %s from %d
- Unknown type '%s' from child %d
- You have chosen to measure elapsed time instead of user CPU time.
- internal error loading RSA key number %d
- This is a key...
- 0123456789ab
- RSA sign failure. No RSA sign will be done.
- private
- RSA sign failure
- +R1:%ld:%d:%.2f
- %ld %d bit private RSA's in %.2fs
- RSA verify failure. No RSA verify will be done.
- public
- RSA verify failure
- +R2:%ld:%d:%.2f
- %ld %d bit public RSA's in %.2fs
- DSA sign failure. No DSA sign will be done.
- DSA sign failure
- +R3:%ld:%d:%.2f
- %ld %d bit DSA signs in %.2fs
- DSA verify failure. No DSA verify will be done.
- DSA verify failure
- +R4:%ld:%d:%.2f
- %ld %d bit DSA verify in %.2fs
- ECDSA failure.
- ECDSA sign failure. No ECDSA sign will be done.
- ECDSA sign failure
- +R5:%ld:%d:%.2f
- %ld %d bit ECDSA signs in %.2fs
- ECDSA verify failure. No ECDSA verify will be done.
- ECDSA verify failure
- +R6:%ld:%d:%.2f
- %ld %d bit ECDSA verify in %.2fs

- ECDH failure.
- ECDH key generation failure.
- ECDH computations don't match.
- +R7:%ld:%d:%.2f
- %ld %d-bit ECDH ops in %.2fs
- options:
- The 'numbers' are in 1000s of bytes per second processed.
- type
- %7d bytes
- +F:%d:%s
- %11.2fk
- %11.2f
- %18ssign verify sign/s verify/s
- +F2:%u:%u:%f:%f
- rsa %4u bits %8.6fs %8.6fs %8.1f %8.1f
- +F3:%u:%u:%f:%f
- dsa %4u bits %8.6fs %8.6fs %8.1f %8.1f
- %30ssign verify sign/s verify/s
- +F4:%u:%u:%f:%f
- %4u bit ecDSA (%s) %8.4fs %8.4fs %8.1f %8.1f
- %30sop op/s
- +F5:%u:%u:%f:%f
- %4u bit ECDH (%s) %8.4fs %8.1f
- hmac(md5)
- des cbc
- des ede3
- idea cbc
- seed cbc
- rc2 cbc
- rc5-32/12 cbc
- blowfish cbc
- cast cbc
- aes-128 cbc
- aes-192 cbc
- aes-256 cbc
- camellia-128 cbc
- camellia-192 cbc
- camellia-256 cbc
- aes-128 ige
- aes-192 ige
- aes-256 ige
- string to make the random number generator think it has entropy
- secp160r1
- nistp192
- nistp224
- nistp256
- nistp384
- nistp521
- nistk163
- nistk233
- nistk283
- nistk409

- nistk571
- nistb163
- nistb233
- nistb283
- nistb409
- nistb571
- localhost:4433
- -reuse
- -www option too long
- usage: s_time
- -connect host:port - host:port to connect to (default is %s)
- -nbio - Run with non-blocking IO
- -ssl2 - Just use SSLv2
- -ssl3 - Just use SSLv3
- -bugs - Turn on SSL bug compatibility
- -new - Just time new connections
- -reuse - Just time connection reuse
- -www page - Retrieve 'page' from the site
- SSL_CIPHER
- No CIPHER specified
- Collecting connection statistics for %d seconds
- GET %s HTTP/1.0
- %d connections in %.2fs; %.2f connections/user sec, bytes read %ld
- %d connections in %ld real seconds, %ld bytes read per connection
- Now timing with session id reuse.
- Unable to get connection
- starting
- apps.c
- %s Policies:
-
- Require explicit Policy: %s
- Authority
- PKCS12
- Invalid Policy "%s"
- unrecognized purpose
- -verify_depth
- invalid depth
- -attime
- Error parsing timestamp %s
- -ignore_critical
- -issuer_checks
- -crl_check
- -crlcheckall
- -policy_check
- -explicit_policy
- -inhibit_any
- -inhibit_map
- -x509_strict
- -extended_crl
- -use_deltas
- -policy_print
- -checksssig

- Subject does not start with '/'.
- escape character at end of string
- end of string encountered while processing type of subject name element #%%d
- Subject Attribute %s has no known NID, skipped
- No value provided for Subject Attribute %s, skipped
- file name too long
- %s.attr
- %s.attr.%s
- unable to rename %s to %s
- reason
- unable to open '%s'
- unique_subject = %s
- error creating serial number index:(%ld,%ld,%ld)
- error creating name index:(%ld,%ld,%ld)
- error converting serial to ASN.1 format
- Out of memory
- unable to load number from %s
- error converting number from bin to BIGNUM
- Error configuring OpenSSL
- enabling auto ENGINE support
- dynamic
- SO_PATH
- invalid engine "%s"
- SETUSERINTERFACE
- can't use that engine
- engine "%s" set.
- copyall
- bad input format specified for %s
- Error opening %s %s
- certificates
- unable to load %s
- Error reading %s %s
- no keyfile specified
- no engine specified
- bad input format specified for key file
- Error loading PKCS12 file for %s
- Passphrase callback error for %s
- Mac verify error (wrong password?) in PKCS12 file for %s
- cannot load %s from engine
- Error reading header on certificate
- unable to load certificate
- oid_section
- problem loading oid section %s
- problem creating object %s=%s
- Can't read environment variable %s
- Can't open file %s
- Can't access file descriptor %s
- Can't open BIO for stdin
- Invalid password argument "%s"
- Error reading password from BIO
- pass phrase
- User interface error

- aborted!
- OpenSSL application user interface
- issuer=
- error on line %ld of db attribute file '%s'
- esc_2253
- esc_ctrl
- esc_msb
- use_quote
- ignore_type
- show_type
- dump_all
- dump_nostr
- dump_der
- compat
- sepcommaplus
- sepcommaplus_space
- sepsemiplus_space
- sep_multiline
- dn_rev
- nofname
- space_eq
- dump_unknown
- RFC2253
- oneline
- multiline
- ca_default
- compatible
- no_header
- no_version
- no_serial
- no_signame
- no_validity
- no_subject
- no_issuer
- no_pubkey
- no_extensions
- no_sigdump
- no_aux
- no_attributes
- ext_default
- ext_error
- ext_parse
- ext_dump
- SSL 2.0
- SSL 3.0
- TLS 1.0
- TLS 1.1
- TLS 1.2
- DTLS 1.0
- , CLIENT-CERTIFICATE
- , ERROR:
- UNSUPPORTED-CERTIFICATE-TYPE-ERROR

- NO-CIPHER-ERROR
- BAD-CERTIFICATE-ERROR
- , CLIENT-HELLO
- , CLIENT-MASTER-KEY
- , CLIENT-FINISHED
- , SERVER-HELLO
- , SERVER-VERIFY
- , SERVER-FINISHED
- , REQUEST-CERTIFICATE
- ChangeCipherSpec
- , fatal
- , warning
- close_notify
- unexpected_message
- badrecordmac
- decryption_failed
- record_overflow
- decompression_failure
- handshake_failure
- bad_certificate
- unsupported_certificate
- certificate_revoked
- certificate_expired
- certificate_unknown
- illegal_parameter
- unknown_ca
- access_denied
- decode_error
- decrypt_error
- export_restriction
- protocol_version
- insufficient_security
- internal_error
- user_canceled
- no_renegotiation
- unsupported_extension
- certificate_unobtainable
- unrecognized_name
- bad*certificate*status_response
- bad*certificate*hash_value
- , HelloRequest
- , ClientHello
- , ServerHello
- , HelloVerifyRequest
- , Certificate
- , ServerKeyExchange
- , CertificateRequest
- , ServerHelloDone
- , CertificateVerify
- , ClientKeyExchange
- , HeartbeatRequest
- %s %s%s [length %04lx]%s%s

- unknownpskidentity
- , Finished
- , Heartbeat
- DTLS 1.0 (bad)
- NO-CERTIFICATE-ERROR
- Handshake
- , HeartbeatResponse
- s_cb.c
- error setting random cookie secret
- TLS padding
- server name
- max fragment length
- client certificate URL
- trusted CA keys
- truncated HMAC
- status request
- user mapping
- client authz
- server authz
- cert type
- elliptic curves
- EC point formats
- signature algorithms
- use SRTP
- heartbeat
- session ticket
- renegotiation info
- next protocol
- server
- client
- TLS %s extension "%s" (id=%d), len=%d
- SSL_connect
- SSL_accept
- undefined
- SSL3 alert %s:%s:%s
- %s:failed in %s
- %s:error in %s
- read from %p [%p] (%lu bytes => %ld (0x%lX))
- write to %p [%p] (%lu bytes => %ld (0x%lX))
- error setting certificate
- error setting private key
- Private key does not match the certificate public key
- unable to get certificate from '%s'
- unable to get private key from '%s'
- depth=%d
-
- verify error:num=%d:%s
- verify return:%d
- getservbyname failure for %s
- %u.%u.%u.%u
- invalid IP address
- gethostbyname failure

- gethostbyname addr is not AF_INET
- no port defined
- errno=%d
- accept
- bad gethostbyaddr
- s_socket.c
- socket
- keepalive
- connect
- unable to write 'random state'
- unable to load 'random state'
- This means that the random number generator has not been seeded
- with much random data.
- Consider setting the RANDFILE environment variable to point at a file that
- 'random' data can be kept in (the file will be overwritten).
- usage:version -[avbofpd]
- %s (Library: %s)
- OpenSSL 1.0.1h 5 Jun 2014
- options:
- unable to load SSL_SESSION
- Context too long
- No certificate present
- unable to write SSL_SESSION
- unable to write X509
- usage: sess_id args
- -text - print ssl session id details
- -cert - output certificate
- -context arg - set the session ID context
- Error in cipher list
- 0x%02X,0x%02X,0x%02X -
- 0x%02X,0x%02X -
- 0x%02X,0x%02X,0x%02X,0x%02X -
- usage: ciphers args
- -v - verbose mode, a textual listing of the SSL/TLS ciphers in OpenSSL
- -V - even more verbose
- -ssl2 - SSL2 mode
- -ssl3 - SSL3 mode
- -tls1 - TLS1 mode
- -toseq
- Can't open input file %s
- Error reading certs file %s
- Error reading sequence file %s
- Netscape certificate sequence utility
- Usage nseq [options]
- -in file input file
- -out file output file
- -toseq output NS Sequence file
- %s, Iteration %ld
- Unknown PBE algorithm %s
- %s:
- %s:
-

-
- Key bag
- Bag Attributes
- Key Attributes
- Shrouded Keybag:
- Certificate bag
- Safe Contents bag
- Warning unsupported bag type:
- PKCS7 Data
- PKCS7 Encrypted data:
- -nokeys
- -keyex
- -keysig
- -nocerts
- -clcerts
- -cacerts
- -twopass
- -nomacver
- -descert
- -export
- -noiter
- -maciter
- -nomaciter
- -nomac
- -macalg
- -certpbe
- -keypbe
- -caname
- -password
- Usage: pkcs12 [options]
- -export output PKCS12 file
- -chain add certificate chain
- -inkey file private key if not infile
- -certfile f add all certs in f
- -CApath arg - PEM format directory of CA's
- -CAfile arg - PEM format file of CA's
- -name "name" use name as friendly name
- -caname "nm" use nm as CA friendly name (can be used more than once).
- -in infile input filename
- -out outfile output filename
- -noout don't output anything, just verify.
- -nomacver don't verify MAC.
- -nocerts don't output certificates.
- -clcerts only output client certificates.
- -cacerts only output CA certificates.
- -nokeys don't output private keys.
- -info give info about PKCS#12 structure.
- -des encrypt private keys with DES
- -des3 encrypt private keys with triple DES (default)
- -idea encrypt private keys with idea
- -seed encrypt private keys with seed
- -aes128, -aes192, -aes256

- encrypt PEM output with cbc aes
- -camellia128, -camellia192, -camellia256
- encrypt PEM output with cbc camellia
- -nodes don't encrypt private keys
- -noiter don't use encryption iteration
- -nomaciter don't use MAC iteration
- -maciter use MAC iteration
- -nomac don't generate MAC
- -twopass separate MAC, encryption passwords
- -descrypt encrypt PKCS#12 certificates with triple DES (default RC2-40)
- -certpbe alg specify certificate PBE algorithm (default RC2-40)
- -keypbe alg specify private key PBE algorithm (default 3DES)
- -macalg alg digest algorithm used in MAC (default SHA1)
- -keyex set MS key exchange type
- -keysig set MS key signature type
- -password p set import/export password source
- -passin p input file pass phrase source
- -passout p output file pass phrase source
- -engine e use engine e, possibly a hardware device.
- -rand file%cfile%c...
- load the file (or the files in the directory) into
- the random number generator
- -CSP name Microsoft CSP name
- -LMK Add local machine keyset attribute to private key
-
- Error opening input file %s
-
- Enter MAC Password:
- Nothing to do!
- private key
- No certificate matches private key
- certificates from certfile
- Memory allocation error
- Error %s getting chain.
- Enter Export Password:
- Unknown digest algorithm %s
- Enter Import Password:
- MAC Iteration %ld
- Mac verify error: invalid password?
- MAC verified OK
- Error outputting keys and certificates
- -topk8
- -nocrypt
- -nooct
- -embed
- Usage pkcs8 [options]
- -inform X input format (DER or PEM)
- -passin arg input file pass phrase source
- -outform X output format (DER or PEM)
- -passout arg output file pass phrase source
- -topk8 output PKCS8 file
- -nooct use (nonstandard) no octet format

- -embed use (nonstandard) embedded DSA parameters format
- -nsdb use (nonstandard) DSA Netscape DB format
- -noiter use 1 as iteration count
- -nocrypt use or expect unencrypted private key
- -v2 alg use PKCS#5 v2.0 and cipher "alg"
- -v1 obj use PKCS#5 v1.5 and cipher "alg"
- Error converting key
- Enter Encryption Password:
- Error encrypting key
- Error reading key
- Enter Password:
- Error decrypting key
- Warning: broken key encoding:
- No Octet String in PrivateKey
- DSA parameters included in PrivateKey
- DSA public key include in PrivateKey
- DSA private key value is negative
- Unknown broken type
- -text_pub
- Usage pkey [options]
- Usage pkeyparam [options]
- -text print parameters as text
- -noout don't output encoded parameters
- Error reading parameters
- Usage: pkeyutl [options]
- -sigfile file signature file (verify operation only)
- -pubin input is a public key
- -certin input is a certificate carrying a public key
- -pkeyopt X:Y public key options
- -verifyrecover verify with public key, recover original data
- -derive derive shared secret
- -passin arg pass phrase source
- -sigfile
- -peerkey
- -peerkey command before -inkey
- Peer Key
- Error reading peer key %s
- -peerform
- -verifyrecover
- -derive
- -pkeyopt command before -inkey
- Signature file specified for non verify
- No signature file specified for verify
- Error Opening Input File
- Error Creating Output File
- Can't open signature file %s
- Error reading signature data
- Signature Verification Failure
- Signature Verified Successfully
- pkeyutl.c
- Public Key operation error
- -challenge

- -spksect
- %s [options]
- -key arg create SPKAC using private key
- -passin arg input file pass phrase source
- -challenge arg challenge string
- -spkac arg alternative SPKAC name
- -noout don't print SPKAC
- -verify verify SPKAC signature
- -engine e use engine e, possibly a hardware device.
- Error opening output file
- SPKAC=%s
- Error opening input file
- Error parsing config file
- Can't find SPKAC called "%s"
- Error loading SPKAC
- Signature OK
- Signature Failure
- -resign
- -pk7out
- -rc2-40
- -rc2-128
- -rc2-64
- -nointern
- -nochain
- -noattr
- -nodetach
- -nosmimecap
- -nosigs
- -stream
- -indef
- -noindef
- -nooldmime
- -crlfeol
- -signer
- -recip
- Unknown digest %s
- Illegal -inkey without -signer
- -content
- Multiple signers or keys not allowed
- No signer certificate specified
- No recipient certificate or key specified
- No recipient(s) certificate(s) specified
- Usage smime [options] cert.pem ...
- -encrypt encrypt message
- -decrypt decrypt encrypted message
- -sign sign message
- -verify verify signed message
- -pk7out output PKCS#7 structure
- -des3 encrypt with triple DES
- -des encrypt with DES
- -seed encrypt with SEED
- -rc2-40 encrypt with RC2-40 (default)

- -rc2-64 encrypt with RC2-64
- -rc2-128 encrypt with RC2-128
- encrypt PEM output with cbc aes
- encrypt PEM output with cbc camellia
- -nointern don't search certificates in message for signer
- -nosigs don't verify message signature
- -noverify don't verify signers certificate
- -nocerts don't include signers certificate when signing
- -nodetach use opaque signing
- -noattr don't include any signed attributes
- -binary don't translate message to text
- -certfile file other certificates file
- -signer file signer certificate file
- -recip file recipient certificate file for decryption
- -in file input file
- -inform arg input format SMIME (default), PEM or DER
- -inkey file input private key (if not signer or recipient)
- -keyform arg input private key format (PEM or ENGINE)
- -out file output file
- -outform arg output format SMIME (default), PEM or DER
- -content file supply or override content for detached signature
- -to addr to address
- -from ad from address
- -subject s subject
- -text include or delete text MIME headers
- -CApath dir trusted certificates directory
- -CAfile file trusted certificates file
- -crl_check check revocation status of signer's certificate using CRLs
- -crlcheckall check revocation status of signer's certificate chain using CRLs
- -engine e use engine e, possibly a hardware device.
- -passin arg input file pass phrase source
- load the file (or the files in the directory) into
- cert.pem recipient certificate(s) for encryption
- recipient certificate file
- signing key file
- Bad input format for PKCS#7 file
- Error reading S/MIME message
- Can't read content file %s
- signer certificate
- Error creating PKCS#7 structure
- Error decrypting PKCS#7 structure
- Verification successful
- Verification failure
- To: %s
- From: %s
- Subject: %s
- Bad output format for PKCS#7 file
- Error writing signers to %s
- -sign_receipt
- -verify_retcode
- -verify_receipt
- -cmsout

- -data_out
- -data_create
- -digest_verify
- -digest_create
- -compress
- -uncompress
- -EncryptedData_decrypt
- -EncryptedData_encrypt
- -debug_decrypt
- -nosignercert_verify
- -keyid
- -nocontentverify
- -noattrverify
- -receiptrequestprint
- -receiptrequestall
- -receiptrequestfirst
- -receiptrequestfrom
- -receiptrequestto
- -secretkey
- Invalid key %s
- -secretkeyid
- Invalid id %s
- -pwri_password
- -econtent_type
- Invalid OID %s
- -certsout
- -rctform
- No Signed Receipts Recipients
- Signed receipts only allowed with -sign
- Usage cms [options] cert.pem ...
- -cmsout output CMS structure
- -certsout file certificate output file
- -keyid use subject key identifier
- No secret key id
- receipt signer certificate file
- Bad input format for CMS file
- Error writing certs to %s
- Can't open receipt file %s
- Bad input format for receipt
- Error reading receipt
- Signed Receipt Request Creation Error
- Error creating CMS structure
- Error decrypting CMS using secret key
- Error decrypting CMS using private key
- Error decrypting CMS using password
- Error decrypting CMS structure
- Signer %d:
- No Receipt Request
- Receipt Request Parse Error
- Signed Content ID:
- Receipts From
- List:

- : First Tier
- Unknown (%d)
- Receipts To:
- Bad output format for CMS file
- Usage: rand [options] num
- -out file - write to file
- -engine e - use engine e, possibly a hardware device.
- -rand file%cfile%c... - seed PRNG from files
- -base64 - base64 encode output
- -hex - hex encode output
- engine.c
- [Error]: internal stack error
- [Error]: command name too long
- [Failure]: %s
- [Success]: %s
- (%s) %s
- Loaded: (%s) %s
- [available]
- [unavailable]
-
- %s: %s
- %s%s(input flags):
-
- [Internal]
- NUMERIC
- STRING
- NO_INPUT
- <0x%04X>
-
- usage: engine opts [engine ...]
- -v[v[v]] - verbose mode, for each engine, list its 'control commands'
- -vv will additionally display each command's description
- -vvv will also add the input flags for each command
- -vvv will also show internal input flags
- -c - for each engine, also list the capabilities
- -t[t] - for each engine, check that they are really available
- -tt will display error trace for unavailable engines
- -pre - runs command 'cmd' against the ENGINE before any attempts to load it (if -t is used)
- -post - runs command 'cmd' against the ENGINE after loading it
- (only used if -t is also provided)
- NB: -pre and -post will be applied to all ENGINES supplied on the command line, or all supported ENGINES if none are specified.
- Eg. '-pre "SOPATH:/lib/libdriver.so"' calls command "SOPATH" with argument "/lib/libdriver.so".
- Error creating connect BIO
- Error creating SSL context.
- Error connecting BIO
- Can't get connection fd
- Timeout on connect
- Unexpected retry condition
- Timeout on request

- Select error
- Error querying OCSP responder
- HTTP/1.0 200 OK
- Content-type: application/ocsp-response
- Content-Length: %d
- Illegal timeout value %s
- -header
- -ignore_err
- -nonce
- -no_nonce
- -respnocerts
- -respkeyid
- -no_certs
- -nosignatureverify
- -nocertverify
- -no_chain
- -nocertchecks
- -no_explicit
- -trust_other
- -no_intern
- -req_text
- -resp_text
- -reqin
- -respin
- -VAfile
- -sign_other
- -verify_other
- -validity_period
- Illegal validity period %s
- -status_age
- Illegal validity age %s
- -reqout
- -respout
- issuer certificate
- No issuer certificate specified
- Error Creating OCSP request
- Error converting serial number %s
- -index
- Illegal update period %s
- -nrequest
- Illegal accept count %s
- -ndays
- -rsigner
- -rother
- OCSP utility
- Usage ocsd [options]
- -out file output filename
- -issuer file issuer certificate
- -cert file certificate to check
- -serial n serial number to check
- -signer file certificate to sign OCSP request with
- -signkey file private key to sign OCSP request with

- -sign_other file additional certificates to include in signed request
- -no_certs don't include any certificates in signed request
- -req_text print text form of request
- -resp_text print text form of response
- -text print text form of request and response
- -reqout file write DER encoded OCSP request to "file"
- -respout file write DER encoded OCSP response to "file"
- -reqin file read DER encoded OCSP request from "file"
- -respin file read DER encoded OCSP response from "file"
- -nonce add OCSP nonce to request
- -no_nonce don't add OCSP nonce to request
- -url URL OCSP responder URL
- -host host:n send OCSP request to host on port n
- -path path to use in OCSP request
- -CApath dir trusted certificates directory
- -CAfile file trusted certificates file
- -VAfile file validator certificates file
- -validity_period n maximum validity discrepancy in seconds
- -status_age n maximum status age in seconds
- -noverify don't verify response at all
- -verify_other file additional certificates to search for signer
- -trust_other don't verify additional certificates
- -no_intern don't search certificates contained in response for signer
- -nosignatureverify don't check signature on response
- -nocertverify don't check signing certificate
- -no_chain don't chain verify response
- -nocertchecks don't do additional checks on signing certificate
- -port num
- port to run responder on
- -index file
- certificate status index file
- -CA file
- CA certificate
- -rsigner file
- responder certificate to sign responses with
- -rkey file
- responder key to sign responses with
- -rother file
- other certificates to include in response
- -respnocerts don't include any certificates in response
- -nmin n
- number of minutes before next update
- -ndays n
- number of days before next update
- -respkeyid identify response by signing certificate key ID
- -nrequest n number of requests to accept (default unlimited)
- - use specified digest in the request
- Error Opening OCSP request file
- Error reading OCSP request
- Error setting up accept BIO
- responder certificate
- Error loading responder certificate

- responder other certificates
- responder private key
- Waiting for OCSP client connections...
- Error accepting connection
- Invalid request
- Error parsing OCSP request
- Need an OCSP request for this operation!
- Error loading signer certificate
- signer certificates
- signer private key
- Error signing OCSP request
- Error opening file %s
- Need a responder certificate, key and CA for this operation!
- ocsd.c
- Error Opening OCSP response file
- Error reading OCSP response
- Responder Error: %s (%d)
- validator certificate
- Error parsing response
- WARNING: no nonce in response
- Nonce Verify error
- Response Verify Failure
- Response verify OK
- ERROR: No Status found.
- WARNING: Status times invalid.
- This Update:
- Next Update:
- Reason: %s
- Revocation Time:
- -generate
- -checks
- Unknown option '%s'
- No prime specified
- Specify the number of bits.
- is %sprime
- %-14s hex
- %-14s number of checks
- -checks
- Response is not generated.
- Response has been generated.
- Warning: could not open file %s for reading, using serial number: 1
- Error during serial number generation.
- could not save serial number to %s
- -section
- -query
- -digest
- -token_in
- -token_out
- -reply
- -queryfile
- Error getting password.
- bad digest, %d bytes must be specified

- cannot convert %s to OID
- could not create nonce
- could not create query
- invalid digest string
- memory allocation failure
- Verification:
- FAILED
- usage:
- ts -query [-rand file%cfile%c...] [-config configfile] [-data filetohash] [-digest digest_bytes][-
- ts -reply [-config configfile] [-section tsa_section] [-queryfile request.tsq] [-passin password] [-
- ts -verify [-data filetohash] [-digest digest_bytes] [-queryfile request.tsq] -in response.tsr [-t
- %s "%s"
- %d = "%s"
- User entry
- g N entry
- Creating
- user="%s"
- g="%s"
- N="%s"
- Internal error creating SRP verifier
- gNid=%s salt = "%s"
- verifier = "%s"
- -delete
- -modify
- -userinfo
- -dbfile and -configfile cannot be specified together.
- Exactly one of the options -add, -delete, -modify -list must be specified.
- Need at least one user for options -add, -delete, -modify.
- -passin, -passout arguments only valid with one user.
- trying to read defaultsrp in " BASESECTION "
- default_srp
- trying to read srpvfile in section "%s"
- srpvfile
- Trying to read SRP verifier file "%s"
- Database initialised
- Default g and N
- No g and N value for index "%s"
- Database has no g N information.
- Starting user processing
- Processing user "%s"
- List all users
- user "%s" does not exist, ignored. t
- user "%s" reactivated.
- Cannot create srp verifier for user "%s", operation abandoned .
- failed to update srpvfile
- user "%s" does not exist, operation ignored.
- user "%s" already updated, operation ignored.
- Verifying password for user "%s"
- Validating
- user="%s"
- srp_verifier="%s"
- srp_usersalt="%s"

- g="%s"
- N="%s"
- Pass %s
- Internal error validating SRP verifier
- Invalid password for user "%s", operation abandoned.
- Password for user "%s" ok.
- Cannot create srp verifier for user "%s", operation abandoned.
- user "%s" does not exist, operation ignored. t
- user "%s" revoked. t
- User proccession done.
- Trying to update srpvfile.
- Temporary srpvfile created.
- srpvfile updated.
- User errors %d.
- SRP terminating with code %d.
- usage: srp [args] [user]
- -verbose Talk alot while doing things
- -config file A config file
- -name arg The particular srp definition to use
- -srpvfile arg The srp verifier file name
- -add add an user and srp verifier
- -modify modify the srp verifier of an existing user
- -delete delete user from verifier file
- -list list user
- -gn arg g and N values to be used for new verifier
- -userinfo arg additional info to be set for user
- -engine e - use engine e, possibly a hardware device.
- ./0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz
- 4ah7=.J[
- q"dYiN
- lz*!,l
- EwnW`W
- yR
- (w 1q,
- >
- lZL,YV
-
- e!S_()O
- (P9gS,<
- "-->Z1
- *kX_Hx
- cP"/XXyk
- ^@ H{?
- _!1trkd
- -time arg - max number of seconds to collect data, default %d
- -verify arg - turn on peer certificate verification, arg == depth
- -cert arg - certificate file to use, PEM format assumed
- -key arg - RSA file to use, PEM format assumed, key is in cert file
- file if not specified by this option
- -CApath arg - PEM format directory of CA's
- -CAfile arg - PEM format file of CA's
- -cipher - preferred cipher to use, play with 'openssl ciphers'

- *dyldestubbinding_helper*
- *_dyldfunc_lookup*
- *_SortFnByName*
- *functionLHASH_COMP*
- *functionLHASH_HASH*
- *listmd_fn*
- *docmd*
- *listcipher_fn*
- *lockdbg_cb*
- *_check*
- *reqcheck_len*
- *dosign_init*
- *checkend*
- *setkeygen_ctx*
- *buildsubject*
- *genpkeycb*
- *listmd_fn*
- *dhcb*
- *showciphers*
- *dopasswd*
- *dhcb*
- *dobody*
- *_certify*
- *writenew_certificate*
- *dorevoke*
- *dsacb*
- *ecparamprint_var*
- *_callb*
- *genrsacb*
- *genpkeycb*
- *nextproto_cb*
- *printstats*
- *loaddh_param*
- *certstatus_cb*
- *wwwbody*
- *ss/srpserverparam_cb*
- *ss/servername_cb*
- *pskserver_cb*
- *tmprsa_cb*
- *generatesession_id*
- *svbody*
- *printstuff*
- *ocspresp_cb*
- *ss/srpverifyparam_cb*
- *ss/givesrpclientpwnpcb*
- *ss/servername_cb*
- *nextproto_cb*
- *pskclient_cb*
- *sigdone*
- *_sstrsep*

- *printresult*
- *pkeyprint_message*
- *printmessage*
- *KDF1SHA1*
- *_doConnection*
- *indexname_qual*
- *nodesprint*
- *indexserialLHASHCOMP*
- *indexnameLHASHHASH*
- *indexserialLHASHHASH*
- *setmulti_opts*
- *loadcerts_crls*
- *loadnetscape_key*
- *loadpkcs12*
- *appget_pass*
- *uiclose*
- *uiwrite*
- *uiread*
- *uiopen*
- *indexnameLHASHCOMP*
- *_GetHostByName*
- *hostip*
- *setpbe*
- *_usage*
- *dokeyop*
- *smimecb*
- *makenames_stack*
- *savecerts*
- *gnamesstack_print*
- *cmscb*
- *_identity*
- *appendbuf*
- *utildo_cmds*
- *sendocsp_response*
- *verifycb*
- *BIOOpenwithdefault*
- *loadconfig_file*
- *replycommand*
- *serialcb*
- *printentry*
- *getindex*
- *printuser*
- *srpcreate_user*
- *_magic.15718*
- **_func.15272**
- **_func.15483**
- **_func.15366**
- **_func.15484**
- **_func.15520**
- **_func.15614**

- **_func**.18010
- **_func**.17769
- *mdseed*
- *cov2char*
- *_C.26.17748*
- *_C.27.17772*
- *_C.26.17771*
- *_lengths*
- *testcurves_bits*.16818
- *testcurves*.16816
- *dsabits*.16815
- *rsadata_length*.16812
- *rsabits*.16810
- *_ckey32*.16791
- *_ckey24*.16790
- *_key32*.16789
- *_key24*.16788
- *_key16*.16787
- *dyld_machheader*
- *causage*
- *crlusage*
- *x509usage*
- *scert_file*
- *_tlscstatp*
- *scert_file2*
- *_keymatexportlen*
- *serversessionid_context*
- *acceptsocket*
- *dh512p*
- *dh512g*
- *pskidentity*
- *_keymatexportlen*
- *_usertime*
- *_names*
- *_key3*.16796
- *_key2*.16795
- *_key*.16794
- *_sep*.17628
- *dsa2048priv*
- *dsa2048pub*
- *dsa2048p*
- *dsa2048q*
- *dsa2048g*
- *dsa1024priv*
- *dsa1024pub*
- *dsa1024p*
- *dsa1024q*
- *dsa1024g*
- *dsa512priv*
- *dsa512pub*
- *dsa512p*

- *dsa512q*
- *dsa512g*
- *_test512*
- *_test1024*
- *_test2048*
- *_test4096*
- *_maxTime*
- *_umsg.17155*
- *sessid_usage*
- *ciphersusage*
- *engineusage*
- *srpusage*
- *ctrlreasons*
- *_str.18011*
- *_text.18279*
- *_space.18265*
- *pskidentity*
- *_space.18110*
- *testcurves_names.16817*
- *rsadata.16811*
- *extbl.16514*
- *certtbl.16507*
- *_modes.16794*
- *vverbose*
- *reqconf*
- *_batch*
- *_buf.15966*
- *_buf.15765*
- *_n.15703*
- *passwdstatic.15273*
- *outbuf.15357*
- *_section*
- *_preserve*
- *msiehack*
- *_extconf*
- *bioout*
- *_reqfile*
- *localargc*
- *snbio*
- *snbio_test*
- *sserver_verify*
- *skey_file*
- *sdcert_file*
- *sdkey_file*
- *_cipher*
- *sdebug*
- *stlsectdebug*
- *stlsectstatus*
- *smsg*
- *squiet*
- *enabletimeouts*

- *certchain*
- *sessionid_prefix*
- *engineid*
- *skey_file2*
- *srtpprofiles*
- *_keymatexportlabel*
- *bios_out*
- *pskidentity_hint.17727*
- *rsatmp.18422*
- *socketmtu*
- *localargv*
- *srpcallback_parm*
- *cPause*
- *cquiet*
- *cign_eof*
- *cdebug*
- *cmsg*
- *cshowcerts*
- *cnbio*
- *ctlsextdebug*
- *cstatus_req*
- *_keymatexportlabel*
- *bioc_out*
- *nextproto*
- *mdfake*
- *_results*
- *rsareresults*
- *dsareresults*
- *ecdsareresults*
- *ecdhrefsults*
- *stime_meth*
- *tmctx*
- *stbugs*
- *tmcipher*
- *tcert_file*
- *tkey_file*
- *_CAfile*
- *_CApath*
- *_perform*
- *bytesread*
- *swww_path*
- *tmverify*
- *tnbio*
- *_tmstart.17206*
- *loadconfig_called.16660*
- *uimethod*
- *_pwnbio.16209*
- *ghbnmiss*
- *ghbnhits*
- *_from.17226*

- *ghbncache*
- *_seeded*
- *_egdsocket*
- *_section*
- *_NXArgc*
- *_NXArgv*
- *_progname*
- *_mhexecute_header*
- *addoid_section*
- *algprint*
- *appRANDallowwrite_file*
- *appRANDloadfile*
- *appRANDloadfiles*
- *appRANDwritefile*
- *appinit*
- *appisdir*
- *apppasswd*
- *apptminterval*
- *appsslinfocallback*
- *argsverify*
- *asn1parsemain*
- *biodump_callback*
- *bioerr*
- *bioto_mem*
- *camain*
- *certload*
- *chopupargs*
- *ciphersmain*
- *cmsmain*
- *_config*
- *cookieinitialized*
- *cookiesecret*
- *copyextensions*
- *crl2pkcs7main*
- *crlmain*
- *defaultconfig_file*
- *destroyui_method*
- *dgstmain*
- *dhmain*
- *dhparammain*
- *doX509CRLsign*
- *doX509REQsign*
- *doX509_sign*
- *dofp*
- *doserver*
- *dsamain*
- *dsaparammain*
- *dumpcert_text*
- *dumpcertskeysp12*
- *dumpcertspkeysbag*

- *dumpcertspkeysbags*
- *ecmain*
- *ecparammain*
- *encmain*
- *enginemain*
- *_environ*
- *errstmain*
- *extracthost_port*
- *extractport*
- *freeindex*
- *_functions*
- *gendhmain*
- *gendsamain*
- *generatecookie_callback*
- *genpkeymain*
- *genrsamain*
- *getcert_chain*
- *getdsa1024*
- *getdsa2048*
- *getdsa512*
- *hexprin*
- *indexindex*
- *indexname_cmp*
- *initclient*
- *initgen_str*
- *loadcert*
- *loadcerts*
- *loadconfig*
- *loadctrls*
- *loadindex*
- *loadkey*
- *loadpubkey*
- *loadserial*
- *makeconfig_name*
- *makerevocation_str*
- *makerevoked*
- *msgcb*
- *nextprotos_parse*
- *nseqmain*
- *ocspmain*
- *oldentry_print*
- *parseaname*
- *parseyesno*
- *passwdmain*
- *passwordcallback*
- *pkcs12main*
- *pkcs7main*
- *pkcs8main*
- *pkeyctrl_string*
- *pkeymain*

- *pkeyparammain*
- *pkeyutlmain*
- *policiesprint*
- *primemain*
- *printattribs*
- *printhname*
- *processresponder*
- *programname*
- *pskkey*
- *randmain*
- *randserial*
- *rawread_stdin*
- *rawwrite_stdout*
- *reqmain*
- *rotateindex*
- *rotateserial*
- *rsamain*
- *rsautlmain*
- *sclient_main*
- *scrif*
- *sserver_main*
- *stime_main*
- *saveindex*
- *saveserial*
- *sessid_main*
- *setcert_ex*
- *setcertkeystuff*
- *setcert_stuff*
- *setext_copy*
- *sethex*
- *setname_ex*
- *setupengine*
- *setupui_method*
- *setupverify*
- *smimemain*
- *speedmain*
- *spkacmain*
- *srpmain*
- *srtpprofiles*
- *_str2fmt*
- *tlsextcb*
- *tsmain*
- *unpackrevinfo*
- *verifycallback*
- *verifycookie_callback*
- *verifydepth*
- *verifyerr*
- *verifyerror*
- *verifymain*
- *verifyreturn_error*

- *versionmain*
- *x509main*
- *AEScbc_encrypt*
- *AESEncrypt*
- *AESEsig_encrypt*
- *AESEptions*
- *AESEsetencryptkey*
- *ASN1ENUMERATED_free*
- *ASN1ENUMERATED_new*
- *ASN1ENUMERATED_set*
- *ASN1GENERALIZEDTIME_free*
- *ASN1GENERALIZEDTIME_new*
- *ASN1GENERALIZEDTIME_print*
- *ASN1GENERALIZEDTIMEsetstring*
- *ASN1INTEGER_free*
- *ASN1INTEGER_get*
- *ASN1INTEGER_new*
- *ASN1INTEGER_set*
- *ASN1INTEGERtoBN*
- *ASN1OBJECT_free*
- *ASN1PRINTABLE_type*
- *ASN1STRING_cmp*
- *ASN1STRING_data*
- *ASN1STRING_length*
- *ASN1STRING_set*
- *ASN1STRINGsetdefaultmaskasc*
- *ASN1TIME_free*
- *ASN1TIME_new*
- *ASN1TIME_print*
- *ASN1TIMEsetstring*
- *ASN1TYPE_free*
- *ASN1TYPE_get*
- *ASN1TYPE_new*
- *ASN1UNIVERSALSTRINGtostring*
- *ASN1UTCTIME_free*
- *ASN1UTCTIME_new*
- *ASN1UTCTIMEsetstring*
- *ASN1d2i_bio*
- *ASN1generate_nconf*
- *ASN1i2d_bio*
- *ASN1itemd2ibio*
- *ASN1itemi2dbio*
- *ASN1parse_dump*
- *BFcbc_encrypt*
- *BFoptions*
- *BFset_key*
- *BIOctrl*
- *BIOdebug_callback*
- *BIOdump*
- *BIOdump_indent*

- *BIOf_base64*
- *BIOf_buffer*
- *BIOf_cipher*
- *BIOf_md*
- *BIOfnbiotest*
- *BIOf_ssl*
- *BIOf_zlib*
- *BIOfree*
- *BIOfree_all*
- *BIOgetcallbackarg*
- *BIOgets*
- *BIOint_ctrl*
- *BIOnew*
- *BIOnew_accept*
- *BIOnew_connect*
- *BIOnew_dgram*
- *BIOnew_fd*
- *BIOnew_file*
- *BIOnew_fp*
- *BIOnew_socket*
- *BIOnew_ssl*
- *BIONumber_read*
- *BIONumber_written*
- *BIOpop*
- *BIOprintf*
- *BIOpush*
- *BIOputs*
- *BIOread*
- *BIOs_connect*
- *BIOs_file*
- *BIOs_mem*
- *BIOs_null*
- *BIOset_callback*
- *BIOsetcallbackarg*
- *BIOset_flags*
- *BIOsnprintf*
- *BIOsocksouldretry*
- *BIOsocket_ioctl*
- *BIOtest_flags*
- *BIOwrite*
- *BNCTX_free*
- *BNCTX_new*
- *BNadd_word*
- *BNbin2bn*
- *BNbn2bin*
- *BNbn2dec*
- *BNbn2hex*
- *BNcmp*
- *BNdec2bn*
- *BNfree*

- *BNgenerateprimeex*
- *BNhex2bn*
- *BNisprimeex*
- *BNmod_exp*
- *BNnew*
- *BNnum_bits*
- *BNoptions*
- *BNprint*
- *BNpseudo_rand*
- *BNrshift1*
- *BNset_word*
- *BNtoASN1INTEGER*
- *BUFMEM_free*
- *BUFMEM_grow*
- *BUFMEMgrowclean*
- *BUFMEM_new*
- *BUFstrdup*
- *BUFstrcat*
- *BUFstrlcpy*
- *CASTcbc_encrypt*
- *CASTset_key*
- *CMSCContentInfo_free*
- *CMSCContentInfoprintctx*
- *CMSEncryptedData_decrypt*
- *CMSEncryptedData_encrypt*
- *CMSReceiptRequest_create0*
- *CMSReceiptRequest_free*
- *CMSReceiptRequestget0values*
- *CMSadd0recipientkey*
- *CMSadd0recipientpassword*
- *CMSadd1_ReceiptRequest*
- *CMSadd1_signer*
- *CMScompress*
- *CMSdata*
- *CMSdata_create*
- *CMSdecrypt*
- *CMSdecryptset1key*
- *CMSdecryptset1password*
- *CMSdecryptset1pkey*
- *CMSdigest_create*
- *CMSdigest_verify*
- *CMSencrypt*
- *CMSfinal*
- *CMSget0_SignerInfos*
- *CMSget0_signers*
- *CMSget1_ReceiptRequest*
- *CMSget1_certs*
- *CMSset1_eContentType*
- *CMSsign*
- *CMSsign_receipt*

- *CMSuncompress*
- *CMSverify*
- *CMSverify_receipt*
- *COMPzlib_cleanup*
- *CONFfree*
- *CONFget_section*
- *CONFload*
- *CONFmodules_load*
- *CONFmodules_unload*
- *CRYPTOCleanupall_ex_data*
- *CRYPTOdbg_free*
- *CRYPTOdbggetoptions*
- *CRYPTOdbg_malloc*
- *CRYPTOdbg_realloc*
- *CRYPTOdbgsetoptions*
- *CRYPTOfree*
- *CRYPTOgcm128_aad*
- *CRYPTOgcm128_new*
- *CRYPTOgcm128_release*
- *CRYPTOgcm128_setiv*
- *CRYPTOmalloc*
- *CRYPTOmem_ctrl*
- *CRYPTOmem_leaks*
- *CRYPTOrealloc*
- *CRYPTOsetlockingcallback*
- *CRYPTOsetmemdebug_functions*
- *CRYPTOsetmemdebug_options*
- *CRYPTOsetmemfunctions*
- *Camelliacbc_encrypt*
- *Camelliaset_key*
- *DEScrypt*
- *DESede3cbccencrypt*
- *DESncbc_encrypt*
- *DESoptions*
- *DESsetkeyunchecked*
- *DHcheck*
- *DHfree*
- *DHgenerateparametersex*
- *DHnew*
- *DHparamsprint*
- *DSAdup_DH*
- *DSAfree*
- *DSAgenerate_key*
- *DSAgenerateparametersex*
- *DSAnew*
- *DSAprint*
- *DSAsign*
- *DSaverify*
- *DSApramsdup*
- *DSApramsprint*

- *DTLSv1client_method*
- *DTLSv1server_method*
- *ECDHcompute_key*
- *ECDSAsign*
- *ECDSAverify*
- *ECPKParametersprint*
- *ECGROUP_check*
- *ECGROUP_free*
- *ECGROUPget0generator*
- *ECGROUPgetcofactor*
- *ECGROUPgetcurve_GFp*
- *ECGROUPgetdegree*
- *ECGROUPgetorder*
- *ECGROUPgetpointconversionform*
- *ECGROUPmethodof*
- *ECGROUPnewbycurvename*
- *ECGROUPsetasn1_flag*
- *ECGROUPsetpointconversionform*
- *ECGROUPsetseed*
- *ECKEY_free*
- *ECKEYgeneratekey*
- *ECKEYget0group*
- *ECKEYget0public_key*
- *ECKEY_new*
- *ECKEYnewbycurvename*
- *ECKEYprecomputemult*
- *ECKEY_print*
- *ECKEYsetasn1_flag*
- *ECKEYsetconv_form*
- *ECKEYsetgroup*
- *ECMETHODgetfield_type*
- *ECPOINT_point2bn*
- *ECgetbuiltincurves*
- *ENGINEby_id*
- *ENGINEcleanup*
- *ENGINEctrl*
- *ENGINEctrl_cmd*
- *ENGINEctrlcmdstring*
- *ENGINEfinish*
- *ENGINEfree*
- *ENGINEget_DH*
- *ENGINEget_DSA*
- *ENGINEget_RAND*
- *ENGINEget_RSA*
- *ENGINEget_ciphers*
- *ENGINEget_digests*
- *ENGINEget_first*
- *ENGINEget_id*
- *ENGINEget_name*
- *ENGINEget_next*

- *ENGINEgetpkeyasn1methstr*
- *ENGINEgetpkeymeths*
- *ENGINEinit*
- *ENGINEloadbuiltinengines*
- *ENGINEloadprivatekey*
- *ENGINEloadpublickey*
- *ENGINEregisterallcomplete*
- *ENGINEset_default*
- *ERRclear_error*
- *ERRerrorstringn*
- *ERRfree_strings*
- *ERRget_error*
- *ERRgetstringtable*
- *ERRloadcryptostings*
- *ERRpeek_error*
- *ERRpeek/lasterror*
- *ERRprint_errors*
- *ERRprintererrorsfp*
- *ERRreasonerrorstring*
- *ERRremovethreadstate*
- *EVPBytesToKey*
- *EVPCIPHERCTXcleanup*
- *EVPCIPHERCTXinit*
- *EVPCIPHERCTXset_flags*
- *EVPCIPHERCTXset_padding*
- *EVPCIPHERdoall_sorted*
- *EVPCIPHER_flags*
- *EVPCIPHERivlength*
- *EVPCIPHER_nid*
- *EVPCipherInit_ex*
- *EVPDecryptFinal_ex*
- *EVPDecryptInit_ex*
- *EVPDecryptUpdate*
- *EVPDigest*
- *EVPDigestFinal*
- *EVPDigestFinal_ex*
- *EVPDigestInit*
- *EVPDigestInit_ex*
- *EVPDigestSignFinal*
- *EVPDigestSignInit*
- *EVPDigestUpdate*
- *EVPDigestVerifyFinal*
- *EVPDigestVerifyInit*
- *EVPEncryptFinal_ex*
- *EVPEncryptInit_ex*
- *EVPEncryptUpdate*
- *EVPMDCTXcleanup*
- *EVPMDCTXinit*
- *EVPMDCTXmd*
- *EVPMDCTXset_flags*

- *EVPMDdoall_sorted*
- *EVPMD_flags*
- *EVPMD_size*
- *EVPMD_type*
- *EVPPKCS82PKEY*
- *EVPPKEY2PKCS8_broken*
- *EVPPKEYCTXctrl*
- *EVPPKEYCTXctrl_str*
- *EVPPKEYCTXfree*
- *EVPPKEYCTXgetappdata*
- *EVPPKEYCTXgetkeygeninfo*
- *EVPPKEYCTXnew*
- *EVPPKEYCTXnew_id*
- *EVPPKEYCTXsetappdata*
- *EVPPKEYCTXset_cb*
- *EVPPKEYadd1attrbyNID*
- *EVPPKEYasn1find*
- *EVPPKEYasn1find_str*
- *EVPPKEYasn1get0*
- *EVPPKEYasn1get0_info*
- *EVPPKEYasn1get_count*
- *EVPPKEYbaseid*
- *EVPPKEY_bits*
- *EVPPKEYcopyparameters*
- *EVPPKEY_decrypt*
- *EVPPKEYdecryptfinit*
- *EVPPKEY_derive*
- *EVPPKEYderiveinit*
- *EVPPKEYderiveset_peer*
- *EVPPKEY_encrypt*
- *EVPPKEYencryptfinit*
- *EVPPKEY_free*
- *EVPPKEYget0asn1*
- *EVPPKEYget1DSA*
- *EVPPKEYget1RSA*
- *EVPPKEYgetdefaultdigestnid*
- *EVPPKEY_id*
- *EVPPKEY_keygen*
- *EVPPKEYkeygeninit*
- *EVPPKEYmissingparameters*
- *EVPPKEY_new*
- *EVPPKEYnewmac_key*
- *EVPPKEY_paramgen*
- *EVPPKEYparamgeninit*
- *EVPPKEYprintparams*
- *EVPPKEYprintprivate*
- *EVPPKEYprintpublic*
- *EVPPKEYsaveparameters*
- *EVPPKEYset1DSA*
- *EVPPKEYset1RSA*

- *EVPPKEY_sign*
- *EVPPKEYsigninit*
- *EVPPKEY_size*
- *EVPPKEY_verify*
- *EVPPKEYverifyinit*
- *EVPPKEYverifyrecover*
- *EVPPKEYverifyrecover_init*
- *EVPaes128cbc*
- *EVPaes192cbc*
- *EVPaes256cbc*
- *EVPcamellia128cbc*
- *EVPcamellia192cbc*
- *EVPcamellia256cbc*
- *EVPcleanup*
- *EVPdes_cbc*
- *EVPdesede3cbc*
- *EVPget_cipherbyname*
- *EVPget_digestbyname*
- *EVPidea_cbc*
- *EVPmd4*
- *EVPmd5*
- *EVPmdc2*
- *EVPr240cbc*
- *EVPr264cbc*
- *EVPr2_cbc*
- *EVPreadpwstring*
- *EVPripemd160*
- *EVPseed_cbc*
- *EVPsha1*
- *GENERALNAMES_free*
- *GENERALNAMES_new*
- *GENERALNAME_free*
- *GENERALNAME_print*
- *HMACCTX_cleanup*
- *HMACCTX_init*
- *HMACFinal*
- *HMACInit_ex*
- *HMACUpdate*
- *NCONFfree*
- *NCONFgetnumbere*
- *NCONFget_section*
- *NCONFget_string*
- *NCONFload*
- *NCONFload_bio*
- *NCONFnew*
- *NETSCAPECERTSEQUENCEfree*
- *NETSCAPECERTSEQUENCEnew*
- *NETSCAPESPKIb64decode*
- *NETSCAPESPKIb64encode*
- *NETSCAPESPKI_free*

- *NETSCAPESPKIgetpubkey*
- *NETSCAPESPKI_new*
- *NETSCAPESPKI_print*
- *NETSCAPESPKIsetpubkey*
- *NETSCAPESPKI_sign*
- *NETSCAPESPKI_verify*
- *NETSCAPEX509_free*
- *NETSCAPEX509_it*
- *OBJNAMEdoall_sorted*
- *OBJcleanup*
- *OBJcreate*
- *OBJcreate_objects*
- *OBJnid2ln*
- *OBJnid2obj*
- *OBJnid2sn*
- *OBJobj2nid*
- *OBJsn2nid*
- *OBJtxt2nid*
- *OBJtxt2obj*
- *OCSPPBASICRESP_free*
- *OCSPPBASICRESP_new*
- *OCSPCERTID_free*
- *OCSPPREQUESTaddext*
- *OCSPPREQUEST_free*
- *OCSPPREQUEST_new*
- *OCSPPREQUEST_print*
- *OCSPPREQCTXadd1_header*
- *OCSPPREQCTXfree*
- *OCSPPREQCTXset1_req*
- *OCSPPRESPONSE_free*
- *OCSPPRESPONSE_new*
- *OCSPPRESPONSE_print*
- *OCSPPSINGLERESPadd1ext_i2d*
- *OCSPPbasicadd1status*
- *OCSPPbasic_sign*
- *OCSPPbasic_verify*
- *OCSPPcertidnew*
- *OCSPPcertstatusstr*
- *OCSPPcerttoid*
- *OCSPPcheck_nonce*
- *OCSPPcheck_validity*
- *OCSPPcopy_nonce*
- *OCSPPcrlreasonstr*
- *OCSPPidget0info*
- *OCSPPidissuercmp*
- *OCSPPonereqget0id*
- *OCSPPparse_url*
- *OCSPPrequestadd0id*
- *OCSPPrequestadd1nonce*
- *OCSPPrequestonereqcount*

- *OCSPrequestonereqget0*
- *OCSPrequest_sign*
- *OCSPrespfindstatus*
- *OCSPresponse_create*
- *OCSPresponseget1basic*
- *OCSPresponse_status*
- *OCSPresponsestatusstr*
- *OCSPsendreq_nbio*
- *OCSPsendreq_new*
- *OPENSSLaddallalgorithms_noconf*
- *OPENSSLcleanse*
- *OPENSSLloadbuiltinmodules*
- *OPENSSLuni2asc*
- *_OpenSSLDie*
- *PBEPARAMfree*
- *PEMX509INFOread_bio*
- *PEMreadbioCMS*
- *PEMreadbioDHparams*
- *PEMreadbioDSAParams*
- *PEMreadbioECPKParameters*
- *PEMreadbioECPrivateKey*
- *PEMreadbioEC_PUBKEY*
- *PEMreadbioNETSCAPECERTSEQUENCE*
- *PEMreadbioPKCS7*
- *PEMreadbioPKCS8*
- *PEMreadbioPKCS8PRIVKEY_INFO*
- *PEMreadbioPUBKEY*
- *PEMreadbioParameters*
- *PEMreadbioPrivateKey*
- *PEMreadbioRSAPublicKey*
- *PEMreadbioSSL_SESSION*
- *PEMreadbioX509*
- *PEMreadbioX509_AUX*
- *PEMreadbioX509_CRL*
- *PEMreadbioX509_REQ*
- *PEMwritebioCMS_stream*
- *PEMwritebioDHparams*
- *PEMwritebioDSAPrivateKey*
- *PEMwritebioDSA_PUBKEY*
- *PEMwritebioDSAParams*
- *PEMwritebioECPKParameters*
- *PEMwritebioECPrivateKey*
- *PEMwritebioEC_PUBKEY*
- *PEMwritebioNETSCAPECERTSEQUENCE*
- *PEMwritebioPKCS7*
- *PEMwritebioPKCS7_stream*
- *PEMwritebioPKCS8*
- *PEMwritebioPKCS8PRIVKEY_INFO*
- *PEMwritebioPUBKEY*
- *PEMwritebioParameters*

- *PEMwritebioPrivateKey*
- *PEMwritebioRSAPrivateKey*
- *PEMwritebioRSAPublicKey*
- *PEMwritebioRSA_PUBKEY*
- *PEMwritebioSSL_SESSION*
- *PEMwritebioX509*
- *PEMwritebioX509_AUX*
- *PEMwritebioX509_CRL*
- *PEMwritebioX509_REQ*
- *PEMwritebioX509REQNEW*
- *PKCS12SAFE BAG_free*
- *PKCS12certbag2x509*
- *PKCS12create*
- *PKCS12decrypt_skey*
- *PKCS12free*
- *PKCS12getattrgen*
- *PKCS12parse*
- *PKCS12set_mac*
- *PKCS12unpack_authsafes*
- *PKCS12unpack_p7data*
- *PKCS12unpack_p7encdata*
- *PKCS12verify_mac*
- *PKCS7SIGNED_new*
- *PKCS7decrypt*
- *PKCS7encrypt*
- *PKCS7final*
- *PKCS7free*
- *PKCS7get0_signers*
- *PKCS7new*
- *PKCS7print_ctx*
- *PKCS7sign*
- *PKCS7signaddsigner*
- *PKCS7toTSTST_INFO*
- *PKCS7verify*
- *PKCS8PRIVKEYINFO_free*
- *PKCS8decrypt*
- *PKCS8encrypt*
- *RANDbytes*
- *RANDcleanup*
- *RANDegd*
- *RANDfile_name*
- *RANDload_file*
- *RANDpseudo_bytes*
- *RANDseed*
- *RANDstatus*
- *RANDwrite_file*
- *RC2cbc_encrypt*
- *RC2set_key*
- *RC4options*
- *RC4set_key*

- *RSAPKCS1_SSLeay*
- *RSACheck_key*
- *RSAsfree*
- *RSAGeneratekeyex*
- *RSANew*
- *RSANew_method*
- *RSAPrint*
- *RSAPrivate_decrypt*
- *RSAPrivate_encrypt*
- *RSAPublic_decrypt*
- *RSAPublic_encrypt*
- *RSASetdefaultmethod*
- *RSASign*
- *RSASize*
- *RSVerify*
- *SEEDcbc_encrypt*
- *SEEDset_key*
- *_SHA256*
- *_SHA512*
- *SMIMEread_CMS*
- *SMIMEread_PKCS7*
- *SMIMEwrite_CMS*
- *SMIMEwrite_PKCS7*
- *SRPVBASEgetby_user*
- *SRPVBASE_init*
- *SRPVBASE_new*
- *SRPcheckknowngN_param*
- *SRPcreate_verifier*
- *SRPgetdefaultgN*
- *SSL_CIPHER_description*
- *SSL_CIPHER_getid*
- *SSL_CIPHER_getname*
- *SSL_CIPHER_getversion*
- *SSL_COMP_getname*
- *SSLCTXcallbackctrl*
- *SSLCTXcheckprivate_key*
- *SSLCTX_ctrl*
- *SSLCTX_free*
- *SSLCTXgetcert_store*
- *SSLCTXloadverify_locations*
- *SSLCTX_new*
- *SSLCTXset1param*
- *SSLCTXsetcipher_list*
- *SSLCTXsetclientCAlist*
- *SSLCTXsetclientcertengine*
- *SSLCTXsetcookiegeneratecb*
- *SSLCTXsetcookieverifycb*
- *SSLCTXsetdefaultverifypaths*
- *SSLCTXsetgenerate_sessionid*
- *SSLCTXsetinfo_callback*

- `SSLCTXsetnextprotoselect_cb`
- `SSLCTXsetnextprotosadvertised_cb`
- `SSLCTXsetpskclientcallback`
- `SSLCTXsetpskservercallback`
- `SSLCTXsetquiet_shutdown`
- `SSLCTXsetsessionidcontext`
- `SSLCTXsetsrpcbarg`
- `SSLCTXsetsrpclientpwd_callback`
- `SSLCTXsetsrp_strength`
- `SSLCTXsetsrp_username`
- `SSLCTXsetsrpusernamecallback`
- `SSLCTXsetsrpverifyparam_callback`
- `SSLCTXsettlsextrusesrtp`
- `SSLCTXsettmprsacallback`
- `SSLCTXsetverify`
- `SSLCTXusePrivateKey`
- `SSLCTXusePrivateKey_file`
- `SSLCTXusecertificate`
- `SSLCTXusecertificate_file`
- `SSLCTXusepskidentityhint`
- `SSLSESSION_free`
- `SSLSESSIONget0peer`
- `SSLSESSION_new`
- `SSLSESSION_print`
- `SSLSESSIONset1id_context`
- `SSLaccept`
- `SSLalertdescstring_long`
- `SSLalertypestring_long`
- `SSLcache_hit`
- `SSLcallback_ctrl`
- `SSLclear`
- `SSLconnect`
- `SSLctrl`
- `SSLdo_handshake`
- `SSLexportkeyingmaterial`
- `SSLfree`
- `SSLget0nextproto_negotiated`
- `SSLgetSSLCTX`
- `SSLget_certificate`
- `SSLgetciphelist`
- `SSLget_ciphers`
- `SSLgetclientCA_list`
- `SSLgetcurrentcipher`
- `SSLgetcurrentcompression`
- `SSLgetcurrentexpansion`
- `SSLget_error`
- `SSLget_fd`
- `SSLgetpeercert_chain`
- `SSLgetpeercertificate`
- `SSLget_rbio`

- `SSLgetselectedsrtp_profile`
- `SSLget_servername`
- `SSLgetservernametype`
- `SSLget_session`
- `SSLgetsharedciphers`
- `SSLgetsrpN`
- `SSLgetsrpg`
- `SSLgetsrpusername`
- `SSLgetverifyresult`
- `SSLget_wbio`
- `SSLhasmatchingsession_id`
- `SSLlibrary_init`
- `SSLloadclientCA_file`
- `SSLloaderrorstrings`
- `SSLnew`
- `SSLpending`
- `SSLread`
- `SSLrenegotiate`
- `SSLselectnextproto`
- `SSLsetSSLCTX`
- `SSLsetacceptstate`
- `SSLset_bio`
- `SSLsetconnectstate`
- `SSLset_debug`
- `SSLsetmsgcallback`
- `SSLset_session`
- `SSLsetsessionid_context`
- `SSLset_shutdown`
- `SSLsetsrpserver_param`
- `SSLset_verify`
- `SSLshutdown`
- `SSLstate`
- `SSLstatestringlong`
- `SSLversion`
- `SSLwrite`
- `_SSLeay`
- `SSLeayversion`
- `SSLv23client_method`
- `SSLv23server_method`
- `SSLv2client_method`
- `SSLv2server_method`
- `SSLv3client_method`
- `SSLv3server_method`
- `TLSv11clientmethod`
- `TLSv11servemethod`
- `TLSv12clientmethod`
- `TLSv12servemethod`
- `TLSv1client_method`
- `TLSv1server_method`
- `TSCONFgettsa_section`

- *TSCONFloadcerts*
- *TSCONFsetaccuracy*
- *TSCONFsetcerts*
- *TSCONFsetclockprecisiondigits*
- *TSCONFsetcrypto_device*
- *TSCONFsetdef_policy*
- *TSCONFsetdigests*
- *TSCONFsetesscertid_chain*
- *TSCONFsetordering*
- *TSCONFsetpolicies*
- *TSCONFsetserial*
- *TSCONFsetsigner_cert*
- *TSCONFsetsigner_key*
- *TSCONFsetsa_name*
- *TMSGIMPRINTfree*
- *TMSGIMPRINTnew*
- *TMSGIMPRINTset_algo*
- *TMSGIMPRINTset_msg*
- *TSREQ_free*
- *TSREQ_new*
- *TSREQprintbio*
- *TSREQsetcert_req*
- *TSREQsetmsg_imprint*
- *TSREQsetnonce*
- *TSREQsetpolicy_id*
- *TSREQsetversion*
- *TSREQtoTSVERIFYCTX*
- *TSRESPCTXaddfailureinfo*
- *TSRESPCTXfree*
- *TSRESPCTXnew*
- *TSRESPCTXsetstatusinfo*
- *TSRESPcreatereponse*
- *TSRESP_free*
- *TSRESPgettoken*
- *TSRESPgettst_info*
- *TSRESP_new*
- *TSRESPprintbio*
- *TSRESPsetstatus_info*
- *TSRESPsettst_info*
- *TSRESPverifyresponse*
- *TSRESPverifytoken*
- *TSSTATUS/INFOfree*
- *TSSTATUS/INFOnew*
- *TSTST/INFOfree*
- *TSTST/INFOprint_bio*
- *TSVERIFYCTXfree*
- *TSVERIFYCTXnew*
- *TXTDBcreateindex*
- *TXTDB_free*
- *TXTDBgetby_index*

- *TXTDB_insert*
- *TXTDB_read*
- *TXTDB_write*
- *UIOpenSSL*
- *Uladdininputstring*
- *Uladdverifystring*
- *Ulconstruct_prompt*
- *Ulcreate_method*
- *Ulctrl*
- *Uldestroy_method*
- *Ulfree*
- *Ulget0userdata*
- *Ulgetinputflags*
- *Ulgetstringtype*
- *Ulmethodgetcloser*
- *Ulmethodgetopener*
- *Ulmethodgetreader*
- *Ulmethodgetwriter*
- *Ulmethodsetcloser*
- *Ulmethodsetopener*
- *Ulmethodsetreader*
- *Ulmethodsetwriter*
- *Ulnew_method*
- *Ulprocess*
- *Ulset_result*
- *_WHIRLPOOL*
- *X509V3EXTCRLadd_nconf*
- *X509V3EXTREQadd_nconf*
- *X509V3EXTaddnconf*
- *X509V3add_value*
- *X509V3conf_free*
- *X509V3parse_list*
- *X509V3set_ctx*
- *X509V3set_nconf*
- *X509ALGOR_free*
- *X509ALGOR_new*
- *X509CRLadd0revoked*
- *X509CRLadd1ext_i2d*
- *X509CRL_digest*
- *X509CRL_free*
- *X509CRLgetext_d2i*
- *X509CRL_new*
- *X509CRL_print*
- *X509CRLsetissuer_name*
- *X509CRLsetlastUpdate*
- *X509CRLsetnextUpdate*
- *X509CRLsetversion*
- *X509CRLsignctx*
- *X509CRL_sort*
- *X509CRL_verify*

- X509EXTENSION_free
- X509EXTENSION_getobject
- X509INFO_free
- X509LOOKUP_ctrl
- X509LOOKUP_file
- X509LOOKUP_hashdir
- X509NAMEENTRY_free
- X509NAMEENTRY_get_data
- X509NAMEENTRY_get_object
- X509NAME_addentry
- X509NAME_addentrybyNID
- X509NAME_addentrybytxt
- X509NAME_deleteentry
- X509NAME_dup
- X509NAME_entrycount
- X509NAME_free
- X509NAME_getentry
- X509NAME_getindexbyNID
- X509NAME_getindexbyOBJ
- X509NAME_hash
- X509NAME_hashold
- X509NAME_new
- X509NAME_online
- X509NAME_printex
- X509NAME_printex_fp
- X509OBJECT_freecontents
- X509POLICYNODE_print
- X509PURPOSE_get0
- X509PURPOSE_get0name
- X509PURPOSE_get0sname
- X509PURPOSE_getby_sname
- X509PURPOSE_getcount
- X509PURPOSE_getid
- X509REQ_add1attrbyNID
- X509REQ_add1attrbytxt
- X509REQ_checkprivate_key
- X509REQ_free
- X509REQ_getextensions
- X509REQ_getpubkey
- X509REQ_new
- X509REQ_print
- X509REQ_printex
- X509REQ_setpubkey
- X509REQ_setsubject_name
- X509REQ_setversion
- X509REQ_signctx
- X509REQ_verify
- X509REVOKED_add1ext_i2d
- X509REVOKED_new
- X509REVOKED_setrevocationDate

- X509REVOKEDsetserialNumber
- X509SIG_free
- X509STORECTXcleanup
- X509STORECTXfree
- X509STORECTXget0parentctx
- X509STORECTXget0policytree
- X509STORECTXget1_chain
- X509STORECTXgetcurrentcert
- X509STORECTXget_error
- X509STORECTXgeterrorddepth
- X509STORECTXgetexplicitpolicy
- X509STORECTXinit
- X509STORECTXnew
- X509STORECTXset0_crls
- X509STORECTXset_cert
- X509STORECTXset_flags
- X509STORECTXtrusted_stack
- X509STOREaddlookup
- X509STORE_free
- X509STOREgetby_subject
- X509STOREloadlocations
- X509STORE_new
- X509STOREset1param
- X509STOREsetdefault_paths
- X509STOREsetflags
- X509STOREsetverify_cb
- X509VERIFYPARAMadd0_policy
- X509VERIFYPARAMfree
- X509VERIFYPARAMnew
- X509VERIFYPARAMset_depth
- X509VERIFYPARAMset_flags
- X509VERIFYPARAMset_purpose
- X509VERIFYPARAMset_time
- X509add1rejectobject
- X509add1trustobject
- X509add_ext
- X509alias_get0
- X509alias_set1
- X509checkprivatekey
- X509check_purpose
- X509cmp_time
- X509delete_ext
- X509digest
- X509email_free
- X509free
- X509get0pubkeybitstr
- X509get1_email
- X509get1_ocsp
- X509getdefaultcert_area
- X509get_ext

- X509getextby_OBJ
- X509gettextcount
- X509getissuename
- X509get_pubkey
- X509get_serialNumber
- X509getsubjectname
- X509gmtime_adj
- X509issuernamemhash
- X509issuernamemhash_old
- X509keyid_set1
- X509new
- X509ocspid_print
- X509policytreeget0_policies
- X509policytreeget0userpolicies
- X509print
- X509print_ex
- X509reject_clear
- X509setissuename
- X509set_pubkey
- X509set_serialNumber
- X509setsubjectname
- X509set_version
- X509sign
- X509sign_ctx
- X509subjectnamemhash
- X509subjectnamemhash_old
- X509timeadjex
- X509toX509REQ
- X509trust_clear
- X509verify
- X509verify_cert
- X509verifycerterror_string
- __DefaultRuneLocale
- _assert_rtn
- _error
- _maskrune
- _stderrp
- _stdinp
- _stdoutp
- _toupper
- a2iASN1_INTEGER
- a2iGENERAL_NAME
- _abort
- _accept\$UNIX2003
- _access
- _alarm
- b2iPVK_bio
- b2iPrivateKey_bio
- b2iPublicKey_bio
- _bind\$UNIX2003

- `_close$UNIX2003`
- `_connect$UNIX2003`
- `d2iASN1_TYPE`
- `d2iCMS_bio`
- `d2iDHparams`
- `d2iDSAParams`
- `d2iECPKParameters`
- `d2iECPrivateKey_bio`
- `d2iECPUBKEYbio`
- `d2iOCSP_REQUEST`
- `d2iOCSP_RESPONSE`
- `d2iPBEPARAM`
- `d2iPKCS12_bio`
- `d2iPKCS7_bio`
- `d2iPKCS8PRIVKEYINFObio`
- `d2iPKCS8_bio`
- `d2iPUBKEY_bio`
- `d2iPrivateKey_bio`
- `d2iRSAPrivateKey`
- `d2iRSAPublicKey_bio`
- `d2iRSA_NET`
- `d2iSSL_SESSION`
- `d2iTSREQbio`
- `d2iTSRESPbio`
- `d2iX509CRLbio`
- `d2iX509REQbio`
- `d2iX509_bio`
- `_fclose`
- `_fdopen`
- `_fflush`
- `_fgets`
- `_fileno`
- `_fopen`
- `_fprintf$LDBL128`
- `_fputc`
- `_fputs$UNIX2003`
- `_fwrite$UNIX2003`
- `_getenv`
- `_gethostbyaddr`
- `_gethostbyname`
- `_getservbyname`
- `_getsockname$UNIX2003`
- `i2aASN1_INTEGER`
- `i2aASN1_OBJECT`
- `i2bPVK_bio`
- `i2bPrivateKey_bio`
- `i2bPublicKey_bio`
- `i2dASN1_TYPE`
- `i2dCMSbiostream`
- `i2dDHparams`
- `i2dDSAPrivateKey_bio`

- *i2dDSAPUBKEYbio*
- *i2dDSAPparams*
- *i2dECPKParameters*
- *i2dECPrivateKey_bio*
- *i2dECPUBKEYbio*
- *i2dOCSP_REQUEST*
- *i2dOCSP_RESPONSE*
- *i2dPKCS12_bio*
- *i2dPKCS7_bio*
- *i2dPKCS7biostream*
- *i2dPKCS8PRIVKEYINFObio*
- *i2dPKCS8_bio*
- *i2dPUBKEY_bio*
- *i2dPrivateKey_bio*
- *i2dRSAPrivateKey_bio*
- *i2dRSAPublicKey_bio*
- *i2dRSA_NET*
- *i2dRSAPUBKEYbio*
- *i2dSSL_SESSION*
- *i2dTSREQbio*
- *i2dTSRESPbio*
- *i2dX509*
- *i2dX509CRLbio*
- *i2dX509_NAME*
- *i2dX509_PUBKEY*
- *i2dX509REQbio*
- *i2dX509_bio*
- *ideacbc_encrypt*
- *ideaoptions*
- *ideasetencryptkey*
- *lhfree*
- *lhinsert*
- *lhnew*
- *lhnodestatsbio*
- *lhnodeusagestats_bio*
- *lhretrieve*
- *lhstats_bio*
- *lhstrhash*
- *_listen\$UNIX2003*
- *_malloc*
- *_memcmp*
- *_memcpy*
- *_memset*
- *_perror*
- *_printf\$LDBL128*
- *_putchar*
- *_qsort*
- *_read\$UNIX2003*
- *_realloc*
- *_rename*

- *s2i*ASN1_INTEGER
- *_select*\$UNIX2003
- *_setsockopt*
- *_setvbuf*
- *_shutdown*
- *_signal*
- *skdelete*
- *skfree*
- *sknew_null*
- *sknum*
- *skpop_free*
- *skpush*
- *skshift*
- *skvalue*
- *_sleep*\$UNIX2003
- *_socket*
- *_sscanf*\$LDBL128
- *_strcasecmp*
- *_strchr*
- *_strcmp*
- *_strcpy*
- *stringto_hex*
- *_strlen*
- *_strncat*
- *_strncmp*
- *_strrchr*
- *_strspn*
- *_strstr*
- *_sysconf*
- *_times*
- *_write*\$UNIX2003

UTF-8 Strings

No detected.

UTF-16LE Strings

No detected.

Extracted URLs

- <http://etherx.jabber.org/streams>'

Base64 Strings

- Possible Base64 Encoded String: blowfish -> Decoded: nZ0~+!
- Possible Base64 Encoded String: blowfish -> Decoded: nZ0~+!

File Entropy Analysis

- **Entropy:** 6.24

- **Status:** This file is likely packed or encrypted.
-

VirusTotal Analysis

Scan Date: 2021-08-08 19:34:23

Scan Results

- Malicious: 0
- Suspicious: 0
- Undetected: 61
- Harmless: 0
- Timeout: 0
- Confirmed-timeout: 1
- Failure: 1
- Type-unsupported: 13

Community Votes

- Harmless: 0
- Malicious: 0

Detailed Engine Results

Engine Name	Detection Category	Detection
No results	No results	No results
