

CS2010: ALGORITHMS AND DATA STRUCTURES

Lecture 1: Module Overview & Introduction

Vasileios Koutavas

School of Computer Science and Statistics




Trinity College Dublin

Coláiste na Tríonóide, Baile Átha Cliath

The University of Dublin

→ **Objective:** learn to solve computational problems **efficiently**



“Algorithms + Data Structures = Programs”

— Niklaus Wirth



→ **Algorithm:** The steps to **correctly** perform a task that answers a **general**¹ computational problem

- **Algorithm:** The steps to **correctly** perform a task that answers a **general**¹ computational problem
 - What is the median age of all people in Ireland?

- **Algorithm:** The steps to **correctly** perform a task that answers a **general**¹ computational problem
 - What is the median age of all people in Ireland?
 - What is the quickest path from here to Marrakech?

- **Algorithm:** The steps to **correctly** perform a task that answers a **general**¹ computational problem
 - What is the median age of all people in Ireland?
 - What is the quickest path from here to Marrakech?

¹Algorithms answering the above questions had better work when the population of Ireland changes & for other holiday destinations!

- **Algorithm:** The steps to **correctly** perform a task that answers a **general**¹ computational problem
 - What is the median age of all people in Ireland?
 - What is the quickest path from here to Marrakech?
- **Data Structures:** The methods to store the information needed for the algorithm.

¹Algorithms answering the above questions had better work when the population of Ireland changes & for other holiday destinations!

WHAT ABOUT EFFICIENCY?

Are these good measures of a program's efficiency?

- How long it takes the program to run on my laptop
- How long it takes the program to run on the fastest computer
- How long it takes the program to run on the slowest computer
- How long it takes the program to run with the largest input
- How long it takes the program to run with the smallest input

WHAT ABOUT EFFICIENCY?

Established measure: how well the program **scales** to larger inputs

- When I **double** the input size my program takes **the same** time to run on the same computer (*constant running time*).
- When I **double** the input size my program takes **twice** the time to run on the same computer (*linear running time*).
- ...

WHAT ABOUT EFFICIENCY?

Established measure: how well the program **scales** to larger inputs

- When I **double** the input size my program takes **the same** time to run on the same computer (*constant running time*).
- When I **double** the input size my program takes **twice** the time to run on the same computer (*linear running time*).
- ...

We also care about **memory needed**:

- When I **double** the input size my program needs **the same** amount of memory to run (*constant memory space*).
- When I **double** the input size my program takes **twice** the amount of memory to run (*linear memory space*).
- ...

- Learn **the most common A&DS** that every CS graduate must know.
 - Example algorithms: Merge Sort, Union-Find, Dijkstra's Shortest Path Tree, ...

- Learn **the most common A&DS** that every CS graduate must know.
 - Example algorithms: Merge Sort, Union-Find, Dijkstra's Shortest Path Tree, ...
- Identify which known algorithms/data structures **best fit** specific problems
 - Example: What is the best algorithm for finding the median?
 - It depends:² QuickSelect, MedianOfMedians, IntroSelect, using SoftHeaps

²[https://www.quora.com/](https://www.quora.com/What-is-the-most-efficient-algorithm-to-find-the-kth-smallest-element-in-an-array)

What-is-the-most-efficient-algorithm-to-find-the-kth-smallest-element

- Learn to **evaluate** new algorithms
 - Efficiency: **calculate** the running time and memory usage
 - We are interested mostly on **how well they scale**
 - **Worst-case**, average-case, best-case, **amortised** performance
 - Experimentally measure performance
 - Calculate performance using mathematical methods (big-O notation, tilde notation, cost models, ...)
 - Correctness: **rigorous testing** and some informal correctness arguments

- Learn to **evaluate** new algorithms
 - Efficiency: **calculate** the running time and memory usage
 - We are interested mostly on **how well they scale**
 - **Worst-case**, average-case, best-case, **amortised** performance
 - Experimentally measure performance
 - Calculate performance using mathematical methods (big-O notation, tilde notation, cost models, ...)
 - Correctness: **rigorous testing** and some informal correctness arguments
- Learn to use **Abstract Data Types**: the interfaces of Data Structures

- Learn to **evaluate** new algorithms
 - Efficiency: **calculate** the running time and memory usage
 - We are interested mostly on **how well they scale**
 - **Worst-case**, average-case, best-case, **amortised** performance
 - Experimentally measure performance
 - Calculate performance using mathematical methods (big-O notation, tilde notation, cost models, ...)
 - Correctness: **rigorous testing** and some informal correctness arguments
- Learn to use **Abstract Data Types**: the interfaces of Data Structures
- Practice **implementing** A&DS in Java

CS2010 LOGISTICS

<https://www.scss.tcd.ie/Vasileios.Koutavas/teaching/cs2010/>

EXAMPLE PROBLEM

A software engineer was asked to design an algorithm which will input two **unsorted** arrays of integers, **A** (of size N) and **B** (also of size N), and will output **true** when all integers in **A** are present in **B**. The engineer came up with **two** alternatives:

```
boolean isContained1(int[] A, int[] B) {
    boolean AInB = true;
    for (int i = 0; i < A.length; i++) {
        boolean iInB = linearSearch(B, A[i]);
        AInB = AInB && iInB;
    }
    return AInB;
}

boolean isContained2(int[] A, int[] B) {
    int[] C = new int[B.length];
    for (int i = 0; i < B.length; i++) { C[i] = B[i] }
    sort(C); // heapsort
    boolean AInC = true;
    for (int i = 0; i < A.length; i++) {
        boolean iInC = binarySearch(C, A[i]);
        AInC = AInC && iInC;
    }
}
```

- (a) Calculate the worst-case running time of each of the two implementations using the asymptotic Θ notation.
- (b) For each implementation, how much extra memory space is it required to store copies of the elements in **A** and **B**? You should take into account any copies made within the methods **sort**, **linearSearch**, and **binarySearch**.
- (c) Find an implementation which is more efficient than both of the engineer's implementation.

WHY?

<http://www.youtube.com/embed/vSi6YoTPWLw?rel=0&start=8&end=165>

WHY?

→ To get a technology job


<http://www.careercup.com>



WHY?

→ To create the “New Google”

<http://en.wikipedia.org/wiki/PageRank>



WHY?

→ To make science

<http://ocw.mit.edu/courses/biological-engineering/>

20-482j-foundations-of-algorithms-and-computational-techniques-in

Foundations of Algorithms and Computational Techniques in Systems Biology


COURSE HOME <

SYLLABUS

LECTURE NOTES

ASSIGNMENTS

DOWNLOAD COURSE
MATERIALS



Instructor(s)

Prof. Bruce Tidor

Prof. Jacob White

MIT Course Number

20.482J / 6.581J

As Taught In

Spring 2006

Level

Graduate

Translated Versions

简体字

CITE THIS COURSE

The role of the Rad checkpoint complex was inferred from the 3-D structure predicted by comparative modeling at Lawrence Livermore National Laboratory. The Rad complex delays cell division to allow time for DNA repair to take place. (Image courtesy of the **U.S. Department of Energy Genomics: GTL Program.**)

WHY?

→ To play the stock market

[http://www.theguardian.com/business/2012/oct/21/
superstar-traders-lost-magic](http://www.theguardian.com/business/2012/oct/21/superstar-traders-lost-magic)

One theory for the decline of the superstar trader is the rise of the analytical nerd and computerised algorithmic trading. Schmidt says: "The superstars are confronted with a changing market. The punting around is not working. You now need to be either a traditional long-term stock picker, a very short-term person working on algorithms, or a combination of both. There is no future for guys like Coffey.

WHY?

→ To rule the world!

[http://www.theguardian.com/science/2013/jul/01/
how-algorithms-rule-world-nsa](http://www.theguardian.com/science/2013/jul/01/how-algorithms-rule-world-nsa)

theguardian

[News](#) | [Sport](#) | [Comment](#) | [Culture](#) | [Business](#) | [Money](#) | [Life & style](#) |

[News](#) > [Science](#) > [Mathematics](#)

How algorithms rule the world

The NSA revelations highlight the role sophisticated algorithms play in sifting through masses of data. But more surprising is their widespread use in our everyday lives. So should we be more wary of their power?

WHY?

→ For fun!

http://en.wikipedia.org/wiki/Tower_of_Hanoi

