Chapter 9 Multimedia Networking



Computer Networking: A Top Down Approach

7th edition
Jim Kurose, Keith Ross
Pearson/Addison Wesley
April 2016

Multimedia networking: outline

9.1 multimedia networking applications
9.2 streaming *stored* video
9.3 voice-over-IP

Multimedia: audio

- analog audio signal sampled at constant rate
  - telephone: 8,000 samples/sec
  - CD music: 44,100 samples/sec
- each sample quantized, i.e., rounded
  - e.g., 2^8=256 possible quantized values
  - each quantized value represented by bits, e.g., 8 bits for 256 values



Multimedia: audio

- example: 8,000 samples/sec, 256 quantized values: 64,000 bps
- receiver converts bits back to analog signal:
  - some quality reduction


quantization error
quantized value of analog value
audio signal amplitude
analog signal
time
sampling rate (*N* sample/sec)

example rates

- CD: 1.411 Mbps
- MP3: 96, 128, 160 kbps
- Internet telephony: 5.3 kbps and up
- Tidal Music Service, Siruis Satellite, Google Play Music?

Multimedia: video

- video: sequence of images displayed at constant rate
  - e.g., 24 images/sec
- digital image: array of pixels
  - each pixel represented by bits
- coding: use redundancy *within* and *between* images to decrease # bits used to encode image
  - spatial (within image)
  - temporal (from one image to next)

spatial coding example: instead of sending *N* values of same color (all purple), send only two values: color value (*purple*) *and number of repeated values* (N)

frame *i*

temporal coding example: instead of sending complete frame at i+1, send only differences from frame i

frame *i+1*

Multimedia: video

- CBR: (constant bit rate): video encoding rate fixed
- VBR: (variable bit rate): video encoding rate changes as amount of spatial, temporal coding changes
- examples:
  - MPEG 1 (CD-ROM) 1.5 Mbps
  - MPEG2 (DVD) 3-6 Mbps
  - MPEG4 (often used in Internet, < 1 Mbps)
  - H.264
  - H.265

spatial coding example: instead of sending *N* values of same color (all purple), send only two values: color value (*purple*) *and number of repeated values* (N)

frame *i*

temporal coding example: instead of sending complete frame at i+1, send only differences from frame i

frame *i+1*

Multimedia networking: 3 application types

- *streaming, stored* audio, video
  - *streaming:* can begin playout before downloading entire file
  - *stored (at server):* can transmit faster than audio/video will be rendered (implies storing/buffering at client)
  - e.g., YouTube, Netflix, Hulu
- *conversational* voice/video over IP
  - interactive nature of human-to-human conversation limits delay tolerance
  - e.g., Skype
- *streaming live* audio, video
  - e.g., live sporting event (futbol)

Multimedia networking: outline

9.1 multimedia networking applications
9.2 streaming *stored* video
9.3 voice-over-IP

Streaming stored video:



Cumulative data
1. video recorded (e.g., 30 frames/sec)
2. video sent
network delay (fixed in this example)
3. video received, played out at client (30 frames/sec)
time

streaming: at this time, client playing out early part of video, while server still sending later part of video

Streaming stored video: challenges

- continuous playout constraint: once client playout begins, playback must match original timing
  - … but network delays are variable (jitter), so will need client-side buffer to match playout requirements
- other challenges:
  - client interactivity: pause, fast-forward, rewind, jump through video
  - video packets may be lost, retransmitted

Streaming stored video: revisited



- *client-side buffering and playout delay:* compensate for network-added delay, delay jitter

Client-side buffering, playout



Client-side buffering, playout



1. Initial fill of buffer until playout begins at t_p
2. playout begins at $t_{p,}$
3. buffer fill level varies over time as fill rate x(t) varies and playout rate r is constant

Client-side buffering, playout



playout buffering: average fill rate ($\bar{x}$), playout rate (r):

- $\bar{x} < r$: buffer eventually empties (causing freezing of video playout until buffer again fills)
- $\bar{x} > r$: buffer will not empty, provided initial playout delay is large enough to absorb variability in x(t)
  - *initial playout delay tradeoff:* buffer starvation less likely with larger delay, but larger delay until user begins watching

Streaming multimedia: UDP

- server sends at rate appropriate for client
  - often: send rate = encoding rate = constant rate
  - transmission rate can be oblivious to congestion levels
- error recovery: application-level, time permitting
- RTP [RFC 2326]: multimedia payload types
- UDP may *not* go through firewalls

Streaming multimedia: HTTP

- multimedia file retrieved via HTTP GET
- send at maximum possible rate under TCP



- fill rate fluctuates due to TCP congestion control, retransmissions (in-order delivery)
- larger playout delay: smooth TCP delivery rate
- HTTP/TCP passes more easily through firewalls

Multimedia networking: outline

Voice-over-IP (VoIP)

- *VoIP end-end-delay requirement*: needed to maintain "conversational" aspect
  - higher delays noticeable, impair interactivity
  - < 150 msec: good
  - > 400 msec bad
  - includes application-level (packetization, playout), network delays
- *session initialization:* how does callee advertise IP address, port number, encoding algorithms?
- *value-added services:* call forwarding, screening, recording
- *emergency services:* 911

VoIP characteristics

- speaker' s audio: alternating talk spurts, silent periods.
  - 64 kbps during talk spurt
  - pkts generated only during talk spurts
  - 20 msec chunks at 8 Kbytes/sec: 160 bytes of data
- application-layer header added to each chunk
- chunk+header encapsulated into UDP or TCP segment
- application sends segment into socket every 20 msec during talkspurt

VoIP: packet loss, delay

- *network loss:* IP datagram lost due to network congestion (router buffer overflow)
- *delay loss:* IP datagram arrives too late for playout at receiver
  - delays: processing, queueing in network; end-system (sender, receiver) delays
  - typical maximum tolerable delay: 400 ms
- *loss tolerance:* depending on voice encoding, loss concealment, packet loss rates between 1% and 10% can be tolerated

Delay jitter


Cumulative data
constant bit rate transmission
variable network delay (jitter)
client reception
buffered data
constant bit rate playout at client
client playout delay
time

- end-to-end delays of two consecutive packets: difference can be more or less than 20 msec (transmission time difference)

VoIP: fixed playout delay

- receiver attempts to playout each chunk exactly *q* msecs after chunk was generated.
  - chunk has time stamp *t:* play out chunk at *t+q*
  - chunk arrives after *t+q*: data arrives too late for playout: data "lost"
- tradeoff in choosing *q*:
  - *large q:* less packet loss
  - *small q:* better interactive experience

VoIP: fixed playout delay

- sender generates packets every 20 msec during talk spurt.
- first packet received at time r
- first playout schedule: begins at p
- second playout schedule: begins at p'



VoiP: recovery from packet loss (1)

Challenge: recover from packet loss given small tolerable delay between original transmission and playout

- each ACK/NAK takes ~ one RTT
- alternative: *Forward Error Correction (FEC)*
  - send enough bits to allow recovery without retransmission (recall two-dimensional parity in Ch. 5)

simple FEC

- for every group of *n* chunks, create redundant chunk by exclusive OR-ing *n* original chunks
- send *n+1* chunks, increasing bandwidth by factor *1/n*
- can reconstruct original *n* chunks if at most one lost chunk from *n+1* chunks, with playout delay

VoiP: recovery from packet loss (2)

another FEC scheme:

- "piggyback lower quality stream"
- send lower resolution audio stream as redundant information
- e.g., nominal stream PCM at 64 kbps and redundant stream GSM at 13 kbps



- non-consecutive loss: receiver can conceal loss
- generalization: can also append (n-1)st and (n-2)nd low-bit rate chunk

VoiP: recovery from packet loss (3)



interleaving to conceal loss:

- audio chunks divided into smaller units, e.g. four 5 msec units per 20 msec audio chunk
- packet contains small units from different chunks

- if packet lost, still have *most* of every original chunk
- no redundancy overhead, but increases playout delay

Voice-over-IP: Skype

- proprietary application-layer protocol (inferred via reverse engineering)
  - encrypted msgs
- P2P components:
  - clients: Skype peers connect directly to each other for VoIP call
  - super nodes (SN): Skype peers with special functions
  - overlay network: among SNs to locate SCs
  - login server



P2P voice-over-IP: Skype

Skype client operation:

1. joins Skype network by contacting SN (IP address cached) using TCP
2. logs-in (username, password) to centralized Skype login server
3. obtains IP address for callee from SN, SN overlay
   - or client buddy list
4. initiate call directly to callee



Skype: peers as relays

- *problem:* both Alice, Bob are behind "NATs"
  - NAT prevents outside peer from initiating connection to insider peer
  - inside peer *can* initiate connection to outside
- relay solution: Alice, Bob maintain open connection to their SNs
  - Alice signals her SN to connect to Bob
  - Alice' s SN connects to Bob' s SN
  - Bob' s SN connects to Bob over open connection Bob initially initiated to his SN



Multimedia networking: Done!

Chapter 9 is complete!

That's all folks!!!!!!