Game Library & Backlog Tracker

API endpoint definitions | M223 individual project

Main application functions

1. User registration and login. 2. Browse and manage games. 3. Browse and manage genres. 4. Add, update, and remove games from a personal library. 5. Track game progress and ratings.

Endpoint overview

Endpoint URL	HTTP method	Description	Required data
/auth/register	POST	Create a user account.	Body: username, password
/auth/login	POST	Authenticate and receive a JWT.	Body: username, password
/games	GET	List available games.	None
/games/{id}	GET	Retrieve one game.	Path: game ID
/games	POST	Create a game record.	Body: title, description, releaseDate, genreId
/games/{id}	PUT	Update a game record.	Path: game ID; body: title, description, releaseDate, genreId
/games/{id}	DELETE	Delete a game record.	Path: game ID
/genres	GET	List available genres.	None
/genres	POST	Create a genre.	Body: name
/genres/{id}	PUT	Rename a genre.	Path: genre ID; body: name
/genres/{id}	DELETE	Delete a genre.	Path: genre ID
/library	GET	List the logged-in user’s library entries.	Authorization: Bearer JWT
/library	POST	Add a game to the user’s library.	Authorization: Bearer JWT; body: gameId, status, rating (optional)
/library/{id}	PUT	Update a library entry’s status or rating.	Authorization: Bearer JWT; path: library entry ID; body: status, rating (optional)
/library/{id}	DELETE	Remove a game from the user’s library.	Authorization: Bearer JWT; path: library entry ID

Data conventions

ApplicationUser: username, passwordHash. Game: title, description, releaseDate, genreId. Genre: name. LibraryEntry: userId, gameId, status, rating. Allowed status values: NOT_STARTED, PLAYING, COMPLETED, DROPPED. Rating: 1–10, optional. Playtime tracking is intentionally excluded.