Car Brand & Colour Classification in Tashkent

CSAI-3210 Introduction to AI — Midterm report, Fall 2026, Webster University in Tashkent

Repository: https://github.com/FirdavsJurakulov/CSAI_midterm (final commit tagged `midterm`)

1. Team, repository and contributions

Team: Firdavs Jurakulov (individual submission). All work was done by me: photo collection (two street sessions, 26 and 27 Oct), labelling and checking of every car including the ambiguous ones, choice of architecture, training runs, evaluation, test-day rehearsal and this report, with the AI assistance described in Section 7.

The repository contains all code (crop extraction, Commons crawler, label merge, training of both models, evaluation, inference), the label file, all crops and masks, and all weights.

2. Data

Brands. 41 brand labels: the 24 brands named in the brief, plus Chevrolet's local predecessor Daewoo, Lada, and the Chinese brands I actually met in the streets and car parks (Aion, Deepal, AITO, Voyah, Dongfeng, Tank, Xiaomi, GAC, Denza, Seres, Stelato, Avatr, Venucia, GWM) and a few others (Porsche, Tesla, Genesis). Brand = the badge, named in English (Lixiang → Li Auto). 30 brands have 76–439 cars each; the last 11 have only 1–6 cars (own photos only) and are effectively unseen by the model.

Sources. (1) **Own photos**: 192 phone photos of Tashkent streets and car parks taken by me on 26–27 Oct (day and evening, all angles), 433 labelled cars. The second session targeted new residential complexes and dealer streets to find Chinese brands. (2) **Wikimedia Commons** (CC BY / CC BY-SA, public domain): 4,893 cars downloaded with my crawler `scripts/fetch_commons.py` via the public MediaWiki API, one car per photo; author, licence and URL of every file are kept in `data/external/*/metadata.csv`. I used Commons rather than Stanford Cars / CompCars because those sets contain almost none of the 2022–2026 Chinese models that dominate Tashkent today.

Labelling. Each photo goes through the detector (`scripts/extract_crops.py`), which saves one crop + mask per car. Own crops were labelled by hand (brand from the badge; colour as a person would name it in daylight); crops with an unreadable badge were shown as a contact sheet and labelled by me (48 ambiguous cars on 27 Oct), unidentifiable / tiny / blurry cars were left out, as were crops showing faces. Commons crops take the brand from the Commons category; colour from the file's colour category when present (2,351 Commons crops have no colour label and are used for brand only). Noisy Commons files (interiors, logos, old joint-venture models, trucks) are removed by filename rules and by detector class/confidence. Labels: `data/labels.csv`, one line per car.

Split. Grouped, leakage-free: own photos are split by *source photo* (30% of photos to validation, so two crops of one photo never sit on both sides); Commons by file (15%). Result: 4,468 train / 858 validation crops (123 own). Final test-day models are retrained on train + validation.

Brand	Own	Commons	Total
Chevrolet	245	194	439
BYD	53	167	220
BMW	5	196	201
Kia	14	187	201
Changan	9	188	197
Volkswagen	2	190	192
Zeekr	8	184	192
Hyundai	2	188	190
Leapmotor	11	178	189
Li Auto	7	181	188
Aion	1	184	185

Brand	Own	Commons	Total
Dongfeng	3	182	185
Nissan	1	183	184
Mercedes-Benz	0	183	183
Exeed	0	183	183
Geely	0	182	182
Daewoo	15	165	180
Toyota	0	178	178
Hongqi	6	164	170
Jetour	1	166	167
Voyah	3	163	166
AITO	6	159	165

Brand	Own	Commons	Total
Haval	0	163	163
Deepal	4	141	145
Chery	6	121	127
Lada	3	120	123
JAC	0	123	123
Omoda	0	117	117
Tank	0	87	87
Jaecoo	0	76	76
Own only: Xiaomi 6, Porsche 5, GAC 4, Tesla, Stelato, Denza, GWM, Seres 2 each, Avatr, Genesis, Venucia 1 each			
Total	**433**	**4,893**	**5,326**

Colour	Own	Commons	Total
white	192	910	1,102
grey/silver	68	503	571
black	147	386	533
blue	6	334	340
red	7	182	189
brown/beige	7	78	85
yellow/orange	0	85	85
green	6	64	70
no label	0	2,351	2,351



BYD / black (own)




Chevrolet / white (own)



Zeekr / black (own)



Leapmotor / black (own)



Li Auto / black (own)



Hongqi / black (own)



Chery / black (own)



Changan / white (own)



AITO / black (own)



Daewoo / red (own)



Kia / black (own)



Xiaomi / grey (own)



Haval / white (commons)



Jetour / grey (commons)




Geely / white (commons)



Exeed / - (commons)

Sample crops produced by the detector, with their labels (own Tashkent photos and Wikimedia Commons).

3. Architecture



Multi-car strategy: detector + per-car classifier. Scoring is per car and every extra prediction costs a point, so the pipeline needs exactly one prediction per car and explicit control over which cars are reported. A COCO-pretrained YOLO11s-seg (used as-is, not a car-brand model) finds the cars; small or low-confidence detections are dropped (thresholds in `configs/default.yaml`).

Brand: DINOv2 ViT-S/14 (self-supervised ViT, 21.6 M parameters), trained by me in two stages. Crops are letterboxed (padded, not centre-cropped, because cars are wide) to 224 px. Embedding = CLS token concatenated with the mean of the patch tokens (768-d), the standard DINOv2 linear-probe recipe. *Stage A*: backbone frozen, features cached once (original + mirrored), only the MLP head is trained (0.83 M parameters, 13 s). *Stage B*: the last 4 of 12 transformer blocks + final norm are fine-tuned together with the head (7.9 M trainable parameters) on augmented images; the frozen first 8 blocks run without gradients so this fits a 4 GB GPU. Stage B replaces stage A only if it is better on validation — it is: 0.718 vs 0.668 overall, 0.772 vs 0.748 on own photos.

Colour: my own non-neural model. DINOv2 is trained with colour-jitter augmentation, so its features are partly colour-blind; a separate model on explicit colour statistics is more reliable and easy to explain. Only pixels inside the (eroded) YOLO mask are used, so road, sky and other cars do not leak in. Windows, tyres and shadows are dark in every car, so features are computed twice — on the whole mask and on its lower-middle band (doors, mostly paint): saturation-weighted hue histogram of coloured pixels (18 bins), saturation and value histograms (8+8), colourful-pixel fraction, Lab mean/std/percentiles. A HistGradientBoosting classifier (class-balanced, own photos weighted ×3) maps the 100 features to the 8 colours.

Size and speed. YOLO11s-seg 10.1 M + DINOv2 21.6 M + head 0.8 M parameters; colour model ≈ 10 MB of trees. About 1 s per photo on a GTX 1650 laptop GPU, a few seconds on CPU, fully offline (all weights in the repository).

Why this design. DINOv2 features are strong for fine-grained, few-shot recognition, which suits ~100–200 cars per brand; ViT-S fits my 4 GB GPU. Stage A gives a working baseline in seconds; stage B is the improvement that has to beat it. I also compared heads on the same frozen features (table below): the MLP clearly beats logistic regression, kNN and gradient boosting (XGBoost, CatBoost, LightGBM). Trees split on one feature at a time, which suits hand-made tabular features (I do use them for colour) but not dense 768-d embeddings in which the information is spread over many dimensions.

Head on frozen DINOv2 features (26 Oct split, 788 val crops)	Val acc.	Own photos	Macro-F1	Train time
MLP head (ours)	**0.666**	0.774	**0.651**	11 s
LightGBM	0.543	0.736	0.531	282 s
XGBoost	0.524	0.717	0.508	211 s
CatBoost	0.520	0.774	0.507	297 s
Logistic regression	0.494	0.717	0.478	2 s
kNN (k = 10, cosine)	0.473	0.717	0.461	0 s


4. Training

- **Loss:** cross-entropy with label smoothing 0.1, weighted per sample: inverse square root of the class frequency (rare brands are not drowned out) × 3 for own Tashkent photos (they match test conditions).
- **Stage A:** AdamW, lr 1e-3, weight decay 0.05, cosine schedule, 100 epochs, batch 256, dropout 0.5, hidden 1024. Augmentation: horizontal mirror (cached). 13 s after a one-off 3 min feature extraction.
- **Stage B:** AdamW, lr 2e-5 for the backbone blocks and 3e-4 for the head (warm-started from stage A), 1 warm-up epoch then cosine, 8 epochs, batch 32, mixed precision (fp16). Augmentation: random 85–100 % sub-crop (detector box jitter), mirror, perspective (p = 0.3), colour jitter, 5 % greyscale, Gaussian blur (p = 0.3, phone photos of a screen are soft). ≈ 5 min per epoch on the GTX 1650 (GPU-bound); validation accuracy by epoch 0.579, 0.634, 0.653, 0.657, 0.718. Training was stopped after epoch 5 of 8 because of the deadline (≈ 27 min); the epoch-5 checkpoint (trained on the train split only) is the test-day brand model.
- **Colour:** HistGradientBoosting, 400 iterations, lr 0.05, 31 leaves, L2 1.0, balanced classes, own photos ×3. Trains in seconds.
- **Hardware:** laptop, NVIDIA GTX 1650 4 GB, 16 GB RAM, Windows 11, Python 3.11, PyTorch 2.11 + CUDA 12.6, timm, Ultralytics.

5. Evaluation

Validation (858 crops, 123 own)	All	Own Tashkent photos	Commons
Brand, stage A (frozen + MLP)	0.668	0.748	0.654
Brand, stage B (fine-tuned last 4 blocks) — used on test day	**0.718**	**0.772**	**0.709**
Colour (504 colour-labelled crops)	0.780	0.732	0.795

Colour per class (F1): red 0.92, green 0.89, white 0.88, black 0.80, yellow 0.72, blue 0.66, grey 0.60, brown 0.30. Grey/silver is confused with white (bright reflections) and with black (shadows, evening photos); brown/beige is rare (85 cars) and sits between grey, white and yellow.



Row-normalised brand confusion matrix, stage A, validation split (numbers are counts).

Error analysis

Best brands (F1 ≥ 0.85): BMW, Tank, Zeekr, Deepal, Li Auto, Jaecoo — each has a very distinctive front (kidney grille, boxy Tank body, Zeekr light bar, Li Auto's full-width lamp). **Classic pairs** are confused as expected: Daewoo ↔ Chevrolet (the same Nexia/Matiz/Gentra bodies with a different badge — the badge is a few pixels at 224 px), Kia ↔ Hyundai (shared platforms), Mercedes ↔ Daewoo/Chevrolet in old Commons photos. On own photos the largest error is Daewoo → Chevrolet. Toyota, Hyundai and Kia (F1 ≈ 0.40) suffer from very different model generations under one badge.

Chinese brands. Half of the test is Chinese brands, and they are the hardest part. (1) *Group families look alike*: Chery, Jetour, Exeed, Omoda and Jaecoo are all Chery Group; Haval and Tank are Great Wall; Changan, Deepal and Avatr are Changan; Dongfeng and Voyah; Geely and Zeekr. Shared platforms, lamps and proportions make Haval → Jetour, Geely → Dongfeng and Chery → Jetour/Exeed the most frequent Chinese confusions; Haval (0.38), Geely (0.40), Chery (0.43) and JAC (0.29) are the weakest brands. (2) *Generic modern SUV design*: from the side or rear, many 2023–2025 crossovers differ mainly in the badge and lamp signature. (3) *Data*: most Chinese-brand examples come from Commons (photographed in China, often older facelifts), while my own photos contain only 1–11 cars for most Chinese brands and none for Geely, Haval, JAC, Exeed, Omoda, Jaecoo, Tank. My second photo session (27 Oct) targeted this gap and added the first local examples of Zeekr, Leapmotor, Li Auto, AITO, Hongqi, Chery and Xiaomi. (4) Brands seen only 1–6 times (Xiaomi, GAC, Denza, Stelato, Avatr…) cannot be learnt yet; on test day they will receive a wrong brand but can still earn the colour share. Stage B targets (1)–(2): fine-tuning lets the backbone attend to badges, grilles and lamp shapes instead of generic body shape.

Own phone-camera tests. [fill in after the rehearsal: N photos of cars shown on a screen, photographed with the phone, transferred and predicted; time per photo; how many cars right for brand / colour; extra predictions]. On four of my street photos the full pipeline took 0.5–1.8 s per photo.

6. How to run on test day

```
git clone https://github.com/FirdavsJurakulov/CSAI_midterm.git && cd CSAI_midterm
python -m venv .venv && .venv\Scripts\activate && pip install -r requirements.txt   (done before class)
python -m carbrand.predict incoming/photo.jpg
```

1. Photograph the screen with the phone; send the photo to the laptop (Telegram Saved Messages / cable) into `incoming/`.
2. Run the command above; it prints e.g. `photo.jpg: BYD white; Chevrolet grey` (cars left to right) in about 1–2 s and saves an annotated copy in `runs/predict/`.
3. Copy the printed list to the answer sheet. No internet is needed: every weight file is loaded from `weights/`.

7. Reflection and AI-use statement

With two more weeks I would (1) photograph a few hundred more cars per Chinese brand in Tashkent, especially Haval, Geely, Chery, Jetour, Exeed, Omoda/Jaecoo and JAC, for which I have no or almost no own photos, and the newer brands (Xiaomi, GAC, Denza, Avatr); (2) fine-tune at 336 px or train a second-stage classifier on a zoomed badge/grille region so the badge becomes readable; (3) tune the detector thresholds on a set of real multi-car test-style photos taken off a screen; (4) label colour for the Commons crops that have none and collect more beige/brown and grey cars.

AI use. I used **Claude Code (Anthropic)** as a coding assistant throughout the project: to propose and discuss the architecture, write and debug the Python code (crop extraction, Wikimedia Commons crawler, training, colour model, inference script), suggest first-pass labels for my own crops (every label was checked and the 48 ambiguous cars were labelled by me), run the training, and draft this report, which I then edited. All design

decisions, data collection, final labels and the results were reviewed by me, and I can explain every part of the pipeline. No AI tools are used during the live test. [edit if you used other tools]

Data credit: Wikimedia Commons contributors (individual authors and licences listed per file in `data/external/*/metadata.csv`). Pretrained weights: DINOv2 (Oquab et al., 2023, Meta AI; via timm), YOLO11 (Ultralytics, COCO).