

CHAPTER 29 — MAGNETIC FIELDS DUE TO CURRENTS

MCQ Practice Bank | 40 Conceptual + 20 Numerical | Answers & Explanations Included

PART A — CONCEPTUAL MCQs (40 Questions)

Section 1: Biot–Savart Law (Q1–Q8)

Q1

A moving charged particle produces a magnetic field around itself. This fundamental observation is the basis of which combined field of study?

(A) Electrostatics

(B) Electromagnetism

(C) Nuclear physics

(D) Optics

Ans:
B

Electromagnetism is defined as the combined study of electric and magnetic effects. The relationship between moving charges and magnetic fields is its central feature.

Q2

In the Biot–Savart law, $d\vec{B} = (\mu_0/4\pi)(i d\vec{s} \times \hat{r})/r^2$, what does $\hat{r}$ represent?

(A) The magnetic field vector

(B) A unit vector pointing from element to point P

(C) The current direction vector

(D) The perpendicular distance

Ans:
B

$\hat{r}$ is the unit vector directed from the current-length element $i d\vec{s}$ toward the field point P. Its direction determines the direction of $d\vec{B}$ via the cross product.

Q3

Why is summing magnetic field contributions from current elements more complex than summing electric field contributions from charge elements?

(A) Magnetic fields are stronger

(B) The permeability constant is involved

(C) Current-length element $i d\vec{s}$ is a vector, while charge element dq is a scalar

(D) Magnetic fields obey superposition differently

Ans:
C

A charge element dq is a scalar, making integration straightforward. A current-length element $i d\vec{s}$ is a vector (product of scalar current and vector $d\vec{s}$), making the cross product and integration more complex.

Q4

The magnetic field lines produced by a long straight current-carrying wire are:

(A) Straight lines parallel to the wire

(B) Straight lines perpendicular to the wire

(C) Concentric circles centered on the wire

(D) Ellipses around the wire

Ans: C	<i>As confirmed by iron filing experiments (Fig. 29-3), the magnetic field lines of a long straight wire form concentric circles centered on the wire.</i>
-------------------------	--

Q5	For the Biot–Savart law, if angle θ between $i \, d\vec{s}$ and $\hat{r}$ is 0° , the contribution dB is:
-----------	---

- (A) Maximum
(C) Zero

- (B) Half of maximum
(D) Undefined

Ans: C	<i>$dB = (\mu_0/4\pi)(i \, ds \sin\theta)/r^2$. When $\theta = 0^\circ$, $\sin\theta = 0$, so $dB = 0$. Straight sections pointing directly at P contribute nothing to the field at P.</i>
-------------------------	--

Q6	In Sample Problem 29-1 (circular arc with two straight sections), why do the two straight sections contribute zero magnetic field at center C ?
-----------	---

- (A) The current is too small
(C) They are too far from C

- (B) Their extensions pass through C ($\theta = 0^\circ$ or 180°)
(D) They carry current in opposite directions

Ans: B	<i>For section 1, angle $\theta = 0^\circ$ between $d\vec{s}$ and $\hat{r}$, so $\sin 0^\circ = 0$. For section 2, $\theta = 180^\circ$, so $\sin 180^\circ = 0$. Both contributions vanish.</i>
-------------------------	--

Q7	The magnetic field at the center of a full circular loop of radius R carrying current i is:
-----------	---

- (A) $\mu_0 i / (4\pi R)$
(C) $\mu_0 i / (2R)$

- (B) $\mu_0 i / (2\pi R)$
(D) $\mu_0 i \pi / (4R)$

Ans: C	<i>For a circular arc, $B = \mu_0 i \phi / (4\pi R)$. For a full circle $\phi = 2\pi$, giving $B = \mu_0 i (2\pi) / (4\pi R) = \mu_0 i / (2R)$.</i>
-------------------------	--

Q8	A semi-infinite straight wire produces a magnetic field at a perpendicular point of:
-----------	--

- (A) $\mu_0 i / (2\pi R)$
(C) $\mu_0 i / (\pi R)$

- (B) $\mu_0 i / (4\pi R)$
(D) $2\mu_0 i / (\pi R)$

Ans: B	<i>Integrating the Biot–Savart law from 0 to ∞ (instead of $-\infty$ to $+\infty$) gives exactly half the infinite wire result: $B = \mu_0 i / (4\pi R)$.</i>
-------------------------	---

Section 2: Force Between Parallel Currents (Q9–Q14)

Q9	Two long parallel wires carry currents in the same direction. The force between them is:
-----------	--

- (A) Repulsive

- (B) Attractive

(C) Zero

(D) Alternating

Ans:
B *Parallel currents in the same direction produce magnetic fields that create an attractive force between the wires. This is a fundamental result from $\vec{F} = i\vec{L} \times \vec{B}$.*

Q10 Two long parallel wires carry currents in opposite directions. The force between them is:

(A) Attractive

(B) Repulsive

(C) Zero

(D) Perpendicular to both wires

Ans:
B *Anti-parallel currents create repulsive forces. Each wire lies in the other's magnetic field, and the cross product gives a force directed away from the other wire.*

Q11 In the force formula $F_{ba} = \mu_0 L i_a i_b / (2\pi d)$, what does 'd' represent?

(A) Diameter of the wire

(B) Length of wire segment

(C) Perpendicular separation between wires

(D) Distance to field point P

Ans:
C *d is the perpendicular distance separating the two parallel wires. The force decreases as the separation increases.*

Q12 In a rail gun, the conducting fuse between the rails is immediately vaporized by the current. The projectile is then accelerated by:

(A) Electrostatic force

(B) Gravitational force

(C) Magnetic force on the conducting gas replacing the fuse

(D) Thermal expansion

Ans:
C *After the fuse vaporizes, it becomes a conducting gas. The magnetic field between the rails (due to current in rails) exerts a force $\vec{F} = i\vec{L} \times \vec{B}$ on this gas, which pushes the projectile out along the rails.*

Q13 To find the force on wire b due to wire a, the correct procedure is:

(A) Find the force directly using Coulomb's law equivalent

(B) First find the field due to wire b at wire a, then find force

(C) First find the field due to wire a at wire b, then find force on b

(D) Average the fields of both wires

Ans:
C *The correct method: (1) Calculate the magnetic field B_a produced by wire a at the location of wire b, then (2) calculate the force on wire b using $\vec{F}_{ba} = i_b \vec{L} \times \vec{B}_a$.*

Q14 A rail gun can accelerate a projectile to approximately:

(A) 1 km/s in 10 s

(B) 10 km/s in 1 ms

(C) 100 m/s in 1 s

(D) 5 km/s in 1 s

Ans:

B

According to the text, the magnetic force accelerates the projectile by up to $5 \times 10^6 g$ and launches it at about 10 km/s, all within 1 millisecond.

Section 3: Ampere's Law (Q15–Q22)

Q15	Ampere's Law states: $\oint \vec{B} \cdot d\vec{s} = \mu_0 i_{\text{enc}}$. The line integral is evaluated:	
	(A) Over an open surface	(B) Around a closed loop called the Amperian loop
	(C) Along the wire carrying current	(D) Along a straight path from start to end
Ans: B	<i>The integral is a closed line integral (loop integral) around a chosen closed path called the Amperian loop. The choice of this loop is strategic.</i>	
Q16	When using Ampere's law, currents that pass OUTSIDE the Amperian loop:	
	(A) Contribute fully to i_{enc}	(B) Contribute half to i_{enc}
	(C) Contribute zero to i_{enc} (they cancel)	(D) Are always positive
Ans: C	<i>Only the NET current enclosed (passing through) the Amperian loop surface matters. Currents outside the loop produce equal and opposite contributions when integrated around the loop, summing to zero.</i>	
Q17	Using the right-hand rule for Ampere's law: if you curl your right hand around the Amperian loop in the direction of integration, a current parallel to your outstretched thumb is assigned:	
	(A) Negative sign	(B) Positive sign
	(C) Zero sign	(D) Imaginary sign
Ans: B	<i>The sign convention: curl fingers in direction of integration; outstretched thumb direction = positive current. Opposite direction = negative current. So $i_{\text{enc}} = i_1 - i_2$ if i_1 is positive.</i>	
Q18	For a long straight wire using Ampere's law with a circular Amperian loop of radius $r > R$ (outside the wire), the result for B is:	
	(A) $B = \mu_0 i / (4\pi r)$	(B) $B = \mu_0 i / (2\pi r)$
	(C) $B = \mu_0 i r / (2\pi R^2)$	(D) $B = 0$
Ans: B	<i>For $r > R$, $B(2\pi r) = \mu_0 i_{\text{enc}} = \mu_0 i$, giving $B = \mu_0 i / (2\pi r)$. This matches the Biot–Savart result, validating Ampere's law.</i>	
Q19	For a long straight wire using Ampere's law at a point INSIDE ($r < R$), the enclosed current is:	
	(A) The total current i	(B) Zero
	(C) $i(\pi r^2 / \pi R^2) = i(r^2 / R^2)$	(D) $i / (2\pi)$

Ans: C	<i>Since the current is uniformly distributed, the enclosed current is proportional to the enclosed area: $i_{enc} = i \times (\pi r^2 / \pi R^2) = ir^2/R^2$.</i>
-------------------------	---

Q20	Inside a long straight wire of radius R carrying current i , the magnetic field B varies with distance r from the center as:
------------	--

- (A) $B \propto 1/r$
(C) $B \propto r$

- (B) B is constant
(D) $B \propto r^2$

Ans: C	<i>From $B = (\mu_0 i / 2\pi R^2) r$, we see B is directly proportional to r inside the wire. It increases linearly from zero at the center to maximum at the wire surface.</i>
-------------------------	--

Q21	Ampere's law is most easily applied (rather than Biot–Savart) when the current distribution has:
------------	--

- (A) Complex asymmetric geometry
(C) Very small current

- (B) High symmetry (straight wire, solenoid, toroid)
(D) Alternating current

Ans: B	<i>Ampere's law requires a strategic choice of Amperian loop that exploits symmetry to make B constant (or zero) along each section of the loop, simplifying the integral $\oint \mathbf{B} \cdot d\mathbf{s}$.</i>
-------------------------	---

Q22	In the hollow cylinder problem (inner radius a , outer radius b), for a point at radius r where $a < r < b$, the field is found using:
------------	--

- (A) $B = \mu_0 i / (2\pi r)$ directly
(C) $B = \mu_0 i$ in formula

- (B) The integral $i_{enc} = \int J dA$ from a to r
(D) Zero since it's inside a conductor

Ans: B	<i>The current density $J = cr^2$ varies with r, so i_{enc} must be found by integrating J over the annular area from a to r: $i_{enc} = \int_a^r cr^2 (2\pi r dr) = \pi c(r^4 - a^4)/2$.</i>
-------------------------	--

Section 4: Solenoids and Toroids (Q23–Q30)

Q23	A solenoid is described as:
------------	-----------------------------

- (A) A single circular loop of wire
(C) Two parallel wires close together

- (B) A long tightly wound helical coil of wire
(D) A wire bent into a toroidal shape

Ans: B	<i>A solenoid is a long, tightly wound helical coil of wire. When the length $\gg$ diameter, the interior field is strong, uniform, and axial; exterior field ≈ 0.</i>
-------------------------	--

Q24	For an ideal solenoid, the magnetic field OUTSIDE is approximately:	
	(A) Equal to the interior field (C) Half the interior field	(B) Twice the interior field (D) Approximately zero
Ans: D	<i>For an ideal solenoid (length $\gg$ diameter), the external magnetic field is considered zero. All field is confined inside. Real solenoids have weak external fields.</i>	
Q25	The formula $B = \mu_0 in$ for a solenoid, where n is:	
	(A) Number of total turns N (C) Number of layers	(B) Number of turns per unit length (N/L) (D) Current in each turn
Ans: B	<i>n is defined as the number of turns per unit length (N/L), with units turns/meter. This is different from the total turns N. $B = \mu_0 in$ is independent of the solenoid's diameter.</i>	
Q26	When deriving $B = \mu_0 in$ using Ampere's law with a rectangular loop, which segment of the loop contributes the most to $\oint \mathbf{B} \cdot d\mathbf{s}$?	
	(A) The outer side (outside solenoid) (C) The inner side ab (inside solenoid, parallel to axis)	(B) The two sides perpendicular to axis (D) All four sides equally
Ans: C	<i>Outside: $B \approx 0$ (no contribution). Perpendicular sides: $B \perp d\mathbf{s}$ so $\cos 90^\circ = 0$ (no contribution). Only the inner segment ab parallel to B contributes: $B \cdot h = \mu_0 in h \rightarrow B = \mu_0 in$.</i>	
Q27	The magnetic field of a solenoid does NOT depend on:	
	(A) The current i through the wire (C) The diameter of the solenoid	(B) The number of turns per unit length n (D) The permeability constant μ_0
Ans: C	<i>$B = \mu_0 in$ contains only μ_0, i, and n. The solenoid diameter does not appear in the formula. This is why adding identical layers simply multiplies n.</i>	
Q28	A toroid differs from a solenoid in that the toroid:	
	(A) Has fewer turns (C) Has a stronger field	(B) Is bent into a closed donut (torus) shape (D) Uses less current
Ans: B	<i>A toroid is a solenoid that has been bent into a closed ring (torus/donut shape). This configuration confines the magnetic field entirely within the torus.</i>	

Q29

Inside a toroid, the magnetic field:

(A) Is uniform (constant with r)(B) Decreases as $1/r$ (stronger near inner edge)(C) Increases with r (stronger near outer edge)

(D) Is zero

Ans:
B

$B = \mu_0 i N / (2\pi r)$. Since $B \propto 1/r$, the field is stronger near the inner radius and weaker near the outer radius of the toroid. Unlike a solenoid, the field is NOT uniform.

Q30

Outside the toroid (and in its central hole), the magnetic field is:

(A) Equal to the interior field

(B) Half the interior field

(C) Zero

(D) Twice the interior field

Ans:
C

For an Amperian loop outside the toroid, all N windings pass through the loop, but half go one way and half the other — they cancel. $i_{\text{enc}} = 0$, so $B = 0$. Similarly for the central hole.

Section 5: Mixed Conceptual (Q31–Q40)

Q31	μ_0 (permeability of free space) has the value: (A) $8.85 \times 10^{-12} \text{ T}\cdot\text{m/A}$ (C) $4\pi \times 10^{-7} \text{ N/A}^2$	(B) $4\pi \times 10^{-7} \text{ T}\cdot\text{m/A}$ (D) Both B and C are equivalent correct values
Ans: D	$\mu_0 = 4\pi \times 10^{-7} \text{ T}\cdot\text{m/A} = 4\pi \times 10^{-7} \text{ N/A}^2 \approx 1.257 \times 10^{-6} \text{ T}\cdot\text{m/A}$. These are equivalent expressions of the same constant.	
Q32	The right-hand rule for determining the direction of B around a wire states: (A) Point thumb in B direction; fingers show current (C) Grasp wire with thumb in current direction; fingers curl in B direction	(B) Point fingers in B direction; thumb shows current (D) Hold wire with palm facing B
Ans: C	Right-hand rule: grasp the wire with your right hand, extended thumb pointing in the direction of current flow. Your curled fingers then point in the direction of the magnetic field lines.	
Q33	The Biot–Savart law for magnetic fields is analogous to which law for electric fields? (A) Gauss's law (C) Coulomb's law	(B) Faraday's law (D) Lenz's law
Ans: C	Both laws describe the field created by a source: Coulomb's law gives E due to a charge element dq , while Biot–Savart gives dB due to a current element $i \, ds$. Both have $1/r^2$ dependence.	
Q34	If the current in a long straight wire is doubled, the magnetic field at a fixed perpendicular distance R : (A) Remains the same (C) Quadruples	(B) Doubles (D) Halves
Ans: B	$B = \mu_0 i / (2\pi R)$. Since B is directly proportional to i , doubling the current doubles the magnetic field at any fixed perpendicular distance.	
Q35	If the perpendicular distance from a long straight wire is tripled (keeping current constant), the magnetic field: (A) Triples (C) Decreases to $1/9$	(B) Decreases to $1/3$ (D) Remains the same
Ans: B	$B = \mu_0 i / (2\pi R)$. Since $B \propto 1/R$, tripling R reduces B to $1/3$ of its original value.	

Q36	Which of the following configurations produces the MOST uniform magnetic field?	
	(A) A single long straight wire	(B) Two parallel wires with currents in same direction
	(C) An ideal solenoid (interior)	(D) A toroid (interior)
Ans: C	<i>Inside an ideal solenoid, $B = \mu_0 i n$ is uniform (same magnitude and direction throughout). A toroid's field varies as $1/r$; parallel wires and single wires produce non-uniform fields.</i>	

Q37	The direction of the magnetic field at the center of a circular loop of current is:	
	(A) In the plane of the loop	(B) Perpendicular to the plane of the loop (along axis)
	(C) Along the radius of the loop	(D) At 45° to the loop plane
Ans: B	<i>By the right-hand rule for the arc, at the center C, the cross product $d\vec{s} \times \hat{r}$ points perpendicular to the loop plane (into or out of the page depending on current direction).</i>	

Q38	In the Biot–Savart law, dB is maximum when angle θ between $i d\vec{s}$ and $\hat{r}$ is:	
	(A) 0°	(B) 45°
	(C) 90°	(D) 180°
Ans: C	<i>$dB \propto \sin\theta$. This is maximum when $\theta = 90^\circ$, i.e., when the current element is perpendicular to the line joining it to field point P.</i>	

Q39	The principle that magnetic fields, like electric fields, can be added (superimposed) to find a net field is:	
	(A) Newton's third law applied to fields	(B) Conservation of magnetic flux
	(C) The principle of superposition	(D) Faraday's principle
Ans: C	<i>The principle of superposition states that fields from different sources add vectorially. This allows calculation of net field B by integrating all dB contributions from current-length elements.</i>	

Q40	Which statement about Ampere's law is CORRECT?	
	(A) It only works for straight infinite wires	(B) It is equivalent to Biot–Savart law for symmetric situations
	(C) It gives the field only outside conductors	(D) It requires knowing the field everywhere along the loop

Ans: Ampere's law $\oint \mathbf{B} \cdot d\mathbf{s} = \mu_0 i_{\text{enc}}$ is equivalent to the Biot–Savart law. For symmetric configurations (straight wire, solenoid, toroid), it provides a much simpler calculation.

PART B — NUMERICAL MCQs (20 Questions)

Use $\mu_0 = 4\pi \times 10^{-7} \text{ T}\cdot\text{m/A}$ for all calculations

Q1

A long straight wire carries a current $i = 10 \text{ A}$. The magnetic field at a perpendicular distance $R = 0.05 \text{ m}$ from the wire is: ($\mu_0 = 4\pi \times 10^{-7} \text{ T}\cdot\text{m/A}$)

(A) $4.0 \times 10^{-5} \text{ T}$

(C) $4.0 \times 10^{-6} \text{ T}$

(B) $2.0 \times 10^{-5} \text{ T}$

(D) $8.0 \times 10^{-5} \text{ T}$

Ans: $B = \mu_0 i / (2\pi R) = (4\pi \times 10^{-7} \times 10) / (2\pi \times 0.05) = (4\pi \times 10^{-6}) / (0.1\pi) = 4 \times 10^{-5} \text{ T}.$
A

Q2

A circular loop of radius $R = 0.1 \text{ m}$ carries current $i = 2 \text{ A}$. The magnetic field at the center of the loop is:

(A) $4\pi \times 10^{-6} \text{ T}$

(C) $4\pi \times 10^{-7} \text{ T}$

(B) $2\pi \times 10^{-6} \text{ T}$

(D) $\pi \times 10^{-5} \text{ T}$

Ans: $B = \mu_0 i / (2R) = (4\pi \times 10^{-7} \times 2) / (2 \times 0.1) = 8\pi \times 10^{-7} / 0.2 = 4\pi \times 10^{-6} \text{ T} \approx 1.26 \times 10^{-5} \text{ T}.$
A

Q3

A circular arc subtending angle $\phi = \pi/2$ radians and radius $R = 0.2 \text{ m}$ carries current $i = 4 \text{ A}$. The field at center C is:

(A) $\pi \times 10^{-6} \text{ T}$

(C) $2\pi \times 10^{-6} \text{ T}$

(B) $\pi \times 10^{-7} \text{ T}$

(D) $0.5\pi \times 10^{-7} \text{ T}$

Ans: $B = \mu_0 i \phi / (4\pi R) = (4\pi \times 10^{-7} \times 4 \times \pi/2) / (4\pi \times 0.2) = (4\pi \times 10^{-7} \times 4 \times \pi/2) / (0.8\pi) = (8\pi^2 \times 10^{-7}) / (0.8\pi) = 10\pi \times 10^{-7} = \pi \times 10^{-6} \text{ T}.$
A

Q4

An ideal solenoid has $n = 2000$ turns/m and carries $i = 3 \text{ A}$. The magnetic field inside is:

(A) $6.28 \times 10^{-4} \text{ T}$

(C) $2.4 \times 10^{-3} \text{ T}$

(B) $7.54 \times 10^{-3} \text{ T}$

(D) $4.8 \times 10^{-3} \text{ T}$

Ans: $B = \mu_0 i n = 4\pi \times 10^{-7} \times 3 \times 2000 = 4\pi \times 10^{-7} \times 6000 = 24\pi \times 10^{-4} \approx 2.4 \times 10^{-3} \text{ T}.$
C

Q5

A toroid has $N = 500$ turns, carries current $i = 2 \text{ A}$, and the field point is at radius $r = 0.1 \text{ m}$ from the center. The field inside is:

(A) $1.0 \times 10^{-3} \text{ T}$

(C) $4.0 \times 10^{-4} \text{ T}$

(B) $2.0 \times 10^{-3} \text{ T}$

(D) $2.0 \times 10^{-4} \text{ T}$

Ans: $B = \mu_0 i N / (2\pi r) = (4\pi \times 10^{-7} \times 2 \times 500) / (2\pi \times 0.1) = (4\pi \times 10^{-4}) / (0.2\pi) = 2 \times 10^{-3} / 2 = 1.0 \times 10^{-3} \text{ T}.$
A

Q6

Two long parallel wires are separated by $d = 0.04 \text{ m}$ and carry currents $i_1 = 5 \text{ A}$ and $i_2 = 10 \text{ A}$ in the same direction. The force per unit length between them is:

(A) $2.5 \times 10^{-4} \text{ N/m}$ (attractive)(B) $1.25 \times 10^{-4} \text{ N/m}$ (repulsive)(C) $2.5 \times 10^{-4} \text{ N/m}$ (repulsive)(D) $5.0 \times 10^{-4} \text{ N/m}$ (attractive)

Ans:

A

$F/L = \mu_0 i_1 i_2 / (2\pi d) = (4\pi \times 10^{-7} \times 5 \times 10) / (2\pi \times 0.04) = (2 \times 10^{-5}) / (0.08) = 2.5 \times 10^{-4} \text{ N/m}$. Same direction $\rightarrow$ attractive.

Q7

A solenoid is 0.5 m long, has 1000 total turns, and carries 2 A . What is B inside?

(A) $2.51 \times 10^{-3} \text{ T}$ (B) $5.03 \times 10^{-3} \text{ T}$ (C) $1.26 \times 10^{-3} \text{ T}$ (D) $4.0 \times 10^{-3} \text{ T}$

Ans:

A

$n = N/L = 1000/0.5 = 2000 \text{ turns/m}$. $B = \mu_0 i n = 4\pi \times 10^{-7} \times 2 \times 2000 = 16\pi \times 10^{-4} \approx 5.03 \times 10^{-3} \text{ T}$. Wait — recalculate: $4\pi \times 10^{-7} \times 2 \times 2000 = 1.6\pi \times 10^{-3} \approx 5.03 \times 10^{-3} \text{ T}$. That is answer B. Let me re-check A: $2.51 \times 10^{-3} = \mu_0 \times 1 \times 2000$. So with $i=2 \text{ A} \rightarrow 5.03 \times 10^{-3} \text{ T}$ is correct answer B.

Q8

A solenoid is 0.5 m long, has 1000 total turns, and carries 1 A . What is B inside?

(A) $2.51 \times 10^{-3} \text{ T}$ (B) $5.03 \times 10^{-3} \text{ T}$ (C) $1.26 \times 10^{-3} \text{ T}$ (D) $4.0 \times 10^{-3} \text{ T}$

Ans:

A

$n = 1000/0.5 = 2000 \text{ turns/m}$. $B = \mu_0 i n = 4\pi \times 10^{-7} \times 1 \times 2000 = 8\pi \times 10^{-4} \approx 2.51 \times 10^{-3} \text{ T}$.

Q9

For a long straight wire with $i = 5 \text{ A}$, at what distance R is $B = 10^{-5} \text{ T}$?

(A) 0.1 m (B) 0.05 m (C) 0.2 m (D) 0.01 m

Ans:

A

$R = \mu_0 i / (2\pi B) = (4\pi \times 10^{-7} \times 5) / (2\pi \times 10^{-5}) = (20\pi \times 10^{-7}) / (2\pi \times 10^{-5}) = 10 \times 10^{-2} = 0.1 \text{ m}$.

Q10

A wire carries current $i = 8 \text{ A}$. Using Ampere's law, the field at $r = 0.02 \text{ m}$ outside a wire of radius $R = 0.01 \text{ m}$ is:

(A) $8.0 \times 10^{-5} \text{ T}$ (B) $4.0 \times 10^{-5} \text{ T}$ (C) $1.6 \times 10^{-4} \text{ T}$ (D) $3.2 \times 10^{-5} \text{ T}$

Ans:

A

$B = \mu_0 i / (2\pi r) = (4\pi \times 10^{-7} \times 8) / (2\pi \times 0.02) = (32\pi \times 10^{-7}) / (0.04\pi) = 800 \times 10^{-7} = 8.0 \times 10^{-5} \text{ T}$.

Q11

Inside a wire of radius $R = 0.01 \text{ m}$ carrying $i = 8 \text{ A}$ uniformly, the field at $r = 0.005 \text{ m}$ is:

(A) $4.0 \times 10^{-5} \text{ T}$ (B) $8.0 \times 10^{-5} \text{ T}$

(C) $2.0 \times 10^{-5} \text{ T}$

(D) $1.6 \times 10^{-5} \text{ T}$

Ans:
A $B = (\mu_0 i / 2\pi R^2) r = (4\pi \times 10^{-7} \times 8) / (2\pi \times (0.01)^2) \times 0.005 = (32 \times 10^{-7}) / (2 \times 10^{-4}) \times 0.005 = 1.6 \times 10^{-2} \times 0.005 \times 10^{-3} \dots$
 $B_{\text{surface}} = \mu_0 i / (2\pi R) = 8 \times 10^{-5} \times (0.01) / 0.01 \dots$ At $r = R/2$, $B = B_{\text{surface}} \times (r/R) = 8 \times 10^{-5} \times 0.5 = 4 \times 10^{-5} \text{ T}$.

Q12

Two parallel wires 0.1 m apart carry 10 A each in opposite directions. The force per unit length is: (attractive or repulsive?)

(A) $2 \times 10^{-4} \text{ N/m}$ attractive

(B) $2 \times 10^{-4} \text{ N/m}$ repulsive

(C) $4 \times 10^{-4} \text{ N/m}$ attractive

(D) $1 \times 10^{-4} \text{ N/m}$ repulsive

Ans:
B $F/L = \mu_0 i_1 i_2 / (2\pi d) = (4\pi \times 10^{-7} \times 10 \times 10) / (2\pi \times 0.1) = (4 \times 10^{-5}) / (0.2) = 2 \times 10^{-4} \text{ N/m}$. Opposite directions $\rightarrow$ repulsive.

Q13

A toroid with $N = 1000$ turns, $i = 5 \text{ A}$, inner radius $r_1 = 0.1 \text{ m}$, outer radius $r_2 = 0.2 \text{ m}$. The field at $r = 0.15 \text{ m}$ is approximately:

(A) $3.33 \times 10^{-3} \text{ T}$

(B) $6.67 \times 10^{-3} \text{ T}$

(C) $1.67 \times 10^{-3} \text{ T}$

(D) $5.00 \times 10^{-3} \text{ T}$

Ans:
A $B = \mu_0 i N / (2\pi r) = (4\pi \times 10^{-7} \times 5 \times 1000) / (2\pi \times 0.15) = (20\pi \times 10^{-4}) / (0.3\pi) = 20 \times 10^{-4} / 0.3 \approx 6.67 \times 10^{-3} \text{ T}$. Hmm $\rightarrow$ let me recompute: $(4\pi \times 10^{-7} \times 5000) / (2\pi \times 0.15) = (2 \times 10^{-6} \times 5000) / 0.15 \dots = 10^{-2} / 0.15 \times (2/2) \rightarrow (4\pi \times 10^{-3}) / (0.3\pi) = 4 / 0.3 \times 10^{-3} = 13.3 \times 10^{-3}$. Re-check: $\mu_0 = 4\pi \times 10^{-7}$; $iN = 5000$; $2\pi r = 2\pi \times 0.15 = 0.3\pi$. $B = (4\pi \times 10^{-7} \times 5000) / (0.3\pi) = (4 \times 5000 \times 10^{-7}) / 0.3 = (20000 \times 10^{-7}) / 0.3 = 66667 \times 10^{-7} \approx 6.67 \times 10^{-3} \text{ T}$. Answer is B.

Q14

A toroid with $N = 1000$ turns, $i = 5 \text{ A}$, at $r = 0.3 \text{ m}$. The field is approximately:

(A) $3.33 \times 10^{-3} \text{ T}$

(B) $6.67 \times 10^{-3} \text{ T}$

(C) $1.67 \times 10^{-3} \text{ T}$

(D) $5.00 \times 10^{-3} \text{ T}$

Ans:
A $B = \mu_0 i N / (2\pi r) = (4\pi \times 10^{-7} \times 5 \times 1000) / (2\pi \times 0.3) = (4 \times 5000 \times 10^{-7}) / 0.6 = 20000 \times 10^{-7} / 0.6 = 33333 \times 10^{-7} \approx 3.33 \times 10^{-3} \text{ T}$.

Q15

The sample problem solenoid ($L = 1.23 \text{ m}$, 5 layers $\times$ 850 turns, $i = 5.57 \text{ A}$) gives $B =$

(A) 24.2 mT

(B) 12.1 mT

(C) 48.4 mT

(D) 6.05 mT

Ans:
A $n = 5 \times 850 / 1.23 = 4250 / 1.23 \approx 3455 \text{ turns/m}$. $B = \mu_0 i n = 4\pi \times 10^{-7} \times 5.57 \times 3455 \approx 2.42 \times 10^{-2} \text{ T} = 24.2 \text{ mT}$.

Q16	Two parallel wires at $d=5.3$ cm, $i_1=15$ A, $i_2=32$ A, base angles 45° . Net field magnitude $\approx$	
	(A) $190 \mu\text{T}$ (C) $380 \mu\text{T}$	(B) $95 \mu\text{T}$ (D) $140 \mu\text{T}$
Ans: A	From the sample problem: $B = [\mu_0/(2\pi d \cos 45^\circ)]\sqrt{(i_1^2+i_2^2)} = (4\pi \times 10^{-7})/(2\pi \times 0.053 \times \cos 45^\circ) \times \sqrt{(225+1024)} = 1.89 \times 10^{-4} \text{ T} \approx 190 \mu\text{T}$.	
Q17	For a semi-infinite wire with $i = 4$ A at perpendicular distance $R = 0.02$ m, $B =$	
	(A) $10 \mu\text{T}$ (C) $40 \mu\text{T}$	(B) $20 \mu\text{T}$ (D) $5 \mu\text{T}$
Ans: C	$B = \mu_0 i/(4\pi R) = (4\pi \times 10^{-7} \times 4)/(4\pi \times 0.02) = (16\pi \times 10^{-7})/(0.08\pi) = 200 \times 10^{-7} \times (1/0.02 \times 4) \dots = 4 \times 10^{-7}/0.02 \times (1/\pi) \times \pi = 4 \times 10^{-7}/0.02 = 2 \times 10^{-5} \text{ T} = 20 \mu\text{T}$. Hmm: $\mu_0 i/(4\pi R) = (4\pi \times 10^{-7} \times 4)/(4\pi \times 0.02) = (4 \times 10^{-7} \times 4)/(4 \times 0.02) = 16 \times 10^{-7}/0.08 = 2 \times 10^{-5} = 20 \mu\text{T}$. Answer B.	
Q18	The hollow cylinder sample: $a=2$ cm, $b=4$ cm, $J=cr^2$, $c=3 \times 10^6$ A/m ⁴ , $r=3$ cm. $B \approx$	
	(A) $2.0 \times 10^{-5} \text{ T}$ (C) $1.0 \times 10^{-5} \text{ T}$	(B) $4.0 \times 10^{-5} \text{ T}$ (D) $6.0 \times 10^{-5} \text{ T}$
Ans: A	From the sample problem in the slides: substituting all values yields $B = 2.0 \times 10^{-5} \text{ T}$. The calculation uses $i_{\text{enc}} = \pi c(r^4 - a^4)/2$ then $B = \mu_0 i_{\text{enc}}/(2\pi r)$.	
Q19	A wire of radius $R = 0.005$ m carries $i = 10$ A uniformly. At $r = 0.003$ m (inside), $B =$	
	(A) $2.4 \times 10^{-4} \text{ T}$ (C) $1.2 \times 10^{-4} \text{ T}$	(B) $4.8 \times 10^{-4} \text{ T}$ (D) $6.0 \times 10^{-4} \text{ T}$
Ans: A	$B = (\mu_0 i/(2\pi R^2))r = (4\pi \times 10^{-7} \times 10)/(2\pi \times (0.005)^2) \times 0.003 = (4 \times 10^{-6})/(2 \times 2.5 \times 10^{-5}) \times 0.003 = (4 \times 10^{-6}/5 \times 10^{-5}) \times 0.003 = 0.08 \times 0.003 = 2.4 \times 10^{-4} \text{ T}$.	
Q20	A circular loop radius $R = 0.05$ m, current $i = 10$ A. At center, $B =$	
	(A) $4\pi \times 10^{-5} \text{ T}$ (C) $8\pi \times 10^{-5} \text{ T}$	(B) $2\pi \times 10^{-5} \text{ T}$ (D) $\pi \times 10^{-4} \text{ T}$
Ans: C	$B = \mu_0 i/(2R) = (4\pi \times 10^{-7} \times 10)/(2 \times 0.05) = 40\pi \times 10^{-7}/0.1 = 400\pi \times 10^{-7} = 4\pi \times 10^{-5} \text{ T}$. That is answer A: $4\pi \times 10^{-5} \text{ T}$.	