

PF firewall (FreeBSD, OpenBSD) configuration and debug commands cheat sheet

Author: Yuri Slobodyanyuk, admin@yurisk.info

PF (Packet Filter) management for FreeBSD & OpenBSD

Command	Description
pfctl -d	Disable PF in place, does not survive reboot.
pfctl -ef /etc/pf.conf	Enable PF and load the rule set from file <code>/etc/pf.conf</code> in one go.
pfctl -nf /etc/pf.conf	Parse security rules stored in a file without installing them (dry run).
pfctl -F all pfctl -F rules pfctl -F nat pfctl -F states	Flush, accordingly: <ul style="list-style-type: none">• Everything (filter rules, nat, and stateful table)• Rules only (stateful table of existing connections stay intact)• NAT rules only• Stateful table
pass in quick on egress from 62.13.77.141 to any	'Quick' rule, means allow this traffic to pass through on all interfaces, otherwise we would need 2nd rule allowing this traffic in <i>outgoing</i> direction on egress interface, to allow destined to ANY port/protocol with the source being <code>62.13.77.141</code> and destination being ANY IP address behind the PF firewall. NOTE: here, <code>egress</code> is not a direction, but a group name to which the interface in question (<code>em0</code>) belongs to. In OpenBSD you set it in a file <code>/etc/hostname.em0: group egress</code> or in real-time with the command: <code>ifconfig em0 group egress</code> .