

## Ex:1 Heart Disease Prediction

```
# Import necessary libraries
import numpy as np
import pandas as pd
import tensorflow as tf
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.metrics import accuracy_score, classification_report,
confusion_matrix

# Load the dataset (replace 'heart.csv' with your dataset file)
data = pd.read_csv('heart.csv')

# Prepare the data
X = data.drop('target', axis=1)
y = data['target']

# Split the data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)

# Standardize the input features
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)

# Create a Sequential model
model = tf.keras.Sequential([
    tf.keras.layers.Input(shape=(X_train.shape[1],)),
    tf.keras.layers.Dense(64, activation='relu'),
    tf.keras.layers.Dense(32, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])

# Compile the model
model.compile(optimizer='adam',
              loss='binary_crossentropy',
              metrics=['accuracy'])

# Train the model
model.fit(X_train, y_train, epochs=50, batch_size=32, verbose=0)

# Make predictions
y_pred_prob = model.predict(X_test)
y_pred = (y_pred_prob > 0.5).astype(int)

# Evaluate the model
```

```

accuracy = accuracy_score(y_test, y_pred)
conf_matrix = confusion_matrix(y_test, y_pred)
classification_rep = classification_report(y_test, y_pred)

# Print the results
print(f'Accuracy: {accuracy}')
print(f'Confusion Matrix:\n{conf_matrix}')
print(f'Classification Report:\n{classification_rep}')

```

## 2: Knn Supervised Algorithm

```

from sklearn.neighbors import KNeighborsClassifier
from sklearn.model_selection import train_test_split
from sklearn.datasets import load_iris
import numpy as np
import matplotlib.pyplot as plt

irisData = load_iris()

# Create feature and target arrays
X = irisData.data
y = irisData.target

# Split into training and test set
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size = 0.2, random_state=42)

neighbors = np.arange(1, 9)
train_accuracy = np.empty(len(neighbors))
test_accuracy = np.empty(len(neighbors))

# Loop over K values
for i, k in enumerate(neighbors):
    knn = KNeighborsClassifier(n_neighbors=k)
    knn.fit(X_train, y_train)

    # Compute training and test data accuracy
    train_accuracy[i] = knn.score(X_train, y_train)
    test_accuracy[i] = knn.score(X_test, y_test)

# Generate plot
plt.plot(neighbors, test_accuracy, label = 'Testing dataset Accuracy')
plt.plot(neighbors, train_accuracy, label = 'Training dataset Accuracy')

plt.legend()

```

```
plt.xlabel('n_neighbors')
plt.ylabel('Accuracy')
plt.show()
```

### 3. K-Means Clustering UnSupervised

```
#Creating a DataFrame for two-dimensional dataset
#Finding the centroids of 3 clusters, and then of 4 clusters
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.cluster import KMeans

data = {
    'x': [25, 34, 22, 27, 33, 33, 31, 22, 35, 34, 67, 54, 57, 43, 50, 57, 59,
          52, 65, 47, 49, 48, 35, 33, 44, 45, 38,
          43, 51, 46],
    'y': [79, 51, 53, 78, 59, 74, 73, 57, 69, 75, 51, 32, 40, 47, 53, 36, 35,
          58, 59, 50, 25, 20, 14, 12, 20, 5, 29, 27,
          8, 7]
}

df = pd.DataFrame(data)
print(df)

data = {
    'x': [25, 34, 22, 27, 33, 33, 31, 22, 35, 34, 67, 54, 57, 43, 50, 57, 59,
          52, 65, 47, 49, 48, 35, 33, 44, 45, 38,
          43, 51, 46],
    'y': [79, 51, 53, 78, 59, 74, 73, 57, 69, 75, 51, 32, 40, 47, 53, 36, 35,
          58, 59, 50, 25, 20, 14, 12, 20, 5, 29, 27,
          8, 7]
}

df = pd.DataFrame(data)

kmeans = KMeans(n_clusters=3).fit(df)
centroids = kmeans.cluster_centers_
print(centroids)

plt.scatter(df['x'], df['y'], c=kmeans.labels_.astype(float), s=50, alpha=0.5)
plt.scatter(centroids[:, 0], centroids[:, 1], c='red', s=50)
plt.show()
```

```

data = {
    'x': [25, 34, 22, 27, 33, 33, 31, 22, 35, 34, 67, 54, 57, 43, 50, 57, 59,
          52, 65, 47, 49, 48, 35, 33, 44, 45, 38,
          43, 51, 46],
    'y': [79, 51, 53, 78, 59, 74, 73, 57, 69, 75, 51, 32, 40, 47, 53, 36, 35,
          58, 59, 50, 25, 20, 14, 12, 20, 5, 29, 27,
          8, 7]
}

df = pd.DataFrame(data)

kmeans = KMeans(n_clusters=4).fit(df)
centroids = kmeans.cluster_centers_
print(centroids)

plt.scatter(df['x'], df['y'], c=kmeans.labels_.astype(float), s=50, alpha=0.5)
plt.scatter(centroids[:, 0], centroids[:, 1], c='red', s=50)
plt.show()

```

## 4. Backpropagation Neural Network using Python

```

# Import Libraries
import numpy as np
import pandas as pd
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
import matplotlib.pyplot as plt

# Load dataset
data = load_iris()

# Get features and target
X=data.data
y=data.target

# Get dummy variable
y = pd.get_dummies(y).values

y[:3]

#Split data into train and test data
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=20,
random_state=4)

# Initialize variables

```

```

learning_rate = 0.1
iterations = 5000
N = y_train.size

# number of input features
input_size = 4

# number of hidden layers neurons
hidden_size = 2

# number of neurons at the output layer
output_size = 3

results = pd.DataFrame(columns=["mse", "accuracy"])
# Initialize weights
np.random.seed(10)

# initializing weight for the hidden layer
W1 = np.random.normal(scale=0.5, size=(input_size, hidden_size))

# initializing weight for the output layer
W2 = np.random.normal(scale=0.5, size=(hidden_size , output_size))
def sigmoid(x):
    return 1 / (1 + np.exp(-x))

def mean_squared_error(y_pred, y_true):
    return ((y_pred - y_true)**2).sum() / (2*y_pred.size)

def accuracy(y_pred, y_true):
    acc = y_pred.argmax(axis=1) == y_true.argmax(axis=1)
    return acc.mean()
for itr in range(iterations):

    # feedforward propagation
    # on hidden layer
    Z1 = np.dot(X_train, W1)
    A1 = sigmoid(Z1)

    # on output layer
    Z2 = np.dot(A1, W2)
    A2 = sigmoid(Z2)

    # Calculating error
    mse = mean_squared_error(A2, y_train)
    acc = accuracy(A2, y_train)
    results=results.append({"mse":mse, "accuracy":acc},ignore_index=True )

```

```

# backpropagation
E1 = A2 - y_train
dW1 = E1 * A2 * (1 - A2)

E2 = np.dot(dW1, W2.T)
dW2 = E2 * A1 * (1 - A1)

# weight updates
W2_update = np.dot(A1.T, dW1) / N
W1_update = np.dot(X_train.T, dW2) / N

W2 = W2 - learning_rate * W2_update
W1 = W1 - learning_rate * W1_update
results.mse.plot(title="Mean Squared Error")
results.accuracy.plot(title="Accuracy")
plt.show()

# feedforward
Z1 = np.dot(X_test, W1)
A1 = sigmoid(Z1)

Z2 = np.dot(A1, W2)
A2 = sigmoid(Z2)

acc = accuracy(A2, y_test)
print("Accuracy: {}".format(acc))

```

## 5. LINEAR REGRESSION

```

import numpy as np
import matplotlib.pyplot as plt

def estimate_coef(x, y):
    # number of observations/points
    n = np.size(x)

    # mean of x and y vector
    m_x = np.mean(x)
    m_y = np.mean(y)

    # calculating cross-deviation and deviation about x
    SS_xy = np.sum(y*x) - n*m_y*m_x

```

```

SS_xx = np.sum(x*x) - n*m_x*m_x

# calculating regression coefficients
b_1 = SS_xy / SS_xx
b_0 = m_y - b_1*m_x

return (b_0, b_1)

def plot_regression_line(x, y, b):
    # plotting the actual points as scatter plot
    plt.scatter(x, y, color = "m",
                marker = "o", s = 30)

    # predicted response vector
    y_pred = b[0] + b[1]*x

    # plotting the regression line
    plt.plot(x, y_pred, color = "g")

    # putting labels
    plt.xlabel('x')
    plt.ylabel('y')

    # function to show plot
    plt.show()

def main():
    # observations / data
    x = np.array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
    y = np.array([1, 3, 2, 5, 7, 8, 8, 9, 10, 12])

    # estimating coefficients
    b = estimate_coef(x, y)
    print("Estimated coefficients:\nb_0 = {} \
          \nb_1 = {}".format(b[0], b[1]))

    # plotting regression line
    plot_regression_line(x, y, b)

if __name__ == "__main__":
    main()

```