

Assignment – 12

Name - Md. Firoze Baba

firozebaba68@gmail.com

Task 1:

Balanced Binary Tree Check:

Write a function to check if a given binary tree is balanced. A balanced tree is one where the height of two subtrees of any node never differs by more than one.

Program:

```
public class TreeNode {
    int element;
    TreeNode left;
    TreeNode right;

    public TreeNode(int x) {
        element = x;
    }
}

public class BinaryTree {
    public boolean isBalanced(TreeNode root) {
        return checkHeight(root) != -1;
    }
    private int checkHeight(TreeNode root) {
        if(root==null) {
            return 0;
        }
        int leftheight=checkHeight(root.left);
        if(leftheight == -1) {
            return -1;
        }
        int rightheight=checkHeight(root.right);
        if(rightheight == -1) {
            return -1;
        }
        if(Math.abs(leftheight - rightheight)>1) {
            return -1;
        }
        return Math.max(leftheight, rightheight)+1;
    }
    public static void main(String[] args) {
        TreeNode root=new TreeNode(3);
        root.left = new TreeNode(9);
        root.left.left=new TreeNode(5);
        root.right=new TreeNode(20);
        root.right.left=new TreeNode(15);
        root.right.right=new TreeNode(7);
        BinaryTree bt= new BinaryTree();
        System.out.println("Is the binary tree balance? "
            +bt.isBalanced(root));
    }
}
```

```
}
```

Output:

Is the binary tree balance? True

Task 2:

Trie for Prefix Checking:

Implement a trie data structure in C# that supports insertion of strings and provides a method to check if a given string is a prefix of any word in the trie.

Program:

```
public class TrieNode {
    TrieNode[] child;
    boolean isEndOfWord;
    TrieNode() {
        child = new TrieNode[26];
        isEndOfWord = false;
    }
}
public class TrieDS {

    private TrieNode root;

    public TrieDS() {
        root = new TrieNode();
    }
    public void insert(String word) {
        TrieNode node = root;
        for (char c : word.toCharArray()) {
            int index = c - 'a';
            if (node.child[index] == null) {
                node.child[index] = new TrieNode();
            }
            node = node.child[index];
        }
        node.isEndOfWord = true;
    }
    public boolean search(String word) {
        TrieNode node = root;
        for (char c : word.toCharArray()) {
            int index = c - 'a';
            if (node.child[index] == null) {
                return false;
            }
            node = node.child[index];
        }
        return node != null && node.isEndOfWord;
    }
    public boolean startsWith(String prefix) {
```

```

        TrieNode node = root;
        for (char c : prefix.toCharArray()) {
            int index = c - 'a';
            if (node.child[index] == null) {
                return false;
            }
            node = node.child[index];
        }
        return true;
    }

    public static void main(String[] args) {
        TrieDS tds = new TrieDS();

        tds.insert("mani");
        tds.insert("teja");
        tds.insert("pavan");

        System.out.println("Is 'Man' a prefix? " +
            tds.startsWith("man"));
        System.out.println("Is 'Teja' a prefix? " +
            tds.startsWith("te"));
        System.out.println("Is 'vang' a prefix? " +
            tds.startsWith("vang"));
    }
}

```

Output:

```

Is 'Man' a prefix? true
Is 'Teja' a prefix? true
Is 'vang' a prefix? False

```

Task 3:

Implementing Heap Operations:

Code a min-heap in C# with methods for insertion, deletion, and fetching the minimum element. Ensure that the heap property is maintained after each operation.

Program:

```

import java.util.ArrayList;
import java.util.List;

public class MinHeap {
    private List<Integer> heap;
    public MinHeap() {
        heap = new ArrayList<>();
    }
    public void insert(int value) {
        heap.add(value);
        heapifyUp(heap.size() - 1);
    }
}

```

```

    }

    private void heapifyUp(int index) {
        int parentIndex = (index - 1) / 2;
        while (index > 0 && heap.get(index) <
heap.get(parentIndex)) {
            swap(index, parentIndex);
            index = parentIndex;
            parentIndex = (index - 1) / 2;
        }
    }

    public int deleteMin() {
        if (isEmpty()) {
            throw new IllegalStateException("Heap is empty");
        }
        int min = heap.get(0);
        int lastElement = heap.remove(heap.size() - 1);
        if (!isEmpty()) {
            heap.set(0, lastElement);
            heapifyDown(0);
        }
        return min;
    }

    private void heapifyDown(int index) {
        int smallest = index;
        int leftChild = 2 * index + 1;
        int rightChild = 2 * index + 2;

        if (leftChild < heap.size() && heap.get(leftChild) <
heap.get(smallest)) {
            smallest = leftChild;
        }
        if (rightChild < heap.size() && heap.get(rightChild) <
heap.get(smallest)) {
            smallest = rightChild;
        }
        if (smallest != index) {
            swap(index, smallest);
            heapifyDown(smallest);
        }
    }

    public int getMin() {
        if (isEmpty()) {
            throw new IllegalStateException("Heap is empty");
        }
        return heap.get(0);
    }

    public boolean isEmpty() {
        return heap.isEmpty();
    }

    private void swap(int i, int j) {

```

```

        int temp = heap.get(i);
        heap.set(i, heap.get(j));
        heap.set(j, temp);
    }
    public static void main(String[] args) {
        MinHeap minHeap = new MinHeap();
        minHeap.insert(3);
        minHeap.insert(2);
        minHeap.insert(1);
        System.out.println("Minimum element: " +
minHeap.getMin());
        minHeap.deleteMin();
        System.out.println("Minimum element after deletion: "
            + minHeap.getMin());
    }
}

```

Output:

```

Minimum element: 1
Minimum element after deletion: 2

```

Task 4:

Graph Edge Addition Validation:

Given a directed graph, write a function that adds an edge between two nodes and then checks if the graph still has no cycles. If a cycle is created, the edge should not be added.

Program:

```

import java.util.ArrayList;
import java.util.List;

public class Graph {
    private int V; // Number of vertices
    private List<List<Integer>> adj;
    public Graph(int V) {
        this.V = V;
        adj = new ArrayList<>(V);
        for (int i = 0; i < V; i++) {
            adj.add(new ArrayList<>());
        }
    }
    public void addEdge(int u, int v) {
        adj.get(u).add(v);
    }

    public boolean hasCycle() {
        boolean[] visited = new boolean[V];
        boolean[] recursionStack = new boolean[V];

        for (int i = 0; i < V; i++) {

```

```

        if (isCyclicUtil(i, visited, recursionStack)) {
            return true;
        }
    }
    return false;
}

private boolean isCyclicUtil(int v, boolean[] visited,
boolean[]
recursionStack) {
    if (recursionStack[v]) {
        return true;.
    }

    if (visited[v]) {
        return false;    }
    visited[v] = true;
    recursionStack[v] = true;

    List<Integer> neighbors = adj.get(v);
    for (Integer neighbor : neighbors) {
        if (isCyclicUtil(neighbor, visited, recursionStack)) {
            return true;
        }
    }
    recursionStack[v] = false; // Backtrack
    return false;
}
public boolean addEdgeAndCheckForCycle(int u, int v) {
    addEdge(u, v);
    if (hasCycle()) {
        adj.get(u).remove((Integer) v);
        return false;
    }
    return true;
}
public static void main(String[] args) {
    Graph graph = new Graph(4);
    graph.addEdge(0, 1);
    graph.addEdge(1, 2);
    graph.addEdge(2, 3);

    System.out.println("Adding edge from 3 to 0: "
        + graph.addEdgeAndCheckForCycle(3, 0));
    System.out.println("Adding edge from 3 to 1: "
        + graph.addEdgeAndCheckForCycle(3, 1));
}
}

```

Output:

Adding edge from 3 to 0: false

Adding edge from 3 to 1: false

Task 5:

Breadth-First Search (BFS) Implementation:

For a given undirected graph, implement BFS to traverse the graph starting from a given node and print each node in the order it is visited.

Program:

```
public class BFS {
    public static void bfsTraversal(Map<Integer, List<Integer>>
graph, int startNode) {
        Set<Integer> visited = new HashSet<>();
        Queue<Integer> queue = new LinkedList<>();
        visited.add(startNode);
        queue.add(startNode);
        while (!queue.isEmpty()) {
            int currentNode = queue.poll();
            System.out.print(currentNode + " ");
            List<Integer> neighbors = graph.get(currentNode);
            if (neighbors != null) {
                for (int neighbor : neighbors) {
                    if (!visited.contains(neighbor)) {
                        visited.add(neighbor);
                        queue.add(neighbor);
                    }
                }
            }
        }
    }
}

public static void main(String[] args) {
    Map<Integer, List<Integer>> graph = new HashMap<>();

    graph.put(0, Arrays.asList(1, 2));
    graph.put(1, Arrays.asList(0, 3, 4));
    graph.put(2, Arrays.asList(0, 5, 6));
    graph.put(3, Arrays.asList(1));
    graph.put(4, Arrays.asList(1));
    graph.put(5, Arrays.asList(2));
    graph.put(6, Arrays.asList(2));

    int startNode = 0;
    System.out.println("BFS traversal starting from node "
        + startNode + ":");
    bfsTraversal(graph, startNode);
}
```

```
    }  
}
```

Output:

BFS traversal starting from node 0:
0 1 2 3 4 5 6

Task 6:

Depth-First Search (DFS) Recursive

Write a recursive DFS function for a given undirected graph. The function should visit every node and print it out.

Program:

```
import java.util.ArrayList;  
import java.util.HashMap;  
import java.util.List;  
import java.util.Map;  
public class DepthFirstSearch {  
    public void dfs(int node, boolean[] visited, Map<Integer,  
List<Integer>> graph) {  
        visited[node] = true;  
        System.out.println(node);  
        for (int neighbor : graph.get(node)) {  
            if (!visited[neighbor]) {  
                dfs(neighbor, visited, graph);  
            }  
        }  
    }  
    public void addEdge(Map<Integer, List<Integer>> graph, int u,  
int v) {  
        if (!graph.containsKey(u)) {  
            graph.put(u, new ArrayList<>());  
        }  
        if (!graph.containsKey(v)) {  
            graph.put(v, new ArrayList<>());  
        }  
        graph.get(u).add(v);  
        graph.get(v).add(u); // Since the graph is undirected  
    }  
    public static void main(String[] args) {  
        DepthFirstSearch dfs = new DepthFirstSearch();  
        Map<Integer, List<Integer>> graph = new HashMap<>();  
        dfs.addEdge(graph, 0, 1);  
        dfs.addEdge(graph, 0, 2);  
        dfs.addEdge(graph, 1, 2);  
        dfs.addEdge(graph, 2, 0);  
        dfs.addEdge(graph, 2, 3);  
        dfs.addEdge(graph, 3, 3);  
        boolean[] visited = new boolean[graph.size()];  
        dfs.dfs(2, visited, graph);  
    }  
}
```



```
    }  
}
```

Output:

2
0
1
3