

Local development (my-chat)

Stack

Compose file: `deploy/local/docker-compose.local.yml`

Manage only through Taskfile (`task local:*`), not raw `docker compose` unless debugging Taskfile itself.

Service	Container	Host ports
postgres	my-chat-postgres-local	33432 → 5432
auth-proxy	my-chat-auth-proxy-local	33081
main-service	my-chat-main-service-local	8080, metrics 9100
notification-worker	my-chat-notification-worker-local	(none)
message-expirer	my-chat-message-expirer-local	metrics 9101
prometheus	my-chat-prometheus-local	9090

DB (local): `postgres://chat_service:chat_service@localhost:33432/chat_service`

Migrations run with main-service (includes Sprint 6 010 credentials, 011 push_subscription).

Seed is manual — not mounted in compose: `deploy/local/seed-users.sql`.

Commands

```
task local:up          # build + start + wait healthy
task local:down        # stop, keep volumes
task local:down:clean  # stop + wipe volumes (full reset)
task local:ps          # status
task local:logs        # all logs
task local:logs:service -- main-service
task local:restart -- auth-proxy
task local:build       # images only
```

Quality gates (after code changes):

```
task lint
task test
task test:integration # spins its own postgres on 33433 (not local 33432)
```

Seed users (Sprint 6 credentials)

After `local:up` (or after `down:clean + up`), apply seed:

```
docker compose -f deploy/local/docker-compose.local.yml exec -T postgres \
  psql -U chat_service -d chat_service < deploy/local/seed-users.sql
```

Username	Password	UUID
alice	password123	11111111-1111-1111-1111-111111111111
bob	password123	22222222-2222-2222-2222-222222222222
Dialog	—	dddddddd-dddd-dddd-dddd-dddddddddddd

Login API (breaking change Sprint 6): { "username": "alice", "password": "password123" }
— **not** `user_id`.

Register (main-service, no auth): **POST** <http://localhost:8080/api/v1/users/register>.

Smoke

1. `task local:ps` — all services up / healthy.
2. Auth via curl (Debug UI / mobile may still send `user_id` until Sprint 6 client work):

```
curl -sS -X POST http://localhost:33081/api/v1/auth/login \
  -H 'Content-Type: application/json' \
  -d '{"username":"alice","password":"password123"}'
```

3. Debug UI: <http://localhost:8080/debug> (two tabs) — chat/WS shortcuts still useful; **login shortcut may fail** until updated to username/password.
4. HTTP <http://localhost:8080>, WS <ws://localhost:8080/ws/connect?token=...>
5. Broader flows: [docs/debug-manual-test.md](#) (seed/login sections may lag Sprint 6 — prefer curl + seed above).

Push locally: worker uses **devlog/noop**, not real Web Push, until Sprint 6 §7 lands. No media/upload stack.

Troubleshooting

Symptom	Check
Port in use	<code>task local:ps</code> ; stop conflicting process or <code>local:down</code>
Service crash-loop	<code>task local:logs:service -- <name></code>
Auth 401 / invalid_credentials	seed applied? username/password (not UUID)? auth-proxy + postgres healthy
Login via Debug UI fails	UI still posts <code>user_id</code> — use curl until §14
WS fails	main-service logs; token from login

Symptom	Check
Stale schema	<code>task local:down:clean</code> then <code>local:up</code> , then re-run seed
Lint/test before claim "works"	always <code>task lint</code> (repo rule)

Do not

- Expose or commit real prod secrets into local configs.
- Assume integration tests use the local compose DB (they use `deploy/test/` on 33433).
- Assume Web Push or PWA works locally before Sprint 6 §7–14 are done.