

FO/SA/7.4/03				Transf. No.		TI-169015	
Customer:		Australia		Designer		Pahan	
Cust. No.:				Date		2016-01-26	
0V Blue P1 50/60Hz 100V Brown P2 117V White 0V Red P3 50/60Hz 100V Grey P4 117V Black Green 1 U=260V , 0.1A Uo= 287.09 V S1 Yellow 0V S2 Green U=260V , 0.1A Uo= 287.09 V Violet1 U=26V , 0.25A Uo= 28.67 V S3 Orange 0V S4 Violet U=26V , 0.25A Uo= 28.67 V							
Classification							
Protection against electrical shock:				Isolating Transformer			
Protection index				IP00			
Protection against short-circuit and abnormal use:				Not short-circuit proof			
Mobility / Intended use:				build-in-transformer			
Time of operation:				continuous operation			
Ambient temperature / Material classification				ta40/A			
Revision history		No.	name	date	description		
		B					
		C					
1. Power65 VA= 100% nominal loadOD = 92 mmmaxexcl. leads 2. Temp.-rise (calc.)37 °C at 100% nominal loadH = 40 mmmaxexcl. leads 3. Electr. tolerances+/-3% 4. Meeting safety standardsEN 61558-1; EN 61558-2-4;weight = 0.835 kgsapprox.							
Mounting or Assembling: 1 pc metal washer + 2 pcs rubber pads 70mm							

FO/SA/7.4/03		Transf. No.	TI-169015
Customer:	Australia	Designer	Pahan
Cust. No.:		Date	2016-01-26

Terminations: All leads from 1015 AWG 22 200mm ends stripped to 8mm
Primary in common PVC tube 50mm

Label:



Transformer No : TI-169015 65 VA ta 40/A
PRI1,2: 0-100-117V BU-BN-WH 50/60Hz
PRI3,4: 0-100-117V RD-GY-BK 50/60Hz
SEC1,2: 260-0-260V GN1-YE-GN
SEC3,4: 26-0-26V VT1-OG-VT



Reference No./00

↑

Print our reference no. here