

# WX106D

## High-Base Magnesium Sulfonate Detergent

Series: Sulfonate Detergents

Provides good detergency for blending low-ash automotive lubricants; widely used in API GF-5, FA-4 and higher-tier additive packages.

ATTRIBUTES

High Base Number

Magnesium

Low Ash

END USES

Engine oils



### Technical Parameters

| PROPERTY                                        | SPECIFICATION | TEST METHOD |
|-------------------------------------------------|---------------|-------------|
| Kinematic Viscosity @100 °C, mm <sup>2</sup> /s | Report        | GB/T 265    |
| Magnesium, %                                    | ≥8.5          | ASTM D4951  |
| Density @20 °C, g/cm <sup>3</sup>               | ≥1.10         | GB/T 2540   |
| Flash Point (Open Cup), °C                      | ≥170          | GB/T 3536   |
| Total Base Number, mg KOH/g                     | ≥395          | SH/T 0251   |

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

#### Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu  
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn