

WX151

Mono-Alkenyl Succinimide Ashless Dispersant

Series: Ashless Dispersants

Made with BASF polyisobutylene. Excellent control of low-temperature sludge and high-temperature carbon deposit formation, outstanding low-temperature dispersancy, and good solubilization of high-temperature soot. Blended with detergents and antioxidant/anti-corrosion agents for premium gasoline engine oils; also a key raw material for fuel additives. Produced by a thermal (chlorine-free) process, offering better thermal-oxidative stability and dispersancy than chlorination-route products.



ATTRIBUTES

Mono-Succinimide

Chlorine-Free

END USES

Engine oils

Fuel additives & specialty

Technical Parameters

PROPERTY	SPECIFICATION	TEST METHOD
Appearance	Reddish-brown viscous transparent liquid	Visual
Kinematic Viscosity @100 °C, mm ² /s	≥220	GB/T 265
Total Base Number, mg KOH/g	45-60	SH/T 0251
Nitrogen, %	≥2.0	SH/T 0224
Color (Diluted)	≤3.0	GB/T 6540
Mechanical Impurities, %	≤0.08	GB/T 511
Flash Point (Open Cup), °C	≥180	GB/T 3530
Water Content, %	≤0.08	GB/T 260
Turbidity, JTU	≤60	SH/T 0028

Values are release specifications from the product TDS unless marked typical; the certificate of analysis shipped with each lot is the reference for that lot. Treat rates are guidance and depend on base oil and target performance level — our technical team is available to confirm dosage for your formulation.

Wuxi South Petroleum Additives Co., Ltd.

ADDRESS

48 Daqiao Road, Shitangwan, Huishan District, Wuxi, Jiangsu
214185, China

TEL

+86 510 8326 0848

EMAIL

sale@wxnfcn.com

WEB

www.wxnfcn.cn